

SEPA BUSINESS-TO-BUSINESS DIRECT DEBIT SCHEME CUSTOMER-TO-BANK IMPLEMENTATION GUIDELINES

Abstract	This document sets out the rules for implementing Version 7.0 of the SEPA Business-to-Business Direct Debit Scheme Rulebook based on Version 2009 of the customer-to-bank direct debit ISO 20022 XML message standards.
Document Reference	EPC131-08
Issue	Version 7.0 Approved
Date of Issue	26 January 2015
Reason for Issue	Approval for publication by the December 2014 Plenary
Reviewed by	EPC
Produced by	EPC
Authorised by	EPC
Circulation	Publicly available
Effective Date	20 November 2016
Note	Changed in line with the approved changes to the Rulebook effective 2016.

TABLE OF CONTENTS

0	DOCUMENT INFORMATION	2
0.1	REFERENCES.....	2
0.2	CHANGE HISTORY	2
0.3	PURPOSE OF DOCUMENT.....	3
1	INTRODUCTION.....	4
1.1	COVERAGE OF THESE SEPA IMPLEMENTATION GUIDELINES.....	4
1.2	USE OF THESE GUIDELINES BY THE INSTRUCTING AND INSTRUCTED PARTIES.....	6
1.3	NOTATION CONVENTIONS	6
1.4	CHARACTER SET	8
1.5	GENERAL MESSAGE ELEMENT SPECIFICATIONS.....	9
1.5.1	<i>BIC</i>	9
1.5.2	<i>Identifier of the Creditor (AT-02)</i>	9
1.5.3	<i>Mandate Identification (AT-01 Unique Mandate Reference)</i>	10
1.5.4	<i>SMNDA</i>	10
1.6	IMPLEMENTATION OF ISO 20022 XML RULES	10
2	RECOMMENDED CUSTOMER-TO-BANK AND BANK-TO-CUSTOMER MESSAGES.....	11
2.1	BUSINESS CUSTOMER TO BANK DIRECT DEBIT COLLECTION DATASET (DS-03)	11
2.1.1	<i>Use of Customer Direct Debit Initiation (pain.008.001.02)</i>	11
2.2	CUSTOMER TO BANK REVERSAL INSTRUCTION FOR A COLLECTION (BASED ON DS-07 AND DS-03)	42
2.2.1	<i>Use of the Customer to Bank Payment Reversal (pain.007.001.02)</i>	42
2.2.2	<i>Message Element Specifications</i>	54
2.3	BANK TO CUSTOMER DIRECT DEBIT REJECT DATASET (BASED ON DS-05).....	54
2.3.1	<i>Use of the Customer Payment Status Report (pain.002.001.03)</i>	54
2.3.2	<i>Message Element Specifications</i>	66

0 DOCUMENT INFORMATION

0.1 References

This section lists relevant documents of interest.

	Document Number	Title	Issued by:
[1]	EPC222-07	SEPA Business-to-Business Direct Debit Scheme Rulebook Version 7.0	EPC
[2]	-	ISO 20022 XML Direct Debits and Related message standards, September 2009: <ul style="list-style-type: none"> • Initiation • Clearing and Settlement 	ISO 20022
[3]	ISO 3166	Country Codes	ISO
[4]	ISO 4217	Currency Code List	ISO
[5]	ISO 9362	Business Identifier Codes (BIC)	ISO
[6]	ISO 13616	IBAN: International Bank Account Number	ISO ¹
[7]	ISO/IEC 7064	Information technology - Security techniques - Check character systems	ISO
[8]	EPC129-09	SEPA B2B Direct Debit Scheme E-Mandate Service Implementation Guidelines	EPC
[9]	EPC217-08	SEPA Requirements for an Extended Character Set	EPC

0.2 Change History

Issue number	Dated	Reason for revision
V1.1	20081218	EPC Plenary approval 17 December 2008
V1.2	20090630	EPC Plenary approval June 2009
V2.0	20091101	EPC Plenary approval October 2009
V3.0	20101101	EPC Plenary approval September 2010
V4.0	20111117	EPC Plenary approval September 2011
V5.0	20121130	EPC Plenary approval September 2012

¹ See also http://www.swift.com/products/bic_registration/iban_format_registration

V6.0	20141125	EPC Plenary approval October 2014
V7.0	20150126	EPC Plenary approval December 2014

0.3 Purpose of Document

The objective of these Guidelines is to define the rules to be applied to the ISO 20022 XML message standards for the implementation of the SEPA Business-to-Business Direct Debits in the customer-to-bank space.

1 INTRODUCTION

This document sets out the SEPA rules for implementing the business-to-business (B2B) customer-to-bank direct debit ISO 20022 XML initiation message standards. The SEPA B2B Direct Debit Scheme Rulebook defines data sets which are implemented in the relevant ISO 20022 XML message standard as follows.

SEPA Direct Debit Scheme Rulebook	ISO 20022 XML Message Standards
DS-03 <i>Business Customer to bank Collection</i>	Customer Direct Debit Initiation (pain.008.001.02)
DS-06 <i>Bank to Business Customer Direct Debit Information</i>	Statements/advice ISO 20022 XML standards are covered separately
<i>Reject based on DS-05 for the Bank to Customer space</i>	Reject – Customer Payment Status Report (pain.002.001.03)

The use of customer-to-bank and bank-to-customer XML standards is recommended as are these Guidelines.

1.1 Coverage of these SEPA Implementation Guidelines

The purpose of these SEPA Implementation Guidelines, hereafter referred to as the Guidelines, is to provide guidance on the use of the payment initiation Global ISO 20022 XML standards (the ‘pain’ messages) in initiating SEPA B2B Direct Debit payments as defined in the SEPA B2B Direct Debit scheme rulebook and supplemented by processing requirements.

The implementation of the messages and the compliance with these guidelines are strongly recommended.

The Guidelines are fully aligned to the SEPA B2B requirements as defined in the Rulebook and identify message elements needed for initiating SEPA payments while recognising message elements that may be available for use in Additional Optional Services (AOS), as shown below.

Global ISO 20022 XML Message Standards			
Message elements from the ISO messages corresponding to Rulebook requirements	Message elements that are mandatory in the ISO messages or needed for Processing	Message elements from the ISO messages available for use by AOS within an EPC Governance framework	Message elements from ISO messages not applicable to SEPA
EPC Implementation Guidelines for SEPA B2B subset, identifying elements <ul style="list-style-type: none"> - to be used as defined in ISO - to be used with SEPA usage rules (from or completing the Rulebook) 		To be developed and documented by AOS Communities	Not available for use in SEPA payments
SEPA B2B Payments			

Figure 1

These Guidelines define the SEPA B2B Direct Debit Mandatory Subset² of the Global ISO 20022 XML standard that consists of message elements:

- required in the Rulebook as business requirements
- needed for processing by banks, clearing and settlement mechanisms and bank customers

Elements needed for specific national regulatory requirements are not considered in these guidelines. They have to be dealt with at national level without being regarded as an AOS.

These message elements define the **SEPA B2B Direct Debit service** and are denoted by yellow shading in the message structures given in the following chapters. Only these elements are further detailed with relevant SEPA B2B Direct Debit requirements, such as the use of the message element, its components or the values that must be used. Usage rules, for example, may indicate limits on the number of repetitions, or code value restrictions, while format rules may be used to indicate the allowable combinations of components of a message element.

These Guidelines also recognise message elements and the usage rules in the ISO 20022 XML standard that may be available for use in an AOS, subject to a governance framework to be defined by the EPC. The definition and documentation of these message elements are a matter for the AOS communities involved. These message elements are denoted by white shading.

Where there are message elements that do not apply to SEPA payments, these are denoted with red shading in the right-most column of the message structures. To date, few such message elements have been identified.

² The SEPA Business-to-Business Direct Debit Mandatory subset is hereafter known as the SEPA B2B Direct Debit service.

1.2 Use of these Guidelines by the instructing and instructed parties³

- SEPA B2B Direct Debit payments are executed using messages only containing message elements defined as part of the SEPA B2B Direct Debit Subset (shaded yellow in Figure 2).
- Payments that include message elements that are defined and documented by AOS communities (shaded white in Figure 2) are considered as SEPA payments, but not as SEPA B2B Direct Debit payments.
- It is the responsibility of the instructing customer and instructed bank of the message to ensure that message elements defined for use in an AOS are only included in messages sent to AOS community members.
- The instructed bank receiving a message containing AOS-related message elements, but which is not a member of this AOS community, may ignore the information, that is, not use it for processing, nor forward it to the next party in the chain. The instructed bank, however, may reject the message for this reason.

1.3 Notation Conventions

The Guidelines are presented in a similar format than the one used in the ISO 20022 XML standard.

#	SEPA Mult	Message Element	SEPA Core Requirements
1.00	1..1	Message root +Group Header ++Sublevel 1 +++Sublevel 2	<i>SEPA Usage Rule(s)</i> (e.g. Mandatory) <i>SEPA Format Rule(s)</i> ISO Name ISO Definition XML Tag Type (Yellow: Message Element that is part of the SEPA Core Service)
	1..1		XML Tag xs:choice
1.01	1..1	Message root +Group Header ++Sublevel 1 +++Sublevel 2 ++++Sublevel 3	<i>SEPA Rulebook</i> (Attribute used in Rulebook) <i>SEPA Usage Rule(s)</i> (e.g. Only 'SEPA' is allowed.) ISO Name ISO Definition XML Tag Type ISO Length <i>SEPA Length</i> (Yellow: Message Element that is part of the SEPA Core Service)
			SEPA Code restrictions
			SEPA <i>SingleEuroPaymentsArea</i> <i>Payment must be executed following the Single Euro Payments Area scheme.</i>

³ Instructing and instructed parties include CSMs.

1.02	1..1	Message root +Group Header ++Sublevel 1 +++Sublevel 2 ++++Sublevel 3	<i>ISO Name</i> <i>ISO Definition</i> <i>XML Tag</i> <i>Type</i> (White: Message Element that is not part of the Core Service but is available for use in a SEPA AOS)
1.0n	0..1	Message root +Group Header ++Sublevel 1	<i>ISO Name</i> <i>ISO Definition</i> <i>XML Tag</i> <i>Type</i> (Red: Message Element that is not to be used in SEPA Payments)

Figure 2

Where:

- Column 1 indicates the message element Index number specific to these Implementation Guidelines. As a result, the Index numbers differ from the ones used in the relating ISO 20022 Message Definition Report, PDF version.

Components of message elements that are not allowed in SEPA payments or where no SEPA requirements are defined are not displayed in full as the ISO 20022 XML standard applies.

- Column 2 indicates the mandatory or optional status and the number of repetitions defined by the SEPA Core Requirements, e.g.:
 - 0..1 element is optional and may only be present once
 - 0..n element is optional with unlimited repetition
 - 1..1 element is mandatory and must be present exactly once
 - 1..n element is mandatory with unlimited repetition

The displayed SEPA multiplicity may thus differ from the one of the ISO 20022 XML standard. When an element is shaded yellow, possible remaining ISO 20022 occurrences are available for use in an AOS.

Empty elements are not allowed (i.e. a message shall not contain elements without content).

- Column 3 indicates the full path of an element where the last line contains the name of the message element as defined in the ISO 20022 XML standard. When an element contains sub-elements these are indented to the right and noted with a plus sign (+) per level.
- Column 4 specifies in italic characters the SEPA Core Requirements as additional rules to those specified in the ISO 20022 XML standard, which are shown in non-italic characters.
 - When defined in the Rulebook, the attribute is indicated by the attribute name and where applicable, the number, i.e., AT-*nn*. Those message elements are shaded yellow.
 - When the message element relates to inter-bank processing requirements, it is shaded yellow.
 - When the message element specified in the ISO 20022 XML standard is used for SEPA payments without change (regarding the definition and any usage rules), no specific SEPA Core requirements are provided and is shaded yellow.

- When the message element is specified in the ISO 20022 XML standard as optional, but is mandatory in SEPA Core requirements, this is specified as ‘Mandatory’ and is shaded yellow.
- When the message element is not available for use in SEPA payments, this is indicated with red shading. Note that these message elements are similarly not available for use in an AOS.
- The SEPA length is indicated for every message element (if applicable), even if it is the same length as in the ISO 20022 XML standard.

Column 4 may also indicate conditional relationships between components of a message element, for example, either component 1 or component 2 must be present, but not both (indicated, in empty lines without index number, in the column 4 with XML Tag ‘xs:choice’). In such case, the choice is to be made between the two following sub-elements, if both are shaded yellow.

1.4 Character Set

The character set issue centres on the use of the full set of characters in the message elements. Two considerations are:

- While banks and their customers must be allowed to use the character set currently in use at national level,
- Banks and their customers throughout SEPA cannot be required to support the full character set used in SEPA countries.

Therefore:

- The ISO 20022 XML messages allow for the full range of global language requirements (UTF-8)
- Banks and their customers must be able to support the Latin character set commonly used in international communication, as follows:

a b c d e f g h i j k l m n o p q r s t u v w x y z

A B C D E F G H I J K L M N O P Q R S T U V W X Y Z

0 1 2 3 4 5 6 7 8 9

/ - ? : () . , ' +

Space

- References, identifications and identifiers must respect the following:
 - Content is restricted to the Latin character set as defined above
 - Content must not start or end with a ‘/’
 - Content must not contain ‘//’s

However, there may be bilateral or multilateral agreements to support one or more sets of characters beyond the Latin character set referred to above.

1.5 General Message Element Specifications

1.5.1 BIC

The BIC used to identify financial institutions (Agents in the ISO 20022 XML standards) may be either BIC 11 or BIC 8.

1.5.2 Identifier of the Creditor (AT-02)

The Creditor is identified in the scheme by an identifier as defined below. In these Guidelines, this identifier is indicated in the ISO 20022 data element ‘Creditor Scheme Identification’. The creditor can be a legal entity, or an association that is not a legal entity, or a person.

This identifier must be stable over time, to enable the Debtor and the Debtor Bank to come back to the Creditor for Refunds and complaints, and to check the existence of a valid Mandate at the presentation of Collections by the Creditor.

The Creditor identifier has the attributes defined in the Rulebook under AT-02.

This section also applies to AT-18 ‘The identifier of the original Creditor who issued the Mandate’.

The data element is case and space insensitive.

Format Rule:

- Positions 1 and 2 contain the ISO country code
- Positions 3 and 4 contain the check digits
- Positions 5 to 7 contain the Creditor Business Code. When the Creditor Business Code is not used, then the value is set to ‘ZZZ’. The Creditor Business Code cannot contain spaces.
- Positions 8 up to 35 contain the country-specific identifier
- Note: the calculation of the check digit requires the following preliminary steps:
 - Disregard positions 5 to 7
 - Take the country-specific part, positions 8 to 35, and delete all non-alphanumeric characters
 - Add the ISO country code and ‘00’ to the right-hand end
 - Convert letters to digits in accordance with conversion table 1
 - Apply the check character system MOD 97-10 (see ISO 7064)

A = 10	G = 16	M = 22	S = 28	Y = 34
B = 11	H = 17	N = 23	T = 29	Z = 35
C = 12	I = 18	O = 24	U = 30	
D = 13	J = 19	P = 25	V = 31	
E = 14	K = 20	Q = 26	W = 32	
F = 15	L = 21	R = 27	X = 33	

Table 1

1.5.3 Mandate Identification (AT-01 Unique Mandate Reference)

This data element is case insensitive. For example: Mandate Identification 123AAa45678, 123aaA45678, 123aaa45678 and 123AAA45678 shall be considered identical.

1.5.4 SMNDA

In the previous versions of the Guidelines, the acronym ‘SMNDA’ was used to indicate Same Mandate with a **New Debtor Agent**. However, when the Creditor only receives the IBAN it will not always be possible to derive if an account change took place in the same or in another bank. To better accommodate this situation, the definition of the acronym ‘SMNDA’ has been updated to indicate Same Mandate with a **New Debtor Account**.

1.6 Implementation of ISO 20022 XML rules

This document should be read in conjunction with the ISO 20022 XML message standards.

2 RECOMMENDED CUSTOMER-TO-BANK AND BANK-TO-CUSTOMER MESSAGES

The Guidelines prescribe, where relevant and dictated by the Rulebooks, usage rules for the EPC recommended customer-to-bank and bank-to-customer ISO 20022 XML messages. The message elements identified with yellow shading must be provided when mandatory. However, message elements known by the Creditor Bank may be filled in by the Creditor Bank in order to populate the subsequent inter-bank message

The elements shaded yellow specify the SEPA B2B Direct Debit Requirements and are defined in the Rulebook, are required for inter-bank and customer-to-bank processing or are mandatory in the ISO message standards.

2.1 Business Customer to Bank Direct Debit Collection Dataset (DS-03)

2.1.1 Use of Customer Direct Debit Initiation (pain.008.001.02)

The message is used to transport the SEPA B2B Collection instruction from the Creditor to the Creditor Bank.

The message caters for bulk and single direct debit instructions.

#	SEPA Mult	Message Element	SEPA Core Requirements	
		Document	XML Tag Type	Document Document
	1..1	Customer Direct Debit Initiation V02	ISO Name ISO Definition XML Tag Type	Customer Direct Debit Initiation V02 The CustomerDirectDebitInitiation message is sent by the initiating party to the forwarding agent or creditor's agent. It is used to request single or bulk collection(s) of funds from one or various debtor's account(s) to a creditor. CstmrDrctDbtInittn CustomerDirectDebitInitiationV02
1.0	1..1	Customer Direct Debit Initiation V02 +Group Header	ISO Name ISO Definition XML Tag Type	Group Header Set of characteristics shared by all individual transactions included in the message. GrpHdr GroupHeader39
1.1	1..1	Customer Direct Debit Initiation V02 +Group Header ++Message Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Message Identification Point to point reference, assigned by the instructing party and sent to the next party in the chain, to unambiguously identify the message. Usage: The instructing party has to make sure that MessageIdentification is unique per instructed party for a pre-agreed period. MsgId Max35Text 1 .. 35 1 .. 35
1.2	1..1	Customer Direct Debit Initiation V02 +Group Header ++Creation Date Time	ISO Name ISO Definition XML Tag Type	Creation Date Time Date and time at which a (group of) payment instruction(s) was created by the instructing party. CreDtTm ISODateTime
1.3	0..2	Customer Direct Debit Initiation V02 +Group Header ++Authorisation	ISO Name ISO Definition XML Tag Type	Authorisation User identification or any user key that allows to check if the initiating party is allowed to initiate transactions from the account specified in the initiation. Usage: The content is not of a technical nature, but reflects the organisational structure at the initiating side. The authorisation element can typically be used in relay scenarios, payment initiations, payment returns or payment reversals that are initiated on behalf of a different party than the initiating party. Authstn Authorisation1Choice
1.4	1..1	Customer Direct Debit Initiation V02 +Group Header ++Number Of Transactions	ISO Name ISO Definition XML Tag Type Pattern	Number Of Transactions Number of individual transactions contained in the message. NbOfTx Max15NumericText [0-9]{1,15}

#	SEPA Mult	Message Element	SEPA Core Requirements
1.5	0..1	Customer Direct Debit Initiation V02 +Group Header ++Control Sum	<p>SEPA Format Rule(s) <i>The fractional part has a maximum of two digits.</i></p> <p>ISO Name Control Sum</p> <p>ISO Definition Total of all individual amounts included in the message, irrespective of currencies.</p> <p>XML Tag CtrlSum</p> <p>Type DecimalNumber</p> <p>SEPA FractDigits 2</p> <p>TotalDigits 18</p>
1.6	1..1	Customer Direct Debit Initiation V02 +Group Header ++Initiating Party	<p>ISO Name Initiating Party</p> <p>ISO Definition Party that initiates the payment.</p> <p>Usage: This can either be the creditor or a party that initiates the direct debit on behalf of the creditor.</p> <p>XML Tag InitgPty</p> <p>Type PartyIdentification32</p>
1.7	0..1	Customer Direct Debit Initiation V02 +Group Header ++Initiating Party +++Name	<p>SEPA Usage Rule(s) <i>'Name' is limited to 70 characters in length.</i></p> <p>ISO Name Name</p> <p>ISO Definition Name by which a party is known and which is usually used to identify that party.</p> <p>XML Tag Nm</p> <p>Type Max140Text</p> <p>ISO Length 1 .. 140</p> <p>SEPA Length 1 .. 70</p>
1.8	0..1	Customer Direct Debit Initiation V02 +Group Header ++Initiating Party +++Postal Address	<p>ISO Name Postal Address</p> <p>ISO Definition Information that locates and identifies a specific address, as defined by postal services.</p> <p>XML Tag PstlAdr</p> <p>Type PostalAddress6</p>
1.9	0..1	Customer Direct Debit Initiation V02 +Group Header ++Initiating Party +++Identification	<p>ISO Name Identification</p> <p>ISO Definition Unique and unambiguous identification of a party.</p> <p>XML Tag Id</p> <p>Type Party6Choice</p>
	1..1		XML Tag xs:choice
1.10	1..1	Customer Direct Debit Initiation V02 +Group Header ++Initiating Party +++Identification ++++Organisation Identification	<p>SEPA Usage Rule(s) <i>Either 'BIC or BEI' or one occurrence of 'Other' is allowed.</i></p> <p>ISO Name Organisation Identification</p> <p>ISO Definition Unique and unambiguous way to identify an organisation.</p> <p>XML Tag OrgId</p> <p>Type OrganisationIdentification4</p>
1.11	1..1	Customer Direct Debit Initiation V02 +Group Header ++Initiating Party +++Identification ++++Private Identification	<p>SEPA Usage Rule(s) <i>Either 'Date and Place of Birth' or one occurrence of 'Other' is allowed.</i></p> <p>ISO Name Private Identification</p> <p>ISO Definition Unique and unambiguous identification of a person, eg, passport.</p> <p>XML Tag PrvtId</p> <p>Type PersonIdentification5</p>
1.12	0..1	Customer Direct Debit Initiation V02 +Group Header ++Initiating Party +++Country Of Residence	<p>ISO Name Country Of Residence</p> <p>ISO Definition Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.</p> <p>XML Tag CtryOfRes</p> <p>Type CountryCode</p> <p>Pattern [A-Z]{2,2}</p>

#	SEPA Mult	Message Element	SEPA Core Requirements	
1.13	0..1	Customer Direct Debit Initiation V02 +Group Header ++Initiating Party +++Contact Details	ISO Name ISO Definition XML Tag Type	Contact Details Set of elements used to indicate how to contact the party. CtctDtls ContactDetails2
1.14	0..1	Customer Direct Debit Initiation V02 +Group Header ++Forwarding Agent	ISO Name ISO Definition XML Tag Type	Forwarding Agent Financial institution that receives the instruction from the initiating party and forwards it to the next agent in the payment chain for execution. FwdgAgt BranchAndFinancialInstitutionIdentification4
2.0	1..n	Customer Direct Debit Initiation V02 +Payment Information	ISO Name ISO Definition XML Tag Type	Payment Information Set of characteristics that apply to the credit side of the payment transactions included in the direct debit transaction initiation. PmtInf PaymentInstructionInformation4
2.1	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Payment Information Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Payment Information Identification Unique identification, as assigned by a sending party, to unambiguously identify the payment information group within the message. PmtInfId Max35Text 1 .. 35 1 .. 35
2.2	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Payment Method	ISO Name ISO Definition XML Tag Type	Payment Method Specifies the means of payment that will be used to move the amount of money. PmtMtd PaymentMethod2Code
2.3	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Batch Booking	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>If present and contains 'true', batch booking is requested. If present and contains 'false', booking per transaction is requested. If element is not present, pre-agreed customer-to-bank conditions apply.</i> Batch Booking Identifies whether a single entry per individual transaction or a batch entry for the sum of the amounts of all transactions within the group of a message is requested. Usage: Batch booking is used to request and not order a possible batch booking. BtchBookg BatchBookingIndicator
2.4	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Number Of Transactions	ISO Name ISO Definition XML Tag Type Pattern	Number Of Transactions Number of individual transactions contained in the payment information group. NbOfTx Max15NumericText [0-9]{1,15}
2.5	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Control Sum	SEPA Format Rule(s) ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits	<i>The fractional part has a maximum of two digits.</i> Control Sum Total of all individual amounts included in the group, irrespective of currencies. CtrlSum DecimalNumber 2 18

#	SEPA Mult	Message Element	SEPA Core Requirements
2.6	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Payment Type Information	<i>SEPA Usage Rule(s)</i> Mandatory ISO Name Payment Type Information ISO Definition Set of elements used to further specify the type of transaction. XML Tag PmtTpInf Type PaymentTypeInformation20
2.7	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Payment Type Information +++Instruction Priority	ISO Name Instruction Priority ISO Definition Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the instruction. XML Tag InstrPrty Type Priority2Code
2.8	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Payment Type Information +++Service Level	<i>SEPA Usage Rule(s)</i> Mandatory ISO Name Service Level ISO Definition Agreement under which or rules under which the transaction should be processed. XML Tag SvcLvl Type ServiceLevel8Choice
	1..1		XML Tag xs:choice
2.9	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Payment Type Information +++Service Level ++++Code	<i>SEPA Rulebook</i> AT-20 The identification code of the B2B Scheme. <i>SEPA Usage Rule(s)</i> Only 'SEPA' is allowed. ISO Name Code ISO Definition Specifies a pre-agreed service or level of service between the parties, as published in an external service level code list. XML Tag Cd Type ExternalServiceLevel1Code ISO Length 1 .. 4 SEPA Length 1 .. 4
			SEPA Code Restrictions
			SEPA <i>SingleEuroPaymentsArea</i> Payment must be executed following the Single Euro Payments Area scheme.
2.10	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Payment Type Information +++Service Level ++++Proprietary	ISO Name Proprietary ISO Definition Specifies a pre-agreed service or level of service between the parties, as a proprietary code. XML Tag Prtry Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35
2.11	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Payment Type Information +++Local Instrument	<i>SEPA Usage Rule(s)</i> Mandatory ISO Name Local Instrument ISO Definition User community specific instrument. Usage: This element is used to specify a local instrument, local clearing option and/or further qualify the service or service level. XML Tag LclInstrm Type LocalInstrument2Choice
	1..1		XML Tag xs:choice

#	SEPA Mult	Message Element	SEPA Core Requirements
2.12	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Payment Type Information +++Local Instrument ++++Code	<p>SEPA Rulebook AT-20 The identification code of the B2B Scheme.</p> <p>SEPA Usage Rule(s) Only 'B2B' is allowed. 'B2B' is used to indicate a B2B direct debit. The mixing of different Local Instrument values is not allowed in the same message.</p> <p>ISO Name Code</p> <p>ISO Definition Specifies the local instrument, as published in an external local instrument code list.</p> <p>XML Tag Cd</p> <p>Type ExternalLocalInstrument1Code</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p> <p>SEPA Code Restrictions</p> <p>B2B SEPA Business to Business Direct Debit Transaction is related to SEPA business to business direct debit. Region: EMEA ISO Country Code: SEPA ISO Currency Code: EUR Payment System: PEACH cDD/CT/ Both/ Other: DD Corp2Bk, Bk2Bk, or Both:</p>
2.13	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Payment Type Information +++Local Instrument ++++Proprietary	<p>ISO Name Proprietary</p> <p>ISO Definition Specifies the local instrument, as a proprietary code.</p> <p>XML Tag Prtry</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>
2.14	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Payment Type Information +++Sequence Type	<p>SEPA Rulebook AT-21 Transaction / Sequence Type.</p> <p>SEPA Usage Rule(s) Mandatory If 'Amendment Indicator' is 'true', and 'Original Debtor Account' is set to 'SMNDA', this message element indicates either 'FRST', 'RCUR', 'FNAL' or 'OOFF' (all four codes allowed, no restrictions).</p> <p>ISO Name Sequence Type</p> <p>ISO Definition Identifies the direct debit sequence, such as first, recurrent, final or one-off.</p> <p>XML Tag SeqTp</p> <p>Type SequenceType1Code</p>
2.15	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Payment Type Information +++Category Purpose	<p>SEPA Rulebook AT-59 Category purpose of the Collection.</p> <p>SEPA Usage Rule(s) Depending on the agreement between the Creditor and the Creditor Bank, 'Category Purpose' may be forwarded to the Debtor Bank.</p> <p>ISO Name Category Purpose</p> <p>ISO Definition Specifies the high level purpose of the instruction based on a set of pre-defined categories. Usage: This is used by the initiating party to provide information concerning the processing of the payment. It is likely to trigger special processing by any of the agents involved in the payment chain.</p> <p>XML Tag Ctgypurp</p> <p>Type CategoryPurpose1Choice</p>

#	SEPA Mult	Message Element	SEPA Core Requirements	
2.16	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Requested Collection Date	<i>SEPA Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-11 Due Date of the Collection.</i> Requested Collection Date Date and time at which the creditor requests that the amount of money is to be collected from the debtor. ReqdColltnDt ISODate
2.17	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor	ISO Name ISO Definition XML Tag Type	Creditor Party to which an amount of money is due. Cdtr PartyIdentification32
2.18	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor +++Name	<i>SEPA Rulebook</i> <i>SEPA Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type ISO Length <i>SEPA Length</i>	<i>AT-03 Name of the Creditor.</i> <i>Mandatory</i> <i>'Name' is limited to 70 characters in length.</i> Name Name by which a party is known and which is usually used to identify that party. Nm Max140Text 1 .. 140 1 .. 70
2.19	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor +++Postal Address	<i>SEPA Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-05 Address of the Creditor.</i> Postal Address Information that locates and identifies a specific address, as defined by postal services. PstlAdr PostalAddress6
2.20	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor +++Postal Address ++++Address Type	ISO Name ISO Definition XML Tag Type	Address Type Identifies the nature of the postal address. AdrTp AddressType2Code
2.21	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor +++Postal Address ++++Department	ISO Name ISO Definition XML Tag Type ISO Length <i>SEPA Length</i>	Department Identification of a division of a large organisation or building. Dept Max70Text 1 .. 70 1 .. 70
2.22	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor +++Postal Address ++++Sub Department	ISO Name ISO Definition XML Tag Type ISO Length <i>SEPA Length</i>	Sub Department Identification of a sub-division of a large organisation or building. SubDept Max70Text 1 .. 70 1 .. 70
2.23	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor +++Postal Address ++++Street Name	ISO Name ISO Definition XML Tag Type ISO Length <i>SEPA Length</i>	Street Name Name of a street or thoroughfare. StrtNm Max70Text 1 .. 70 1 .. 70
2.24	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor +++Postal Address ++++Building Number	ISO Name ISO Definition XML Tag Type ISO Length <i>SEPA Length</i>	Building Number Number that identifies the position of a building on a street. BldgNb Max16Text 1 .. 16 1 .. 16

#	SEPA Mult	Message Element	SEPA Core Requirements	
2.25	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor +++Postal Address ++++Post Code	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Post Code Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail. PstCd Max16Text 1 .. 16 1 .. 16
2.26	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor +++Postal Address ++++Town Name	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Town Name Name of a built-up area, with defined boundaries, and a local government. TwnNm Max35Text 1 .. 35 1 .. 35
2.27	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor +++Postal Address ++++Country Sub Division	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Country Sub Division Identifies a subdivision of a country such as state, region, county. CtrySubDvsn Max35Text 1 .. 35 1 .. 35
2.28	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor +++Postal Address ++++Country	ISO Name ISO Definition XML Tag Type Pattern	Country Nation with its own government. Ctry CountryCode [A-Z]{2,2}
2.29	0..2	Customer Direct Debit Initiation V02 +Payment Information ++Creditor +++Postal Address ++++Address Line	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>Only two occurrences are allowed.</i> Address Line Information that locates and identifies a specific address, as defined by postal services, presented in free format text. AdrLine Max70Text 1 .. 70 1 .. 70
2.30	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor +++Identification	ISO Name ISO Definition XML Tag Type	Identification Unique and unambiguous identification of a party. Id Party6Choice
2.31	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor +++Country Of Residence	ISO Name ISO Definition XML Tag Type Pattern	Country Of Residence Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed. CtryOfRes CountryCode [A-Z]{2,2}
2.32	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor +++Contact Details	ISO Name ISO Definition XML Tag Type	Contact Details Set of elements used to indicate how to contact the party. CtctDtls ContactDetails2

#	SEPA Mult	Message Element	SEPA Core Requirements
2.33	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor Account	<p>SEPA Rulebook AT-04 Account Number of the Creditor.</p> <p>ISO Name Creditor Account</p> <p>ISO Definition Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction.</p> <p>XML Tag CdtrAcct</p> <p>Type CashAccount16</p>
2.34	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor Account +++Identification	<p>SEPA Usage Rule(s) Only IBAN is allowed.</p> <p>ISO Name Identification</p> <p>ISO Definition Unique and unambiguous identification for the account between the account owner and the account servicer.</p> <p>XML Tag Id</p> <p>Type AccountIdentification4Choice</p>
2.35	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor Account +++Type	<p>ISO Name Type</p> <p>ISO Definition Specifies the nature, or use of the account.</p> <p>XML Tag Tp</p> <p>Type CashAccountType2</p>
2.36	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor Account +++Currency	<p>ISO Name Currency</p> <p>ISO Definition Identification of the currency in which the account is held.</p> <p>Usage: Currency should only be used in case one and the same account number covers several currencies and the initiating party needs to identify which currency needs to be used for settlement on the account.</p> <p>XML Tag Ccy</p> <p>Type ActiveOrHistoricCurrencyCode</p> <p>Pattern [A-Z]{3,3}</p>
2.37	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor Account +++Name	<p>ISO Name Name</p> <p>ISO Definition Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account.</p> <p>Usage: The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number.</p> <p>XML Tag Nm</p> <p>Type Max70Text</p> <p>ISO Length 1 .. 70</p> <p>SEPA Length 1 .. 70</p>
2.38	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor Agent	<p>ISO Name Creditor Agent</p> <p>ISO Definition Financial institution servicing an account for the creditor.</p> <p>XML Tag CdtrAgt</p> <p>Type BranchAndFinancialInstitutionIdentification4</p>
2.39	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor Agent +++Financial Institution Identification	<p>SEPA Usage Rule(s) Either BIC or 'Other/Identification' must be used.</p> <p>ISO Name Financial Institution Identification</p> <p>ISO Definition Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.</p> <p>XML Tag FinInstnId</p> <p>Type FinancialInstitutionIdentification7</p>

#	SEPA Mult	Message Element	SEPA Core Requirements	
2.40	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor Agent +++Financial Institution Identification ++++BIC	<i>SEPA Rulebook</i>	<i>AT-12 BIC of the Creditor bank. The BIC is mandatory for non-EU/non-EEA cross-border SEPA transactions.</i>
			ISO Name	BIC
			ISO Definition	Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".
			XML Tag	BIC
			Type	BICIdentifier
			Pattern	[A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}
2.41	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor Agent +++Financial Institution Identification ++++Clearing System Member Identification	ISO Name	Clearing System Member Identification
			ISO Definition	Information used to identify a member within a clearing system.
			XML Tag	ClrSysMmbId
			Type	ClearingSystemMemberIdentification2
2.42	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor Agent +++Financial Institution Identification ++++Name	ISO Name	Name
			ISO Definition	Name by which an agent is known and which is usually used to identify that agent.
			XML Tag	Nm
			Type	Max140Text
			ISO Length	1 .. 140
			SEPA Length	1 .. 140
2.43	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor Agent +++Financial Institution Identification ++++Postal Address	ISO Name	Postal Address
			ISO Definition	Information that locates and identifies a specific address, as defined by postal services.
			XML Tag	PstlAdr
			Type	PostalAddress6
2.44	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor Agent +++Financial Institution Identification ++++Other	ISO Name	Other
			ISO Definition	Unique identification of an agent, as assigned by an institution, using an identification scheme.
			XML Tag	Othr
			Type	GenericFinancialIdentification1
2.45	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor Agent +++Financial Institution Identification ++++Other +++++Identification	<i>SEPA Usage Rule(s)</i>	<i>Only 'NOTPROVIDED' is allowed.</i>
			ISO Name	Identification
			ISO Definition	Unique and unambiguous identification of a person.
			XML Tag	Id
			Type	Max35Text
			ISO Length	1 .. 35
			SEPA Length	1 .. 35
2.46	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor Agent +++Financial Institution Identification ++++Other +++++Scheme Name	ISO Name	Scheme Name
			ISO Definition	Name of the identification scheme.
			XML Tag	SchmeNm
			Type	FinancialIdentificationSchemeName1Choice
2.47	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor Agent +++Financial Institution Identification ++++Other +++++Issuer	ISO Name	Issuer
			ISO Definition	Entity that assigns the identification.
			XML Tag	Issr
			Type	Max35Text
			ISO Length	1 .. 35
			SEPA Length	1 .. 35

#	SEPA Mult	Message Element	SEPA Core Requirements	
2.48	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor Agent +++Branch Identification	ISO Name ISO Definition XML Tag Type	Branch Identification Identifies a specific branch of a financial institution. Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level. BrnchId BranchData2
2.49	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor Agent Account	ISO Name ISO Definition XML Tag Type	Creditor Agent Account Unambiguous identification of the account of the creditor agent at its servicing agent in the payment chain. CdtrAgtAcct CashAccount16
2.50	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Ultimate Creditor	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>This data element may be present either at 'Payment Information' or at 'Direct Debit Transaction Information' level.</i> Ultimate Creditor Ultimate party to which an amount of money is due. UltmtCdtr PartyIdentification32
2.51	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Ultimate Creditor +++Name	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>AT-38 Name of the Creditor Reference Party. 'Name' is limited to 70 characters in length.</i> Name Name by which a party is known and which is usually used to identify that party. Nm Max140Text 1 .. 140 1 .. 70
2.52	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Ultimate Creditor +++Postal Address	ISO Name ISO Definition XML Tag Type	Postal Address Information that locates and identifies a specific address, as defined by postal services. PstlAdr PostalAddress6
2.53	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Ultimate Creditor +++Identification	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-39 Identification code of the Creditor Reference Party.</i> Identification Unique and unambiguous identification of a party. Id Party6Choice
	1..1		XML Tag	xs:choice
2.54	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Ultimate Creditor +++Identification ++++Organisation Identification	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>Either 'BIC or BEI' or one occurrence of 'Other' is allowed.</i> Organisation Identification Unique and unambiguous way to identify an organisation. OrgId OrganisationIdentification4
2.55	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Ultimate Creditor +++Identification ++++Private Identification	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>Either 'Date and Place of Birth' or one occurrence of 'Other' is allowed.</i> Private Identification Unique and unambiguous identification of a person, eg, passport. PrvtId PersonIdentification5

#	SEPA Mult	Message Element	SEPA Core Requirements	
2.56	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Ultimate Creditor +++Country Of Residence	ISO Name ISO Definition XML Tag Type Pattern	Country Of Residence Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed. CtryOfRes CountryCode [A-Z]{2,2}
2.57	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Ultimate Creditor +++Contact Details	ISO Name ISO Definition XML Tag Type	Contact Details Set of elements used to indicate how to contact the party. CtctDtls ContactDetails2
2.58	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Charge Bearer	ISO Name ISO Definition XML Tag Type	<i>SEPA Usage Rule(s)</i> Only 'SLEV' is allowed. It is recommended that this element be specified at 'Payment Information' level. Charge Bearer Specifies which party/parties will bear the charges associated with the processing of the payment transaction. ChrgBr ChargeBearerType1Code
			<i>SEPA Code Restrictions</i>	
			<i>SLEV</i>	<i>FollowingServiceLevel</i> Charges are to be applied following the rules agreed in the service level and/or scheme.
2.59	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Charges Account	ISO Name ISO Definition XML Tag Type	Charges Account Account used to process charges associated with a transaction. Usage: Charges account should be used when charges have to be booked to an account different from the account identified in debtor's account. ChrgsAcct CashAccount16
2.60	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Charges Account Agent	ISO Name ISO Definition XML Tag Type	Charges Account Agent Agent that services a charges account. Usage: Charges account agent should only be used when the charges account agent is different from the creditor agent. ChrgsAcctAgt BranchAndFinancialInstitutionIdentification4
2.61	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor Scheme Identification	ISO Name ISO Definition XML Tag Type	<i>SEPA Usage Rule(s)</i> It is recommended that all transactions within the same 'Payment Information' block have the same 'Creditor Scheme Identification'. This data element must be present at either 'Payment Information' or 'Direct Debit Transaction' level. Creditor Scheme Identification Credit party that signs the mandate. CdtrSchmEld PartyIdentification32
2.62	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor Scheme Identification +++Name	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Name Name by which a party is known and which is usually used to identify that party. Nm Max140Text 1 .. 140 1 .. 140

#	SEPA Mult	Message Element	SEPA Core Requirements	
2.63	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor Scheme Identification +++Postal Address	ISO Name ISO Definition XML Tag Type	Postal Address Information that locates and identifies a specific address, as defined by postal services. PstAdr PostalAddress6
2.64	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor Scheme Identification +++Identification	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-02 Identifier of the Creditor. Mandatory Identification Unique and unambiguous identification of a party. Id Party6Choice
	1..1		XML Tag	xs:choice
2.65	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor Scheme Identification +++Identification ++++Organisation Identification	ISO Name ISO Definition XML Tag Type	Organisation Identification Unique and unambiguous way to identify an organisation. OrgId OrganisationIdentification4
2.66	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor Scheme Identification +++Identification ++++Private Identification	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Private Identification is used to identify either an organisation or a private person. Private Identification Unique and unambiguous identification of a person, eg, passport. PrvtId PersonIdentification5
2.67	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor Scheme Identification +++Identification ++++Private Identification +++++Date And Place Of Birth	ISO Name ISO Definition XML Tag Type	Date And Place Of Birth Date and place of birth of a person. DtAndPlcOfBirth DateAndPlaceOfBirth
2.68	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor Scheme Identification +++Identification ++++Private Identification +++++Other	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Only one occurrence of 'Other' is allowed, and no other sub-elements are allowed. 'Identification' must be used with an identifier described in General Message Element Specifications, Chapter 1.5.2. 'Proprietary' under 'Scheme Name' must specify 'SEPA'. Other Unique identification of a person, as assigned by an institution, using an identification scheme. Othr GenericPersonIdentification1
2.69	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor Scheme Identification +++Country Of Residence	ISO Name ISO Definition XML Tag Type Pattern	Country Of Residence Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed. CtryOfRes CountryCode [A-Z]{2,2}
2.70	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Creditor Scheme Identification +++Contact Details	ISO Name ISO Definition XML Tag Type	Contact Details Set of elements used to indicate how to contact the party. CtctDtls ContactDetails2

#	SEPA Mult	Message Element	SEPA Core Requirements	
2.71	1..n	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information	ISO Name ISO Definition XML Tag Type	Direct Debit Transaction Information Set of elements used to provide information on the individual transaction(s) included in the message. DrctDbtTxInf DirectDebitTransactionInformation9
2.72	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Payment Identification	ISO Name ISO Definition XML Tag Type	Payment Identification Set of elements used to reference a payment instruction. PmtId PaymentIdentification1
2.73	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Payment Identification ++++Instruction Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Instruction Identification Unique identification as assigned by an instructing party for an instructed party to unambiguously identify the instruction. Usage: the instruction identification is a point to point reference that can be used between the instructing party and the instructed party to refer to the individual instruction. It can be included in several messages related to the instruction. InstrId Max35Text 1 .. 35 1 .. 35
2.74	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Payment Identification ++++End To End Identification	SEPA Rulebook ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>AT-10 Creditor's reference of the direct debit Collection.</i> End To End Identification Unique identification assigned by the initiating party to unambiguously identify the transaction. This identification is passed on, unchanged, throughout the entire end-to-end chain. Usage: The end-to-end identification can be used for reconciliation or to link tasks relating to the transaction. It can be included in several messages related to the transaction. EndToEndId Max35Text 1 .. 35 1 .. 35
2.75	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Payment Type Information	ISO Name ISO Definition XML Tag Type	Payment Type Information Set of elements used to further specify the type of transaction. PmtTpInf PaymentTypeInformation20

#	SEPA Mult	Message Element	SEPA Core Requirements
2.76	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Instructed Amount	<p>SEPA Rulebook AT-06 Amount of the Collection in Euro. SEPA Usage Rule(s) Only 'EUR' is allowed. Amount must be 0.01 or more and 999999999.99 or less. SEPA Format Rule(s) The fractional part has a maximum of two digits.</p> <p>ISO Name Instructed Amount ISO Definition Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.</p> <p>XML Tag InstdAmt Type ActiveOrHistoricCurrencyAndAmount SEPA FractDigits 2 TotalDigits 18 SEPA Inclusive 0.01 .. 999999999.99</p>
2.77	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Charge Bearer	<p>SEPA Usage Rule(s) Only 'SLEV' is allowed. ISO Name Charge Bearer ISO Definition Specifies which party/parties will bear the charges associated with the processing of the payment transaction.</p> <p>XML Tag ChrgBr Type ChargeBearerType1Code</p> <p>SEPA Code Restrictions</p> <p>SLEV FollowingServiceLevel Charges are to be applied following the rules agreed in the service level and/or scheme.</p>
2.78	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction	<p>SEPA Usage Rule(s) Mandatory ISO Name Direct Debit Transaction ISO Definition Set of elements providing information specific to the direct debit mandate.</p> <p>XML Tag DrctDbtTx Type DirectDebitTransaction6</p>
2.79	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Mandate Related Information	<p>SEPA Usage Rule(s) Mandatory ISO Name Mandate Related Information ISO Definition Set of elements used to provide further details of the direct debit mandate signed between the creditor and the debtor.</p> <p>XML Tag MndtRltdInf Type MandateRelatedInformation6</p>
2.80	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Mandate Related Information +++++Mandate Identification	<p>SEPA Rulebook AT-01 Unique Mandate Reference. SEPA Usage Rule(s) Mandatory ISO Name Mandate Identification ISO Definition Unique identification, as assigned by the creditor, to unambiguously identify the mandate.</p> <p>XML Tag MndtId Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35</p>
2.81	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Mandate Related Information +++++Date Of Signature	<p>SEPA Rulebook AT-25 Date of Signing of the Mandate. SEPA Usage Rule(s) Mandatory ISO Name Date Of Signature ISO Definition Date on which the direct debit mandate has been signed by the debtor.</p> <p>XML Tag DtOfSgnt Type ISODate</p>

#	SEPA Mult	Message Element	SEPA Core Requirements	
2.82	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Mandate Related Information +++++Amendment Indicator	ISO Name ISO Definition XML Tag Type	Amendment Indicator Indicator notifying whether the underlying mandate is amended or not. AmdmntInd TrueFalseIndicator
2.83	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Mandate Related Information +++++Amendment Information Details	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-24 Reason for Amendment of the Mandate. The reason from the Rulebook is indicated by using the following message sub-elements.</i> <i>Mandatory if 'Amendment Indicator' is 'true'.</i> Amendment Information Details List of mandate elements that have been modified. AmdmntInfDtls AmendmentInformationDetails6
2.84	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Mandate Related Information +++++Amendment Information Details ++++++Original Mandate Identification	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>AT-19 Unique Mandate Reference as given by the Original Creditor who issued the Mandate.</i> <i>Mandatory if changes occur in 'Mandate Identification', otherwise not to be used.</i> Original Mandate Identification Unique identification, as assigned by the creditor, to unambiguously identify the original mandate. OrgnlMndtId Max35Text 1 .. 35 1 .. 35
2.85	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Mandate Related Information +++++Amendment Information Details ++++++Original Creditor Scheme Identification	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>Mandatory if changes occur in 'Creditor Scheme Identification' ('Name' and/or 'Identification'), otherwise not to be used.</i> Original Creditor Scheme Identification Original creditor scheme identification that has been modified. OrgnlCdtrSchmeId PartyIdentification32
2.86	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Mandate Related Information +++++Amendment Information Details ++++++Original Creditor Scheme Identification +++++++Name	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>Original AT-03 Name of the Creditor.</i> <i>If present the new 'Name' must be specified under 'Creditor'.</i> <i>'Name' is limited to 70 characters in length.</i> Name Name by which a party is known and which is usually used to identify that party. Nm Max140Text 1 .. 140 1 .. 70
2.87	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Mandate Related Information +++++Amendment Information Details ++++++Original Creditor Scheme Identification +++++++Postal Address	ISO Name ISO Definition XML Tag Type	Postal Address Information that locates and identifies a specific address, as defined by postal services. PstlAdr PostalAddress6

#	SEPA Mult	Message Element	SEPA Core Requirements	
2.88	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Mandate Related Information +++++Amendment Information Details ++++++Original Creditor Scheme Identification +++++++Identification	<i>SEPA Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-18 Identifier of the original Creditor who issued the Mandate.</i> Identification Unique and unambiguous identification of a party. Id Party6Choice
	1..1		XML Tag	xs:choice
2.89	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Mandate Related Information +++++Amendment Information Details ++++++Original Creditor Scheme Identification +++++++Identification +++++++Organisation Identification	ISO Name ISO Definition XML Tag Type	Organisation Identification Unique and unambiguous way to identify an organisation. OrgId OrganisationIdentification4
2.90	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Mandate Related Information +++++Amendment Information Details ++++++Original Creditor Scheme Identification +++++++Identification +++++++Private Identification	<i>SEPA Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>Private Identification is used to identify either an organisation or a private person.</i> Private Identification Unique and unambiguous identification of a person, eg, passport. PrvtId PersonIdentification5
2.91	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Mandate Related Information +++++Amendment Information Details ++++++Original Creditor Scheme Identification +++++++Identification +++++++Private Identification +++++++Date And Place Of Birth	ISO Name ISO Definition XML Tag Type	Date And Place Of Birth Date and place of birth of a person. DtAndPlcOfBirth DateAndPlaceOfBirth
2.92	0..n	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Mandate Related Information +++++Amendment Information Details ++++++Original Creditor Scheme Identification +++++++Identification +++++++Private Identification +++++++Other	<i>SEPA Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>Only one occurrence of 'Other' is allowed, and no other sub-elements are allowed. 'Identification' must be used with an identifier described in General Message Element Specifications, Chapter 1.5.2. 'Proprietary' under 'Scheme Name' must specify 'SEPA'.</i> Other Unique identification of a person, as assigned by an institution, using an identification scheme. Oth GenericPersonIdentification1

#	SEPA Mult	Message Element	SEPA Core Requirements	
2.93	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Mandate Related Information +++++Amendment Information Details ++++++Original Creditor Scheme Identification +++++++Country Of Residence	ISO Name ISO Definition XML Tag Type Pattern	Country Of Residence Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed. CtryOfRes CountryCode [A-Z]{2,2}
2.94	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Mandate Related Information +++++Amendment Information Details ++++++Original Creditor Scheme Identification +++++++Contact Details	ISO Name ISO Definition XML Tag Type	Contact Details Set of elements used to indicate how to contact the party. CtctDtls ContactDetails2
2.95	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Mandate Related Information +++++Amendment Information Details ++++++Original Creditor Agent	ISO Name ISO Definition XML Tag Type	Original Creditor Agent Original creditor agent that has been modified. OrgnCdtrAgt BranchAndFinancialInstitutionIdentification4
2.96	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Mandate Related Information +++++Amendment Information Details ++++++Original Creditor Agent Account	ISO Name ISO Definition XML Tag Type	Original Creditor Agent Account Original creditor agent account that has been modified. OrgnCdtrAgtAcct CashAccount16
2.97	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Mandate Related Information +++++Amendment Information Details ++++++Original Debtor	ISO Name ISO Definition XML Tag Type	Original Debtor Original debtor that has been modified. OrgnDbtr PartyIdentification32
2.98	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Mandate Related Information +++++Amendment Information Details ++++++Original Debtor Account	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>To use 'Identification' under 'Other' under 'Identification' with code 'SMNDA' to indicate same mandate with new Debtor Account. Or In case of an account change within the same bank, IBAN is allowed.</i> Original Debtor Account Original debtor account that has been modified. OrgnDbtrAcct CashAccount16
2.99	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Mandate Related Information +++++Amendment Information Details ++++++Original Debtor Agent	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>Not to be used if element 'Original Debtor Account' is populated with 'SMNDA'.</i> Original Debtor Agent Original debtor agent that has been modified. OrgnDbtrAgt BranchAndFinancialInstitutionIdentification4

#	SEPA Mult	Message Element	SEPA Core Requirements	
2.100	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Mandate Related Information +++++Amendment Information Details ++++++Original Debtor Agent Account	ISO Name ISO Definition XML Tag Type	Original Debtor Agent Account Original debtor agent account that has been modified. OrgnDbtrAgtAcct CashAccount16
2.101	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Mandate Related Information +++++Amendment Information Details ++++++Original Final Collection Date	ISO Name ISO Definition XML Tag Type	Original Final Collection Date Original final collection date that has been modified. OrgnFnlColltnDt ISODate
2.102	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Mandate Related Information +++++Amendment Information Details ++++++Original Frequency	ISO Name ISO Definition XML Tag Type	Original Frequency Original frequency that has been modified. OrgnFrqcy Frequency1Code
2.103	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Mandate Related Information +++++Electronic Signature	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	AT-16 Placeholder for the Electronic Signature Data, if applicable. AT-17 Type of Mandate (paper, e-Mandate). AT-60 Reference of the validation made by the Debtor Bank (if present in DS-03). If the direct debit is based on an EPC electronic mandate, this data element must contain AT-60 which is the reference to the Mandate Acceptance Report made by the Debtor Bank. This data element is not to be used if the mandate is a paper mandate. Electronic Signature Additional security provisions, such as a digital signature, as provided by the debtor. ElectrncSgntr Max1025Text 1 .. 1025 1 .. 1025
2.104	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Mandate Related Information +++++First Collection Date	ISO Name ISO Definition XML Tag Type	First Collection Date Date of the first collection of a direct debit as per the mandate. FrstColltnDt ISODate
2.105	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Mandate Related Information +++++Final Collection Date	ISO Name ISO Definition XML Tag Type	Final Collection Date Date of the final collection of a direct debit as per the mandate. FnlColltnDt ISODate
2.106	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Mandate Related Information +++++Frequency	ISO Name ISO Definition XML Tag Type	Frequency Regularity with which direct debit instructions are to be created and processed. Frqcy Frequency1Code

#	SEPA Mult	Message Element	SEPA Core Requirements
2.107	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Creditor Scheme Identification	<i>SEPA Usage Rule(s)</i> It is recommended that all transactions within the same 'Payment Information' block have the same 'Creditor Scheme Identification'. This data element must be present at either 'Payment Information' or 'Direct Debit Transaction' level. ISO Name Creditor Scheme Identification ISO Definition Credit party that signs the mandate. XML Tag CctrSchmeld Type PartyIdentification32
2.108	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Creditor Scheme Identification +++++Name	ISO Name Name ISO Definition Name by which a party is known and which is usually used to identify that party. XML Tag Nm Type Max140Text ISO Length 1 .. 140 SEPA Length 1 .. 140
2.109	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Creditor Scheme Identification +++++Postal Address	ISO Name Postal Address ISO Definition Information that locates and identifies a specific address, as defined by postal services. XML Tag PstlAdr Type PostalAddress6
2.110	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Creditor Scheme Identification +++++Identification	<i>SEPA Rulebook</i> AT-02 Identifier of the Creditor. <i>SEPA Usage Rule(s)</i> Mandatory ISO Name Identification ISO Definition Unique and unambiguous identification of a party. XML Tag Id Type Party6Choice
	1..1		XML Tag xs:choice
2.111	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Creditor Scheme Identification +++++Identification +++++Organisation Identification	ISO Name Organisation Identification ISO Definition Unique and unambiguous way to identify an organisation. XML Tag OrgId Type OrganisationIdentification4
2.112	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Creditor Scheme Identification +++++Identification +++++Private Identification	<i>SEPA Usage Rule(s)</i> Private Identification is used to identify either an organisation or a private person. ISO Name Private Identification ISO Definition Unique and unambiguous identification of a person, eg, passport. XML Tag PrvtId Type PersonIdentification5
2.113	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Creditor Scheme Identification +++++Identification +++++Private Identification +++++Date And Place Of Birth	ISO Name Date And Place Of Birth ISO Definition Date and place of birth of a person. XML Tag DtAndPlcOfBirth Type DateAndPlaceOfBirth

#	SEPA Mult	Message Element	SEPA Core Requirements
2.114	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Creditor Scheme Identification +++++Identification ++++++Private Identification +++++++Other	<p>SEPA Usage Rule(s) Only one occurrence of 'Other' is allowed, and no other sub-elements are allowed. 'Identification' must be used with an identifier described in General Message Element Specifications, Chapter 1.5.2. 'Proprietary' under 'Scheme Name' must specify 'SEPA'.</p> <p>ISO Name Other ISO Definition Unique identification of a person, as assigned by an institution, using an identification scheme. XML Tag Othr Type GenericPersonIdentification1</p>
2.115	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Creditor Scheme Identification +++++Country Of Residence	<p>ISO Name Country Of Residence ISO Definition Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed. XML Tag CtryOfRes Type CountryCode Pattern [A-Z]{2,2}</p>
2.116	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Creditor Scheme Identification +++++Contact Details	<p>ISO Name Contact Details ISO Definition Set of elements used to indicate how to contact the party. XML Tag CtctDtls Type ContactDetails2</p>
2.117	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Pre Notification Identification	<p>ISO Name Pre Notification Identification ISO Definition Unique and unambiguous identification of the pre-notification which is sent separately from the direct debit instruction. Usage: The direct debit pre-notification is used to reconcile separately sent collection information with the direct debit transaction information. XML Tag PreNtfctnId Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35</p>
2.118	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Pre Notification Date	<p>ISO Name Pre Notification Date ISO Definition Date on which the creditor notifies the debtor about the amount and date on which the direct debit instruction will be presented to the debtor's agent. XML Tag PreNtfctnDt Type ISODate</p>
2.119	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Ultimate Creditor	<p>SEPA Usage Rule(s) This data element may be present either at 'Payment Information' or at 'Direct Debit Transaction Information' level.</p> <p>ISO Name Ultimate Creditor ISO Definition Ultimate party to which an amount of money is due. XML Tag UltmtCdtr Type PartyIdentification32</p>

#	SEPA Mult	Message Element	SEPA Core Requirements
2.120	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Ultimate Creditor ++++Name	<i>SEPA Rulebook</i> AT-38 Name of the Creditor Reference Party. <i>SEPA Usage Rule(s)</i> 'Name' is limited to 70 characters in length. ISO Name Name ISO Definition Name by which a party is known and which is usually used to identify that party. XML Tag Nm Type Max140Text ISO Length 1 .. 140 SEPA Length 1 .. 70
2.121	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Ultimate Creditor ++++Postal Address	ISO Name Postal Address ISO Definition Information that locates and identifies a specific address, as defined by postal services. XML Tag PstlAdr Type PostalAddress6
2.122	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Ultimate Creditor ++++Identification	<i>SEPA Rulebook</i> AT-39 Identification code of the Creditor Reference Party. ISO Name Identification ISO Definition Unique and unambiguous identification of a party. XML Tag Id Type Party6Choice
	1..1		XML Tag xs:choice
2.123	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Ultimate Creditor ++++Identification +++++Organisation Identification	<i>SEPA Usage Rule(s)</i> Either 'BIC or BEI' or one occurrence of 'Other' is allowed. ISO Name Organisation Identification ISO Definition Unique and unambiguous way to identify an organisation. XML Tag OrgId Type OrganisationIdentification4
2.124	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Ultimate Creditor ++++Identification +++++Private Identification	<i>SEPA Usage Rule(s)</i> Either 'Date and Place of Birth' or one occurrence of 'Other' is allowed. ISO Name Private Identification ISO Definition Unique and unambiguous identification of a person, eg, passport. XML Tag PrvtId Type PersonIdentification5
2.125	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Ultimate Creditor ++++Country Of Residence	ISO Name Country Of Residence ISO Definition Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed. XML Tag CtryOfRes Type CountryCode Pattern [A-Z]{2,2}
2.126	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Ultimate Creditor ++++Contact Details	ISO Name Contact Details ISO Definition Set of elements used to indicate how to contact the party. XML Tag CtctDtls Type ContactDetails2
2.127	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Debtor Agent	ISO Name Debtor Agent ISO Definition Financial institution servicing an account for the debtor. XML Tag DbtrAgt Type BranchAndFinancialInstitutionIdentification4

#	SEPA Mult	Message Element	SEPA Core Requirements
2.128	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Debtor Agent ++++Financial Institution Identification	<i>SEPA Usage Rule(s)</i> Either BIC or 'Other/Identification' must be used. ISO Name Financial Institution Identification ISO Definition Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme. XML Tag FinInstnId Type FinancialInstitutionIdentification7
2.129	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Debtor Agent ++++Financial Institution Identification +++++BIC	<i>SEPA Rulebook</i> AT-13 BIC of the Debtor Bank. The BIC is mandatory for non-EU/non-EEA cross-border SEPA transactions. ISO Name BIC ISO Definition Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)". XML Tag BIC Type BICIdentifier Pattern [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}
2.130	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Debtor Agent ++++Financial Institution Identification +++++Clearing System Member Identification	ISO Name Clearing System Member Identification ISO Definition Information used to identify a member within a clearing system. XML Tag ClrSysMmbId Type ClearingSystemMemberIdentification2
2.131	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Debtor Agent ++++Financial Institution Identification +++++Name	ISO Name Name ISO Definition Name by which an agent is known and which is usually used to identify that agent. XML Tag Nm Type Max140Text ISO Length 1 .. 140 <i>SEPA Length</i> 1 .. 140
2.132	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Debtor Agent ++++Financial Institution Identification +++++Postal Address	ISO Name Postal Address ISO Definition Information that locates and identifies a specific address, as defined by postal services. XML Tag PstlAdr Type PostalAddress6
2.133	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Debtor Agent ++++Financial Institution Identification +++++Other	ISO Name Other ISO Definition Unique identification of an agent, as assigned by an institution, using an identification scheme. XML Tag Othr Type GenericFinancialIdentification1
2.134	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Debtor Agent ++++Financial Institution Identification +++++Other +++++Identification	<i>SEPA Usage Rule(s)</i> Only 'NOTPROVIDED' is allowed. ISO Name Identification ISO Definition Unique and unambiguous identification of a person. XML Tag Id Type Max35Text ISO Length 1 .. 35 <i>SEPA Length</i> 1 .. 35

#	SEPA Mult	Message Element	SEPA Core Requirements	
2.135	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Debtor Agent ++++Financial Institution Identification +++++Other ++++++Scheme Name	ISO Name ISO Definition XML Tag Type	Scheme Name Name of the identification scheme. SchmeNm FinancialIdentificationSchemeName1Choice
2.136	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Debtor Agent ++++Financial Institution Identification +++++Other ++++++Issuer	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Issuer Entity that assigns the identification. Issr Max35Text 1 .. 35 1 .. 35
2.137	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Debtor Agent ++++Branch Identification	ISO Name ISO Definition XML Tag Type	Branch Identification Identifies a specific branch of a financial institution. Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level. BrnchId BranchData2
2.138	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Debtor Agent Account	ISO Name ISO Definition XML Tag Type	Debtor Agent Account Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain. DbtrAgtAcct CashAccount16
2.139	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Debtor	ISO Name ISO Definition XML Tag Type	Debtor Party that owes an amount of money to the (ultimate) creditor. Dbtr PartyIdentification32
2.140	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Debtor ++++Name	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	AT-14 Name of the Debtor. Mandatory 'Name' is limited to 70 characters in length. Name Name by which a party is known and which is usually used to identify that party. Nm Max140Text 1 .. 140 1 .. 70
2.141	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Debtor ++++Postal Address	SEPA Rulebook ISO Name ISO Definition XML Tag Type	AT-09 Address of the Debtor. Postal Address Information that locates and identifies a specific address, as defined by postal services. PstlAdr PostalAddress6
2.142	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Debtor ++++Postal Address +++++Address Type	ISO Name ISO Definition XML Tag Type	Address Type Identifies the nature of the postal address. AdrTp AddressType2Code

#	SEPA Mult	Message Element	SEPA Core Requirements	
2.143	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Debtor ++++Postal Address +++++Department	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Department Identification of a division of a large organisation or building. Dept Max70Text 1 .. 70 1 .. 70
2.144	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Debtor ++++Postal Address +++++Sub Department	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Sub Department Identification of a sub-division of a large organisation or building. SubDept Max70Text 1 .. 70 1 .. 70
2.145	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Debtor ++++Postal Address +++++Street Name	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Street Name Name of a street or thoroughfare. StrtNm Max70Text 1 .. 70 1 .. 70
2.146	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Debtor ++++Postal Address +++++Building Number	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Building Number Number that identifies the position of a building on a street. BldgNb Max16Text 1 .. 16 1 .. 16
2.147	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Debtor ++++Postal Address +++++Post Code	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Post Code Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail. PstCd Max16Text 1 .. 16 1 .. 16
2.148	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Debtor ++++Postal Address +++++Town Name	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Town Name Name of a built-up area, with defined boundaries, and a local government. TwnNm Max35Text 1 .. 35 1 .. 35
2.149	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Debtor ++++Postal Address +++++Country Sub Division	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Country Sub Division Identifies a subdivision of a country such as state, region, county. CtrySubDvsn Max35Text 1 .. 35 1 .. 35
2.150	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Debtor ++++Postal Address +++++Country	ISO Name ISO Definition XML Tag Type Pattern	Country Nation with its own government. Ctry CountryCode [A-Z]{2,2}

#	SEPA Mult	Message Element	SEPA Core Requirements
2.151	0..2	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Debtor ++++Postal Address +++++Address Line	<i>SEPA Usage Rule(s)</i> Only two occurrences are allowed. ISO Name Address Line ISO Definition Information that locates and identifies a specific address, as defined by postal services, presented in free format text. XML Tag AdrLine Type Max70Text ISO Length 1 .. 70 SEPA Length 1 .. 70
2.152	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Debtor ++++Identification	<i>SEPA Rulebook</i> AT-27 Debtor identification code. ISO Name Identification ISO Definition Unique and unambiguous identification of a party. XML Tag Id Type Party6Choice
	1..1		XML Tag xs:choice
2.153	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Debtor ++++Identification +++++Organisation Identification	<i>SEPA Usage Rule(s)</i> Either 'BIC or BEI' or one occurrence of 'Other' is allowed. ISO Name Organisation Identification ISO Definition Unique and unambiguous way to identify an organisation. XML Tag OrgId Type OrganisationIdentification4
2.154	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Debtor ++++Identification +++++Private Identification	<i>SEPA Usage Rule(s)</i> Either 'Date and Place of Birth' or one occurrence of 'Other' is allowed. ISO Name Private Identification ISO Definition Unique and unambiguous identification of a person, eg, passport. XML Tag PrvtId Type PersonIdentification5
2.155	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Debtor ++++Country Of Residence	ISO Name Country Of Residence ISO Definition Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed. XML Tag CtryOfRes Type CountryCode Pattern [A-Z]{2,2}
2.156	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Debtor ++++Contact Details	ISO Name Contact Details ISO Definition Set of elements used to indicate how to contact the party. XML Tag CtctDtls Type ContactDetails2
2.157	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Debtor Account	<i>SEPA Rulebook</i> AT-07 Account Number of the Debtor. <i>SEPA Usage Rule(s)</i> Only IBAN is allowed. ISO Name Debtor Account ISO Definition Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction. XML Tag DbtrAcct Type CashAccount16
2.158	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Ultimate Debtor	<i>SEPA Usage Rule(s)</i> Mandatory, if provided by the Debtor in the Mandate. ISO Name Ultimate Debtor ISO Definition Ultimate party that owes an amount of money to the (ultimate) creditor. XML Tag UltmtDbtr Type PartyIdentification32

#	SEPA Mult	Message Element	SEPA Core Requirements
2.159	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Ultimate Debtor ++++Name	<p>SEPA Rulebook AT-15 Name of the Debtor Reference Party. SEPA Usage Rule(s) 'Name' is limited to 70 characters in length. Mandatory, if provided by the Debtor in the mandate.</p> <p>ISO Name Name ISO Definition Name by which a party is known and which is usually used to identify that party.</p> <p>XML Tag Nm Type Max140Text ISO Length 1 .. 140 SEPA Length 1 .. 70</p>
2.160	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Ultimate Debtor ++++Postal Address	<p>ISO Name Postal Address ISO Definition Information that locates and identifies a specific address, as defined by postal services.</p> <p>XML Tag PstlAdr Type PostalAddress6</p>
2.161	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Ultimate Debtor ++++Identification	<p>SEPA Rulebook AT-37 Identification code of the Debtor Reference Party. ISO Name Identification ISO Definition Unique and unambiguous identification of a party.</p> <p>XML Tag Id Type Party6Choice</p>
	1..1		XML Tag xs:choice
2.162	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Ultimate Debtor ++++Identification +++++Organisation Identification	<p>SEPA Usage Rule(s) Either 'BIC or BEI' or one occurrence of 'Other' is allowed.</p> <p>ISO Name Organisation Identification ISO Definition Unique and unambiguous way to identify an organisation.</p> <p>XML Tag OrgId Type OrganisationIdentification4</p>
2.163	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Ultimate Debtor ++++Identification +++++Private Identification	<p>SEPA Usage Rule(s) Either 'Date and Place of Birth' or one occurrence of 'Other' is allowed.</p> <p>ISO Name Private Identification ISO Definition Unique and unambiguous identification of a person, eg, passport.</p> <p>XML Tag PrvtId Type PersonIdentification5</p>
2.164	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Ultimate Debtor ++++Country Of Residence	<p>ISO Name Country Of Residence ISO Definition Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.</p> <p>XML Tag CtryOfRes Type CountryCode Pattern [A-Z]{2,2}</p>
2.165	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Ultimate Debtor ++++Contact Details	<p>ISO Name Contact Details ISO Definition Set of elements used to indicate how to contact the party.</p> <p>XML Tag CtctDtls Type ContactDetails2</p>

#	SEPA Mult	Message Element	SEPA Core Requirements	
2.166	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Instruction For Creditor Agent	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Instruction For Creditor Agent Further information, related to the processing of the payment instruction, that may need to be acted upon by the creditor agent, depending on agreement between creditor and the creditor agent. InstrForCdtrAgt Max140Text 1 .. 140 1 .. 140
2.167	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Purpose	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-58 Purpose of the Collection.</i> Purpose Underlying reason for the payment transaction. Usage: Purpose is used by the end-customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain. Purp Purpose2Choice
	1..1		XML Tag	xs:choice
2.168	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Purpose ++++Code	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Code Underlying reason for the payment transaction, as published in an external purpose code list. Cd ExternalPurpose1Code 1 .. 4 1 .. 4
2.169	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Purpose ++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Proprietary Purpose, in a proprietary form. Prtry Max35Text 1 .. 35 1 .. 35
2.170	0..10	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Regulatory Reporting	ISO Name ISO Definition XML Tag Type	Regulatory Reporting Information needed due to regulatory and statutory requirements. RgltryRptg RegulatoryReporting3
2.171	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Tax	ISO Name ISO Definition XML Tag Type	Tax Set of elements used to provide details on the tax. Tax TaxInformation3
2.172	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Related Remittance Information	ISO Name ISO Definition XML Tag Type	Related Remittance Information Set of elements used to provide information related to the handling of the remittance information by any of the agents in the transaction processing chain. RltdRmtInf RemittanceLocation2

#	SEPA Mult	Message Element	SEPA Core Requirements
2.173	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Remittance Information	<p>SEPA Rulebook AT-22 Remittance information from the Creditor.</p> <p>SEPA Usage Rule(s) Either 'Structured' or 'Unstructured', may be present.</p> <p>ISO Name Remittance Information</p> <p>ISO Definition Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system.</p> <p>XML Tag RmtInf</p> <p>Type RemittanceInformation5</p>
2.174	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Remittance Information ++++Unstructured	<p>SEPA Usage Rule(s) 'Unstructured' may carry structured remittance information, as agreed between the Creditor and the Debtor. Only one occurrence of 'Unstructured' is allowed.</p> <p>ISO Name Unstructured</p> <p>ISO Definition Information supplied to enable the matching/ reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in an unstructured form.</p> <p>XML Tag Ustrd</p> <p>Type Max140Text</p> <p>ISO Length 1 .. 140</p> <p>SEPA Length 1 .. 140</p>
2.175	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Remittance Information ++++Structured	<p>SEPA Usage Rule(s) 'Structured' can be used, provided the tags and the data within the 'Structured' element do not exceed 140 characters in length. Only one occurrence of 'Structured' is allowed.</p> <p>ISO Name Structured</p> <p>ISO Definition Information supplied to enable the matching/ reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in a structured form.</p> <p>XML Tag Strd</p> <p>Type StructuredRemittanceInformation7</p>
2.176	0..n	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Remittance Information ++++Structured +++++Referred Document Information	<p>ISO Name Referred Document Information</p> <p>ISO Definition Set of elements used to identify the documents referred to in the remittance information.</p> <p>XML Tag RfrdDocInf</p> <p>Type ReferredDocumentInformation3</p>
2.177	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Remittance Information ++++Structured +++++Referred Document Amount	<p>ISO Name Referred Document Amount</p> <p>ISO Definition Set of elements used to provide details on the amounts of the referred document.</p> <p>XML Tag RfrdDocAmt</p> <p>Type RemittanceAmount1</p>
2.178	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Remittance Information ++++Structured +++++Creditor Reference Information	<p>SEPA Usage Rule(s) When present, the Creditor Bank is not obliged to validate the reference information. When used, both 'Type' and 'Reference' must be present.</p> <p>ISO Name Creditor Reference Information</p> <p>ISO Definition Reference information provided by the creditor to allow the identification of the underlying documents.</p> <p>XML Tag CdtrRefInf</p> <p>Type CreditorReferenceInformation2</p>

#	SEPA Mult	Message Element	SEPA Core Requirements	
2.179	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Remittance Information ++++Structured +++++Creditor Reference Information ++++++Type	ISO Name ISO Definition XML Tag Type	Type Specifies the type of creditor reference. Tp CreditorReferenceType2
2.180	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Remittance Information ++++Structured +++++Creditor Reference Information ++++++Type +++++++Code Or Proprietary	ISO Name ISO Definition XML Tag Type	Code Or Proprietary Coded or proprietary format creditor reference type. CdOrPrtry CreditorReferenceType1Choice
	1..1		XML Tag	xs:choice
2.181	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Remittance Information ++++Structured +++++Creditor Reference Information ++++++Type +++++++Code Or Proprietary +++++++Code	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>Only 'SCOR' is allowed.</i> Code Type of creditor reference, in a coded form. Cd DocumentType3Code
			SEPA Code Restrictions	
			SCOR	<i>StructuredCommunicationReference Document is a structured communication reference provided by the creditor to identify the referred transaction.</i>
2.182	1..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Remittance Information ++++Structured +++++Creditor Reference Information ++++++Type +++++++Code Or Proprietary +++++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Proprietary Creditor reference type, in a proprietary form. Prtry Max35Text 1 .. 35 1 .. 35
2.183	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Remittance Information ++++Structured +++++Creditor Reference Information ++++++Type +++++++Issuer	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Issuer Entity that assigns the credit reference type. Issr Max35Text 1 .. 35 1 .. 35

#	SEPA Mult	Message Element	SEPA Core Requirements
2.184	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Remittance Information ++++Structured +++++Creditor Reference Information ++++++Reference	<p>SEPA Usage Rule(s) <i>If 'Creditor' Reference contains a check digit, the receiving bank is not required to validate this. If the receiving bank validates the check digit and if this validation fails, the bank may continue its processing and send the transaction to the next party in the chain. RF Creditor Reference may be used (ISO 11649).</i></p> <p>ISO Name ISO Definition</p> <p>Reference Unique reference, as assigned by the creditor, to unambiguously refer to the payment transaction.</p> <p>Usage: If available, the initiating party should provide this reference in the structured remittance information, to enable reconciliation by the creditor upon receipt of the amount of money.</p> <p>If the business context requires the use of a creditor reference or a payment remit identification, and only one identifier can be passed through the end-to-end chain, the creditor's reference or payment remittance identification should be quoted in the end-to-end transaction identification.</p> <p>XML Tag Type ISO Length SEPA Length</p> <p>Ref Max35Text 1 .. 35 1 .. 35</p>
2.185	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Remittance Information ++++Structured +++++Invoicer	<p>ISO Name ISO Definition</p> <p>Invoicer Identification of the organisation issuing the invoice, when it is different from the creditor or ultimate creditor.</p> <p>XML Tag Type</p> <p>Invcr PartyIdentification32</p>
2.186	0..1	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Remittance Information ++++Structured +++++Invoicee	<p>ISO Name ISO Definition</p> <p>Invoicee Identification of the party to whom an invoice is issued, when it is different from the debtor or ultimate debtor.</p> <p>XML Tag Type</p> <p>Invcee PartyIdentification32</p>
2.187	0..3	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Remittance Information ++++Structured +++++Additional Remittance Information	<p>ISO Name ISO Definition</p> <p>Additional Remittance Information Additional information, in free text form, to complement the structured remittance information.</p> <p>XML Tag Type ISO Length SEPA Length</p> <p>AddtLRmtInf Max140Text 1 .. 140 1 .. 140</p>

2.2 Customer to Bank Reversal Instruction for a Collection (Based on DS-07 and DS-03)

2.2.1 Use of the Customer to Bank Payment Reversal (pain.007.001.02)

The use of this message is recommended. The message elements identified with yellow shading must be provided when mandatory. However, message elements known by the Creditor Bank may be filled in by the Creditor's Bank for populating the subsequent inter-bank message. This is a matter between the Creditor and the Creditor's Bank.

The message is used to transport the Customer to Bank Reversal Instruction for a Collection sent by the Creditor to the Creditor bank.

The message caters for bulk and single reversal instructions.

Note: Attribute AT-R1 in DS-07 is indicated by the 'Message Name', 'pain.007.001.02' and the 'Original Message Name Identification', 'pain.008.001.02'.

Note: Message elements under 'Original Transaction Reference' sequence are based on DS-03 attributes.

#	SEPA Mult	Message Element	SEPA Core Requirements	
		Document	XML Tag Type	Document Document
	1..1	Customer Payment Reversal V02	ISO Name ISO Definition XML Tag Type	Customer Payment Reversal V02 The CustomerPaymentReversal message is sent by the initiating party to the next party in the payment chain. It is used to reverse a payment previously executed. CstmrPmtRvsl CustomerPaymentReversalV02
1.0	1..1	Customer Payment Reversal V02 +Group Header	ISO Name ISO Definition XML Tag Type	Group Header Set of characteristics shared by all individual transactions included in the message. GrpHdr GroupHeader40
1.1	1..1	Customer Payment Reversal V02 +Group Header ++Message Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Message Identification Point to point reference, as assigned by the instructing party, and sent to the next party in the chain to unambiguously identify the message. Usage: The instructing party has to make sure that MessageIdentification is unique per instructed party for a pre-agreed period. MsgId Max35Text 1 .. 35 1 .. 35
1.2	1..1	Customer Payment Reversal V02 +Group Header ++Creation Date Time	ISO Name ISO Definition XML Tag Type	Creation Date Time Date and time at which the message was created. CreDtTm ISODateTime
1.3	0..2	Customer Payment Reversal V02 +Group Header ++Authorisation	ISO Name ISO Definition XML Tag Type	Authorisation User identification or any user key to be used to check whether the initiating party is allowed to initiate transactions from the account specified in the message. Usage: The content is not of a technical nature, but reflects the organisational structure at the initiating side. The authorisation element can typically be used in relay scenarios, payment initiations, payment returns or payment reversals that are initiated on behalf of a party different from the initiating party. Authstn Authorisation1Choice
1.4	0..1	Customer Payment Reversal V02 +Group Header ++Batch Booking	ISO Name ISO Definition XML Tag Type	Batch Booking Identifies whether a single entry per individual transaction or a batch entry for the sum of the amounts of all transactions within the group of a message is requested. Usage: Batch booking is used to request and not order a possible batch booking. BtchBookg BatchBookingIndicator
1.5	1..1	Customer Payment Reversal V02 +Group Header ++Number Of Transactions	ISO Name ISO Definition XML Tag Type Pattern	Number Of Transactions Number of individual transactions contained in the message. NbOfTxs Max15NumericText [0-9]{1,15}

#	SEPA Mult	Message Element	SEPA Core Requirements	
1.6	0..1	Customer Payment Reversal V02 +Group Header ++Control Sum	ISO Name Control Sum ISO Definition Total of all individual amounts included in the message, irrespective of currencies. XML Tag CtrlSum Type DecimalNumber SEPA FractDigits 17 TotalDigits 18	
1.7	0..1	Customer Payment Reversal V02 +Group Header ++Group Reversal	SEPA Usage Rule(s) <i>It is recommended that 'false' is used.</i> ISO Name Group Reversal ISO Definition Indicates whether the reversal applies to the whole group of transactions or to individual transactions within the original group. XML Tag GrpRvsl Type TrueFalseIndicator	
1.8	0..1	Customer Payment Reversal V02 +Group Header ++Initiating Party	ISO Name Initiating Party ISO Definition Party that initiates the reversal message. Usage: This can be either the creditor or a party that initiates the reversal of the direct debit on behalf of the creditor. XML Tag InitgPty Type PartyIdentification32	
1.9	0..1	Customer Payment Reversal V02 +Group Header ++Initiating Party +++Name	SEPA Usage Rule(s) <i>'Name' is limited to 70 characters in length.</i> ISO Name Name ISO Definition Name by which a party is known and which is usually used to identify that party. XML Tag Nm Type Max140Text ISO Length 1 .. 140 SEPA Length 1 .. 70	
1.10	0..1	Customer Payment Reversal V02 +Group Header ++Initiating Party +++Postal Address	ISO Name Postal Address ISO Definition Information that locates and identifies a specific address, as defined by postal services. XML Tag PstlAdr Type PostalAddress6	
1.11	0..1	Customer Payment Reversal V02 +Group Header ++Initiating Party +++Identification	ISO Name Identification ISO Definition Unique and unambiguous identification of a party. XML Tag Id Type Party6Choice	
	1..1		XML Tag xs:choice	
1.12	1..1	Customer Payment Reversal V02 +Group Header ++Initiating Party +++Identification ++++Organisation Identification	SEPA Usage Rule(s) <i>Either 'BIC or BEI' or one occurrence of 'Other' is allowed.</i> ISO Name Organisation Identification ISO Definition Unique and unambiguous way to identify an organisation. XML Tag OrgId Type OrganisationIdentification4	
1.13	1..1	Customer Payment Reversal V02 +Group Header ++Initiating Party +++Identification ++++Private Identification	SEPA Usage Rule(s) <i>Either 'Date and Place of Birth' or one occurrence of 'Other' is allowed.</i> ISO Name Private Identification ISO Definition Unique and unambiguous identification of a person, eg, passport. XML Tag PrvtId Type PersonIdentification5	

#	SEPA Mult	Message Element	SEPA Core Requirements	
1.14	0..1	Customer Payment Reversal V02 +Group Header ++Initiating Party +++Country Of Residence	ISO Name ISO Definition XML Tag Type Pattern	Country Of Residence Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed. CtryOfRes CountryCode [A-Z]{2,2}
1.15	0..1	Customer Payment Reversal V02 +Group Header ++Initiating Party +++Contact Details	ISO Name ISO Definition XML Tag Type	Contact Details Set of elements used to indicate how to contact the party. CtctDtls ContactDetails2
1.16	0..1	Customer Payment Reversal V02 +Group Header ++Forwarding Agent	ISO Name ISO Definition XML Tag Type	Forwarding Agent Financial institution that receives the instruction from the initiating party and forwards it to the next agent in the payment chain. FwdgAgt BranchAndFinancialInstitutionIdentification4
1.17	0..1	Customer Payment Reversal V02 +Group Header ++Debtor Agent	ISO Name ISO Definition XML Tag Type	Debtor Agent Financial institution servicing an account for the debtor. DbtrAgt BranchAndFinancialInstitutionIdentification4
1.18	0..1	Customer Payment Reversal V02 +Group Header ++Creditor Agent	<i>SEPA Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-12 BIC of the Creditor bank.</i> Creditor Agent Financial institution servicing an account for the creditor. CdtrAgt BranchAndFinancialInstitutionIdentification4
2.0	1..1	Customer Payment Reversal V02 +Original Group Information	ISO Name ISO Definition XML Tag Type	Original Group Information Information concerning the original group of transactions, to which the message refers. OrgnlGrpInf OriginalGroupInformation22
2.1	1..1	Customer Payment Reversal V02 +Original Group Information ++Original Message Identification	ISO Name ISO Definition XML Tag Type ISO Length <i>SEPA Length</i>	Original Message Identification Point to point reference, as assigned by the original instructing party, to unambiguously identify the original message. OrgnlMsgId Max35Text 1 .. 35 1 .. 35
2.2	1..1	Customer Payment Reversal V02 +Original Group Information ++Original Message Name Identification	ISO Name ISO Definition XML Tag Type ISO Length <i>SEPA Length</i>	Original Message Name Identification Specifies the original message name identifier to which the message refers. OrgnlMsgNmId Max35Text 1 .. 35 1 .. 35
2.3	0..1	Customer Payment Reversal V02 +Original Group Information ++Original Creation Date Time	ISO Name ISO Definition XML Tag Type	Original Creation Date Time Date and time at which the original message was created. OrgnlCreDtTm ISODateTime

#	SEPA Mult	Message Element	SEPA Core Requirements
2.4	0..1	Customer Payment Reversal V02 +Original Group Information ++Reversal Reason Information	<i>SEPA Usage Rule(s)</i> Only one occurrence is allowed. ISO Name Reversal Reason Information ISO Definition Set of elements used to provide detailed information on the reversal reason. XML Tag RvslRsnInf Type ReversalReasonInformation6
2.5	0..1	Customer Payment Reversal V02 +Original Group Information ++Reversal Reason Information +++Originator	ISO Name Originator ISO Definition Party that issues the reversal. XML Tag Orgtr Type PartyIdentification32
2.6	0..1	Customer Payment Reversal V02 +Original Group Information ++Reversal Reason Information +++Reason	<i>SEPA Usage Rule(s)</i> 'Reason' must be present either in 'Original Group Information', 'Original Payment Information and Reversal' or 'Transaction Information'. ISO Name Reason ISO Definition Specifies the reason for the reversal. XML Tag Rsn Type ReversalReason4Choice
	1..1		XML Tag xs:choice
2.7	1..1	Customer Payment Reversal V02 +Original Group Information ++Reversal Reason Information +++Reason ++++Code	<i>SEPA Rulebook</i> AT-31 Reversal reason code. See Message Element Specifications below. ISO Name Code ISO Definition Reason for the reversal, as published in an external reason code list. XML Tag Cd Type ExternalReversalReason1Code ISO Length 1 .. 4 SEPA Length 1 .. 4
2.8	1..1	Customer Payment Reversal V02 +Original Group Information ++Reversal Reason Information +++Reason ++++Proprietary	ISO Name Proprietary ISO Definition Reason for the reversal, in a proprietary form. XML Tag Prtry Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35
2.9	0..n	Customer Payment Reversal V02 +Original Group Information ++Reversal Reason Information +++Additional Information	ISO Name Additional Information ISO Definition Further details on the reversal reason. XML Tag AddtlInf Type Max105Text ISO Length 1 .. 105 SEPA Length 1 .. 105
3.0	0..n	Customer Payment Reversal V02 +Original Payment Information And Reversal	ISO Name Original Payment Information And Reversal ISO Definition Information concerning the original payment information, to which the reversal message refers. XML Tag OrgnlPmtInfAndRvsl Type OriginalPaymentInformation2
3.1	0..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Reversal Payment Information Identification	ISO Name Reversal Payment Information Identification ISO Definition Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the reversed payment information group. Usage: The instructing party is the party sending the reversal message and not the party that sent the original instruction that is being reversed. XML Tag RvslPmtInfId Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35

#	SEPA Mult	Message Element	SEPA Core Requirements	
3.2	1..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Original Payment Information Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Payment Information Identification Unique identification, as assigned by the original sending party, to unambiguously identify the original payment information group. OrgnlPmtInflId Max35Text 1 .. 35 1 .. 35
3.3	0..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Original Number Of Transactions	ISO Name ISO Definition XML Tag Type Pattern	Original Number Of Transactions Number of individual transactions contained in the original payment information group. OrgnlNbOfTxS Max15NumericText [0-9]{1,15}
3.4	0..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Original Control Sum	ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits	Original Control Sum Total of all individual amounts included in the original payment information group, irrespective of currencies. OrgnlCtrlSum DecimalNumber 17 18
3.5	0..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Batch Booking	ISO Name ISO Definition XML Tag Type	Batch Booking Identifies whether a single entry per individual transaction or a batch entry for the sum of the amounts of all transactions within the group of a message is requested. Usage: Batch booking is used to request and not order a possible batch booking. BtchBookg BatchBookingIndicator
3.6	0..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Payment Information Reversal	ISO Name ISO Definition XML Tag Type	Payment Information Reversal Indicates whether or not the reversal applies to the complete original payment information group or to individual transactions within that group. PmtInfRvsl TrueFalseIndicator
3.7	0..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Reversal Reason Information	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>Only one occurrence is allowed.</i> Reversal Reason Information Set of elements used to provide detailed information on the reversal reason. RvslRsnInf ReversalReasonInformation6
3.8	0..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Reversal Reason Information +++Originator	ISO Name ISO Definition XML Tag Type	Originator Party that issues the reversal. Orgtr PartyIdentification32
3.9	0..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Reversal Reason Information +++Reason	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>'Reason' must be present either in 'Original Group Information', 'Original Payment Information and Reversal', or 'Transaction Information'.</i> Reason Specifies the reason for the reversal. Rsn ReversalReason4Choice
	1..1		XML Tag	xs:choice

#	SEPA Mult	Message Element	SEPA Core Requirements	
3.10	1..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Reversal Reason Information +++Reason ++++Code	<i>SEPA Rulebook</i> ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>AT-31 Reversal reason code.</i> Code Reason for the reversal, as published in an external reason code list. Cd ExternalReversalReason1Code 1 .. 4 1 .. 4
3.11	1..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Reversal Reason Information +++Reason ++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Proprietary Reason for the reversal, in a proprietary form. Prtry Max35Text 1 .. 35 1 .. 35
3.12	0..n	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Reversal Reason Information +++Additional Information	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Additional Information Further details on the reversal reason. AddtInf Max105Text 1 .. 105 1 .. 105
3.13	0..n	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Transaction Information	ISO Name ISO Definition XML Tag Type	Transaction Information Set of elements used to provide information on the original transactions to which the reversal message refers. TxInf PaymentTransactionInformation28
3.14	0..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Transaction Information +++Reversal Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Reversal Identification Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the reversed transaction. Usage: The instructing party is the party sending the reversal message and not the party that sent the original instruction that is being reversed. RvslId Max35Text 1 .. 35 1 .. 35
3.15	0..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Transaction Information +++Original Instruction Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Instruction Identification Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction. OrgnlInstrId Max35Text 1 .. 35 1 .. 35
3.16	1..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Transaction Information +++Original End To End Identification	<i>SEPA Rulebook</i> <i>SEPA Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>AT-10 Creditor reference of the direct debit Collection.</i> <i>Mandatory</i> Original End To End Identification Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction. OrgnlEndToEndId Max35Text 1 .. 35 1 .. 35

#	SEPA Mult	Message Element	SEPA Core Requirements
3.17	0..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Transaction Information +++Original Instructed Amount	<p>SEPA Rulebook AT-06 Amount of the Collection in euro. SEPA Usage Rule(s) Only 'EUR' is allowed. Amount must be 0.01 or more and 999999999.99 or less. SEPA Format Rule(s) The fractional part has a maximum of two digits.</p> <p>ISO Name Original Instructed Amount ISO Definition Amount of money, as provided in the original transaction, to be moved between the debtor and the creditor, before deduction of charges, expressed in the currency, as ordered by the original initiating party.</p> <p>XML Tag OrgnInstdAmt Type ActiveOrHistoricCurrencyAndAmount SEPA FractDigits 2 TotalDigits 18 SEPA Inclusive 0.01 .. 999999999.99</p>
3.18	0..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Transaction Information +++Reversed Instructed Amount	<p>SEPA Usage Rule(s) Amount of the Reversal must be the same as the Amount of the Collection in euro (AT-06). Only 'EUR' is allowed. Amount must be 0.01 or more and 999999999.99 or less. SEPA Format Rule(s) The fractional part has a maximum of two digits.</p> <p>ISO Name Reversed Instructed Amount ISO Definition Amount of money to be moved between the debtor and the creditor, before deduction of charges, in the reversed transaction.</p> <p>XML Tag RvsdInstdAmt Type ActiveOrHistoricCurrencyAndAmount SEPA FractDigits 2 TotalDigits 18 SEPA Inclusive 0.01 .. 999999999.99</p>
3.19	0..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Transaction Information +++Charge Bearer	<p>SEPA Usage Rule(s) Only 'SLEV' is allowed. ISO Name Charge Bearer ISO Definition Specifies if the creditor and/or debtor will bear the charges associated with the processing of the payment transaction.</p> <p>Usage: The ChargeBearer applies to the reversal message, not to the original instruction.</p> <p>XML Tag ChrgBr Type ChargeBearerType1Code</p> <p>SEPA Code Restrictions</p> <p>SLEV FollowingServiceLevel Charges are to be applied following the rules agreed in the service level and/or scheme.</p>
3.20	0..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Transaction Information +++Reversal Reason Information	<p>SEPA Usage Rule(s) Only one occurrence is allowed. ISO Name Reversal Reason Information ISO Definition Set of elements used to provide detailed information on the reversal reason.</p> <p>XML Tag RvslRsnInf Type ReversalReasonInformation6</p>
3.21	0..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Transaction Information +++Reversal Reason Information ++++Originator	<p>ISO Name Originator ISO Definition Party that issues the reversal. XML Tag Orgtr Type PartyIdentification32</p>

#	SEPA Mult	Message Element	SEPA Core Requirements
3.22	0..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Transaction Information +++Reversal Reason Information ++++Reason	<p><i>SEPA Usage Rule(s)</i> 'Reason' must be present either in 'Original Group Information', 'Original Payment Information and Reversal' or 'Transaction Information'.</p> <p>ISO Name Reason ISO Definition Specifies the reason for the reversal. XML Tag Rsn Type ReversalReason4Choice</p>
	1..1		XML Tag xs:choice
3.23	1..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Transaction Information +++Reversal Reason Information ++++Reason +++++Code	<p><i>SEPA Rulebook</i> AT-31 Reversal reason code.</p> <p>ISO Name Code ISO Definition Reason for the reversal, as published in an external reason code list. XML Tag Cd Type ExternalReversalReason1Code ISO Length 1 .. 4 SEPA Length 1 .. 4</p>
3.24	1..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Transaction Information +++Reversal Reason Information ++++Reason +++++Proprietary	<p>ISO Name Proprietary ISO Definition Reason for the reversal, in a proprietary form. XML Tag Prtry Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35</p>
3.25	0..n	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Transaction Information +++Reversal Reason Information ++++Additional Information	<p>ISO Name Additional Information ISO Definition Further details on the reversal reason. XML Tag AddtlInf Type Max105Text ISO Length 1 .. 105 SEPA Length 1 .. 105</p>
3.26	1..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Transaction Information +++Original Transaction Reference	<p><i>SEPA Rulebook</i> An exact copy of all attributes of the received DS-03 which is being reversed.</p> <p><i>SEPA Usage Rule(s)</i> Mandatory The message elements under 'Original Transaction Reference' must be populated with the same value as the message elements of the original instruction, as defined within the following elements.</p> <p>ISO Name Original Transaction Reference ISO Definition Set of key elements used to identify the original transaction that is being referred to. XML Tag OrgnlTxRef Type OriginalTransactionReference13</p>
3.27	0..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Transaction Information +++Original Transaction Reference ++++Interbank Settlement Amount	<p>ISO Name Interbank Settlement Amount ISO Definition Amount of money moved between the instructing agent and the instructed agent. XML Tag IntrBkSttlmAmt Type ActiveOrHistoricCurrencyAndAmount SEPA FractDigits 5 TotalDigits 18 SEPA Inclusive 0 ..</p>
3.28	0..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Transaction Information +++Original Transaction Reference ++++Amount	<p>ISO Name Amount ISO Definition Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party. XML Tag Amt Type AmountType3Choice</p>

#	SEPA Mult	Message Element	SEPA Core Requirements	
3.29	0..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Transaction Information +++Original Transaction Reference ++++Interbank Settlement Date	ISO Name ISO Definition XML Tag Type	Interbank Settlement Date Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. IntrBkSttlmDt ISODate
3.30	0..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Transaction Information +++Original Transaction Reference ++++Requested Collection Date	SEPA Rulebook ISO Name ISO Definition XML Tag Type	AT-11 Due date of the Collection. Requested Collection Date Date and time at which the creditor requests that the amount of money is to be collected from the debtor. ReqdColltnDt ISODate
3.31	0..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Transaction Information +++Original Transaction Reference ++++Requested Execution Date	ISO Name ISO Definition XML Tag Type	Requested Execution Date Date at which the initiating party requests the clearing agent to process the payment. Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank. ReqdExctnDt ISODate
3.32	0..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Transaction Information +++Original Transaction Reference ++++Creditor Scheme Identification	SEPA Rulebook ISO Name ISO Definition XML Tag Type	AT-02 Identifier of the Creditor. Creditor Scheme Identification Credit party that signs the mandate. CdtrSchmeId PartyIdentification32
3.33	0..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Transaction Information +++Original Transaction Reference ++++Settlement Information	ISO Name ISO Definition XML Tag Type	Settlement Information Specifies the details on how the settlement of the original transaction(s) between the instructing agent and the instructed agent was completed. SttlmInf SettlementInformation13
3.34	0..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Transaction Information +++Original Transaction Reference ++++Payment Type Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	AT-20 Identification code of the Scheme. AT-21 Transaction / Sequence Type. AT-59 Category purpose of the Collection. Payment Type Information Set of elements used to further specify the type of transaction. PmtTpInf PaymentTypeInfo22
3.35	0..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Transaction Information +++Original Transaction Reference ++++Payment Method	ISO Name ISO Definition XML Tag Type	Payment Method Specifies the means of payment that will be used to move the amount of money. PmtMtd PaymentMethod4Code

#	SEPA Mult	Message Element	SEPA Core Requirements	
3.36	1..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Transaction Information +++Original Transaction Reference ++++Mandate Related Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-01 Unique Mandate reference.</i> <i>AT-16 Placeholder for the electronic signature data, if applicable.</i> <i>AT-17 Type of Mandate (paper, e-Mandate).</i> <i>AT-18 Identifier of the original Creditor who issued the Mandate.</i> <i>AT-19 Unique Mandate reference as given by the original Creditor who issued the Mandate.</i> <i>AT-24 Reason for Amendment of the Mandate.</i> <i>AT-25 Signing date of the Mandate.</i> <i>AT-60 Reference of the validation made by the Debtor Bank (if present in DS-03).</i> Mandate Related Information Set of elements used to provide further details of the mandate signed between the creditor and the debtor. MndtRltdInf MandateRelatedInformation6
3.37	0..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Transaction Information +++Original Transaction Reference ++++Remittance Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-22 Remittance information.</i> Remittance Information Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system. RmtInf RemittanceInformation5
3.38	0..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Transaction Information +++Original Transaction Reference ++++Ultimate Debtor	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-15 Name of the Debtor Reference Party.</i> <i>AT-37 Identification code of the Debtor Reference Party.</i> Ultimate Debtor Ultimate party that owes an amount of money to the (ultimate) creditor. UltmtDbtr PartyIdentification32
3.39	0..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Transaction Information +++Original Transaction Reference ++++Debtor	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-14 Name of the Debtor.</i> <i>AT-09 Address of the Debtor.</i> <i>AT-27 Debtor identification code.</i> Debtor Party that owes an amount of money to the (ultimate) creditor. Dbtr PartyIdentification32
3.40	0..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Transaction Information +++Original Transaction Reference ++++Debtor Account	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-07 Account number (IBAN) of the Debtor.</i> Debtor Account Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction. DbtrAcct CashAccount16
3.41	0..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Transaction Information +++Original Transaction Reference ++++Debtor Agent	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-13 BIC of the Debtor Bank (if present in DS-03).</i> Debtor Agent Financial institution servicing an account for the debtor. DbtrAgt BranchAndFinancialInstitutionIdentification4

#	SEPA Mult	Message Element	SEPA Core Requirements	
3.42	0..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Transaction Information +++Original Transaction Reference ++++Debtor Agent Account	ISO Name ISO Definition XML Tag Type	Debtor Agent Account Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain. DbtrAgtAcct CashAccount16
3.43	0..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Transaction Information +++Original Transaction Reference ++++Creditor Agent	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-12 BIC of the Creditor Bank (if present in DS-03).</i> Creditor Agent Financial institution servicing an account for the creditor. CdtrAgt BranchAndFinancialInstitutionIdentification4
3.44	0..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Transaction Information +++Original Transaction Reference ++++Creditor Agent Account	ISO Name ISO Definition XML Tag Type	Creditor Agent Account Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction. CdtrAgtAcct CashAccount16
3.45	0..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Transaction Information +++Original Transaction Reference ++++Creditor	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-03 Name of the Creditor.</i> <i>AT-05 Address of the Creditor.</i> Creditor Party to which an amount of money is due. Cdtr PartyIdentification32
3.46	0..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Transaction Information +++Original Transaction Reference ++++Creditor Account	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-04 Account number (IBAN) of the Creditor.</i> Creditor Account Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction. CdtrAcct CashAccount16
3.47	0..1	Customer Payment Reversal V02 +Original Payment Information And Reversal ++Transaction Information +++Original Transaction Reference ++++Ultimate Creditor	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-38 Name of the Credit Reference Party.</i> <i>AT-39 Identification code of the Credit Reference Party.</i> Ultimate Creditor Ultimate party to which an amount of money is due. UltmtCdtr PartyIdentification32

2.2.2 Message Element Specifications

The reasons for the reversal presented in the Rulebook are mapped to the ISO codes in the table below. Other ISO codes may be used when the Creditor has requested the reversal.

ISO Code	ISO Name	SEPA Reason as specified in the Rulebook
AM05	Duplication	Duplicate entry
MS02	NotSpecifiedReasonCustomerGenerated	Reason not specified

2.3 Bank to Customer Direct Debit Reject Dataset (Based on DS-05)

2.3.1 Use of the Customer Payment Status Report (pain.002.001.03)

The code 'RJCT' must be used in 'Group Status', 'Payment Information Status' or 'Transaction Status', to transport the B2B Direct Debit Reject instruction between the bank and its remitting customer.

The message caters for bulk and single reject instructions.

Note: Attribute AT-R1 in DS-05 is implied by the 'Message Name', 'pain.002.001.03', the 'Original Message Name Identification', 'pain.008.001.02' and the 'Status' set to 'RJCT'.

Note: AT-R4 is not applicable to reject instructions.

Note: Message elements under 'Original Transaction Reference' sequences are based on DS-03 attributes.

#	SEPA Mult	Message Element	SEPA Core Requirements	
		Document	XML Tag Type	Document Document
	1..1	Customer Payment Status Report V03	ISO Name ISO Definition XML Tag Type	Customer Payment Status Report V03 The CustomerPaymentStatusReport message is sent by an instructed agent to the payment initiator. It is used to inform this party about the positive or negative status of an instruction (either single, group or file). It is also used to report on a pending instruction. CstmrPmtStsRpt CustomerPaymentStatusReportV03
1.0	1..1	Customer Payment Status Report V03 +Group Header	ISO Name ISO Definition XML Tag Type	Group Header Set of characteristics shared by all individual transactions included in the status report message. GrpHdr GroupHeader36
1.1	1..1	Customer Payment Status Report V03 +Group Header ++Message Identification	SEPA Rulebook ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>AT-R5 Specific reference of the bank initiating the R-message.</i> Message Identification Point to point reference, as assigned by the instructing party, and sent to the next party in the chain to unambiguously identify the message. Usage: The instructing party has to make sure that 'MessageIdentification' is unique per instructed party for a pre-agreed period. MsgId Max35Text 1 .. 35 1 .. 35
1.2	1..1	Customer Payment Status Report V03 +Group Header ++Creation Date Time	ISO Name ISO Definition XML Tag Type	Creation Date Time Date and time at which the message was created. CreDtTm ISODateTime
1.3	0..1	Customer Payment Status Report V03 +Group Header ++Initiating Party	ISO Name ISO Definition XML Tag Type	Initiating Party Party that initiates the status message. InitgPty PartyIdentification32
1.4	0..1	Customer Payment Status Report V03 +Group Header ++Forwarding Agent	ISO Name ISO Definition XML Tag Type	Forwarding Agent Financial institution that receives the instruction from the initiating party and forwards it to the next agent in the payment chain. FwdgAgt BranchAndFinancialInstitutionIdentification4
1.5	0..1	Customer Payment Status Report V03 +Group Header ++Debtor Agent	ISO Name ISO Definition XML Tag Type	Debtor Agent Financial institution servicing an account for the debtor. DbtrAgt BranchAndFinancialInstitutionIdentification4
1.6	0..1	Customer Payment Status Report V03 +Group Header ++Creditor Agent	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-12 BIC code of the Creditor Bank.</i> Creditor Agent Financial institution servicing an account for the creditor. CdtrAgt BranchAndFinancialInstitutionIdentification4

#	SEPA Mult	Message Element	SEPA Core Requirements	
2.0	1..1	Customer Payment Status Report V03 +Original Group Information And Status	ISO Name ISO Definition XML Tag Type	Original Group Information And Status Original group information concerning the group of transactions, to which the status report message refers to. OrgnlGrpInfAndSts OriginalGroupInformation20
2.1	1..1	Customer Payment Status Report V03 +Original Group Information And Status ++Original Message Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Message Identification Point to point reference, as assigned by the original instructing party, to unambiguously identify the original message. OrgnlMsgId Max35Text 1 .. 35 1 .. 35
2.2	1..1	Customer Payment Status Report V03 +Original Group Information And Status ++Original Message Name Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Message Name Identification Specifies the original message name identifier to which the message refers. OrgnlMsgNmId Max35Text 1 .. 35 1 .. 35
2.3	0..1	Customer Payment Status Report V03 +Original Group Information And Status ++Original Creation Date Time	ISO Name ISO Definition XML Tag Type	Original Creation Date Time Date and time at which the original message was created. OrgnlCreDtTm ISODateTime
2.4	0..1	Customer Payment Status Report V03 +Original Group Information And Status ++Original Number Of Transactions	ISO Name ISO Definition XML Tag Type Pattern	Original Number Of Transactions Number of individual transactions contained in the original message. OrgnlNbOfTxS Max15NumericText [0-9]{1,15}
2.5	0..1	Customer Payment Status Report V03 +Original Group Information And Status ++Original Control Sum	ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits	Original Control Sum Total of all individual amounts included in the original message, irrespective of currencies. OrgnlCtrlSum DecimalNumber 17 18
2.6	0..1	Customer Payment Status Report V03 +Original Group Information And Status ++Group Status	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-R1 Type of R-message. Either 'Group Status', 'Payment Information Status' or 'Transaction Status' must be present with the code 'RJCT'. Group Status Specifies the status of a group of transactions. GrpSts TransactionGroupStatus3Code
			SEPA Code Restrictions	
			RJCT	Rejected Payment initiation or individual transaction included in the payment initiation has been rejected.

#	SEPA Mult	Message Element	SEPA Core Requirements
2.7	0..n	Customer Payment Status Report V03 +Original Group Information And Status ++Status Reason Information	<p>SEPA Usage Rule(s) 'Status Reason Information' must be present in 'Original Group Information and Status', 'Original Payment Information and Status' or in 'Transaction Information and Status'.</p> <p>ISO Name Status Reason Information ISO Definition Set of elements used to provide detailed information on the status reason. XML Tag StsRsnInf Type StatusReasonInformation8</p>
2.8	1..1	Customer Payment Status Report V03 +Original Group Information And Status ++Status Reason Information +++Originator	<p>SEPA Rulebook AT-R2 Identification of the type of party that initiated the reject. SEPA Usage Rule(s) Mandatory Limited to BIC to identify the bank or CSM originating the status or 'Name' to indicate a CSM when it has no BIC. 'Name' is limited to 70 characters in length.</p> <p>ISO Name Originator ISO Definition Party that issues the status. XML Tag Orgtr Type PartyIdentification32</p>
2.9	1..1	Customer Payment Status Report V03 +Original Group Information And Status ++Status Reason Information +++Reason	<p>SEPA Rulebook AT-R3 Reason code for non-acceptance of the Collection. SEPA Usage Rule(s) Mandatory</p> <p>ISO Name Reason ISO Definition Specifies the reason for the status report. XML Tag Rsn Type StatusReason6Choice</p>
	1..1		XML Tag xs:choice
2.10	1..1	Customer Payment Status Report V03 +Original Group Information And Status ++Status Reason Information +++Reason ++++Code	<p>SEPA Rulebook See Message Element Specifications below. ISO Name Code ISO Definition Reason for the status, as published in an external reason code list. XML Tag Cd Type ExternalStatusReason1Code ISO Length 1 .. 4 SEPA Length 1 .. 4</p>
2.11	1..1	Customer Payment Status Report V03 +Original Group Information And Status ++Status Reason Information +++Reason ++++Proprietary	<p>ISO Name Proprietary ISO Definition Reason for the status, in a proprietary form. XML Tag Prtry Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35</p>
2.12	0..n	Customer Payment Status Report V03 +Original Group Information And Status ++Status Reason Information +++Additional Information	<p>ISO Name Additional Information ISO Definition Further details on the status reason. Usage: Additional information can be used for several purposes such as the reporting of repaired information.</p> <p>XML Tag AddtlInf Type Max105Text ISO Length 1 .. 105 SEPA Length 1 .. 105</p>
2.13	0..n	Customer Payment Status Report V03 +Original Group Information And Status ++Number Of Transactions Per Status	<p>ISO Name Number Of Transactions Per Status ISO Definition Detailed information on the number of transactions for each identical transaction status. XML Tag NbOfTxSPerSts Type NumberOfTransactionsPerStatus3</p>

#	SEPA Mult	Message Element	SEPA Core Requirements	
3.0	0..n	Customer Payment Status Report V03 +Original Payment Information And Status	ISO Name ISO Definition XML Tag Type	Original Payment Information And Status Information concerning the original payment information, to which the status report message refers. OrgnlPmtInfAndSts OriginalPaymentInformation1
3.1	1..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Original Payment Information Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Payment Information Identification Unique identification, as assigned by the original sending party, to unambiguously identify the original payment information group. OrgnlPmtInfId Max35Text 1 .. 35 1 .. 35
3.2	0..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Original Number Of Transactions	ISO Name ISO Definition XML Tag Type Pattern	Original Number Of Transactions Number of individual transactions contained in the original payment information group. OrgnlNbOfTxS Max15NumericText [0-9]{1,15}
3.3	0..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Original Control Sum	ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits	Original Control Sum Total of all individual amounts included in the original payment information group, irrespective of currencies. OrgnlCtrlSum DecimalNumber 17 18
3.4	0..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Payment Information Status	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-R1 Type of R-message.</i> <i>Either 'Group Status', 'Payment Information Status' or 'Transaction Status' must be present with the code 'RJCT'.</i> Payment Information Status Specifies the status of the payment information group. PmtInfSts TransactionGroupStatus3Code
			SEPA Code Restrictions	
			RJCT	<i>Rejected</i> <i>Payment initiation or individual transaction included in the payment initiation has been rejected.</i>
3.5	0..n	Customer Payment Status Report V03 +Original Payment Information And Status ++Status Reason Information	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>'Status Reason Information' must be present in 'Original Group Information and Status', 'Original Payment Information and Status' or 'Transaction Information and Status'.</i> Status Reason Information Set of elements used to provide detailed information on the status reason. StsRsnInf StatusReasonInformation8

#	SEPA Mult	Message Element	SEPA Core Requirements	
3.6	1..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Status Reason Information +++Originator	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-R2 Identification of the type of party that initiated the reject.</i> Mandatory <i>Limited to BIC to identify the bank or CSM originating the status or 'Name' to indicate a CSM when it has no BIC. 'Name' is limited to 70 characters in length.</i> Originator Party that issues the status. Orgtr PartyIdentification32
3.7	1..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Status Reason Information +++Reason	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-R3 Reason code for non-acceptance of the Collection.</i> Mandatory Reason Specifies the reason for the status report. Rsn StatusReason6Choice
	1..1		XML Tag	xs:choice
3.8	1..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Status Reason Information +++Reason ++++Code	SEPA Rulebook ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>See Message Element Specifications below.</i> Code Reason for the status, as published in an external reason code list. Cd ExternalStatusReason1Code 1 .. 4 1 .. 4
3.9	1..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Status Reason Information +++Reason ++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Proprietary Reason for the status, in a proprietary form. Prtry Max35Text 1 .. 35 1 .. 35
3.10	0..n	Customer Payment Status Report V03 +Original Payment Information And Status ++Status Reason Information +++Additional Information	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Additional Information Further details on the status reason. Usage: Additional information can be used for several purposes such as the reporting of repaired information. AddtlInf Max105Text 1 .. 105 1 .. 105
3.11	0..n	Customer Payment Status Report V03 +Original Payment Information And Status ++Number Of Transactions Per Status	ISO Name ISO Definition XML Tag Type	Number Of Transactions Per Status Detailed information on the number of transactions for each identical transaction status. NbOfTxPerSts NumberOfTransactionsPerStatus3
3.12	0..n	Customer Payment Status Report V03 +Original Payment Information And Status ++Transaction Information And Status	ISO Name ISO Definition XML Tag Type	Transaction Information And Status Set of elements used to provide information on the original transactions to which the status report message refers. TxInfAndSts PaymentTransactionInformation25

#	SEPA Mult	Message Element	SEPA Core Requirements	
3.13	0..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Transaction Information And Status +++Status Identification	SEPA Rulebook ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>AT-R5 Specific reference of the bank that initiated the reject.</i> Status Identification Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the reported status. Usage: The instructing party is the party sending the status message and not the party that sent the original instruction that is being reported on. StsId Max35Text 1 .. 35 1 .. 35
3.14	0..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Transaction Information And Status +++Original Instruction Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Instruction Identification Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction. OrgnlInstrId Max35Text 1 .. 35 1 .. 35
3.15	0..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Transaction Information And Status +++Original End To End Identification	SEPA Rulebook ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>AT-10 Creditor's reference of the Direct Debit Transaction.</i> Original End To End Identification Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction. OrgnlEndToEndId Max35Text 1 .. 35 1 .. 35
3.16	0..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Transaction Information And Status +++Transaction Status	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-R1 Type of R-message</i> <i>'Group Status', Payment Information Status' or 'Transaction Status' must be present with the code 'RJCT'.</i> Transaction Status Specifies the status of a transaction, in a coded form. TxSts TransactionIndividualStatus3Code
			SEPA Code Restrictions	
			RJCT	<i>Rejected</i> <i>Payment initiation or individual transaction included in the payment initiation has been rejected.</i>
3.17	0..n	Customer Payment Status Report V03 +Original Payment Information And Status ++Transaction Information And Status +++Status Reason Information	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>'Status Reason Information' must be present in 'Original Group Information and Status', 'Original Payment Information and Status' or in 'Transaction Information and Status'.</i> Status Reason Information Set of elements used to provide detailed information on the status reason. StsRsnInf StatusReasonInformation8

#	SEPA Mult	Message Element	SEPA Core Requirements
3.18	1..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Transaction Information And Status +++Status Reason Information ++++Originator	<p>SEPA Rulebook AT-R2 Identification of the type of party that initiated the reject.</p> <p>SEPA Usage Rule(s) Mandatory Limited to BIC to identify the bank or CSM originating the status or 'Name' to indicate a CSM when it has no BIC. 'Name' is limited to 70 characters in length.</p> <p>ISO Name Originator ISO Definition Party that issues the status. XML Tag Orgtr Type PartyIdentification32</p>
3.19	1..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Transaction Information And Status +++Status Reason Information ++++Reason	<p>SEPA Rulebook AT-R3 Reason code for non-acceptance.</p> <p>SEPA Usage Rule(s) Mandatory</p> <p>ISO Name Reason ISO Definition Specifies the reason for the status report. XML Tag Rsn Type StatusReason6Choice</p>
	1..1		XML Tag xs:choice
3.20	1..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Transaction Information And Status +++Status Reason Information ++++Reason +++++Code	<p>SEPA Rulebook See Message Element Specifications below.</p> <p>ISO Name Code ISO Definition Reason for the status, as published in an external reason code list. XML Tag Cd Type ExternalStatusReason1Code ISO Length 1 .. 4 SEPA Length 1 .. 4</p>
3.21	1..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Transaction Information And Status +++Status Reason Information ++++Reason +++++Proprietary	<p>ISO Name Proprietary ISO Definition Reason for the status, in a proprietary form. XML Tag Prtry Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35</p>
3.22	0..n	Customer Payment Status Report V03 +Original Payment Information And Status ++Transaction Information And Status +++Status Reason Information ++++Additional Information	<p>ISO Name Additional Information ISO Definition Further details on the status reason.</p> <p>Usage: Additional information can be used for several purposes such as the reporting of repaired information.</p> <p>XML Tag AddtlInf Type Max105Text ISO Length 1 .. 105 SEPA Length 1 .. 105</p>
3.23	0..n	Customer Payment Status Report V03 +Original Payment Information And Status ++Transaction Information And Status +++Charges Information	<p>ISO Name Charges Information ISO Definition Provides information on the charges related to the processing of the rejection of the instruction. Usage: This is passed on for information purposes only. Settlement of the charges will be done separately.</p> <p>XML Tag ChrgsInf Type ChargesInformation5</p>
3.24	0..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Transaction Information And Status +++Acceptance Date Time	<p>ISO Name Acceptance Date Time ISO Definition Point in time when the payment order from the initiating party meets the processing conditions of the account servicing agent. This means that the account servicing agent has received the payment order and has applied checks such as authorisation, availability of funds.</p> <p>XML Tag AccptncDtTm Type ISODateTime</p>

#	SEPA Mult	Message Element	SEPA Core Requirements	
3.25	0..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Transaction Information And Status +++Account Servicer Reference	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Account Servicer Reference Unique reference, as assigned by the account servicing institution, to unambiguously identify the instruction. AcctSvcrRef Max35Text 1 .. 35 1 .. 35
3.26	0..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Transaction Information And Status +++Clearing System Reference	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Clearing System Reference Unique reference, as assigned by a clearing system, to unambiguously identify the instruction. ClrSysRef Max35Text 1 .. 35 1 .. 35
3.27	1..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>An exact copy of all attributes of the received DS-03 which is being rejected.</i> Mandatory <i>The message elements under 'Original Transaction Reference' must be populated with the same value as the message elements of the original instruction, as defined within the following elements.</i> Original Transaction Reference Set of key elements used to identify the original transaction that is being referred to. OrgnlTxRef OriginalTransactionReference13
3.28	0..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Interbank Settlement Amount	ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits SEPA Inclusive	Interbank Settlement Amount Amount of money moved between the instructing agent and the instructed agent. IntrBkSttlmAmt ActiveOrHistoricCurrencyAndAmount 5 18 0 ..
3.29	0..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Amount	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-06 Amount of the Collection in euro.</i> Amount Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party. Amt AmountType3Choice
3.30	0..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Interbank Settlement Date	ISO Name ISO Definition XML Tag Type	Interbank Settlement Date Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. IntrBkSttlmDt ISODate
3.31	0..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Requested Collection Date	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-11 Due date of the Collection.</i> Requested Collection Date Date and time at which the creditor requests that the amount of money is to be collected from the debtor. ReqdColltmDt ISODate

#	SEPA Mult	Message Element	SEPA Core Requirements	
3.32	0..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Requested Execution Date	ISO Name ISO Definition XML Tag Type	Requested Execution Date Date at which the initiating party requests the clearing agent to process the payment. Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank. ReqdExctnDt ISODate
3.33	0..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Creditor Scheme Identification	SEPA Rulebook ISO Name ISO Definition XML Tag Type	AT-02 Identifier of the Creditor. Creditor Scheme Identification Credit party that signs the mandate. CdtrSchmId PartyIdentification32
3.34	0..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Settlement Information	ISO Name ISO Definition XML Tag Type	Settlement Information Specifies the details on how the settlement of the original transaction(s) between the instructing agent and the instructed agent was completed. SttlmInf SettlementInformation13
3.35	1..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Payment Type Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	AT-20 Identification code of the Scheme. AT-21 Transaction / Sequence Type. AT-59 Category purpose of the Collection. Payment Type Information Set of elements used to further specify the type of transaction. PmtTpInf PaymentTypeInformation22
3.36	0..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Payment Method	ISO Name ISO Definition XML Tag Type	Payment Method Specifies the means of payment that will be used to move the amount of money. PmtMtd PaymentMethod4Code
3.37	1..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Mandate Related Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	AT-01 Unique Mandate reference. AT-16 Placeholder for the electronic signature data, if applicable. AT-17 Type of Mandate (paper or electronic). AT-18 Identifier of the original Creditor who issued the Mandate. AT-19 Unique Mandate reference as given by the original Creditor who issued the Mandate. AT-24 Reason for Amendment of the Mandate. AT-25 Signing date of the Mandate. AT-60 Reference of the validation made by the Debtor Bank (if present in DS-03). Mandate Related Information Set of elements used to provide further details of the mandate signed between the creditor and the debtor. MndtRltdInf MandateRelatedInformation6
3.38	0..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Remittance Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	AT-22 Remittance information. Remittance Information Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system. RmtInf RemittanceInformation5

#	SEPA Mult	Message Element	SEPA Core Requirements	
3.39	0..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Ultimate Debtor	<i>SEPA Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-15 Name of the Debtor Reference Party.</i> <i>AT-37 Identification code of the Debtor Reference Party.</i> Ultimate Debtor Ultimate party that owes an amount of money to the (ultimate) creditor. UltmtDbtr PartyIdentification32
3.40	0..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Debtor	<i>SEPA Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-14 Name of the Debtor.</i> <i>AT-09 Address of the Debtor.</i> <i>AT-27 Debtor identification code.</i> Debtor Party that owes an amount of money to the (ultimate) creditor. Dbtr PartyIdentification32
3.41	0..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Debtor Account	<i>SEPA Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-07 Account number (IBAN) of the Debtor.</i> Debtor Account Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction. DbtrAcct CashAccount16
3.42	0..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Debtor Agent	<i>SEPA Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-13 BIC of the Debtor Bank (if present in DS-03).</i> Debtor Agent Financial institution servicing an account for the debtor. DbtrAgt BranchAndFinancialInstitutionIdentification4
3.43	0..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Debtor Agent Account	ISO Name ISO Definition XML Tag Type	Debtor Agent Account Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain. DbtrAgtAcct CashAccount16
3.44	0..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Creditor Agent	<i>SEPA Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-12 BIC of the Creditor Bank (if present in DS-03).</i> Creditor Agent Financial institution servicing an account for the creditor. CdtrAgt BranchAndFinancialInstitutionIdentification4
3.45	0..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Creditor Agent Account	ISO Name ISO Definition XML Tag Type	Creditor Agent Account Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction. CdtrAgtAcct CashAccount16
3.46	0..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Creditor	<i>SEPA Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-03 Name of the Creditor.</i> <i>AT-05 Address of the Creditor.</i> Creditor Party to which an amount of money is due. Cdtr PartyIdentification32

#	SEPA Mult	Message Element	SEPA Core Requirements	
3.47	0..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Creditor Account	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-04 Account number (IBAN) of the Creditor.</i> Creditor Account Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction. CdtrAcct CashAccount16
3.48	0..1	Customer Payment Status Report V03 +Original Payment Information And Status ++Transaction Information And Status +++Original Transaction Reference ++++Ultimate Creditor	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-38 Name of the Creditor Reference Party.</i> <i>AT-39 Identification code of the Creditor Reference Party.</i> Ultimate Creditor Ultimate party to which an amount of money is due. UltmtCdtr PartyIdentification32

2.3.2 Message Element Specifications

The reasons for a **reject by the Creditor Bank or the CSM** as present in the Rulebook are mapped to the ISO codes in the table below. Other ISO codes may be used when the Creditor Bank has rejected the message.

ISO Code	ISO Name	SEPA Reason as specified in the Rulebook
AC01	IncorrectAccountNumber	Account identifier incorrect (i.e. invalid IBAN)
AC04	ClosedAccountNumber	Account closed
AC06	BlockedAccount	Account blocked Account blocked for Direct Debit by the Debtor
AC13	InvalidDebtorAccountType	Debtor account is a consumer account
AG01	TransactionForbidden	Direct debit forbidden on this account for regulatory reasons
AG02	InvalidBankOperationCode	Operation code/transaction code/sequence type incorrect, invalid file format <i>Usage Rule:</i> To be used to indicate an incorrect operation code/transaction code/sequence type
AM04	InsufficientFunds	Insufficient funds
AM05	Duplication	Duplicate collection
BE01	InconsistentWithEndCustomer	Debtor's name does not match with the account holder's name.
BE05	UnrecognisedInitiatingParty	Identifier of the Creditor incorrect.
FF01	InvalidFileFormat	Operation/transaction code incorrect, invalid file format <i>Usage Rule:</i> To be used to indicate an invalid file format
MD01	NoMandate	No Mandate or unable to obtain mandate confirmation from the Debtor
MD02	MissingMandatoryInformationInMandate	Mandate data missing or incorrect
MD07	EndCustomerDeceased	Debtor deceased
MS02	NotSpecifiedReasonCustomerGenerated	Refusal by the Debtor
MS03	NotSpecifiedReasonAgentGenerated	Reason not specified
RC01	BankIdentifierIncorrect	Bank identifier incorrect (i.e. invalid BIC)
RR01	MissingDebtorAccountOrIdentification	Regulatory reason
RR02	MissingDebtorNameOrAddress	Regulatory Reason
RR03	MissingDebtorNameOrAddress	Regulatory Reason
RR04	RegulatoryReason	Regulatory Reason
SL01	DueToSpecificServiceOfferedByDebtor	Specific service offered by the Debtor Bank

ISO Code	ISO Name	SEPA Reason as specified in the Rulebook
	Agent	
DNOR	Debtor bank is not registered	Debtor Bank is not registered under this BIC in the CSM
CNOR	Creditor bank is not registered	Creditor Bank is not registered under this BIC in the CSM

List of changes in Business-to-Business Direct Debit C2B Implementation Guidelines Relative to v6.0

(This list is for information – the changes included in the body of the document are the changes in effect)

SYMBOLS USED

1. Column one contains the identification number of the Change
2. Column two contains the reference(s) to the relevant Index Number
3. Column three contains the reference(s) to the relevant section or message element (including full path)
4. Column four contains a description of the change
5. Column five contains a status code:
 - REJ: Rejected by the SPS WG
 - PEN: Issue pending in the SPS WG
 - ACC: Accepted by the SPS WG in Guidelines
6. Column six contains the type of change:
 - TYPO: Typing and layout errors
 - CLAR: Clarification of the text
 - CHAN: Change in or further alignment with the Rulebook content

N°	#	Section / Message Element	Description	Status	Type
15/01	N/A	1.5.4 SMNDA	In the previous versions of the Guidelines, the acronym 'SMNDA' was used to indicate Same Mandate with a New Debtor Agent . However, when the Creditor only receives the IBAN it will not always be possible to derive if an account change took place in the same or in another bank. To better accommodate this situation, the definition of the acronym 'SMNDA' has been updated to indicate Same Mandate with a New Debtor Account .	ACC	CHAN
15/02	N/A	2.3.1 Use of the Customer Payment Status Report	Update (bold text): The code 'RJCT' must be used in 'Group Status', ' Payment Information Status ' or 'Transaction Status', to transport the B2B Direct Debit Reject instruction between the bank and its remitting customer.	ACC	CLAR
15/03	2.14	Customer Direct Debit Initiation V02 +Payment Information ++Payment Type Information +++Sequence Type	Usage Rule: "If 'Amendment Indicator' is 'true', and 'Original Debtor Agent' is set to 'SMNDA', this message element must indicate 'FRST'" Replaced by: Usage Rule: "If 'Amendment Indicator' is 'true', and 'Original Debtor Account' is set to 'SMNDA', this message element indicates either 'FRST', 'RCUR', 'FNAL' or 'OOFF' (all four codes allowed, no restrictions)." Pre-notice was removed.	ACC	CHAN

N°	#	Section / Message Element	Description	Status	Type
15/04	2.40	Customer Direct Debit Initiation V02 +Payment Information ++Creditor Agent +++Financial Institution Identification ++++BIC	Following text: “The BIC is optional for national transactions except if Member States use the waiver as per Article 16(6) of EU Regulation 260/2012.The BIC is mandatory for EU/EEA cross-border transactions until 31 January 2016 and it will continue to be mandatory for non-EU/non-EEA cross-border SEPA transactions.” Replaced by: “The BIC is mandatory for non-EU/non-EEA cross-border SEPA transactions.”	ACC	CLAR
15/05	2.98	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Mandate Related Information +++++Amendment Information Details ++++++Original Debtor Account	Deleted Usage Rule: “Only IBAN is allowed. To be used only for changes of accounts within the same bank” Added Usage Rule: “To use ‘Identification’ under ‘Other’ under ‘Identification’ with code ‘SMNDA’ to indicate same mandate with new Debtor Account.” or Added Usage Rule: “In case of an account change within the same bank, IBAN is allowed.”	ACC	CHAN
15/06	2.99	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Direct Debit Transaction ++++Mandate Related Information +++++Amendment Information Details ++++++Original Debtor Agent	Deleted Usage Rule: “To use ‘Identification’ under ‘Other’ under ‘Financial Institution Identification’ with code ‘SMNDA’ to indicate same mandate with new Debtor Agent.” Added Usage Rule: “Not to be used if element ‘Original Debtor Account’ is populated with ‘SMNDA’.” Deleted Usage Rule: “To be used with the ‘FRST’ indicator in the ‘Sequence Type’.” Pre-notice was removed.	ACC	CHAN
15/07	2.129	Customer Direct Debit Initiation V02 +Payment Information ++Direct Debit Transaction Information +++Debtor Agent ++++Financial Institution Identification +++++BIC	Following text: “The BIC is optional for national transactions except if Member States use the waiver as per Article 16(6) of EU Regulation 260/2012.The BIC is mandatory for EU/EEA cross-border transactions until 31 January 2016 and it will continue to be mandatory for non-EU/non-EEA cross-border SEPA transactions.” Replaced by: “The BIC is mandatory for non-EU/non-EEA cross-border SEPA transactions.”	ACC	CLAR