



Published on 6 October 2025

Important update

As of 15 November 2026, the unstructured address format can no longer be provided in EPC payment messages.

In this document, every reference to 22 November 2026 is no longer valid and has to be read as 15 November 2026.



SEPA Instant Credit Transfer Scheme Inter-PSP Implementation Guidelines

EPC122-16 / 2025 Version 1.0 / Date issued: 28 November 2024 / Date effective: 5 October 2025 /

Effective time: 03:30:00.000 CET

Public



Abstract

This document sets out the rules for implementing Version 1.1 of the 2025 SEPA Instant Credit Transfer Scheme Rulebook, based on the 2019 message version of the ISO 20022 standard.



TABLE OF CONTENTS

0	DOCUMENT INFORMATION	2
0.1	REFERENCES	2
0.2	CHANGE HISTORY	2
0.3	PURPOSE OF DOCUMENT	3
1	INTRODUCTION	3
1.1	COVERAGE OF THE SEPA IMPLEMENTATION GUIDELINES	4
1.2	USE OF THESE GUIDELINES BY THE INSTRUCTING AND INSTRUCTED PARTIES	6
1.3	NOTATION CONVENTIONS	7
1.4	CHARACTER SET	8
1.5	GENERAL MESSAGE ELEMENT SPECIFICATIONS	9
1.5.1	<i>BIC</i>	9
1.5.2	<i>Timestamps</i>	9
1.6	IMPLEMENTATION OF ISO 20022 XML RULES	9
1.7	CHANGE OVER DATE	9
2	MANDATORY PSP-TO-PSP MESSAGES	10
2.1	INTER-PSP PAYMENT DATASET (DS-02)	10
2.1.1	<i>Use of FI to FI Customer Credit Transfer (pacs.008.001.08)</i>	10
2.2	NEGATIVE CONFIRMATION MESSAGE (DS-03)	38
2.2.1	<i>Use of the FI to FI Payment Status Report (pacs.002.001.10)</i>	38
2.2.2	<i>Message Element Specifications</i>	48
2.3	POSITIVE CONFIRMATION MESSAGE (DS-03)	50
2.3.1	<i>Use of the FI to FI Payment Status Report (pacs.002.001.10)</i>	50
2.4	RECALL OF AN SCT INST DATASET (DS-05)	59
2.4.1	<i>Use of FI-to-FI Payment Cancellation Request (camt.056.001.08)</i>	59
2.5	INTER-PSP NEGATIVE RESPONSE TO A RECALL OF AN SCT INST DATASET (DS-06)	69
2.5.1	<i>Use of Resolution of Investigation (camt.029.001.09)</i>	69
2.6	INTER-PSP POSITIVE RESPONSE TO A RECALL OF AN SCT INST DATASET (DS-06)	80
2.6.1	<i>Use of the Payment Return (pacs.004.001.09)</i>	80
2.7	REQUEST FOR STATUS UPDATE ON A RECALL OF AN SCT INST	95
2.7.1	<i>Use of the FI to FI Payment Status Request (pacs.028.001.03)</i>	95
2.8	DATASET FOR THE SCT INST TRANSACTION STATUS INVESTIGATION MESSAGE SENT BY THE ORIGINATOR PSP (DS-07)	103
2.8.1	<i>Use of FI To FI Payment Status Request (pacs.028.001.03)</i>	103
2.9	REQUEST FOR RECALL BY THE ORIGINATOR DATASET (DS-08)	111
2.9.1	<i>Use of FI To FI Payment Cancellation Request (camt.056.001.08)</i>	111
2.10	INTER-PSP NEGATIVE RESPONSE TO THE REQUEST FOR RECALL BY THE ORIGINATOR DATASET (DS-09)	121
2.10.1	<i>Use of Resolution of Investigation (camt.029.001.09)</i>	121
2.11	INTER-PSP POSITIVE RESPONSE TO THE REQUEST FOR RECALL BY THE ORIGINATOR	132
2.11.1	<i>Use of inter-PSP return credit transfer message (pacs.004.001.09)</i>	132
2.12	REQUEST FOR STATUS UPDATE ON A REQUEST FOR RECALL BY THE ORIGINATOR	147
2.12.1	<i>Use of FI To FI Payment Status Request (pacs.028.001.03)</i>	147
3	LIST OF CHANGES IN THE SCT INST INTER-PSP IMPLEMENTATION GUIDELINES - RELATIVE TO 2023 VERSION V1.2	155



0 Document Information

0.1 References

This section lists relevant documents of interest.

	Document Number	Title	Issued by:
[1]	EPC004-16	SEPA Instant Credit Transfer Scheme Rulebook 2025 Version 1.1	EPC
[2]	-	ISO 20022 XML Credit Transfers and Related Messages Note: The 2025 IGs are based on the 2019 message version of ISO 20022.	ISO 20022
[3]	ISO 3166	Country Codes	ISO
[4]	ISO 4217	Currency Code List	ISO
[5]	ISO 9362	Business Identifier Codes (BIC)	ISO
[6]	ISO 13616	IBAN: International Bank Account Number	ISO ¹
[7]	ISO 11649	Structured creditor reference to remittance information	ISO
[8]	EPC217-08	SEPA Requirements for an Extended Character Set	EPC
[9]	EPC230-15	Clarification Paper on the Use of Slashes in References, Identifications and Identifiers	EPC
[10]	-	XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004	W3C
[11]	EPC153-22	EPC Guidance Document: Provision of Addresses under the EPC Payment Schemes	EPC
[12]	EPC088-22	EPC Guidance Document – Improve Transparency for Retail Payment End-Users	EPC

0.2 Change History

Issue number	Dated	Reason for revision
2017 V1.0	20161124	EPC Board approval November 2016

¹ See also <https://www.swift.com/standards/data-standards/iban-international-bank-account-number>



2017 V1.1	20170719	Scheme Management Board approval July 2017
2017 V1.2	20171114	Scheme Management Board approval October 2017
2019 V1.0	20181031	Scheme Management Board approval October 2018
2021 V1.0	20201029	Scheme Management Board approval October 2020
2023 V1.0	20220428	Scheme Management Board approval April 2022
2025 V1.0	20241031	Approval by the October 2024 Payment Scheme Management Board (PSMB)

0.3 Purpose of Document

The objective of these Guidelines is to define the rules to be applied to the inter-Payment Service Provider (PSP) ISO 20022 XML message standards for the implementation of the SEPA Instant credit transfers (SCT Inst) as defined in the SEPA Instant Credit Transfer Scheme Rulebook.

Note: In section 4.2.3. B of the SCT Inst Rulebook it is stated that "Participants are free to agree on a bilateral or multilateral basis with other Participants on a target maximum execution time of less than 5 seconds. This lower target maximum execution time only applies to those Participants that have concluded such agreement". In this context it is advised to use data elements 'Local Instrument', 'Category Purpose' or a combination of these data elements to uniquely identify transactions falling under such agreements.

Note: The term "bank" has been replaced by "PSP" in all the EPC SEPA payment scheme rulebooks and associated implementation guidelines to formally reflect the changes introduced by the Payment Services Directive (PSD) to the categories of institutions that can offer payment services, and the variety in PSP categories that are eligible to adhere to the EPC SEPA payment schemes. However, please note that in the context of ISO, the term "bank" is still used.

Note: The term 'Customer' is to be understood as 'Payment Service User' (PSU), meaning a natural or legal person making use of a payment service in the capacity of payer, payee, or both. Such person can take up the role of Originator and/or Beneficiary under the Scheme.

1 Introduction

This document sets out the SEPA rules for implementing the inter-PSP credit transfer ISO 20022 XML message standards. The SEPA Instant Credit Transfer Scheme Rulebook defines data sets which are implemented in the relevant ISO 20022 XML message standard as follows:

SEPA Instant Credit Transfer Scheme Rulebook	ISO 20022 XML Message Standards
DS-02 <i>Inter-PSP Payment Dataset</i>	FI to FI Customer Credit Transfer (pacs.008.001.08)
DS-03 <i>Confirmation Message</i>	Negative confirmation (RJCT) – FI to FI Payment Status Report (pacs.002.001.10)



	Positive confirmation (ACCP) – FI to FI Payment Status Report (pacs.002.001.10)
<i>DS-05 The Recall of an SCT Inst Dataset</i>	FI to FI Payment Cancellation Request (camt.056.001.08)
<i>DS-06 Response to a Recall of an SCT Inst Dataset</i>	Negative Response: Resolution of Investigation (camt.029.001.09) Positive Response: Payment Return (pacs.004.001.09)
<i>DS-07 Dataset for the SCT Inst Transaction status investigation message sent by the Originator PSP</i>	FI To FI Payment Status Request (pacs.028.001.03)
<i>DS-08 Request for Recall by the Originator Dataset</i>	FI to FI Payment Cancellation Request (camt.056.001.08)
<i>DS-09 Response to the Request for Recall by the Originator Dataset</i>	Negative Response: Resolution of Investigation (camt.029.001.09) Positive Response: Payment Return (pacs.004.001.09)
<i>Request for Status Update on a Request for Recall (step CT-02.07 under 4.3.2.2)</i> <i>Request for Status Update on a Request for Recall by the Originator (step 4C under 4.3.2.3)</i>	FI To FI Payment Status Request (pacs.028.001.03)

The Guidelines for the inter-PSP instant credit transfer message standards are mandatory.

1.1 Coverage of the SEPA Implementation Guidelines

The purpose of the SEPA Implementation Guidelines, hereafter referred to as the Guidelines, is to provide guidance on the use of the Global ISO 20022 XML standards in making SEPA core payments as defined in the SEPA scheme rulebooks and supplemented by processing requirements.



The Guidelines are fully aligned to the SEPA core requirements as defined in the Rulebook and identify message elements needed for inter-PSP processing while recognising message elements that may be available for use in Additional Optional Services (AOS), as shown below.

Global ISO 20022 XML Message Standards			
Message elements from the ISO messages corresponding to Rulebook requirements	Message elements that are mandatory in the ISO messages or needed for Inter-PSP Processing	Message elements from the ISO messages available for use by AOS within an EPC Governance framework	Message elements from ISO messages not applicable to SEPA
EPC Implementation Guidelines for SEPA Core Mandatory subset, identifying elements <ul style="list-style-type: none">- to be used as defined in ISO- to be used with SEPA usage rules (from or completing the Rulebook) Note: yellow fields can be used in a specific way for an AOS.		To be developed and documented by AOS Communities	Not available for use in SEPA payments
SEPA Payments			

Figure 1

These Guidelines define the SEPA Core Mandatory Subset² of the Global ISO 20022 XML standard that consists of message elements:

- required in the Rulebook as business requirements
- needed for processing by PSPs and clearing and settlement mechanisms

These message elements define the **SEPA core service** and are denoted by yellow shading in the message structures given in the following chapters. Only these elements are further detailed with relevant SEPA core requirements, such as the use of the message element, its components or the values that must be used. Usage rules, for example, may indicate limits on the number of repetitions, or code value restrictions, while format rules may be used to indicate the allowable combinations of components of a message element.

These Guidelines also recognise message elements and the usage rules in the ISO 20022 XML standard that may be available for use in an AOS, subject to a governance framework to be defined by the EPC. The definition and documentation of these message elements are a matter for the AOS communities involved. These message elements are denoted by white shading.

Where there are message elements that do not apply to SEPA payments, these are denoted with red shading in the right-most column of the message structures. To date, few such message elements have been identified.

² The SEPA Core Mandatory Subset is hereafter known as the SEPA core service.



1.2 Use of these Guidelines by the instructing and instructed parties³

- SEPA core payments are executed using messages only containing message elements defined as part of the SEPA Core Mandatory Subset (shaded yellow in Figure 2).
- Payments that include message elements that are defined and documented by AOS communities (shaded white/yellow in Figure 2) are considered as SEPA payments, but not as SEPA core payments.
- It is the responsibility of the instructing PSP of the message to ensure that message elements defined for use in an AOS are only included in messages sent to AOS community members.
- The instructed PSP receiving a message containing AOS-related message elements, but which is not a member of the AOS community, may ignore the information, that is, not use it for processing, nor forward it to the next party in the chain. The instructed PSP, however, may reject the message for this reason.

³ Instructing and instructed parties include CSMs.



1.3 Notation Conventions

The Guidelines are presented in a similar format than the one used in the ISO 20022 XML standard.

#	SEPA Mul	Message Element	SEPA Core Requirements
1.00	1..1	Message root +Group Header ++Sublevel 1 +++Sublevel 2	<i>SEPA Usage Rule(s)</i> (e.g. Mandatory) <i>SEPA Format Rule(s)</i> ISO Name ISO Definition XML Tag Type (Yellow: Message Element that is part of the SEPA Core Service)
	1..1		XML Tag xs:choice
1.01	1..1	Message root +Group Header ++Sublevel 1 +++Sublevel 2 ++++Sublevel 3	<i>SEPA Rulebook</i> (Attribute used in Rulebook) <i>SEPA Usage Rule(s)</i> (e.g. Only 'SEPA' is allowed.) ISO Name ISO Definition XML Tag Type ISO Length <i>SEPA Length</i> (Yellow: Message Element that is part of the SEPA Core Service)
			SEPA Code restrictions
			SEPA <i>SingleEuroPaymentsArea</i> <i>Payment must be executed following the Single Euro Payments Area scheme.</i>
1.02	1..1	Message root +Group Header ++Sublevel 1 +++Sublevel 2 ++++Sublevel 3	ISO Name ISO Definition XML Tag Type (White: Message Element that is not part of the Core Service but is available for use in a SEPA AOS)
1.0n	0..1	Message root +Group Header ++Sublevel 1	ISO Name ISO Definition XML Tag Type (Red: Message Element that is not to be used in SEPA Payments)

Figure 2

Where:

- Column 1 indicates the message element Index number specific to these Implementation Guidelines..
Components of message elements that are not allowed in SEPA payments or where no SEPA requirements are defined are not displayed in full as the ISO 20022 XML standard applies.
- Column 2 indicates the mandatory or optional status and the number of repetitions defined by the SEPA Core Requirements, e.g.:
 - 0..1 element is optional and may only be present once
 - 0..n element is optional with unlimited repetition
 - 1..1 element is mandatory and must be present exactly once
 - 1..n element is mandatory with unlimited repetition



The displayed SEPA multiplicity may thus differ from the one of the ISO 20022 XML standard. When an element is shaded yellow, possible remaining ISO 20022 occurrences are available for use in an AOS.

Empty elements are not allowed (i.e. a message shall not contain elements without content).

- Column 3 indicates the full path of an element where the last line contains the name of the message element as defined in the ISO 20022 XML standard. When an element contains sub-elements these are indented to the right and noted with a plus sign (+) per level.
- Column 4 specifies in italic characters the SEPA Core Requirements as additional rules to those specified in the ISO 20022 XML standard, which are shown in non-italic characters.
 - When defined in the Rulebook, the attribute is indicated by the attribute name and where applicable, the number, i.e., AT-XXXX. Those message elements are shaded yellow.
 - When the message element relates to inter-PSP processing requirements, it is shaded yellow.
 - When the message element specified in the ISO 20022 XML standard is used for SEPA payments without change (regarding the definition and any usage rules), no specific SEPA Core requirements are provided and is shaded yellow.
 - When the message element is specified in the ISO 20022 XML standard as optional, but is mandatory in SEPA Core requirements, this is specified as 'Mandatory' and is shaded yellow.
 - When the message element is not available for use in SEPA payments, this is indicated with red shading. Note that these message elements are similarly not available for use in an AOS.
 - The SEPA length is indicated for every message element (if applicable), even if it is the same length as in the ISO 20022 XML standard.

Column 4 may also indicate conditional relations between message components or elements, e.g. either component 1 or component 2 must be present, component 1 and component 2 are mutually exclusive. For XML Tag "xs:choice" (containing just one subsequent component or element due to applied restrictions on subsequent components or elements) column 4 may indicate, that the "choice" nature is lost due to applied restrictions i.e. only one element is shaded yellow.

1.4 Character Set

The character set issue centres on the use of the full set characters in the message elements. Two considerations are:

- While PSPs must be allowed to use the character set currently in use at national level,
- PSPs throughout SEPA cannot be required to support the full character set used in SEPA countries.

Therefore:

- The ISO 20022 XML messages allow for the full range of global language requirements (UTF-8).



- PSPs must be able to support the Latin character set commonly used in international communication, as follows:
a b c d e f g h i j k l m n o p q r s t u v w x y z
A B C D E F G H I J K L M N O P Q R S T U V W X Y Z
0 1 2 3 4 5 6 7 8 9
/ - ? : () . , ' +
Space
- References, identifications and identifiers must respect the following [9]:
 - Content is restricted to the Latin character set as defined above
 - Content must not start or end with a '/'
 - Content must not contain '//'

Note: When a slash is used as delimiter between the attribute number (AT-XXXX) or code (ABCD) and the data content, no space is allowed directly after this slash.

However, there may be bilateral or multilateral agreements to support one or more sets of characters beyond the Latin character set referred to above.

1.5 General Message Element Specifications

1.5.1 BIC

The BIC used to identify financial institutions (Agents in the ISO 20022 XML standards) may be either BIC 11 or BIC 8.

Depending on the version of the ISO 20022 message used, the BIC of a financial institution may be populated either in a <BIC> or in a <BICFI> element (for the pacs.028 message).

1.5.2 Timestamps

Timestamps must be unambiguous and include milliseconds. The representation of milliseconds must follow the W3C recommendation" [10].

The Timestamp pattern included in the XSD is the following:

```
[0-9]{4}(-[0-9]{2}){2}T[0-9]{2}(:[0-9]{2}){2}(\.[0-9]{0,2}[1-9])?(Z|([-+][0-9]{2}(:[0-9]{2})?))
```

1.6 Implementation of ISO 20022 XML rules

This document should be read in conjunction with the ISO 20022 XML message standards.

1.7 Change Over Date

As from the change-over date, receiving PSPs may only receive messages, including the r-messages, in the new version.

Note: As of 22 November 2026 at 03:30 CET only the use of structured and hybrid addresses will be allowed (i.e. the provision of unstructured addresses is no longer allowed as from this date). For further details, please see EPC Guidance Document "Provision of Addresses under the EPC Payment Schemes" [11].



2 Mandatory PSP-to-PSP Messages

2.1 Inter-PSP Payment Dataset (DS-02)

2.1.1 Use of FI to FI Customer Credit Transfer (pacs.008.001.08)

The message is used to transport the SCT Inst payment instruction from the Originator PSP to the Beneficiary PSP, directly or through intermediaries.

The message caters for a single payment instruction.

Note: The use of SCT Inst is implied by element 'Local Instrument' being mandatory and 'Code' set to "INST" (Instant Credit Transfer) only.



#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements	
		Document	XML Tag Type	Document Document
	1..1	FITo FICustomer Credit Transfer V08	ISO Name ISO Definition XML Tag Type	FITo FICustomer Credit Transfer V08 Scope The FinancialInstitutionToFinancialInstitutionCustomerCreditTransfer message is sent by the debtor agent to the creditor agent, directly or through other agents and/or a payment clearing and settlement system. It is used to move funds from a debtor account to a creditor. FIToFICstmrCdtTrf FIToFICustomerCreditTransferV08
1.0	1..1	FITo FICustomer Credit Transfer V08 +Group Header	ISO Name ISO Definition XML Tag Type	Group Header Set of characteristics shared by all individual transactions included in the message. GrpHdr GroupHeader93
1.1	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Message Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Message Identification Point to point reference, as assigned by the instructing party, and sent to the next party in the chain to unambiguously identify the message. Usage: The instructing party has to make sure that MessageIdentification is unique per instructed party for a pre-agreed period. MsgId Max35Text 1 .. 35 1 .. 35
1.2	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Creation Date Time	ISO Name ISO Definition XML Tag Type	Creation Date Time Date and time at which the message was created. CreDfTm ISODateTime
1.3	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Batch Booking	ISO Name ISO Definition XML Tag Type	Batch Booking Identifies whether a single entry per individual transaction or a batch entry for the sum of the amounts of all transactions within the group of a message is requested. Usage: Batch booking is used to request and not order a possible batch booking. BtchBookg BatchBookingIndicator
1.4	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Number Of Transactions	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type Pattern	<i>The number of transactions is limited to one.</i> Number Of Transactions Number of individual transactions contained in the message. NbOfTxs Max15NumericText [0-9]{1,15}
1.5	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Control Sum	ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits	Control Sum Total of all individual amounts included in the message, irrespective of currencies. CtrlSum DecimalNumber 17 18



#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements
1.6	1..1	FIto FICustomer Credit Transfer V08 +Group Header ++Total Interbank Settlement Amount	<p>SEPA Usage Rule(s) <i>Mandatory.</i> <i>Only 'EUR' is allowed.</i> <i>Amount must be 0.01 or more and 99999999999999.99 or less.</i> <i>The fractional part has a maximum of two digits.</i></p> <p>SEPA Format Rule(s)</p> <p>ISO Name Total Interbank Settlement Amount</p> <p>ISO Definition Total amount of money moved between the instructing agent and the instructed agent.</p> <p>XML Tag TtlIntrBkSttlmAmt</p> <p>Type ActiveCurrencyAndAmount</p> <p>SEPA FractDigits 2</p> <p>TotalDigits 18</p> <p>SEPA Inclusive 0.01 .. 99999999999999.99</p>
1.7	1..1	FIto FICustomer Credit Transfer V08 +Group Header ++Interbank Settlement Date	<p>SEPA Rulebook <i>AT-T051 The Settlement Date of the SCT Inst Transaction.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Interbank Settlement Date</p> <p>ISO Definition Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.</p> <p>XML Tag IntrBkSttlmDt</p> <p>Type ISODate</p>
1.8	1..1	FIto FICustomer Credit Transfer V08 +Group Header ++Settlement Information	<p>ISO Name Settlement Information</p> <p>ISO Definition Specifies the details on how the settlement of the transaction(s) between the instructing agent and the instructed agent is completed.</p> <p>XML Tag SttlmInf</p> <p>Type SettlementInstruction7</p>
1.9	1..1	FIto FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Settlement Method	<p>SEPA Usage Rule(s) <i>Only "CLRG", "INGA" and "INDA" are allowed.</i></p> <p>ISO Name Settlement Method</p> <p>ISO Definition Method used to settle the (batch of) payment instructions.</p> <p>XML Tag SttlmMtd</p> <p>Type SettlementMethod1Code</p> <p>SEPA Code Restrictions</p> <p>CLRG <i>ClearingSystem</i> <i>Settlement is done through a payment clearing system.</i></p> <p>INDA <i>InstructedAgent</i> <i>Settlement is done by the agent instructed to execute a payment instruction.</i></p> <p>INGA <i>InstructingAgent</i> <i>Settlement is done by the agent instructing and forwarding the payment to the next party in the payment chain.</i></p>
1.10	0..1	FIto FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Settlement Account	<p>SEPA Usage Rule(s) <i>Only 'Identification' is allowed.</i></p> <p>ISO Name Settlement Account</p> <p>ISO Definition A specific purpose account used to post debit and credit entries as a result of the transaction.</p> <p>XML Tag SttlmAcct</p> <p>Type CashAccount38</p>
1.11	0..1	FIto FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Clearing System	<p>ISO Name Clearing System</p> <p>ISO Definition Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.</p> <p>XML Tag ClrSys</p> <p>Type ClearingSystemIdentification3Choice</p>
	1..1		XML Tag xs:choice



#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements
1.12	1..1	FIto FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Clearing System ++++Code	<p>ISO Name Code</p> <p>ISO Definition Infrastructure through which the payment instruction is processed, as published in an external clearing system identification code list.</p> <p>XML Tag Cd</p> <p>Type ExternalCashClearingSystem1 Code</p> <p>ISO Length 1 .. 3</p> <p>SEPA Length 1 .. 3</p>
1.13	1..1	FIto FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Clearing System ++++Proprietary	<p>ISO Name Proprietary</p> <p>ISO Definition Clearing system identification in a proprietary form.</p> <p>XML Tag Prtry</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>
1.14	0..1	FIto FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Instructing Reimbursement Agent	<p>ISO Name Instructing Reimbursement Agent</p> <p>ISO Definition Agent through which the instructing agent will reimburse the instructed agent.</p> <p>XML Tag InstgRmbrsmntAgt</p> <p>Type BranchAndFinancialInstitutionIdentification6</p> <p>Usage: If InstructingAgent and InstructedAgent have the same reimbursement agent, then only InstructingReimbursementAgent must be used.</p>
1.15	0..1	FIto FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Instructing Reimbursement Agent Account	<p>ISO Name Instructing Reimbursement Agent Account</p> <p>ISO Definition Unambiguous identification of the account of the instructing reimbursement agent account at its servicing agent in the payment chain.</p> <p>XML Tag InstgRmbrsmntAgtAcct</p> <p>Type CashAccount38</p>
1.16	0..1	FIto FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Instructed Reimbursement Agent	<p>ISO Name Instructed Reimbursement Agent</p> <p>ISO Definition Agent at which the instructed agent will be reimbursed.</p> <p>XML Tag InstdRmbrsmntAgt</p> <p>Type BranchAndFinancialInstitutionIdentification6</p> <p>Usage: If InstructedReimbursementAgent contains a branch of the InstructedAgent, then the party in InstructedAgent will claim reimbursement from that branch/will be paid by that branch.</p> <p>Usage: If InstructingAgent and InstructedAgent have the same reimbursement agent, then only InstructingReimbursementAgent must be used.</p>
1.17	0..1	FIto FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Instructed Reimbursement Agent Account	<p>ISO Name Instructed Reimbursement Agent Account</p> <p>ISO Definition Unambiguous identification of the account of the instructed reimbursement agent account at its servicing agent in the payment chain.</p> <p>XML Tag InstdRmbrsmntAgtAcct</p> <p>Type CashAccount38</p>
1.18	0..1	FIto FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Third Reimbursement Agent	<p>ISO Name Third Reimbursement Agent</p> <p>ISO Definition Agent at which the instructed agent will be reimbursed.</p> <p>XML Tag ThrdRmbrsmntAgt</p> <p>Type BranchAndFinancialInstitutionIdentification6</p> <p>Usage: If ThirdReimbursementAgent contains a branch of the InstructedAgent, then the party in InstructedAgent will claim reimbursement from that branch/will be paid by that branch.</p>



#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements
1.19	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Settlement Information +++Third Reimbursement Agent Account	ISO Name Third Reimbursement Agent Account ISO Definition Unambiguous identification of the account of the third reimbursement agent account at its servicing agent in the payment chain. XML Tag ThrdRmbrsmntAgtAcct Type CashAccount38
1.20	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information	SEPA Usage Rule(s) <i>Mandatory.</i> ISO Name Payment Type Information ISO Definition Set of elements used to further specify the type of transaction. XML Tag PmtTpInf Type PaymentTypeInfo28
1.21	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Instruction Priority	ISO Name Instruction Priority ISO Definition Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the instruction. XML Tag InstrPrty Type Priority2Code
1.22	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Clearing Channel	ISO Name Clearing Channel ISO Definition Specifies the clearing channel to be used to process the payment instruction. XML Tag ClrChanl Type ClearingChannel2Code
1.23	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Service Level	SEPA Usage Rule(s) <i>Mandatory.</i> <i>Only one occurrence is allowed.</i> ISO Name Service Level ISO Definition Agreement under which or rules under which the transaction should be processed. XML Tag SvcLvl Type ServiceLevel8Choice
	1..1		XML Tag xs:choice
1.24	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Service Level ++++Code	SEPA Rulebook <i>AT-T001 The identification code of the SCT Inst Scheme.</i> SEPA Usage Rule(s) <i>Only "SEPA" is allowed.</i> ISO Name Code ISO Definition Specifies a pre-agreed service or level of service between the parties, as published in an external service level code list. XML Tag Cd Type ExternalServiceLevel1Code ISO Length 1 .. 4 SEPA Length 1 .. 4
			SEPA Code Restrictions SEPA <i>SingleEuroPaymentsArea</i> <i>Payment must be executed following the Single Euro Payments Area scheme.</i>
1.25	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Service Level ++++Proprietary	ISO Name Proprietary ISO Definition Specifies a pre-agreed service or level of service between the parties, as a proprietary code. XML Tag Prtry Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35
1.26	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Local Instrument	SEPA Usage Rule(s) <i>Mandatory.</i> ISO Name Local Instrument ISO Definition User community specific instrument. Usage: This element is used to specify a local instrument, local clearing option and/or further qualify the service or service level. XML Tag LclInstrm Type LocalInstrument2Choice



#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements	
	1..1		XML Tag	xs:choice
1.27	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Local Instrument ++++Code	SEPA Rulebook	<i>AT-T001 The identification code of the SCT Inst Scheme</i>
			SEPA Usage Rule(s)	Only "INST" is allowed.
			ISO Name	Code
			ISO Definition	Specifies the local instrument, as published in an external local instrument code list.
			XML Tag	Cd
			Type	ExternalLocalInstrument1Code
			ISO Length	1 .. 35
			SEPA Length	1 .. 35
			SEPA Code Restrictions	
			INST	<i>InstantCreditTransfer Transaction is related to an Instant Credit Transfer. Use case example: SEPA Instant Credit Transfer (SCT Inst)</i>
1.28	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Local Instrument ++++Proprietary	ISO Name	Proprietary
			ISO Definition	Specifies the local instrument, as a proprietary code.
			XML Tag	Prtry
			Type	Max35Text
			ISO Length	1 .. 35
			SEPA Length	1 .. 35
1.29	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Category Purpose	SEPA Rulebook	<i>AT-T008 The category purpose of the SCT Inst Instruction.</i>
			SEPA Usage Rule(s)	<i>Depending on the agreement between the Originator and the Originator PSP, 'Category Purpose' may be forwarded to the Beneficiary PSP.</i>
			ISO Name	Category Purpose
			ISO Definition	Specifies the high level purpose of the instruction based on a set of pre-defined categories. Usage: This is used by the initiating party to provide information concerning the processing of the payment. It is likely to trigger special processing by any of the agents involved in the payment chain.
			XML Tag	CtgyPurp
			Type	CategoryPurpose1Choice
	1..1		XML Tag	xs:choice
1.30	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Category Purpose ++++Code	ISO Name	Code
			ISO Definition	Category purpose, as published in an external category purpose code list.
			XML Tag	Cd
			Type	ExternalCategoryPurpose1Code
			ISO Length	1 .. 4
			SEPA Length	1 .. 4
1.31	1..1	FITo FICustomer Credit Transfer V08 +Group Header ++Payment Type Information +++Category Purpose ++++Proprietary	ISO Name	Proprietary
			ISO Definition	Category purpose, in a proprietary form.
			XML Tag	Prtry
			Type	Max35Text
			ISO Length	1 .. 35
			SEPA Length	1 .. 35
1.32	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Instructing Agent	SEPA Usage Rule(s)	Only 'BICFI' is allowed
			ISO Name	Instructing Agent
			ISO Definition	Agent that instructs the next party in the chain to carry out the (set of) instruction(s).
			XML Tag	InstgAgt
			Type	BranchAndFinancialInstitutionIdentification6



#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements
1.33	0..1	FITo FICustomer Credit Transfer V08 +Group Header ++Instructed Agent	<p>SEPA Usage Rule(s) Only 'BICFI' is allowed.</p> <p>ISO Name Instructed Agent</p> <p>ISO Definition Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s).</p> <p>XML Tag InstdAgt</p> <p>Type BranchAndFinancialInstitutionIdentification6</p>
2.0	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information	<p>SEPA Usage Rule(s) Only one occurrence is allowed.</p> <p>ISO Name Credit Transfer Transaction Information</p> <p>ISO Definition Set of elements providing information specific to the individual credit transfer(s).</p> <p>XML Tag CdtTrfTxInf</p> <p>Type CreditTransferTransaction39</p>
2.1	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Identification	<p>ISO Name Payment Identification</p> <p>ISO Definition Set of elements used to reference a payment instruction.</p> <p>XML Tag PmtId</p> <p>Type PaymentIdentification7</p>
2.2	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Identification +++Instruction Identification	<p>ISO Name Instruction Identification</p> <p>ISO Definition Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the instruction.</p> <p>Usage: The instruction identification is a point to point reference that can be used between the instructing party and the instructed party to refer to the individual instruction. It can be included in several messages related to the instruction.</p> <p>XML Tag InstrId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>
2.3	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Identification +++End To End Identification	<p>SEPA Rulebook AT-T014 Originator's Reference to the SCT Inst Transaction.</p> <p>SEPA Usage Rule(s) A customer reference that must be passed on in the end-to-end chain. In the event that no reference was given, "NOTPROVIDED" must be used.</p> <p>ISO Name End To End Identification</p> <p>ISO Definition Unique identification, as assigned by the initiating party, to unambiguously identify the transaction. This identification is passed on, unchanged, throughout the entire end-to-end chain.</p> <p>Usage: The end-to-end identification can be used for reconciliation or to link tasks relating to the transaction. It can be included in several messages related to the transaction.</p> <p>Usage: In case there are technical limitations to pass on multiple references, the end-to-end identification must be passed on throughout the entire end-to-end chain.</p> <p>XML Tag EndToEndId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>



#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements
2.4	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Identification +++Transaction Identification	<p>SEPA Rulebook AT-T054 The Originator PSP's reference number of the SCT Inst Transaction message.</p> <p>SEPA Usage Rule(s) Mandatory. Must contain a reference that is meaningful to the Originator's PSP and is unique over time.</p> <p>ISO Name Transaction Identification</p> <p>ISO Definition Unique identification, as assigned by the first instructing agent, to unambiguously identify the transaction that is passed on, unchanged, throughout the entire interbank chain. Usage: The transaction identification can be used for reconciliation, tracking or to link tasks relating to the transaction on the interbank level. Usage: The instructing agent has to make sure that the transaction identification is unique for a pre-agreed period.</p> <p>XML Tag TxId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>
2.5	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Identification +++UETR	<p>ISO Name UETR</p> <p>ISO Definition Universally unique identifier to provide an end-to-end reference of a payment transaction.</p> <p>XML Tag UETR</p> <p>Type UUIDv4Identifier</p> <p>Pattern [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}</p>
2.6	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Identification +++Clearing System Reference	<p>ISO Name Clearing System Reference</p> <p>ISO Definition Unique reference, as assigned by a clearing system, to unambiguously identify the instruction.</p> <p>XML Tag ClrSysRef</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>
2.7	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Payment Type Information	<p>ISO Name Payment Type Information</p> <p>ISO Definition Set of elements used to further specify the type of transaction.</p> <p>XML Tag PmtTpInf</p> <p>Type PaymentTypeInformation28</p>
2.8	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Interbank Settlement Amount	<p>SEPA Rulebook AT-T002 The amount of the SCT Inst in Euro.</p> <p>SEPA Usage Rule(s) Only 'EUR' is allowed. Amount must be 0.01 or more and 99999999.99 or less. The fractional part has a maximum of two digits.</p> <p>SEPA Format Rule(s)</p> <p>ISO Name Interbank Settlement Amount</p> <p>ISO Definition Amount of money moved between the instructing agent and the instructed agent.</p> <p>XML Tag IntrBkSttlmAmt</p> <p>Type ActiveCurrencyAndAmount</p> <p>SEPA FractDigits 2</p> <p>TotalDigits 18</p> <p>SEPA Inclusive 0.01 .. 99999999.99</p>
2.9	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Interbank Settlement Date	<p>ISO Name Interbank Settlement Date</p> <p>ISO Definition Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.</p> <p>XML Tag IntrBkSttlmDt</p> <p>Type ISODate</p>



#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements	
2.10	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Settlement Priority	ISO Name ISO Definition XML Tag Type	Settlement Priority Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the settlement instruction. SttlmPrty Priority3Code
2.11	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Settlement Time Indication	ISO Name ISO Definition XML Tag Type	Settlement Time Indication Provides information on the occurred settlement time(s) of the payment transaction. SttlmTmIndctn SettlementDateTimeIndication1
2.12	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Settlement Time Request	ISO Name ISO Definition XML Tag Type	Settlement Time Request Provides information on the requested settlement time(s) of the payment instruction. SttlmTmReq SettlementTimeRequest2
2.13	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Acceptance Date Time	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type Pattern	<i>AT-T056 Timestamp of the SCT Inst Transaction. Mandatory.</i> <i>Timestamps must be unambiguous and include milliseconds. The representation of milliseconds must follow the W3C recommendation. Only UTC time format or local time with UTC offset format can be used.</i> Acceptance Date Time Point in time when the payment order from the initiating party meets the processing conditions of the account servicing agent. This means that the account servicing agent has received the payment order and has applied checks such as authorisation, availability of funds. AcptncDtTm ISODateTime [0-9]{4}(-[0-9]{2}){2}T[0-9]{2}(:[0-9]{2}){2}(\.[0-9]{0,2}[1-9])?(Z ([-+][0-9]{2}(:[0-9]{2})?))
2.14	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Pooling Adjustment Date	ISO Name ISO Definition XML Tag Type	Pooling Adjustment Date Date used for the correction of the value date of a cash pool movement that has been posted with a different value date. PoolgAdjstmntDt ISODate
2.15	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Instructed Amount	ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits SEPA Inclusive	Instructed Amount Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party. Usage: This amount has to be transported unchanged through the transaction chain. InstdAmt ActiveOrHistoricCurrencyAndAmount 5 18 0 ..
2.16	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Exchange Rate	ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits	Exchange Rate Factor used to convert an amount from one currency into another. This reflects the price at which one currency was bought with another currency. XchgRate BaseOneRate 10 11



#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements	
2.17	1..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Charge Bearer	<p>SEPA Usage Rule(s) Only "SLEV" is allowed.</p> <p>ISO Name Charge Bearer</p> <p>ISO Definition Specifies which party/parties will bear the charges associated with the processing of the payment transaction.</p> <p>XML Tag ChrgBr</p> <p>Type ChargeBearerType1Code</p> <p>SEPA Code Restrictions</p> <p>SLEV FollowingServiceLevel Charges are to be applied following the rules agreed in the service level and/or scheme.</p>	
2.18	0..n	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Charges Information	<p>ISO Name Charges Information</p> <p>ISO Definition Provides information on the charges to be paid by the charge bearer(s) related to the payment transaction.</p> <p>XML Tag ChrgsInf</p> <p>Type Charges7</p>	
2.19	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Previous Instructing Agent 1	<p>ISO Name Previous Instructing Agent 1</p> <p>ISO Definition Agent immediately prior to the instructing agent.</p> <p>XML Tag PrvsInstgAgt1</p> <p>Type BranchAndFinancialInstitutionIdentification6</p>	
2.20	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Previous Instructing Agent 1Account	<p>ISO Name Previous Instructing Agent 1Account</p> <p>ISO Definition Unambiguous identification of the account of the previous instructing agent at its servicing agent in the payment chain.</p> <p>XML Tag PrvsInstgAgt1Acct</p> <p>Type CashAccount38</p>	
2.21	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Previous Instructing Agent 2	<p>ISO Name Previous Instructing Agent 2</p> <p>ISO Definition Agent immediately prior to the instructing agent.</p> <p>XML Tag PrvsInstgAgt2</p> <p>Type BranchAndFinancialInstitutionIdentification6</p>	
2.22	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Previous Instructing Agent 2Account	<p>ISO Name Previous Instructing Agent 2Account</p> <p>ISO Definition Unambiguous identification of the account of the previous instructing agent at its servicing agent in the payment chain.</p> <p>XML Tag PrvsInstgAgt2Acct</p> <p>Type CashAccount38</p>	
2.23	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Previous Instructing Agent 3	<p>ISO Name Previous Instructing Agent 3</p> <p>ISO Definition Agent immediately prior to the instructing agent.</p> <p>XML Tag PrvsInstgAgt3</p> <p>Type BranchAndFinancialInstitutionIdentification6</p>	
2.24	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Previous Instructing Agent 3Account	<p>ISO Name Previous Instructing Agent 3Account</p> <p>ISO Definition Unambiguous identification of the account of the previous instructing agent at its servicing agent in the payment chain.</p> <p>XML Tag PrvsInstgAgt3Acct</p> <p>Type CashAccount38</p>	
2.25	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Instructing Agent	<p>ISO Name Instructing Agent</p> <p>ISO Definition Agent that instructs the next party in the chain to carry out the (set of) instruction(s).</p> <p>XML Tag InstgAgt</p> <p>Type BranchAndFinancialInstitutionIdentification6</p>	
2.26	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Instructed Agent	<p>ISO Name Instructed Agent</p> <p>ISO Definition Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s).</p> <p>XML Tag InstdAgt</p> <p>Type BranchAndFinancialInstitutionIdentification6</p>	



#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements	
2.27	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Intermediary Agent 1	ISO Name ISO Definition XML Tag Type	Intermediary Agent 1 Agent between the debtor's agent and the creditor's agent. Usage: If more than one intermediary agent is present, then IntermediaryAgent1 identifies the agent between the DebtorAgent and the IntermediaryAgent2. IntrmyAgt1 BranchAndFinancialInstitutionIdentification6
2.28	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Intermediary Agent 1Account	ISO Name ISO Definition XML Tag Type	Intermediary Agent 1Account Unambiguous identification of the account of the intermediary agent 1 at its servicing agent in the payment chain. IntrmyAgt1Acct CashAccount38
2.29	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Intermediary Agent 2	ISO Name ISO Definition XML Tag Type	Intermediary Agent 2 Agent between the debtor's agent and the creditor's agent. Usage: If more than two intermediary agents are present, then IntermediaryAgent2 identifies the agent between the IntermediaryAgent1 and the IntermediaryAgent3. IntrmyAgt2 BranchAndFinancialInstitutionIdentification6
2.30	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Intermediary Agent 2Account	ISO Name ISO Definition XML Tag Type	Intermediary Agent 2Account Unambiguous identification of the account of the intermediary agent 2 at its servicing agent in the payment chain. IntrmyAgt2Acct CashAccount38
2.31	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Intermediary Agent 3	ISO Name ISO Definition XML Tag Type	Intermediary Agent 3 Agent between the debtor's agent and the creditor's agent. Usage: If IntermediaryAgent3 is present, then it identifies the agent between the IntermediaryAgent 2 and the CreditorAgent. IntrmyAgt3 BranchAndFinancialInstitutionIdentification6
2.32	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Intermediary Agent 3Account	ISO Name ISO Definition XML Tag Type	Intermediary Agent 3Account Unambiguous identification of the account of the intermediary agent 3 at its servicing agent in the payment chain. IntrmyAgt3Acct CashAccount38
2.33	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Debtor	ISO Name ISO Definition XML Tag Type	Ultimate Debtor Ultimate party that owes an amount of money to the (ultimate) creditor. UltmtDbtr PartyIdentification135
2.34	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Debtor +++Name	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>AT-P006 Name of the Originator Reference Party.</i> <i>'Name' is limited to 70 characters in length.</i> Name Name by which a party is known and which is usually used to identify that party. Nm Max140Text 1 .. 140 1 .. 70



#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements	
2.35	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Debtor +++Postal Address	ISO Name ISO Definition XML Tag Type	Postal Address Information that locates and identifies a specific address, as defined by postal services. PstlAdr PostalAddress24
2.36	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Debtor +++Identification	SEPA Rulebook ISO Name ISO Definition XML Tag Type	AT-P007 Identification code of the Originator Reference Party. Identification Unique and unambiguous identification of a party. Id Party38Choice
	1..1		XML Tag	xs:choice
2.37	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Debtor +++Identification ++++Organisation Identification	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Either 'AnyBIC', 'LEI' and/or one occurrence of 'Other' is allowed. Organisation Identification Unique and unambiguous way to identify an organisation. OrgId OrganisationIdentification29
2.38	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Debtor +++Identification ++++Private Identification	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Either 'Date and Place of Birth' or one occurrence of 'Other' is allowed. Private Identification Unique and unambiguous identification of a person, for example a passport. PrvtId PersonIdentification13
2.39	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Debtor +++Country Of Residence	ISO Name ISO Definition XML Tag Type Pattern	Country Of Residence Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed. CtryOfRes CountryCode [A-Z]{2,2}
2.40	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Debtor +++Contact Details	ISO Name ISO Definition XML Tag Type	Contact Details Set of elements used to indicate how to contact the party. CtctDtls Contact4
2.41	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Initiating Party	ISO Name ISO Definition XML Tag Type	Initiating Party Party that initiates the payment. Usage: This can be either the debtor or a party that initiates the credit transfer on behalf of the debtor. InitgPty PartyIdentification135
2.42	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor	ISO Name ISO Definition XML Tag Type	Debtor Party that owes an amount of money to the (ultimate) creditor. Dbtr PartyIdentification135
2.43	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Name	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	AT-P001 Name of the Originator. Mandatory. 'Name' is limited to 70 characters in length. Name Name by which a party is known and which is usually used to identify that party. Nm Max140Text 1 .. 140 1 .. 70



#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements	
2.44	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address	<p>SEPA Rulebook AT-P005 The address of the Originator (only mandatory when the Originator PSP or the Beneficiary PSP is located in a non-EEA SEPA country or territory)</p> <p>SEPA Usage Rule(s) STRUCTURED ADDRESS: Usage is recommended. 'Town Name' and 'Country' are mandatory. 'Address Line' is not allowed. It is recommended to provide as many structured elements as possible. HYBRID ADDRESS: 'Town Name' and 'Country' are mandatory. At least one occurrence of 'Address line' is mandatory. UNSTRUCTURED ADDRESS (As of 22 November 2026 at 03:30 CET only the use of structured and hybrid addresses will be allowed - based on available information at the moment of publication): At least one occurrence of 'Address line' is mandatory. 'Postal Address' sub-elements other than 'Address Line' and 'Country' are forbidden. The use of 'Country' is mandatory when either the Debtor Agent or Creditor Agent is located in a non-EEA SEPA country or territory.</p> <p>ISO Name Postal Address ISO Definition Information that locates and identifies a specific address, as defined by postal services.</p> <p>XML Tag Type PstlAdr PostalAddress24</p>	
2.45	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Address Type	<p>ISO Name Address Type ISO Definition Identifies the nature of the postal address.</p> <p>XML Tag Type AdrTp AddressType3Choice</p>	
2.46	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Department	<p>ISO Name Department ISO Definition Identification of a division of a large organisation or building.</p> <p>XML Tag Type Dept Max70Text</p> <p>ISO Length 1 .. 70 SEPA Length 1 .. 70</p>	
2.47	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Sub Department	<p>ISO Name Sub Department ISO Definition Identification of a sub-division of a large organisation or building.</p> <p>XML Tag Type SubDept Max70Text</p> <p>ISO Length 1 .. 70 SEPA Length 1 .. 70</p>	
2.48	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Street Name	<p>ISO Name Street Name ISO Definition Name of a street or thoroughfare.</p> <p>XML Tag Type StrtNm Max70Text</p> <p>ISO Length 1 .. 70 SEPA Length 1 .. 70</p>	
2.49	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Building Number	<p>ISO Name Building Number ISO Definition Number that identifies the position of a building on a street.</p> <p>XML Tag Type BldgNb Max16Text</p> <p>ISO Length 1 .. 16 SEPA Length 1 .. 16</p>	



#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements	
2.50	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Building Name	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Building Name Name of the building or house. BldgNm Max35Text 1 .. 35 1 .. 35
2.51	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Floor	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Floor Floor or storey within a building. Flr Max70Text 1 .. 70 1 .. 70
2.52	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Post Box	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Post Box Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for. PstBx Max16Text 1 .. 16 1 .. 16
2.53	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Room	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Room Building room number. Room Max70Text 1 .. 70 1 .. 70
2.54	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Post Code	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Post Code Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail. PstCd Max16Text 1 .. 16 1 .. 16
2.55	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Town Name	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Town Name Name of a built-up area, with defined boundaries, and a local government. TwnNm Max35Text 1 .. 35 1 .. 35
2.56	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Town Location Name	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Town Location Name Specific location name within the town. TwnLctnNm Max35Text 1 .. 35 1 .. 35
2.57	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++District Name	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	District Name Identifies a subdivision within a country subdivision. DstrctNm Max35Text 1 .. 35 1 .. 35
2.58	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Country Sub Division	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Country Sub Division Identifies a subdivision of a country such as state, region, county. CtrySubDvsn Max35Text 1 .. 35 1 .. 35



#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements
2.59	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Country	ISO Name Country ISO Definition Nation with its own government. XML Tag Ctry Type CountryCode Pattern [A-Z]{2,2}
2.60	0..2	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Address Line	SEPA Usage Rule(s) <i>Up to two occurrences are allowed.</i> ISO Name Address Line ISO Definition Information that locates and identifies a specific address, as defined by postal services, presented in free format text. XML Tag AdrLine Type Max70Text ISO Length 1 .. 70 SEPA Length 1 .. 70
2.61	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Identification	SEPA Rulebook AT-P004 Originator's Identification Code. ISO Name Identification ISO Definition Unique and unambiguous identification of a party. XML Tag Id Type Party38Choice
	1..1		XML Tag xs:choice
2.62	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Identification ++++Organisation Identification	SEPA Usage Rule(s) <i>Either 'AnyBIC', 'LEI' and/or one occurrence of 'Other' is allowed.</i> ISO Name Organisation Identification ISO Definition Unique and unambiguous way to identify an organisation. XML Tag OrgId Type OrganisationIdentification29
2.63	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Identification ++++Private Identification	SEPA Usage Rule(s) <i>Either 'Date and Place of Birth' or one occurrence of 'Other' is allowed.</i> ISO Name Private Identification ISO Definition Unique and unambiguous identification of a person, for example a passport. XML Tag PrvtId Type PersonIdentification13
2.64	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Country Of Residence	ISO Name Country Of Residence ISO Definition Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed. XML Tag CtryOfRes Type CountryCode Pattern [A-Z]{2,2}
2.65	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Contact Details	ISO Name Contact Details ISO Definition Set of elements used to indicate how to contact the party. XML Tag CtctDtls Type Contact4
2.66	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor Account	SEPA Usage Rule(s) <i>Mandatory.</i> ISO Name Debtor Account ISO Definition Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction. XML Tag DbtrAcct Type CashAccount38
2.67	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor Account +++Identification	SEPA Usage Rule(s) <i>Only IBAN is allowed.</i> ISO Name Identification ISO Definition Unique and unambiguous identification for the account between the account owner and the account servicer. XML Tag Id Type AccountIdentification4Choice
	1..1		XML Tag xs:choice



#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements	
2.68	1..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor Account +++Identification ++++IBAN	SEPA Rulebook ISO Name ISO Definition XML Tag Type Pattern	<i>AT-D001 The IBAN of the account of the Originator.</i> IBAN International Bank Account Number (IBAN) - identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services - International Bank Account Number (IBAN)" version 1997-10-01, or later revisions. IBAN IBAN2007Identifier [A-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}
2.69	1..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor Account +++Identification ++++Other	ISO Name ISO Definition XML Tag Type	Other Unique identification of an account, as assigned by the account servicer, using an identification scheme. Othr GenericAccountIdentification1
2.70	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor Account +++Type	ISO Name ISO Definition XML Tag Type	Type Specifies the nature, or use of the account. Tp CashAccountType2Choice
2.71	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor Account +++Currency	ISO Name ISO Definition XML Tag Type Pattern	Currency Identification of the currency in which the account is held. Usage: Currency should only be used in case one and the same account number covers several currencies and the initiating party needs to identify which currency needs to be used for settlement on the account. Ccy ActiveOrHistoricCurrencyCode [A-Z]{3,3}
2.72	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor Account +++Name	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Name Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account. Usage: The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number. Nm Max70Text 1 .. 70 1 .. 70



#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements
2.73	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor Account +++Proxy	<p>SEPA Rulebook AT-P003 The Proxy/Alias of the account of the Originator.</p> <p>SEPA Usage Rule(s) AT-P003 can only be provided here under the condition that the Originator is given the possibility to validate the IBAN linked to that Alias/Proxy, prior to the authentication of the instruction unless the Originator and the Originator PSP agreed upfront on another arrangement (e.g., through an amendment of the general terms and conditions). Furthermore, the Originator PSP must have an agreement with the Originator and the Beneficiary PSP with the Beneficiary in relation to the treatment and the use of the data provided under such Alias/Proxy i.e. whether it is to be used for the purpose to initiate the transaction and/or to forward it to the Beneficiary PSP and/or the Beneficiary concerned. Sub-element 'Identification' is limited to 320 characters in length.</p> <p>ISO Name Proxy</p> <p>ISO Definition Specifies an alternate assumed name for the identification of the account.</p> <p>XML Tag Prxy</p> <p>Type ProxyAccountIdentification1</p>
2.74	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor Agent	<p>SEPA Rulebook AT-D002 The BIC code of the Originator PSP.</p> <p>SEPA Usage Rule(s) Only 'BICFI' is allowed.</p> <p>ISO Name Debtor Agent</p> <p>ISO Definition Financial institution servicing an account for the debtor.</p> <p>XML Tag DbtrAgt</p> <p>Type BranchAndFinancialInstitutionIdentification6</p>
2.75	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor Agent Account	<p>ISO Name Debtor Agent Account</p> <p>ISO Definition Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain.</p> <p>XML Tag DbtrAgtAcct</p> <p>Type CashAccount38</p>
2.76	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor Agent	<p>SEPA Rulebook AT-C002 The BIC code of the Beneficiary PSP.</p> <p>SEPA Usage Rule(s) Only 'BICFI' is allowed.</p> <p>ISO Name Creditor Agent</p> <p>ISO Definition Financial institution servicing an account for the creditor.</p> <p>XML Tag CdtrAgt</p> <p>Type BranchAndFinancialInstitutionIdentification6</p>
2.77	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor Agent Account	<p>ISO Name Creditor Agent Account</p> <p>ISO Definition Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction.</p> <p>XML Tag CdtrAgtAcct</p> <p>Type CashAccount38</p>
2.78	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor	<p>ISO Name Creditor</p> <p>ISO Definition Party to which an amount of money is due.</p> <p>XML Tag Cdtr</p> <p>Type PartyIdentification135</p>



#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements
2.79	1..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Name	<p>SEPA Rulebook AT-E001 The name of the Beneficiary. SEPA Usage Rule(s) Mandatory. 'Name' is limited to 70 characters in length.</p> <p>ISO Name Name ISO Definition Name by which a party is known and which is usually used to identify that party.</p> <p>XML Tag Nm Type Max140Text ISO Length 1 .. 140 SEPA Length 1 .. 70</p>
2.80	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address	<p>SEPA Rulebook AT-E004 The address of the Beneficiary. SEPA Usage Rule(s) STRUCTURED ADDRESS: Usage is recommended. 'Town Name' and 'Country' are mandatory. 'Address Line' is not allowed. It is recommended to provide as many structured elements as possible. HYBRID ADDRESS: 'Town Name' and 'Country' are mandatory. At least one occurrence of 'Address line' is mandatory. UNSTRUCTURED ADDRESS (As of 22 November 2026 at 03:30 CET only the use of structured and hybrid addresses will be allowed - based on available information at the moment of publication): At least one occurrence of 'Address line' is mandatory. 'Postal Address' sub-elements other than 'Address Line' and 'Country' are forbidden.</p> <p>ISO Name Postal Address ISO Definition Information that locates and identifies a specific address, as defined by postal services.</p> <p>XML Tag PstlAdr Type PostalAddress24</p>
2.81	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Address Type	<p>ISO Name Address Type ISO Definition Identifies the nature of the postal address. XML Tag AdrTp Type AddressType3Choice</p>
2.82	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Department	<p>ISO Name Department ISO Definition Identification of a division of a large organisation or building. XML Tag Dept Type Max70Text ISO Length 1 .. 70 SEPA Length 1 .. 70</p>
2.83	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Sub Department	<p>ISO Name Sub Department ISO Definition Identification of a sub-division of a large organisation or building. XML Tag SubDept Type Max70Text ISO Length 1 .. 70 SEPA Length 1 .. 70</p>
2.84	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Street Name	<p>ISO Name Street Name ISO Definition Name of a street or thoroughfare. XML Tag StrtNm Type Max70Text ISO Length 1 .. 70 SEPA Length 1 .. 70</p>



#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements
2.85	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Building Number	ISO Name Building Number ISO Definition Number that identifies the position of a building on a street. XML Tag BldgNb Type Max16Text ISO Length 1 .. 16 SEPA Length 1 .. 16
2.86	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Building Name	ISO Name Building Name ISO Definition Name of the building or house. XML Tag BldgNm Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35
2.87	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Floor	ISO Name Floor ISO Definition Floor or storey within a building. XML Tag Flr Type Max70Text ISO Length 1 .. 70 SEPA Length 1 .. 70
2.88	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Post Box	ISO Name Post Box ISO Definition Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for. XML Tag PstBx Type Max16Text ISO Length 1 .. 16 SEPA Length 1 .. 16
2.89	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Room	ISO Name Room ISO Definition Building room number. XML Tag Room Type Max70Text ISO Length 1 .. 70 SEPA Length 1 .. 70
2.90	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Post Code	ISO Name Post Code ISO Definition Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail. XML Tag PstCd Type Max16Text ISO Length 1 .. 16 SEPA Length 1 .. 16
2.91	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Town Name	ISO Name Town Name ISO Definition Name of a built-up area, with defined boundaries, and a local government. XML Tag TwnNm Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35
2.92	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Town Location Name	ISO Name Town Location Name ISO Definition Specific location name within the town. XML Tag TwnLctnNm Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35
2.93	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++District Name	ISO Name District Name ISO Definition Identifies a subdivision within a country sub-division. XML Tag DstrctNm Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35



#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements	
2.94	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Country Sub Division	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Country Sub Division Identifies a subdivision of a country such as state, region, county. CtrySubDvsn Max35Text 1 .. 35 1 .. 35
2.95	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Country	ISO Name ISO Definition XML Tag Type Pattern	Country Nation with its own government. Ctry CountryCode [A-Z]{2,2}
2.96	0..2	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Address Line	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>Up to two occurrences are allowed.</i> Address Line Information that locates and identifies a specific address, as defined by postal services, presented in free format text. AdrLine Max70Text 1 .. 70 1 .. 70
2.97	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Identification	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-E005 The Beneficiary identification code.</i> Identification Unique and unambiguous identification of a party. Id Party38Choice
	1..1		XML Tag	xs:choice
2.98	1..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Identification ++++Organisation Identification	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>Either 'AnyBIC', 'LEI' or one occurrence of 'Other' is allowed.</i> Organisation Identification Unique and unambiguous way to identify an organisation. OrgId OrganisationIdentification29
2.99	1..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Identification ++++Private Identification	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>Either 'Date and Place of Birth' or one occurrence of 'Other' is allowed.</i> Private Identification Unique and unambiguous identification of a person, for example a passport. PrvtId PersonIdentification13
2.100	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Country Of Residence	ISO Name ISO Definition XML Tag Type Pattern	Country Of Residence Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed. CtryOfRes CountryCode [A-Z]{2,2}
2.101	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Contact Details	ISO Name ISO Definition XML Tag Type	Contact Details Set of elements used to indicate how to contact the party. CtctDtls Contact4
2.102	1..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor Account	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>Mandatory.</i> Creditor Account Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction. CdtrAcct CashAccount38



#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements
2.103	1..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor Account +++Identification	<p>SEPA Usage Rule(s) Only IBAN is allowed.</p> <p>ISO Name Identification</p> <p>ISO Definition Unique and unambiguous identification for the account between the account owner and the account servicer.</p> <p>XML Tag Id</p> <p>Type AccountIdentification4Choice</p>
	1..1		XML Tag xs:choice
2.104	1..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor Account +++Identification ++++IBAN	<p>SEPA Rulebook AT-C001 The IBAN of the account of the Beneficiary.</p> <p>ISO Name IBAN</p> <p>ISO Definition International Bank Account Number (IBAN) - identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services - International Bank Account Number (IBAN)" version 1997-10-01, or later revisions.</p> <p>XML Tag IBAN</p> <p>Type IBAN2007Identifier</p> <p>Pattern [A-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}</p>
2.105	1..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor Account +++Identification ++++Other	<p>ISO Name Other</p> <p>ISO Definition Unique identification of an account, as assigned by the account servicer, using an identification scheme.</p> <p>XML Tag Othr</p> <p>Type GenericAccountIdentification1</p>
2.106	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor Account +++Type	<p>ISO Name Type</p> <p>ISO Definition Specifies the nature, or use of the account.</p> <p>XML Tag Tp</p> <p>Type CashAccountType2Choice</p>
2.107	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor Account +++Currency	<p>ISO Name Currency</p> <p>ISO Definition Identification of the currency in which the account is held.</p> <p>Usage: Currency should only be used in case one and the same account number covers several currencies and the initiating party needs to identify which currency needs to be used for settlement on the account.</p> <p>XML Tag Ccy</p> <p>Type ActiveOrHistoricCurrencyCode</p> <p>Pattern [A-Z]{3,3}</p>
2.108	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor Account +++Name	<p>ISO Name Name</p> <p>ISO Definition Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account.</p> <p>Usage: The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number.</p> <p>XML Tag Nm</p> <p>Type Max70Text</p> <p>ISO Length 1 .. 70</p> <p>SEPA Length 1 .. 70</p>



#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements	
2.109	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor Account +++Proxy	<p>SEPA Rulebook AT-E003 The Proxy/alias of the account of the Beneficiary.</p> <p>SEPA Usage Rule(s) AT-E003 can only be provided here under the condition that the Originator is given the possibility to validate the IBAN linked to that Alias/Proxy, prior to the authentication of the instruction unless the Originator and the Originator PSP agreed upfront on another arrangement (e.g., through an amendment of the general terms and conditions). Furthermore, the Originator PSP must have an agreement with the Originator and the Beneficiary PSP with the Beneficiary in relation to the treatment and the use of the data provided under such Alias/Proxy i.e. whether it is to be used for the purpose to initiate the transaction and/or to forward it to the Beneficiary PSP and/or the Beneficiary concerned. Sub-element 'Identification' is limited to 320 characters in length.</p> <p>ISO Name Proxy</p> <p>ISO Definition Specifies an alternate assumed name for the identification of the account.</p> <p>XML Tag Prxy</p> <p>Type ProxyAccountIdentification1</p>	
2.110	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Creditor	<p>ISO Name Ultimate Creditor</p> <p>ISO Definition Ultimate party to which an amount of money is due.</p> <p>XML Tag UltmtCdtr</p> <p>Type PartyIdentification135</p>	
2.111	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Creditor +++Name	<p>SEPA Rulebook AT-E007 The name of the Beneficiary Reference Party.</p> <p>SEPA Usage Rule(s) 'Name' is limited to 70 characters in length.</p> <p>ISO Name Name</p> <p>ISO Definition Name by which a party is known and which is usually used to identify that party.</p> <p>XML Tag Nm</p> <p>Type Max140Text</p> <p>ISO Length 1 .. 140</p> <p>SEPA Length 1 .. 70</p>	
2.112	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Creditor +++Postal Address	<p>ISO Name Postal Address</p> <p>ISO Definition Information that locates and identifies a specific address, as defined by postal services.</p> <p>XML Tag PstlAdr</p> <p>Type PostalAddress24</p>	
2.113	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Creditor +++Identification	<p>SEPA Rulebook AT-E010 The identification code of the Beneficiary Reference Party.</p> <p>ISO Name Identification</p> <p>ISO Definition Unique and unambiguous identification of a party.</p> <p>XML Tag Id</p> <p>Type Party38Choice</p>	
	1..1		XML Tag xs:choice	
2.114	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Creditor +++Identification ++++Organisation Identification	<p>SEPA Usage Rule(s) Either 'AnyBIC', 'LEI' or one occurrence of 'Other' is allowed.</p> <p>ISO Name Organisation Identification</p> <p>ISO Definition Unique and unambiguous way to identify an organisation.</p> <p>XML Tag OrgId</p> <p>Type OrganisationIdentification29</p>	



#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements
2.115	1..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Creditor +++Identification ++++Private Identification	SEPA Usage Rule(s) Either 'Date and Place of Birth' or one occurrence of 'Other' is allowed. ISO Name Private Identification ISO Definition Unique and unambiguous identification of a person, for example a passport. XML Tag PrvtId Type PersonIdentification13
2.116	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Creditor +++Country Of Residence	ISO Name Country Of Residence ISO Definition Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed. XML Tag CtryOfRes Type CountryCode Pattern [A-Z]{2,2}
2.117	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Creditor +++Contact Details	ISO Name Contact Details ISO Definition Set of elements used to indicate how to contact the party. XML Tag CctdDtls Type Contact4
2.118	0..n	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Instruction For Creditor Agent	ISO Name Instruction For Creditor Agent ISO Definition Further information related to the processing of the payment instruction, provided by the initiating party, and intended for the creditor agent. XML Tag InstrForCdtrAgt Type InstructionForCreditorAgent1
2.119	0..n	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Instruction For Next Agent	ISO Name Instruction For Next Agent ISO Definition Further information related to the processing of the payment instruction that may need to be acted upon by the next agent. Usage: The next agent may not be the creditor agent. The instruction can relate to a level of service, can be an instruction that has to be executed by the agent, or can be information required by the next agent. XML Tag InstrForNxtAgt Type InstructionForNextAgent1
2.120	0..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Purpose	SEPA Rulebook AT-T007 The purpose of the SCT Inst Instruction. ISO Name Purpose ISO Definition Underlying reason for the payment transaction. Usage: Purpose is used by the end-customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain. XML Tag Purp Type Purpose2Choice
	1..1		XML Tag xs:choice
2.121	1..1	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Purpose +++Code	ISO Name Code ISO Definition Underlying reason for the payment transaction, as published in an external purpose code list. XML Tag Cd Type ExternalPurpose1Code ISO Length 1 .. 4 SEPA Length 1 .. 4



#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements	
2.122	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Purpose +++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Proprietary Purpose, in a proprietary form. Prtry Max35Text 1 .. 35 1 .. 35
2.123	0..10	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Regulatory Reporting	ISO Name ISO Definition XML Tag Type	Regulatory Reporting Information needed due to regulatory and statutory requirements. RgltryRptg RegulatoryReporting3
2.124	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Tax	ISO Name ISO Definition XML Tag Type	Tax Provides details on the tax. Tax TaxInformation8
2.125	0..10	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Related Remittance Information	ISO Name ISO Definition XML Tag Type	Related Remittance Information Provides information related to the handling of the remittance information by any of the agents in the transaction processing chain. RltdRmtInf RemittanceLocation7
2.126	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-T009 The Remittance Information.</i> <i>Either 'Structured' or 'Unstructured' may be present.</i> Remittance Information Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system. RmtInf RemittanceInformation16



#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements
2.127	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Unstructured	<p>SEPA Usage Rule(s) 'Unstructured' may carry structured remittance information, as agreed between the Originator and the Beneficiary. Only one occurrence of 'Unstructured' is allowed.</p> <p>If the commercial trade name of the payee is different from its legal name (AT-E001 The name of the Beneficiary), then the commercial trade name must be provided here. The location of where the transaction took place (if different from AT-E004 The address of the Beneficiary) as well as the transaction date and time can also be provided here. Each piece of information must be followed by a slash to clearly differentiate from the other information included under this data element (a special character other than a slash can be used instead (e.g., "+") in case the slash is used for other purposes). [Example: The Shopping Paradise/Boulevard des Marchands 123/2020-12-24T11:37/Purchase Nr 1234567890.AZ - Merry Christmas.] For further information, please refer to "EPC088-22 EPC Guidance Document – Improve Transparency for Retail Payment End-Users".</p> <p>ISO Name ISO Definition Unstructured Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in an unstructured form.</p> <p>XML Tag Type Ustrd Max140Text</p> <p>ISO Length SEPA Length 1 .. 140 1 .. 140</p>
2.128	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured	<p>SEPA Usage Rule(s) Only one occurrence of 'Structured' is allowed.</p> <p>SEPA Format Rule(s) 'Structured' can be used, provided the tags and the data within the 'Structured' element (i.e. excluding <Strd> and </Strd>) do not exceed 140 characters in length.</p> <p>ISO Name ISO Definition Structured Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in a structured form.</p> <p>XML Tag Type Strd StructuredRemittanceInformation16</p>
2.129	0..n	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Referred Document Information	<p>ISO Name ISO Definition Referred Document Information Provides the identification and the content of the referred document.</p> <p>XML Tag Type RfrdDocInf ReferredDocumentInformation7</p>
2.130	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Referred Document Amount	<p>ISO Name ISO Definition Referred Document Amount Provides details on the amounts of the referred document.</p> <p>XML Tag Type RfrdDocAmt RemittanceAmount2</p>



#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements
2.131	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Creditor Reference Information	<p>SEPA Usage Rule(s) When present, the Creditor PSP is not obliged to validate the reference information. When used both 'Type' and 'Reference' must be present.</p> <p>ISO Name Creditor Reference Information ISO Definition Reference information provided by the creditor to allow the identification of the underlying documents. XML Tag CdtrRefInf Type CreditorReferenceInformation2</p>
2.132	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Creditor Reference Information +++++Type	<p>SEPA Usage Rule(s) Mandatory if 'Creditor Reference Information' is used.</p> <p>ISO Name Type ISO Definition Specifies the type of creditor reference. XML Tag Tp Type CreditorReferenceType2</p>
2.133	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Creditor Reference Information +++++Type ++++++Code Or Proprietary	<p>ISO Name Code Or Proprietary ISO Definition Coded or proprietary format creditor reference type. XML Tag CdOrPrtry Type CreditorReferenceType1Choice</p>
	1..1		<p>XML Tag xs:choice</p>
2.134	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Creditor Reference Information +++++Type ++++++Code Or Proprietary +++++++Code	<p>SEPA Usage Rule(s) Only "SCOR" is allowed.</p> <p>ISO Name Code ISO Definition Type of creditor reference, in a coded form. XML Tag Cd Type DocumentType3Code</p> <p>SEPA Code Restrictions</p> <p>SCOR StructuredCommunicationReference Document is a structured communication reference provided by the creditor to identify the referred transaction.</p>
2.135	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Creditor Reference Information +++++Type ++++++Code Or Proprietary +++++++Proprietary	<p>ISO Name Proprietary ISO Definition Creditor reference type, in a proprietary form. XML Tag Prtry Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35</p>
2.136	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Creditor Reference Information +++++Type ++++++Issuer	<p>SEPA Usage Rule(s) Mandatory if 'Reference' is populated with an identifier issued or governed by a known institution. E.g. "ISO" should be mentioned here if 'Reference' is populated with a RF Creditor Reference (ISO 11649).</p> <p>ISO Name Issuer ISO Definition Entity that assigns the credit reference type. XML Tag Issr Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35</p>



#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements
2.137	1..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured ++++Creditor Reference Information +++++Reference	<p>SEPA Usage Rule(s) <i>Mandatory if 'Creditor Reference Information' is used.</i> <i>If a Creditor Reference contains a check digit, the receiving PSP is not required to validate this. If the receiving PSP validates the check digit and if this validation fails, the PSP may continue its processing and send the transaction to the next party in the chain.</i> <i>RF Creditor Reference must be used (ISO 11649) in case "ISO" is mentioned under 'Issuer'.</i></p> <p>ISO Name ISO Definition Reference Unique reference, as assigned by the creditor, to unambiguously refer to the payment transaction.</p> <p>Usage: If available, the initiating party should provide this reference in the structured remittance information, to enable reconciliation by the creditor upon receipt of the amount of money.</p> <p>If the business context requires the use of a creditor reference or a payment remit identification, and only one identifier can be passed through the end-to-end chain, the creditor's reference or payment remittance identification should be quoted in the end-to-end transaction identification.</p> <p>XML Tag Type ISO Length SEPA Length Ref Max35Text 1 .. 35 1 .. 35</p>
2.138	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured +++++Invoicer	<p>ISO Name ISO Definition Invoicer Identification of the organisation issuing the invoice, when it is different from the creditor or ultimate creditor.</p> <p>XML Tag Type Invr PartyIdentification135</p>
2.139	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured +++++Invoicee	<p>ISO Name ISO Definition Invoicee Identification of the party to whom an invoice is issued, when it is different from the debtor or ultimate debtor.</p> <p>XML Tag Type Invcee PartyIdentification135</p>
2.140	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured +++++Tax Remittance	<p>ISO Name ISO Definition Tax Remittance Provides remittance information about a payment made for tax-related purposes.</p> <p>XML Tag Type TaxRmt TaxInformation7</p>
2.141	0..1	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured +++++Garnishment Remittance	<p>ISO Name ISO Definition Garnishment Remittance Provides remittance information about a payment for garnishment-related purposes.</p> <p>XML Tag Type GrnshmtRmt Garnishment3</p>
2.142	0..3	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Remittance Information +++Structured +++++Additional Remittance Information	<p>ISO Name ISO Definition Additional Remittance Information Additional information, in free text form, to complement the structured remittance information.</p> <p>XML Tag Type ISO Length SEPA Length AddtlRmtInf Max140Text 1 .. 140 1 .. 140</p>



#	SEPA Mult	Message Element	Inter-PSP Payment SEPA Core Requirements	
2.143	0..n	FIto FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1
3.0	0..n	FIto FICustomer Credit Transfer V08 +Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1



2.2 Negative Confirmation Message (DS-03)

2.2.1 Use of the FI to FI Payment Status Report (pacs.002.001.10)

When the code "RJCT" (Rejected) is used in the 'Group Status' or 'Transaction Status', the message transports the negative confirmation between PSPs, directly or through intermediaries.

Reason code "TM01" (Invalid Cut-off Time) is the only reason code that can be used in a negative confirmation message to the Beneficiary PSP. Reason code "TM01" is not allowed in a negative confirmation message to the Originator PSP. Instead the code "AB05" (Time-out Creditor Agent) or "AB06" (Time-out Instructed Agent) can be used.

The message caters for a single negative confirmation instruction.

Note: Attribute AT-R001 'The type of R-message' is implied by the 'Message Name', 'pacs.002.001.10', the 'Original Message Name Identification' must begin with 'pacs.008' (the addition of a variant number and version number is optional), 'Group Status' or 'Transaction Status' set to "RJCT" and 'Payment Type Information' mentioning "INST" (Transaction is related to an Instant Credit Transfer) under 'Local Instrument/Code'.

Note: Message elements under 'Original Transaction Reference' sequence are based on DS-02 attributes."



#	SEPA Mult	Message Element	Negative Confirmation SEPA Core Requirements
		Document	XML Tag Type Document Document
	1..1	FITo FIPayment Status Report V10	ISO Name FITo FIPayment Status Report V10 ISO Definition Scope The FIToFIPaymentStatusReport message is sent by an instructed agent to the previous party in the payment chain. It is used to inform this party about the positive or negative status of an instruction (either single or file). It is also used to report on a pending instruction. XML Tag Type FIToFIPmtStsRpt FIToFIPaymentStatusReportV10
1.0	1..1	FITo FIPayment Status Report V10 +Group Header	ISO Name Group Header ISO Definition Set of characteristics shared by all individual transactions included in the status report message. XML Tag Type GrpHdr GroupHeader91
1.1	1..1	FITo FIPayment Status Report V10 +Group Header ++Message Identification	ISO Name Message Identification ISO Definition Point to point reference, as assigned by the instructing party, and sent to the next party in the chain to unambiguously identify the message. Usage: The instructing party has to make sure that MessageIdentification is unique per instructed party for a pre-agreed period. XML Tag Type MsgId Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35
1.2	1..1	FITo FIPayment Status Report V10 +Group Header ++Creation Date Time	ISO Name Creation Date Time ISO Definition Date and time at which the message was created. XML Tag Type CreDfTm ISODateTime
1.3	0..1	FITo FIPayment Status Report V10 +Group Header ++Instructing Agent	SEPA Usage Rule(s) Only 'BICFI' is allowed. ISO Name Instructing Agent ISO Definition Agent that instructs the next party in the chain to carry out the (set of) instruction(s). Usage: The instructing agent is the party sending the status message and not the party that sent the original instruction that is being reported on. XML Tag Type InstgAgt BranchAndFinancialInstitutionIdentification6
1.4	0..1	FITo FIPayment Status Report V10 +Group Header ++Instructed Agent	SEPA Usage Rule(s) Only 'BICFI' is allowed. ISO Name Instructed Agent ISO Definition Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s). Usage: The instructed agent is the party receiving the status message and not the party that received the original instruction that is being reported on. XML Tag Type InstdAgt BranchAndFinancialInstitutionIdentification6
2.0	1..1	FITo FIPayment Status Report V10 +Original Group Information And Status	SEPA Usage Rule(s) Mandatory. Only one occurrence is allowed. ISO Name Original Group Information And Status ISO Definition Original group information concerning the group of transactions, to which the status report message refers to. XML Tag Type OrgnlGrpInfAndSts OriginalGroupHeader17



#	SEPA Mult	Message Element	Negative Confirmation SEPA Core Requirements
2.1	1..1	FITo FIPayment Status Report V10 +Original Group Information And Status ++Original Message Identification	ISO Name Original Message Identification ISO Definition Point to point reference, as assigned by the original instructing party, to unambiguously identify the original message. XML Tag OrgnMsgId Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35
2.2	1..1	FITo FIPayment Status Report V10 +Original Group Information And Status ++Original Message Name Identification	SEPA Usage Rule(s) <i>Must begin with 'pacs.008'. The addition of a variant number and version number is optional.</i> ISO Name Original Message Name Identification ISO Definition Specifies the original message name identifier to which the message refers. XML Tag OrgnMsgNmId Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35
2.3	0..1	FITo FIPayment Status Report V10 +Original Group Information And Status ++Original Creation Date Time	ISO Name Original Creation Date Time ISO Definition Date and time at which the original message was created. XML Tag OrgnCreDtTm Type ISODateTime
2.4	0..1	FITo FIPayment Status Report V10 +Original Group Information And Status ++Original Number Of Transactions	ISO Name Original Number Of Transactions ISO Definition Number of individual transactions contained in the original message. XML Tag OrgnNbOfTxS Type Max15NumericText Pattern [0-9]{1,15}
2.5	0..1	FITo FIPayment Status Report V10 +Original Group Information And Status ++Original Control Sum	ISO Name Original Control Sum ISO Definition Total of all individual amounts included in the original message, irrespective of currencies. XML Tag OrgnCtrlSum Type DecimalNumber SEPA FractDigits 17 TotalDigits 18
2.6	0..1	FITo FIPayment Status Report V10 +Original Group Information And Status ++Group Status	SEPA Rulebook <i>AT-R001 The type of R Message.</i> SEPA Usage Rule(s) <i>Only "RJCT" is allowed. Either 'Group Status' or 'Transaction Status' must be used.</i> ISO Name Group Status ISO Definition Specifies the status of a group of transactions. XML Tag GrpSts Type ExternalPaymentGroupStatus1Code ISO Length 1 .. 4 SEPA Length 1 .. 4 SEPA Code Restrictions RJCT <i>Rejected Payment initiation or individual transaction included in the payment initiation has been rejected.</i>
2.7	0..1	FITo FIPayment Status Report V10 +Original Group Information And Status ++Status Reason Information	SEPA Usage Rule(s) <i>Only one occurrence is allowed. Must be used when 'Group Status' is present.</i> ISO Name Status Reason Information ISO Definition Provides detailed information on the status reason. XML Tag StsRsnInf Type StatusReasonInformation12



#	SEPA Mult	Message Element	Negative Confirmation SEPA Core Requirements
2.8	1..1	FIto FIPayment Status Report V10 +Original Group Information And Status ++Status Reason Information +++Originator	<p>SEPA Rulebook AT-R002 The identification of the type of party initiating the "R" message.</p> <p>SEPA Usage Rule(s) Mandatory Limited to 'AnyBIC' to identify the PSP or CSM originating the status or 'Name' to indicate a CSM when it has no BIC. 'Name' is limited to 70 characters in length.</p> <p>ISO Name Originator ISO Definition Party that issues the status. XML Tag Orgtr Type PartyIdentification135</p>
2.9	1..1	FIto FIPayment Status Report V10 +Original Group Information And Status ++Status Reason Information +++Reason	<p>SEPA Rulebook AT-R004 The reason code for non-acceptance of the SCT Inst Transaction.</p> <p>SEPA Usage Rule(s) Mandatory.</p> <p>ISO Name Reason ISO Definition Specifies the reason for the status report. XML Tag Rsn Type StatusReason6Choice</p>
	1..1		XML Tag xs:choice
2.10	1..1	FIto FIPayment Status Report V10 +Original Group Information And Status ++Status Reason Information +++Reason ++++Code	<p>SEPA Usage Rule(s) Only "FF01" is allowed.</p> <p>ISO Name Code ISO Definition Reason for the status, as published in an external reason code list. XML Tag Cd Type ExternalStatusReason1Code ISO Length 1 .. 4 SEPA Length 1 .. 4</p>
			<p>SEPA Code Restrictions</p> <p>FF01 InvalidFileFormat File Format incomplete or invalid</p>
2.11	1..1	FIto FIPayment Status Report V10 +Original Group Information And Status ++Status Reason Information +++Reason ++++Proprietary	<p>ISO Name Proprietary ISO Definition Reason for the status, in a proprietary form. XML Tag Prtry Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35</p>
2.12	0..n	FIto FIPayment Status Report V10 +Original Group Information And Status ++Status Reason Information +++Additional Information	<p>ISO Name Additional Information ISO Definition Further details on the status reason.</p> <p>Usage: Additional information can be used for several purposes such as the reporting of repaired information.</p> <p>XML Tag AddtlInf Type Max105Text ISO Length 1 .. 105 SEPA Length 1 .. 105</p>
2.13	0..n	FIto FIPayment Status Report V10 +Original Group Information And Status ++Number Of Transactions Per Status	<p>ISO Name Number Of Transactions Per Status ISO Definition Detailed information on the number of transactions for each identical transaction status. XML Tag NbOfTxSPerSts Type NumberOfTransactionsPerStatus5</p>
3.0	0..1	FIto FIPayment Status Report V10 +Transaction Information And Status	<p>SEPA Usage Rule(s) Only one occurrence is allowed.</p> <p>ISO Name Transaction Information And Status ISO Definition Information concerning the original transactions, to which the status report message refers. XML Tag TxInfAndSts Type PaymentTransaction110</p>



#	SEPA Mult	Message Element	Negative Confirmation SEPA Core Requirements	
3.1	1..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Status Identification	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>AT-R003 The specific reference of the party initiating the Reject.</i> Mandatory. <i>This ID must be forwarded to the Originator PSP and optionally to the Originator (and therefore it is not a point-to-point reference).</i> Status Identification Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the reported status. Usage: The instructing party is the party sending the status message and not the party that sent the original instruction that is being reported on. StsId Max35Text 1 .. 35 1 .. 35
3.2	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Group Information	ISO Name ISO Definition XML Tag Type	Original Group Information Point to point reference, as assigned by the original instructing party, to unambiguously identify the original message. OrgnlGrpInf OriginalGroupInformation29
3.3	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Instruction Identification	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Mandatory if provided in the original instruction. Original Instruction Identification Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction. OrgnlInstrId Max35Text 1 .. 35 1 .. 35
3.4	1..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original End To End Identification	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>AT-T014 The Originator's reference of the SCT Inst Instruction.</i> Mandatory. Original End To End Identification Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction. OrgnlEndToEndId Max35Text 1 .. 35 1 .. 35
3.5	1..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Identification	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>AT-T054 The Originator PSP's reference of the SCT Inst Transaction message.</i> Mandatory. Original Transaction Identification Unique identification, as assigned by the original first instructing agent, to unambiguously identify the transaction. OrgnlTxId Max35Text 1 .. 35 1 .. 35
3.6	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original UETR	ISO Name ISO Definition XML Tag Type Pattern	Original UETR Universally unique identifier to provide the original end-to-end reference of a payment transaction. OrgnlUETR UUIDv4Identifier [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}



#	SEPA Mult	Message Element	Negative Confirmation SEPA Core Requirements
3.7	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Transaction Status	<p>SEPA Rulebook AT-R001 Type of R-message. SEPA Usage Rule(s) Only "RJCT" is allowed. Either 'Group Status' or 'Transaction Status' must be used.</p> <p>ISO Name Transaction Status ISO Definition Specifies the status of a transaction, in a coded form. XML Tag TxSts Type ExternalPaymentTransactionStatus1Code ISO Length 1 .. 4 SEPA Length 1 .. 4</p> <p>SEPA Code Restrictions</p> <p>RJCT Rejected Payment instruction has been rejected.</p>
3.8	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Status Reason Information	<p>SEPA Usage Rule(s) Only one occurrence is allowed. Must be used when 'Transaction Status' is present.</p> <p>ISO Name Status Reason Information ISO Definition Provides detailed information on the status reason. XML Tag StsRsnInf Type StatusReasonInformation12</p>
3.9	1..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Status Reason Information +++Originator	<p>SEPA Rulebook AT-R002 The identification of the type of party initiating the "R" message. SEPA Usage Rule(s) Mandatory Limited to 'AnyBIC' to identify the PSP or CSM originating the status or 'Name' to indicate a CSM when it has no BIC. 'Name' is limited to 70 characters in length.</p> <p>ISO Name Originator ISO Definition Party that issues the status. XML Tag Orgtr Type PartyIdentification135</p>
3.10	1..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Status Reason Information +++Reason	<p>SEPA Rulebook AT-R004 The reason code for non-acceptance of the SCT Inst. SEPA Usage Rule(s) Mandatory.</p> <p>ISO Name Reason ISO Definition Specifies the reason for the status report. XML Tag Rsn Type StatusReason6Choice</p>
	1..1		XML Tag xs:choice
3.11	1..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Status Reason Information +++Reason ++++Code	<p>SEPA Rulebook See Message Element Specifications below.</p> <p>ISO Name Code ISO Definition Reason for the status, as published in an external reason code list. XML Tag Cd Type ExternalStatusReason1Code ISO Length 1 .. 4 SEPA Length 1 .. 4</p>
3.12	1..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Status Reason Information +++Reason ++++Proprietary	<p>ISO Name Proprietary ISO Definition Reason for the status, in a proprietary form. XML Tag Prtry Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35</p>



#	SEPA Mult	Message Element	Negative Confirmation SEPA Core Requirements	
3.13	0..n	FIto FIPayment Status Report V10 +Transaction Information And Status ++Status Reason Information +++Additional Information	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Additional Information Further details on the status reason. Usage: Additional information can be used for several purposes such as the reporting of repaired information. AddtlInf Max105Text 1 .. 105 1 .. 105
3.14	0..n	FIto FIPayment Status Report V10 +Transaction Information And Status ++Charges Information	ISO Name ISO Definition XML Tag Type	Charges Information Provides information on the charges related to the processing of the rejection of the instruction. Usage: This is passed on for information purposes only. Settlement of the charges will be done separately. ChrgsInf Charges7
3.15	1..1	FIto FIPayment Status Report V10 +Transaction Information And Status ++Acceptance Date Time	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-T056 Timestamp of the SCT Inst Transaction. Mandatory.</i> Acceptance Date Time Point in time when the payment order from the initiating party meets the processing conditions of the account servicing agent. This means that the account servicing agent has received the payment order and has applied checks such as authorisation, availability of funds. AcceptncDtTm ISODateTime
3.16	0..1	FIto FIPayment Status Report V10 +Transaction Information And Status ++Effective Interbank Settlement Date	ISO Name ISO Definition XML Tag Type	Effective Interbank Settlement Date Date and time at which a transaction is completed and cleared, that is, payment is effected. FctvIntrBkStlmDt DateAndDateTime2Choice
3.17	0..1	FIto FIPayment Status Report V10 +Transaction Information And Status ++Account Servicer Reference	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Account Servicer Reference Unique reference, as assigned by the account servicing institution, to unambiguously identify the instruction. AcctSvcrRef Max35Text 1 .. 35 1 .. 35
3.18	0..1	FIto FIPayment Status Report V10 +Transaction Information And Status ++Clearing System Reference	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Clearing System Reference Unique reference, as assigned by a clearing system, to unambiguously identify the instruction. ClrSysRef Max35Text 1 .. 35 1 .. 35
3.19	0..1	FIto FIPayment Status Report V10 +Transaction Information And Status ++Instructing Agent	ISO Name ISO Definition XML Tag Type	Instructing Agent Agent that instructs the next party in the chain to carry out the (set of) instruction(s). Usage: The instructing agent is the party sending the status message and not the party that sent the original instruction that is being reported on. InstgAgt BranchAndFinancialInstitutionIdentification6



#	SEPA Mult	Message Element	Negative Confirmation SEPA Core Requirements	
3.20	0..1	FIto FIPayment Status Report V10 +Transaction Information And Status ++Instructed Agent	ISO Name ISO Definition XML Tag Type	Instructed Agent Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s). Usage: The instructed agent is the party receiving the status message and not the party that received the original instruction that is being reported on. InstdAgt BranchAndFinancialInstitutionIdentification6
3.21	1..1	FIto FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference	ISO Name ISO Definition XML Tag Type	<i>SEPA Usage Rule(s) Mandatory.</i> <i>The message elements under 'Original Transaction Reference' must be populated with the same value as the message elements of the original instruction.</i> Original Transaction Reference Key elements used to identify the original transaction that is being referred to. OrgnlTxRef OriginalTransactionReference28
3.22	0..1	FIto FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Interbank Settlement Amount	ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits SEPA Inclusive	Interbank Settlement Amount Amount of money moved between the instructing agent and the instructed agent. IntrBkSttlmAmt ActiveOrHistoricCurrencyAndAmount 5 18 0 ..
3.23	0..1	FIto FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Amount	ISO Name ISO Definition XML Tag Type	Amount Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party. Amt AmountType4Choice
3.24	0..1	FIto FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Interbank Settlement Date	ISO Name ISO Definition XML Tag Type	Interbank Settlement Date Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. IntrBkSttlmDt ISODate
3.25	0..1	FIto FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Requested Collection Date	ISO Name ISO Definition XML Tag Type	Requested Collection Date Date and time at which the creditor requests that the amount of money is to be collected from the debtor. ReqdCollmDt ISODate
3.26	0..1	FIto FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Requested Execution Date	ISO Name ISO Definition XML Tag Type	Requested Execution Date Date at which the initiating party requests the clearing agent to process the payment. Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank. ReqdExctnDt DateAndDateTime2Choice
3.27	0..1	FIto FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Creditor Scheme Identification	ISO Name ISO Definition XML Tag Type	Creditor Scheme Identification Credit party that signs the mandate. CdrSchmeld PartyIdentification135



#	SEPA Mult	Message Element	Negative Confirmation SEPA Core Requirements	
3.28	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Settlement Information	ISO Name ISO Definition XML Tag Type	Settlement Information Specifies the details on how the settlement of the original transaction(s) between the instructing agent and the instructed agent was completed. SttlmInf SettlementInstruction7
3.29	1..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Payment Type Information	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-T001 The identification code of the SCT Inst Scheme. AT-T008 The category purpose of the SCT Inst Instruction. Mandatory. Payment Type Information Set of elements used to further specify the type of transaction. PmtTpInf PaymentTypeInformation27
3.30	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Payment Method	ISO Name ISO Definition XML Tag Type	Payment Method Specifies the means of payment that will be used to move the amount of money. PmtMtd PaymentMethod4Code
3.31	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Mandate Related Information	ISO Name ISO Definition XML Tag Type	Mandate Related Information Provides further details of the mandate signed between the creditor and the debtor. MndtRltdInf MandateRelatedInformation14
3.32	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Remittance Information	ISO Name ISO Definition XML Tag Type	Remittance Information Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system. RmtInf RemittanceInformation16
3.33	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Ultimate Debtor	ISO Name ISO Definition XML Tag Type	Ultimate Debtor Ultimate party that owes an amount of money to the (ultimate) creditor. UltmtDbtr Party40Choice
3.34	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Debtor	ISO Name ISO Definition XML Tag Type	Debtor Party that owes an amount of money to the (ultimate) creditor. Dbtr Party40Choice
3.35	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Debtor Account	ISO Name ISO Definition XML Tag Type	Debtor Account Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction. DbtrAcct CashAccount38
3.36	1..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Debtor Agent	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-D002 The BIC code of the Originator PSP. Mandatory. Debtor Agent Financial institution servicing an account for the debtor. DbtrAgt BranchAndFinancialInstitutionIdentification6
3.37	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Debtor Agent Account	ISO Name ISO Definition XML Tag Type	Debtor Agent Account Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain. DbtrAgtAcct CashAccount38



#	SEPA Mult	Message Element	Negative Confirmation SEPA Core Requirements	
3.38	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Creditor Agent	ISO Name ISO Definition XML Tag Type	Creditor Agent Financial institution servicing an account for the creditor. CdtrAgt BranchAndFinancialInstitutionIdentification6
3.39	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Creditor Agent Account	ISO Name ISO Definition XML Tag Type	Creditor Agent Account Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction. CdtrAgtAcct CashAccount38
3.40	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Creditor	ISO Name ISO Definition XML Tag Type	Creditor Party to which an amount of money is due. Cdtr Party40Choice
3.41	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Creditor Account	ISO Name ISO Definition XML Tag Type	Creditor Account Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction. CdtrAcct CashAccount38
3.42	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Ultimate Creditor	ISO Name ISO Definition XML Tag Type	Ultimate Creditor Ultimate party to which an amount of money is due. UltmtCdtr Party40Choice
3.43	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Purpose	ISO Name ISO Definition XML Tag Type	Purpose Underlying reason for the payment transaction. Usage: Purpose is used by the end customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain. Purp Purpose2Choice
3.44	0..n	FITo FIPayment Status Report V10 +Transaction Information And Status ++Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1
4.0	0..n	FITo FIPayment Status Report V10 +Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1



2.2.2 Message Element Specifications

The reasons for a negative confirmation of the SCT Inst present in the Rulebook are mapped to ISO codes as follows (applies only to 'Transaction Information And Status'):

ISO Code	ISO Name	SEPA Core Reason as specified in the Rulebook
AB05	TimeoutCreditorAgent	Transaction stopped due to timeout at the Creditor Agent.
AB06	TimeoutInstructedAgent	Transaction stopped due to timeout at the Instructed Agent.
AB07	OfflineAgent	Agent of message is not online. Generic usage if it cannot be determined who exactly is not online.
AB08	OfflineCreditorAgent	Creditor Agent is not online.
AB09	ErrorCreditorAgent	Transaction stopped due to error at the Creditor Agent.
AB10	ErrorInstructedAgent	Transaction stopped due to error at the Instructed Agent.
AC01	IncorrectAccountNumber	Account identifier incorrect (i.e. invalid IBAN)
AC04	ClosedAccountNumber	Account closed
AC06	BlockedAccount	Account blocked, reason not specified
AG01	TransactionForbidden	Credit transfer forbidden on this type of account.
AG02	InvalidBankOperationCode	Operation/transaction code incorrect, invalid file format <i>Usage Rule:</i> To be used for incorrect 'operation/transaction' code.
AG09	PaymentNotReceived	Original payment never received.
AG10	AgentSuspended	Agent of message is suspended from the Real Time Payment system. Generic usage if it cannot be determined who exactly is suspended.
AG11	CreditorAgentSuspended	Creditor Agent of message is suspended from the Real Time Payment system.
AM05	Duplication	Duplicate payment
AM23	AmountExceedsSettlementLimit	Transaction amount exceeds settlement limit.
BE04	MissingCreditorAddress	Account address is invalid
MD07	EndCustomerDeceased	Beneficiary deceased



ISO Code	ISO Name	SEPA Core Reason as specified in the Rulebook
MS02	NotSpecifiedReasonCustomerGenerated	By order of the Beneficiary
MS03	NotSpecifiedReasonAgentGenerated	Reason not specified
RC01	BankIdentifierIncorrect	PSP identifier incorrect (i.e. invalid BIC)
RR01	MissingDebtorAccountOrIdentification	Regulatory Reason
RR02	MissingDebtorsNameOrAddress	Regulatory Reason
RR03	MissingCreditorsNameOrAddress	Regulatory Reason
RR04	RegulatoryReason	Regulatory Reason
DNOR	Debtor bank is not registered	Originator PSP is not registered under this BIC in the CSM
CNOR	Creditor bank is not registered	Beneficiary PSP is not registered under this BIC in the CSM

Following code describes the only reason that can be used in a negative confirmation message to the Beneficiary PSP:

ISO Code	ISO Name	SEPA Core Reason as specified in the Rulebook
TM01	InvalidCutOffTime	Time-out – maximum execution time has been exceeded



2.3 Positive Confirmation Message (DS-03)

2.3.1 Use of the FI to FI Payment Status Report (pacs.002.001.10)

When the code "ACCP" (Accepted Customer Profile) is used in the 'Group Status', the message transports the positive confirmation between PSPs, directly or through intermediaries.

The message caters for a single positive confirmation instruction only.

Note: The use case of the message is implied by the Name', 'pacs.002.001.10', the 'Original Message Name Identification' must begin with 'pacs.008' (the addition of a variant number and version number is optional), 'Group Status' set to "ACCP" and 'Payment Type Information' mentioning "INST" (Transaction is related to an Instant Credit Transfer) under 'Local Instrument/Code'.

Note: Message elements under 'Original Transaction Reference' sequence are based on DS-02 attributes.



#	SEPA Mult	Message Element	Positive Confirmation SEPA Core Requirements
		Document	XML Tag Type Document Document
	1..1	FITo FIPayment Status Report V10	ISO Name FITo FIPayment Status Report V10 ISO Definition Scope The FIToFIPaymentStatusReport message is sent by an instructed agent to the previous party in the payment chain. It is used to inform this party about the positive or negative status of an instruction (either single or file). It is also used to report on a pending instruction. XML Tag Type FIToFIPmtStsRpt FIToFIPaymentStatusReportV10
1.0	1..1	FITo FIPayment Status Report V10 +Group Header	ISO Name Group Header ISO Definition Set of characteristics shared by all individual transactions included in the status report message. XML Tag Type GrpHdr GroupHeader91
1.1	1..1	FITo FIPayment Status Report V10 +Group Header ++Message Identification	ISO Name Message Identification ISO Definition Point to point reference, as assigned by the instructing party, and sent to the next party in the chain to unambiguously identify the message. Usage: The instructing party has to make sure that MessageIdentification is unique per instructed party for a pre-agreed period. XML Tag Type MsgId Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35
1.2	1..1	FITo FIPayment Status Report V10 +Group Header ++Creation Date Time	ISO Name Creation Date Time ISO Definition Date and time at which the message was created. XML Tag Type CreDfTm ISODateTime
1.3	0..1	FITo FIPayment Status Report V10 +Group Header ++Instructing Agent	SEPA Usage Rule(s) Only 'BICFI' is allowed. ISO Name Instructing Agent ISO Definition Agent that instructs the next party in the chain to carry out the (set of) instruction(s). Usage: The instructing agent is the party sending the status message and not the party that sent the original instruction that is being reported on. XML Tag Type InstgAgt BranchAndFinancialInstitutionIdentification6
1.4	0..1	FITo FIPayment Status Report V10 +Group Header ++Instructed Agent	SEPA Usage Rule(s) Only 'BICFI' is allowed. ISO Name Instructed Agent ISO Definition Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s). Usage: The instructed agent is the party receiving the status message and not the party that received the original instruction that is being reported on. XML Tag Type InstdAgt BranchAndFinancialInstitutionIdentification6
2.0	1..1	FITo FIPayment Status Report V10 +Original Group Information And Status	SEPA Usage Rule(s) Mandatory. Only one occurrence is allowed ISO Name Original Group Information And Status ISO Definition Original group information concerning the group of transactions, to which the status report message refers to. XML Tag Type OrgnlGrpInfAndSts OriginalGroupHeader17



#	SEPA Mult	Message Element	Positive Confirmation SEPA Core Requirements
2.1	1..1	FITo FIPayment Status Report V10 +Original Group Information And Status ++Original Message Identification	ISO Name Original Message Identification ISO Definition Point to point reference, as assigned by the original instructing party, to unambiguously identify the original message. XML Tag OrgnMsgId Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35
2.2	1..1	FITo FIPayment Status Report V10 +Original Group Information And Status ++Original Message Name Identification	SEPA Usage Rule(s) <i>Must begin with 'pacs.008'. The addition of a variant number and version number is optional.</i> ISO Name Original Message Name Identification ISO Definition Specifies the original message name identifier to which the message refers. XML Tag OrgnMsgNmId Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35
2.3	0..1	FITo FIPayment Status Report V10 +Original Group Information And Status ++Original Creation Date Time	ISO Name Original Creation Date Time ISO Definition Date and time at which the original message was created. XML Tag OrgnCreDtTm Type ISODateTime
2.4	0..1	FITo FIPayment Status Report V10 +Original Group Information And Status ++Original Number Of Transactions	ISO Name Original Number Of Transactions ISO Definition Number of individual transactions contained in the original message. XML Tag OrgnNbOfTxS Type Max15NumericText Pattern [0-9]{1,15}
2.5	0..1	FITo FIPayment Status Report V10 +Original Group Information And Status ++Original Control Sum	ISO Name Original Control Sum ISO Definition Total of all individual amounts included in the original message, irrespective of currencies. XML Tag OrgnCtrlSum Type DecimalNumber SEPA FractDigits 17 TotalDigits 18
2.6	1..1	FITo FIPayment Status Report V10 +Original Group Information And Status ++Group Status	SEPA Usage Rule(s) <i>Mandatory. Only "ACCP" is allowed.</i> ISO Name Group Status ISO Definition Specifies the status of a group of transactions. XML Tag GrpSts Type ExternalPaymentGroupStatus1Code ISO Length 1 .. 4 SEPA Length 1 .. 4 SEPA Code Restrictions ACCP <i>AcceptedCustomerProfile Preceding check of technical validation was successful. Customer profile check was also successful.</i>
2.7	0..n	FITo FIPayment Status Report V10 +Original Group Information And Status ++Status Reason Information	ISO Name Status Reason Information ISO Definition Provides detailed information on the status reason. XML Tag StsRsnInf Type StatusReasonInformation12
2.8	0..n	FITo FIPayment Status Report V10 +Original Group Information And Status ++Number Of Transactions Per Status	ISO Name Number Of Transactions Per Status ISO Definition Detailed information on the number of transactions for each identical transaction status. XML Tag NbOfTxSPerSts Type NumberOfTransactionsPerStatus5



#	SEPA Mult	Message Element	Positive Confirmation SEPA Core Requirements
3.0	1..1	FITo FIPayment Status Report V10 +Transaction Information And Status	<p>SEPA Usage Rule(s) <i>Mandatory.</i> <i>Only once occurrence is allowed.</i></p> <p>ISO Name Transaction Information And Status ISO Definition Information concerning the original transactions, to which the status report message refers.</p> <p>XML Tag TxInfAndSts Type PaymentTransaction110</p>
3.1	1..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Status Identification	<p>SEPA Rulebook <i>AT-T055 The Beneficiary PSP's reference of the SCT Inst Transaction.</i> <i>This ID must be forwarded to the Originator PSP and optionally to the Originator (and therefore it is not a point-to-point reference).</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Status Identification ISO Definition Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the reported status. Usage: The instructing party is the party sending the status message and not the party that sent the original instruction that is being reported on.</p> <p>XML Tag StsId Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35</p>
3.2	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Group Information	<p>ISO Name Original Group Information ISO Definition Point to point reference, as assigned by the original instructing party, to unambiguously identify the original message.</p> <p>XML Tag OrgnlGrpInf Type OriginalGroupInformation29</p>
3.3	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Instruction Identification	<p>SEPA Usage Rule(s) <i>Mandatory if provided in the original instruction.</i></p> <p>ISO Name Original Instruction Identification ISO Definition Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction.</p> <p>XML Tag OrgnlInstrId Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35</p>
3.4	1..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original End To End Identification	<p>SEPA Rulebook <i>AT-T014 The Originator's reference of the SCT Inst Instruction.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Original End To End Identification ISO Definition Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction.</p> <p>XML Tag OrgnlEndToEndId Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35</p>
3.5	1..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Identification	<p>SEPA Rulebook <i>AT-T054 The Originator PSP's reference number of the SCT Inst Transaction message.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Original Transaction Identification ISO Definition Unique identification, as assigned by the original first instructing agent, to unambiguously identify the transaction.</p> <p>XML Tag OrgnlTxId Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35</p>



#	SEPA Mult	Message Element	Positive Confirmation SEPA Core Requirements	
3.6	0..1	FIto FIPayment Status Report V10 +Transaction Information And Status ++Original UETR	ISO Name ISO Definition XML Tag Type Pattern	Original UETR Universally unique identifier to provide the original end-to-end reference of a payment transaction. OrgnUETR UUIV4Identifier [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}
3.7	0..1	FIto FIPayment Status Report V10 +Transaction Information And Status ++Transaction Status	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Transaction Status Specifies the status of a transaction, in a coded form. TxSts ExternalPaymentTransactionStatus1Code 1 .. 4 1 .. 4
3.8	0..n	FIto FIPayment Status Report V10 +Transaction Information And Status ++Status Reason Information	ISO Name ISO Definition XML Tag Type	Status Reason Information Provides detailed information on the status reason. StsRsnInf StatusReasonInformation12
3.9	0..n	FIto FIPayment Status Report V10 +Transaction Information And Status ++Charges Information	ISO Name ISO Definition XML Tag Type	Charges Information Provides information on the charges related to the processing of the rejection of the instruction. Usage: This is passed on for information purposes only. Settlement of the charges will be done separately. ChrgsInf Charges7
3.10	1..1	FIto FIPayment Status Report V10 +Transaction Information And Status ++Acceptance Date Time	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT- T056 Timestamp of the SCT Inst Transaction. Mandatory. Acceptance Date Time Point in time when the payment order from the initiating party meets the processing conditions of the account servicing agent. This means that the account servicing agent has received the payment order and has applied checks such as authorisation, availability of funds. AcptncDtTm ISODateTime
3.11	0..1	FIto FIPayment Status Report V10 +Transaction Information And Status ++Effective Interbank Settlement Date	ISO Name ISO Definition XML Tag Type	Effective Interbank Settlement Date Date and time at which a transaction is completed and cleared, that is, payment is effected. FctvIntrBkStilmDt DateAndDateTime2Choice
3.12	0..1	FIto FIPayment Status Report V10 +Transaction Information And Status ++Account Servicer Reference	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Account Servicer Reference Unique reference, as assigned by the account servicing institution, to unambiguously identify the instruction. AcctSvcrRef Max35Text 1 .. 35 1 .. 35
3.13	0..1	FIto FIPayment Status Report V10 +Transaction Information And Status ++Clearing System Reference	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Clearing System Reference Unique reference, as assigned by a clearing system, to unambiguously identify the instruction. ClrSysRef Max35Text 1 .. 35 1 .. 35



#	SEPA Mult	Message Element	Positive Confirmation SEPA Core Requirements	
3.14	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Instructing Agent	ISO Name ISO Definition XML Tag Type	Instructing Agent Agent that instructs the next party in the chain to carry out the (set of) instruction(s). Usage: The instructing agent is the party sending the status message and not the party that sent the original instruction that is being reported on. InstgAgt BranchAndFinancialInstitutionIdentification6
3.15	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Instructed Agent	ISO Name ISO Definition XML Tag Type	Instructed Agent Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s). Usage: The instructed agent is the party receiving the status message and not the party that received the original instruction that is being reported on. InstdAgt BranchAndFinancialInstitutionIdentification6
3.16	1..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference	ISO Name ISO Definition XML Tag Type	<i>SEPA Usage Rule(s) Mandatory.</i> <i>The message elements under 'Original Transaction Reference' must be populated with the same value as the message elements of the original instruction.</i> Original Transaction Reference Key elements used to identify the original transaction that is being referred to. OrgnlTxRef OriginalTransactionReference28
3.17	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Interbank Settlement Amount	ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits SEPA Inclusive	Interbank Settlement Amount Amount of money moved between the instructing agent and the instructed agent. IntrBkSttlmAmt ActiveOrHistoricCurrencyAndAmount 5 18 0 ..
3.18	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Amount	ISO Name ISO Definition XML Tag Type	Amount Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party. Amt AmountType4Choice
3.19	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Interbank Settlement Date	ISO Name ISO Definition XML Tag Type	Interbank Settlement Date Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. IntrBkSttlmDt ISODate
3.20	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Requested Collection Date	ISO Name ISO Definition XML Tag Type	Requested Collection Date Date and time at which the creditor requests that the amount of money is to be collected from the debtor. ReqdCollmDt ISODate



#	SEPA Mult	Message Element	Positive Confirmation SEPA Core Requirements	
3.21	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Requested Execution Date	ISO Name ISO Definition XML Tag Type	Requested Execution Date Date at which the initiating party requests the clearing agent to process the payment. Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank. ReqdExctnDt DateAndDateTime2Choice
3.22	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Creditor Scheme Identification	ISO Name ISO Definition XML Tag Type	Creditor Scheme Identification Credit party that signs the mandate. CdtrSchmeld PartyIdentification135
3.23	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Settlement Information	ISO Name ISO Definition XML Tag Type	Settlement Information Specifies the details on how the settlement of the original transaction(s) between the instructing agent and the instructed agent was completed. SttlmInf SettlementInstruction7
3.24	1..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Payment Type Information	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-T008 The category purpose of the SCT Inst Instruction. AT-T001 The identification code of the SCT Inst Scheme. Mandatory. Payment Type Information Set of elements used to further specify the type of transaction. PmtTpInf PaymentTypeInfo27
3.25	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Payment Method	ISO Name ISO Definition XML Tag Type	Payment Method Specifies the means of payment that will be used to move the amount of money. PmtMtd PaymentMethod4Code
3.26	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Mandate Related Information	ISO Name ISO Definition XML Tag Type	Mandate Related Information Provides further details of the mandate signed between the creditor and the debtor. MndtRltdInf MandateRelatedInformation14
3.27	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Remittance Information	ISO Name ISO Definition XML Tag Type	Remittance Information Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system. RmtInf RemittanceInformation16
3.28	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Ultimate Debtor	ISO Name ISO Definition XML Tag Type	Ultimate Debtor Ultimate party that owes an amount of money to the (ultimate) creditor. UltmtDbtr Party40Choice
3.29	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Debtor	ISO Name ISO Definition XML Tag Type	Debtor Party that owes an amount of money to the (ultimate) creditor. Dbtr Party40Choice
3.30	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Debtor Account	ISO Name ISO Definition XML Tag Type	Debtor Account Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction. DbtrAcct CashAccount38



#	SEPA Mult	Message Element	Positive Confirmation SEPA Core Requirements	
3.31	1..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Debtor Agent	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-D002 BIC code of the Originator PSP.</i> Mandatory. Debtor Agent Financial institution servicing an account for the debtor. DbtrAgt BranchAndFinancialInstitutionIdentification6
3.32	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Debtor Agent Account	ISO Name ISO Definition XML Tag Type	Debtor Agent Account Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain. DbtrAgtAcct CashAccount38
3.33	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Creditor Agent	ISO Name ISO Definition XML Tag Type	Creditor Agent Financial institution servicing an account for the creditor. CdtrAgt BranchAndFinancialInstitutionIdentification6
3.34	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Creditor Agent Account	ISO Name ISO Definition XML Tag Type	Creditor Agent Account Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction. CdtrAgtAcct CashAccount38
3.35	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Creditor	ISO Name ISO Definition XML Tag Type	Creditor Party to which an amount of money is due. Cdtr Party40Choice
3.36	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Creditor Account	ISO Name ISO Definition XML Tag Type	Creditor Account Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction. CdtrAcct CashAccount38
3.37	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Ultimate Creditor	ISO Name ISO Definition XML Tag Type	Ultimate Creditor Ultimate party to which an amount of money is due. UltmtCdtr Party40Choice
3.38	0..1	FITo FIPayment Status Report V10 +Transaction Information And Status ++Original Transaction Reference +++Purpose	ISO Name ISO Definition XML Tag Type	Purpose Underlying reason for the payment transaction. Usage: Purpose is used by the end customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain. Purp Purpose2Choice
3.39	0..n	FITo FIPayment Status Report V10 +Transaction Information And Status ++Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1



#	SEPA Mult	Message Element	Positive Confirmation SEPA Core Requirements	
4.0	0..n	FIto FIPayment Status Report V10 +Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1



2.4 Recall of an SCT Inst Dataset (DS-05)

2.4.1 Use of FI-to-FI Payment Cancellation Request (camt.056.001.08)

The message is used to submit the request to cancel a pacs.008.001.08 or to cancel specified transactions from the Originator PSP to the next PSP in the chain or to the CSM, or from the CSM to the next PSP in the chain, where the following apply:

- Index 4.3 'Cancellation Identification' can only be populated with AT-R053 'The specific reference of the PSP initiating the Recall'.
- Index 4.19 'Originator' can only be populated with AT-R002 'Identification of the type of party initiating the R-message'.
- Index 4.20 'Reason' is to be populated with AT-R051 'The Recall reason code', where:
 - Index 4.21 'Code' can only be populated with ISO codes "DUPL" (Duplicate payment), "FRAD" (Fraudulent origin) and "TECH" (Technical problem).
- Index 4.23 'Additional Information' is allowed only when "FRAD" is used as Recall reason code and in such case is to be populated with AT-R052 'Additional Information to AT-R051 The Recall reason code'.

The message caters for single or group cancellation requests. Group cancellation requests allow recall of single or multiple transactions from single or multiple original messages.

Note: Attribute AT-R001 'The type of R-message' is implied by the 'Message Name' set to 'camt.056.001.08', the 'Original Message Name Identification' must begin with 'pacs.008' (the addition of a variant number and version number is optional), 'Reason' set to "DUPL", "FRAD" or "TECH" (under 'Code') and 'Payment Type Information' mentioning "INST" (Transaction is related to an Instant Credit Transfer) under 'Local Instrument/Code' .

Note: Message elements under 'Original Transaction Reference' sequence are based on DS-02 attributes.

Note: Only one Recall can be sent for a given SCT Inst Transaction during the periods mentioned in the SCT Inst Rulebook [1]. The Originator PSP is not allowed to send another SCT Inst Recall for the same initial SCT Inst Transaction.



#	SEPA Mult	Message Element	Recall of a SCT Inst SEPA Core Requirements	
		Document	XML Tag Type	Document Document
	1..1	FITo FIPayment Cancellation Request V08	ISO Name ISO Definition	FITo FIPayment Cancellation Request V08 Scope The FIToFIPaymentCancellationRequest message is sent by a case creator/case assigner to a case assignee. This message is used to request the cancellation of an original payment instruction. The FIToFIPaymentCancellationRequest message is exchanged between the instructing agent and the instructed agent to request the cancellation of an interbank payment message previously sent (such as FIToFICustomerCreditTransfer, FIToFICustomerDirectDebit or FinancialInstitutionCreditTransfer). The FIToFIPaymentCancellationRequest message supports both the request for cancellation (the instructed agent - or assignee - has not yet processed and forwarded the payment instruction) as well as the request for refund (payment has been fully processed already by the instructed agent - or assignee). XML Tag Type FIToFIPmtCxlReq FIToFIPaymentCancellationRequestV08
1.0	1..1	FITo FIPayment Cancellation Request V08 +Assignment	ISO Name ISO Definition	Assignment Identifies the assignment of an investigation case from an assigner to an assignee. Usage: The assigner must be the sender of this confirmation and the assignee must be the receiver. XML Tag Type Assgnmt CaseAssignment5
1.1	1..1	FITo FIPayment Cancellation Request V08 +Assignment ++Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Identification Uniquely identifies the case assignment. Id Max35Text 1 .. 35 1 .. 35
1.2	1..1	FITo FIPayment Cancellation Request V08 +Assignment ++Assigner	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>Instructing Party.</i> <i>Limited to 'BICFI' to identify a PSP, 'AnyBIC' to identify a CSM or 'LEI' or 'Name' to indicate a CSM when it has no BIC.</i> <i>'Name' is limited to 70 characters in length.</i> Assigner Party who assigns the case. Usage: This is also the sender of the message. Assgnr Party40Choice
1.3	1..1	FITo FIPayment Cancellation Request V08 +Assignment ++Assignee	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>Instructed Party.</i> <i>Limited to 'BICFI' to identify a PSP, 'AnyBIC' to identify a CSM or 'LEI' or 'Name' to indicate a CSM when it has no BIC.</i> <i>'Name' is limited to 70 characters in length.</i> Assignee Party to which the case is assigned. Usage: This is also the receiver of the message. Assgne Party40Choice



#	SEPA Mult	Message Element	Recall of a SCT Inst SEPA Core Requirements
1.4	1..1	FITo FIPayment Cancellation Request V08 +Assignment ++Creation Date Time	ISO Name Creation Date Time ISO Definition Date and time at which the assignment was created. XML Tag CreDtTm Type ISODateTime
2.0	0..1	FITo FIPayment Cancellation Request V08 +Case	ISO Name Case ISO Definition Identifies the investigation case. XML Tag Case Type Case5
3.0	0..1	FITo FIPayment Cancellation Request V08 +Control Data	ISO Name Control Data ISO Definition Provides details on the number of transactions and the control sum of the message. XML Tag CtrlData Type ControlData1
3.1	1..1	FITo FIPayment Cancellation Request V08 +Control Data ++Number Of Transactions	ISO Name Number Of Transactions ISO Definition Number of individual transactions contained in the message. XML Tag NbOfTxS Type Max15NumericText Pattern [0-9]{1,15}
3.2	0..1	FITo FIPayment Cancellation Request V08 +Control Data ++Control Sum	ISO Name Control Sum ISO Definition Total of all individual amounts included in the message, irrespective of currencies. XML Tag CtrlSum Type DecimalNumber SEPA FractDigits 17 TotalDigits 18
4.0	1..n	FITo FIPayment Cancellation Request V08 +Underlying	ISO Name Underlying ISO Definition Identifies the payment instruction to be cancelled. XML Tag Undrlyg Type UnderlyingTransaction23
4.1	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Original Group Information And Cancellation	ISO Name Original Group Information And Cancellation ISO Definition Provides information on the original message, to which the cancellation refers. XML Tag OrgnlGrpInfAndCxl Type OriginalGroupHeader15
4.2	1..n	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information	SEPA Usage Rule(s) <i>Mandatory.</i> ISO Name Transaction Information ISO Definition Provides information on the original transactions to which the cancellation request message refers. XML Tag TxInf Type PaymentTransaction106
4.3	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Cancellation Identification	SEPA Rulebook <i>AT-R053 The specific reference of the Originator PSP initiating the Recall.</i> SEPA Usage Rule(s) <i>Mandatory.</i> <i>This ID must be forwarded in the handling of the Recall message to the Beneficiary PSP and optionally to the Beneficiary (and therefore it is not a point-to-point reference).</i> ISO Name Cancellation Identification ISO Definition Unique and unambiguous identifier of a cancellation request, as assigned by the assigner. Usage: The cancellation request identification can be used for reconciliation or to link tasks relating to the cancellation request. XML Tag CxIID Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35



#	SEPA Mult	Message Element	Recall of a SCT Inst SEPA Core Requirements	
4.4	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Case	ISO Name ISO Definition XML Tag Type	Case Set of elements to uniquely and unambiguously identify an exception or an investigation workflow. Case Case5
4.5	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Group Information	<i>SEPA Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>Mandatory.</i> Original Group Information Provides information on the original message. OrgnlGrpInf OriginalGroupInformation29
4.6	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Group Information ++++Original Message Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Message Identification Point to point reference assigned by the original instructing party to unambiguously identify the original message. OrgnlMsgId Max35Text 1 .. 35 1 .. 35
4.7	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Group Information ++++Original Message Name Identification	<i>SEPA Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>Must begin with 'pacs.008'. The addition of a variant number and version number is optional.</i> Original Message Name Identification Specifies the original message name identifier to which the message refers, for example, pacs.003.001.01 or MT103. OrgnlMsgNmId Max35Text 1 .. 35 1 .. 35
4.8	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Group Information ++++Original Creation Date Time	ISO Name ISO Definition XML Tag Type	Original Creation Date Time Original date and time at which the message was created. OrgnlCreDtTm ISODateTime
4.9	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Instruction Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Instruction Identification Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction. OrgnlInstrId Max35Text 1 .. 35 1 .. 35
4.10	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original End To End Identification	<i>SEPA Rulebook</i> <i>SEPA Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>AT-T014 The Originator's reference of the SCT Inst Transaction.</i> <i>Mandatory.</i> Original End To End Identification Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction. OrgnlEndToEndId Max35Text 1 .. 35 1 .. 35



#	SEPA Mult	Message Element	Recall of a SCT Inst SEPA Core Requirements	
4.11	1..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Identification	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>AT-T054 The Originator PSP's reference of the SCT Inst Transaction message.</i> Mandatory. Original Transaction Identification Unique identification, as assigned by the original first instructing agent, to unambiguously identify the transaction. OrgnlTxId Max35Text 1 .. 35 1 .. 35
4.12	0..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original UETR	ISO Name ISO Definition XML Tag Type Pattern	Original UETR Universally unique identifier to provide the original end-to-end reference of a payment transaction. OrgnlUETR UUIDv4Identifier [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}
4.13	0..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Clearing System Reference	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Clearing System Reference Unique reference, as assigned by the original clearing system, to unambiguously identify the original instruction. OrgnlClrSysRef Max35Text 1 .. 35 1 .. 35
4.14	1..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Interbank Settlement Amount	SEPA Rulebook SEPA Usage Rule(s) SEPA Format Rule(s) ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits SEPA Inclusive	<i>AT-T002 The amount of the SCT Inst in euro.</i> Mandatory. <i>The fractional part has a maximum of two digits.</i> Original Interbank Settlement Amount Amount of money moved between the instructing agent and the instructed agent, as provided in the original instruction. OrgnlIntrBkStlmAmt ActiveOrHistoricCurrencyAndAmount 2 18 0.01 .. 999999999.99
4.15	1..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Interbank Settlement Date	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-T051 The Settlement Date of the SCT Inst Transaction.</i> Mandatory. Original Interbank Settlement Date Date, as provided in the original transaction, on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. OrgnlIntrBkStlmDt ISODate
4.16	0..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Assigner	ISO Name ISO Definition XML Tag Type	Assigner Party who assigns the case. Usage: This is also the agent that instructs the next party in the chain to carry out the (set of) cancellation request(s). Assgnr BranchAndFinancialInstitutionIdentification6



#	SEPA Mult	Message Element	Recall of a SCT Inst SEPA Core Requirements	
4.17	0..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Assignee	ISO Name ISO Definition XML Tag Type	Assignee Party to which the case is assigned. Usage: This is also the agent that is instructed by the previous party in the chain to carry out the (set of) cancellation request(s). Assgne BranchAndFinancialInstitutionIdentification6
4.18	1..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Cancellation Reason Information	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>Mandatory.</i> <i>Only one occurrence is allowed.</i> Cancellation Reason Information Provides detailed information on the cancellation reason. CxIRsnInf PaymentCancellationReason5
4.19	1..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Cancellation Reason Information ++++Originator	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-R002 Identification of the type of party initiating the "R"-message.</i> <i>Mandatory.</i> <i>Limited to 'AnyBIC' for an Agent or 'Name' for a non-financial institution.</i> <i>'Name' is limited to 70 characters in length.</i> Originator Party that issues the cancellation request. Orgtr PartyIdentification135
4.20	1..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Cancellation Reason Information ++++Reason	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-R051 The Recall reason code.</i> <i>Mandatory.</i> Reason Specifies the reason for the cancellation. Rsn CancellationReason33Choice
	1..1		XML Tag	xs:choice
4.21	1..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Cancellation Reason Information ++++Reason +++++Code	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>Only "DUPL", "FRAD" and "TECH" are allowed.</i> Code Reason for the cancellation request, in a coded form. Cd ExternalCancellationReason1Code 1 .. 4 1 .. 4
SEPA Code Restrictions				
DUPL <i>DuplicatePayment</i> <i>Payment is a duplicate of another payment.</i>				
FRAD <i>FraudulentOrigin</i> <i>Cancellation requested following a transaction that was originated fraudulently. The use of the FraudulentOrigin code should be governed by jurisdictions.</i>				
TECH <i>TechnicalProblem</i> <i>Cancellation requested following technical problems resulting in an erroneous transaction.</i>				
4.22	1..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Cancellation Reason Information ++++Reason +++++Proprietary	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Proprietary Reason for the cancellation request, in a proprietary form. Prtry Max35Text 1 .. 35 1 .. 35



#	SEPA Mult	Message Element	Recall of a SCT Inst SEPA Core Requirements	
4.23	0..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Cancellation Reason Information ++++Additional Information	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>AT-R052 Additional information to AT-R051 The Recall reason code.</i> <i>Only allowed when "FRAD" is used as a Recall reason code.</i> <i>Only one occurrence is allowed.</i> Additional Information Further details on the cancellation request reason. AddtlInf Max105Text 1 .. 105 1 .. 105
4.24	1..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>An exact copy of all attributes of the initially sent DS-02 which is to be cancelled.</i> <i>Mandatory.</i> <i>The message elements under 'Original Transaction Reference' must be populated with the same value as the message elements of the original instruction.</i> Original Transaction Reference Key elements used to identify the original transaction that is being referred to. OrgnlTxRef OriginalTransactionReference28
4.25	0..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Interbank Settlement Amount	ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits SEPA Inclusive	Interbank Settlement Amount Amount of money moved between the instructing agent and the instructed agent. IntrBkSttlmAmt ActiveOrHistoricCurrencyAndAmount 5 18 0 ..
4.26	0..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Amount	ISO Name ISO Definition XML Tag Type	Amount Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party. Amt AmountType4Choice
4.27	0..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Interbank Settlement Date	ISO Name ISO Definition XML Tag Type	Interbank Settlement Date Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. IntrBkSttlmDt ISODate
4.28	0..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Requested Collection Date	ISO Name ISO Definition XML Tag Type	Requested Collection Date Date and time at which the creditor requests that the amount of money is to be collected from the debtor. ReqdCollmDt ISODate
4.29	0..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Requested Execution Date	ISO Name ISO Definition XML Tag Type	Requested Execution Date Date at which the initiating party requests the clearing agent to process the payment. Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank. ReqdExctmDt DateAndDateTime2Choice



#	SEPA Mult	Message Element	Recall of a SCT Inst SEPA Core Requirements	
4.30	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Creditor Scheme Identification	ISO Name ISO Definition XML Tag Type	Creditor Scheme Identification Credit party that signs the mandate. CdtmSchmeld PartyIdentification135
4.31	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Settlement Information	ISO Name ISO Definition XML Tag Type	Settlement Information Specifies the details on how the settlement of the original transaction(s) between the instructing agent and the instructed agent was completed. SttlmInf SettlementInstruction7
4.32	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Payment Type Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T001 The Identification code of the SCT Inst Scheme.</i> <i>AT-T008 The category purpose of the SCT Inst Instruction.</i> Payment Type Information Set of elements used to further specify the type of transaction. PmtTpInf PaymentTypeInfo27
4.33	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Payment Method	ISO Name ISO Definition XML Tag Type	Payment Method Specifies the means of payment that will be used to move the amount of money. PmtMtd PaymentMethod4Code
4.34	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Mandate Related Information	ISO Name ISO Definition XML Tag Type	Mandate Related Information Provides further details of the mandate signed between the creditor and the debtor. MndtRltdInf MandateRelatedInformation14
4.35	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Remittance Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T009 The Remittance information.</i> Remittance Information Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system. RmtInf RemittanceInformation16
4.36	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Ultimate Debtor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-P006 The name of the Originator Reference Party.</i> <i>AT-P007 The identification code of the Originator Reference Party.</i> <i>Only 'Party' is allowed.</i> Ultimate Debtor Ultimate party that owes an amount of money to the (ultimate) creditor. UltmtDbtr Party40Choice
4.37	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Debtor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-P001 The name of the Originator.</i> <i>AT-P005 The address of the Originator.</i> <i>AT-P004 The Originator's identification code.</i> <i>Only 'Party' is allowed.</i> Debtor Party that owes an amount of money to the (ultimate) creditor. Dbtr Party40Choice



#	SEPA Mult	Message Element	Recall of a SCT Inst SEPA Core Requirements	
4.38	1..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Debtor Account	<i>SEPA Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-D001 The IBAN of the account of the Originator.</i> <i>AT-P003 The Proxy/Alias of the account of the Originator.</i> Debtor Account Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction. DbtrAcct CashAccount38
4.39	0..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Debtor Agent	<i>SEPA Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-D002 The BIC code of the Originator PSP.</i> Debtor Agent Financial institution servicing an account for the debtor. DbtrAgt BranchAndFinancialInstitutionIdentification6
4.40	0..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Debtor Agent Account	ISO Name ISO Definition XML Tag Type	Debtor Agent Account Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain. DbtrAgtAcct CashAccount38
4.41	0..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Creditor Agent	<i>SEPA Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-C002 The BIC code of the Beneficiary PSP.</i> Creditor Agent Financial institution servicing an account for the creditor. CdtrAgt BranchAndFinancialInstitutionIdentification6
4.42	0..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Creditor Agent Account	ISO Name ISO Definition XML Tag Type	Creditor Agent Account Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction. CdtrAgtAcct CashAccount38
4.43	0..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Creditor	<i>SEPA Rulebook</i> <i>SEPA Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>AT-E001 The name of the Beneficiary.</i> <i>AT-E004 The address of the Beneficiary.</i> <i>AT-E005 The Beneficiary identification code.</i> <i>Only 'Party' is allowed.</i> Creditor Party to which an amount of money is due. Cdtr Party40Choice
4.44	1..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Creditor Account	<i>SEPA Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-C001 The IBAN of the account of the Beneficiary.</i> <i>AT-E003 The Proxy/Alias of the account of the Beneficiary.</i> Creditor Account Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction. CdtrAcct CashAccount38
4.45	0..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Ultimate Creditor	<i>SEPA Rulebook</i> <i>SEPA Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>AT-E007 The name of the Beneficiary Reference Party.</i> <i>AT-E010 The identification code of the Beneficiary Reference Party.</i> <i>Only 'Party' is allowed.</i> Ultimate Creditor Ultimate party to which an amount of money is due. UltmtCdtr Party40Choice



#	SEPA Mult	Message Element	Recall of a SCT Inst SEPA Core Requirements	
4.46	0..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Purpose	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T007 The purpose of the SCT Inst Instruction.</i> Purpose Underlying reason for the payment transaction. Usage: Purpose is used by the end customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain. Purp Purpose2Choice
4.47	0..n	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1
5.0	0..n	FIto FIPayment Cancellation Request V08 +Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1



2.5 Inter-PSP Negative Response to a Recall of an SCT Inst Dataset (DS-06)

2.5.1 Use of Resolution of Investigation (camt.029.001.09)

In the context of a Recall of an SCT Inst, this message is to be used to transmit a negative response to a:

- Recall message (FI-to-FI Payment Cancellation Request V01, camt.056.001.08);
- Request for Status Update on a Recall message (FI-to-FI Payment Status Request, pacs.028.001.03, refer to section 'Request for Status Update on a Recall message below');

where the following apply:

- Index 3.0 'Status': only sub-element 'Confirmation' can be used, populated with "RJCR" (Rejected Cancellation Request) only.
- Index 4.21 'Additional Information' under 'Cancellation Status Reason Information':
 - A mandatory occurrence starting with "ATR053/" followed by the information as per attribute description 'The specific reference of the Originator PSP initiating the Recall'.
 - In addition:
 - if index 4.19 'Code' under 'Reason' is set to "LEGL", two further occurrences are allowed to precise the reason and these must start with "ATR057/", and/or
 - if 'Code' under 'Reason' was "FRAD" (Fraudulent originated SCT Inst) in the camt.056 (DS-05), then up to ten further optional occurrences are allowed, all starting with "FRAD/" followed by all information available to file a legal claim to recover the funds in case of reason code 'Fraudulent originated SCT Inst'.
 - As a consequence, the 'SEPA Mult.' is set to [1..13].

The message caters for a single or group negative response.

Note: Attribute AT-R001 'The type of R-message' is implied by the 'Message Name', 'camt.029.001.09', the 'Original Message Name Identification' must begin with 'pacs.008' (the addition of a variant number and version number is optional), 'Status' set to "RJCR" and 'Payment Type Information' mentioning "INST" (Transaction is related to an Instant Credit Transfer) under 'Local Instrument/Code'.

Note: Message elements under 'Original Transaction Reference' sequence are based on DS-02 attributes.



#	SEPA Mult	Message Element	Inter-PSP Negative Response to a Recall of a SCT Inst SEPA Core Requirements	
		Document	XML Tag Type	Document Document
	1..1	Resolution Of Investigation V09	ISO Name ISO Definition XML Tag Type	Resolution Of Investigation V09 Scope The ResolutionOfInvestigation message is sent by a case assignee to a case creator/case assigner. This message is used to inform of the resolution of a case, and optionally provides details about. - the corrective action undertaken by the case assignee; - information on the return where applicable. The ResolutionOfInvestigation message should be the sole message to respond to a cancellation request. Details of the underlying transactions and the related statuses for which the cancellation request has been issued may be provided in the CancellationDetails component. RsltnOfInvstgtn ResolutionOfInvestigationV09
1.0	1..1	Resolution Of Investigation V09 +Assignment	ISO Name ISO Definition XML Tag Type	Assignment Identifies the assignment of an investigation case from an assigner to an assignee. Usage: The assigner must be the sender of this confirmation and the assignee must be the receiver. Assgnmt CaseAssignment5
1.1	1..1	Resolution Of Investigation V09 +Assignment ++Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Identification Uniquely identifies the case assignment. Id Max35Text 1 .. 35 1 .. 35
1.2	1..1	Resolution Of Investigation V09 +Assignment ++Assigner	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>Instructing Party.</i> <i>Limited to 'BICFI' to identify a PSP, 'AnyBIC' to identify a CSM or 'LEI' or 'Name' to indicate a CSM when it has no BIC.</i> <i>'Name' is limited to 70 characters in length.</i> Assigner Party who assigns the case. Usage: This is also the sender of the message. Assgnr Party40Choice
1.3	1..1	Resolution Of Investigation V09 +Assignment ++Assignee	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>Instructed Party.</i> <i>Limited to 'BICFI' to identify a PSP, 'AnyBIC' to identify a CSM or 'LEI' or 'Name' to indicate a CSM when it has no BIC.</i> <i>'Name' is limited to 70 characters in length.</i> Assignee Party to which the case is assigned. Usage: This is also the receiver of the message. Assgne Party40Choice
1.4	1..1	Resolution Of Investigation V09 +Assignment ++Creation Date Time	ISO Name ISO Definition XML Tag Type	Creation Date Time Date and time at which the assignment was created. CreDfTm ISODateTime
2.0	0..1	Resolution Of Investigation V09 +Resolved Case	ISO Name ISO Definition XML Tag Type	Resolved Case Identifies a resolved case. RslvdCase Case5



#	SEPA Mult	Message Element	Inter-PSP Negative Response to a Recall of a SCT Inst SEPA Core Requirements
3.0	1..1	Resolution Of Investigation V09 +Status	<p>SEPA Usage Rule(s) Only 'Confirmation' is allowed.</p> <p>ISO Name Status</p> <p>ISO Definition Indicates the status of the investigation.</p> <p>XML Tag Sts</p> <p>Type InvestigationStatus5Choice</p>
	1..1		XML Tag xs:choice
3.1	1..1	Resolution Of Investigation V09 +Status ++Confirmation	<p>SEPA Usage Rule(s) Only "RJCR" is allowed.</p> <p>ISO Name Confirmation</p> <p>ISO Definition Specifies the status of the investigation, in a coded form.</p> <p>XML Tag Conf</p> <p>Type ExternalInvestigationExecutionConfirmation1Code</p> <p>ISO Length 1 .. 4</p> <p>SEPA Length 1 .. 4</p>
			<p>SEPA Code Restrictions</p> <p>RJCR <i>RejectedCancellationRequest</i> Used when a requested cancellation has been rejected.</p>
3.2	1..n	Resolution Of Investigation V09 +Status ++Rejected Modification	<p>ISO Name Rejected Modification</p> <p>ISO Definition Reason for the rejection of a modification request, in a coded form.</p> <p>XML Tag RjctdMod</p> <p>Type ModificationStatusReason1Choice</p>
3.3	1..1	Resolution Of Investigation V09 +Status ++Duplicate Of	<p>ISO Name Duplicate Of</p> <p>ISO Definition Indicates a duplicated case. Usage: When present, the case identified in the message must be closed. The case identified as duplicated (in this component) will be pursued.</p> <p>XML Tag DpctOf</p> <p>Type Case5</p>
3.4	1..1	Resolution Of Investigation V09 +Status ++Assignment Cancellation Confirmation	<p>ISO Name Assignment Cancellation Confirmation</p> <p>ISO Definition Indicates whether the cancellation of the assignment is confirmed or rejected. Usage: If yes, the cancellation of the assignment is confirmed. If no, the cancellation of the assignment is rejected and the investigation process will continue.</p> <p>XML Tag AssgnmtCxlConf</p> <p>Type YesNoIndicator</p>
4.0	1..n	Resolution Of Investigation V09 +Cancellation Details	<p>SEPA Usage Rule(s) Mandatory.</p> <p>ISO Name Cancellation Details</p> <p>ISO Definition Specifies the details of the underlying transactions being cancelled.</p> <p>XML Tag CxlDtls</p> <p>Type UnderlyingTransaction22</p>
4.1	0..1	Resolution Of Investigation V09 +Cancellation Details ++Original Group Information And Status	<p>ISO Name Original Group Information And Status</p> <p>ISO Definition Provides information on the original cancellation message, to which the resolution refers.</p> <p>XML Tag OrgnlGrpInfAndSts</p> <p>Type OriginalGroupHeader14</p>
4.2	0..n	Resolution Of Investigation V09 +Cancellation Details ++Original Payment Information And Status	<p>ISO Name Original Payment Information And Status</p> <p>ISO Definition Provides information on the original (group of) transactions, to which the cancellation status refers.</p> <p>XML Tag OrgnlPmtInfAndSts</p> <p>Type OriginalPaymentInstruction30</p>



#	SEPA Mult	Message Element	Inter-PSP Negative Response to a Recall of a SCT Inst SEPA Core Requirements
4.3	1..n	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status	<i>SEPA Usage Rule(s) Mandatory.</i> ISO Name Transaction Information And Status ISO Definition Provides details on the original transactions to which the cancellation request message refers. XML Tag TxInfAndSts Type PaymentTransaction102
4.4	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Cancellation Status Identification	<i>SEPA Usage Rule(s) Mandatory.</i> ISO Name Cancellation Status Identification ISO Definition Unique and unambiguous identifier of a cancellation request status, as assigned by the assigner. Usage: The cancellation status identification can be used for reconciliation or to link tasks relating to the cancellation request. XML Tag CxlStsId Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35
4.5	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Resolved Case	ISO Name Resolved Case ISO Definition Identifies the resolved case. XML Tag RslvdCase Type Case5
4.6	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Group Information	<i>SEPA Usage Rule(s) Mandatory.</i> ISO Name Original Group Information ISO Definition Provides information on the original message. XML Tag OrgnlGrpInf Type OriginalGroupInformation29
4.7	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Group Information ++++Original Message Identification	ISO Name Original Message Identification ISO Definition Point to point reference assigned by the original instructing party to unambiguously identify the original message. XML Tag OrgnlMsgId Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35
4.8	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Group Information ++++Original Message Name Identification	<i>SEPA Usage Rule(s) Must begin with 'pacs.008'. The addition of a variant number and version number is optional.</i> ISO Name Original Message Name Identification ISO Definition Specifies the original message name identifier to which the message refers, for example, pacs.003.001.01 or MT103. XML Tag OrgnlMsgNmId Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35
4.9	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Group Information ++++Original Creation Date Time	ISO Name Original Creation Date Time ISO Definition Original date and time at which the message was created. XML Tag OrgnlCreDtTm Type ISODateTime
4.10	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Instruction Identification	ISO Name Original Instruction Identification ISO Definition Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction. XML Tag OrgnlInstrId Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35



#	SEPA Mult	Message Element	Inter-PSP Negative Response to a Recall of a SCT Inst SEPA Core Requirements
4.11	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original End To End Identification	<p>SEPA Rulebook AT-T014 The Originator's reference of the SCT Inst Instruction.</p> <p>SEPA Usage Rule(s) Mandatory.</p> <p>ISO Name Original End To End Identification</p> <p>ISO Definition Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction.</p> <p>XML Tag OrgnlEndToEndId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>
4.12	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Identification	<p>SEPA Rulebook AT-T054 The Originator PSP's reference of the SCT Inst Transaction message.</p> <p>SEPA Usage Rule(s) Mandatory.</p> <p>ISO Name Original Transaction Identification</p> <p>ISO Definition Unique identification, as assigned by the original first instructing agent, to unambiguously identify the transaction.</p> <p>XML Tag OrgnlTxId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>
4.13	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Clearing System Reference	<p>ISO Name Original Clearing System Reference</p> <p>ISO Definition Unique reference, as assigned by the original clearing system, to unambiguously identify the original instruction.</p> <p>XML Tag OrgnlClrSysRef</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>
4.14	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original UETR	<p>ISO Name Original UETR</p> <p>ISO Definition Universally unique identifier to provide the original end-to-end reference of a payment transaction.</p> <p>XML Tag OrgnlUETR</p> <p>Type UUIDv4Identifier</p> <p>Pattern [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}</p>
4.15	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Transaction Cancellation Status	<p>SEPA Usage Rule(s) Mandatory. Only "RJCR" is allowed.</p> <p>ISO Name Transaction Cancellation Status</p> <p>ISO Definition Specifies the status of the transaction cancellation request.</p> <p>XML Tag TxCxlSts</p> <p>Type CancellationIndividualStatus1Code</p> <p>SEPA Code Restrictions</p> <p>RJCR RejectedCancellationRequest Cancellation request is rejected</p>
4.16	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Cancellation Status Reason Information	<p>SEPA Usage Rule(s) Mandatory. Only one occurrence is allowed.</p> <p>ISO Name Cancellation Status Reason Information</p> <p>ISO Definition Provides detailed information on the cancellation status reason.</p> <p>XML Tag CxlStsRsnInf</p> <p>Type CancellationStatusReason4</p>



#	SEPA Mult	Message Element	Inter-PSP Negative Response to a Recall of a SCT Inst SEPA Core Requirements
4.17	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Cancellation Status Reason Information ++++Originator	<p>SEPA Rulebook AT-E001 The Name of the Beneficiary or AT-C002 The BIC code of the Beneficiary PSP.</p> <p>SEPA Usage Rule(s) Mandatory. Limited to 'AnyBIC' for an Agent or 'Name' for a non-financial institution. 'Name' is limited to 70 characters in length.</p> <p>ISO Name Originator ISO Definition Party that issues the cancellation status. XML Tag Orgtr Type PartyIdentification135</p>
4.18	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Cancellation Status Reason Information ++++Reason	<p>SEPA Rulebook AT-R057 The Reason Code for non-acceptance of the Recall.</p> <p>SEPA Usage Rule(s) Mandatory.</p> <p>ISO Name Reason ISO Definition Specifies the reason for the status report. XML Tag Rsn Type CancellationStatusReason3Choice</p>
	1..1		XML Tag xs:choice
4.19	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Cancellation Status Reason Information ++++Reason +++++Code	<p>SEPA Usage Rule(s) Only "AC04", "AM04", "ARDT", "CUST", "LEGL", "NOAS" and "NOOR" are allowed.</p> <p>ISO Name Code ISO Definition Reason for the cancellation status, in a coded form. XML Tag Cd Type ExternalPaymentCancellationRejection1Code ISO Length 1 .. 4 SEPA Length 1 .. 4</p> <p>SEPA Code Restrictions</p> <p>AC04 ClosedAccountNumber Account number specified has been closed on the receiver's books.</p> <p>AM04 InsufficientFunds Amount of funds available to cover specified message amount is insufficient.</p> <p>ARDT AlreadyReturned Cancellation not accepted as the transaction has already been returned.</p> <p>CUST CustomerDecision Reported when the cancellation cannot be accepted because of a customer decision (Creditor).</p> <p>LEGL LegalDecision Reported when the cancellation cannot be accepted because of regulatory rules.</p> <p>NOAS NoAnswerFromCustomer No response from beneficiary (to the cancellation request).</p> <p>NOOR NoOriginalTransactionReceived Original transaction (subject to cancellation) never received.</p>
4.20	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Cancellation Status Reason Information ++++Reason +++++Proprietary	<p>ISO Name Proprietary ISO Definition Reason for the status, in a proprietary form. XML Tag Prtry Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35</p>



#	SEPA Mult	Message Element	Inter-PSP Negative Response to a Recall of a SCT Inst SEPA Core Requirements	
4.21	1..13	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Cancellation Status Reason Information ++++Additional Information	<p>SEPA Rulebook AT-R053 The specific reference of the Originator PSP initiating the Recall. AT-R057 Reason code for non-acceptance of the Recall.</p> <p>SEPA Usage Rule(s) Mandatory. First occurrence is mandatory and must start with "ATR053/" followed by the information as per attribute description. When reason code is "LEGL" under 4.19, two further occurrences are allowed to precise the reason and must start with "ATR057/". When reason code was "FRAD" in the camt.056, then up to ten further optional occurrences are allowed, all starting with "FRAD/" followed by all information available to file a legal claim to recover the funds in case of reason code 'Fraudulent originated SCT Inst'</p> <p>ISO Name Additional Information ISO Definition Further details on the cancellation status reason. XML Tag AddtlInf Type Max105Text ISO Length 1 .. 105 SEPA Length 1 .. 105</p>	
4.22	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Resolution Related Information	<p>ISO Name Resolution Related Information ISO Definition Reference of a return or a reversal transaction that is initiated to fix the case under investigation as part of the resolution.</p> <p>XML Tag RsltnRltdInf Type ResolutionData1</p>	
4.23	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Interbank Settlement Amount	<p>ISO Name Original Interbank Settlement Amount ISO Definition Amount of money moved between the instructing agent and the instructed agent, as provided in the original instruction.</p> <p>XML Tag OrgnlIntrBkSttlmAmt Type ActiveOrHistoricCurrencyAndAmount SEPA FractDigits 5 TotalDigits 18 SEPA Inclusive 0 ..</p>	
4.24	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Interbank Settlement Date	<p>ISO Name Original Interbank Settlement Date ISO Definition Date, as provided in the original transaction, on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.</p> <p>XML Tag OrgnlIntrBkSttlmDt Type ISODate</p>	
4.25	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Assigner	<p>ISO Name Assigner ISO Definition Party who assigns the case. Usage: This is also the agent that instructs the next party in the chain to carry out the (set of) cancellation request(s).</p> <p>XML Tag Assgnr Type Party40Choice</p>	
4.26	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Assignee	<p>ISO Name Assignee ISO Definition Party to which the case is assigned. Usage: This is also the agent that is instructed by the previous party in the chain to carry out the (set of) cancellation request(s).</p> <p>XML Tag Assgne Type Party40Choice</p>	



#	SEPA Mult	Message Element	Inter-PSP Negative Response to a Recall of a SCT Inst SEPA Core Requirements
4.27	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference	<p>SEPA Rulebook An exact copy of all attributes of the initially sent DS-02 which is to be cancelled.</p> <p>SEPA Usage Rule(s) Mandatory. The yellow message elements under 'Original Transaction Reference' must be populated with the same value as the message elements of the original instruction.</p> <p>ISO Name Original Transaction Reference ISO Definition Key elements used to identify the original transaction that is being referred to.</p> <p>XML Tag OrgnlTxRef Type OriginalTransactionReference28</p>
4.28	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Interbank Settlement Amount	<p>SEPA Rulebook AT-T002 The amount of the SCT Inst in euro.</p> <p>ISO Name Interbank Settlement Amount ISO Definition Amount of money moved between the instructing agent and the instructed agent.</p> <p>XML Tag IntrBkSttlmAmt Type ActiveOrHistoricCurrencyAndAmount</p> <p>SEPA FractDigits 2 TotalDigits 18 SEPA Inclusive 0.01 .. 999999999.99</p>
4.29	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Amount	<p>ISO Name Amount ISO Definition Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.</p> <p>XML Tag Amt Type AmountType4Choice</p>
4.30	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Interbank Settlement Date	<p>SEPA Rulebook AT-T051 The Settlement Date of the SCT Inst Transaction.</p> <p>ISO Name Interbank Settlement Date ISO Definition Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.</p> <p>XML Tag IntrBkSttlmDt Type ISODate</p>
4.31	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Requested Collection Date	<p>ISO Name Requested Collection Date ISO Definition Date and time at which the creditor requests that the amount of money is to be collected from the debtor.</p> <p>XML Tag ReqdColltnDt Type ISODate</p>
4.32	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Requested Execution Date	<p>ISO Name Requested Execution Date ISO Definition Date at which the initiating party requests the clearing agent to process the payment. Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank.</p> <p>XML Tag ReqdExctnDt Type DateAndDateTime2Choice</p>
4.33	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Creditor Scheme Identification	<p>ISO Name Creditor Scheme Identification ISO Definition Credit party that signs the mandate.</p> <p>XML Tag CdrSchmeld Type PartyIdentification135</p>
4.34	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Settlement Information	<p>ISO Name Settlement Information ISO Definition Specifies the details on how the settlement of the original transaction(s) between the instructing agent and the instructed agent was completed.</p> <p>XML Tag SttlmInf Type SettlementInstruction7</p>



#	SEPA Mult	Message Element	Inter-PSP Negative Response to a Recall of a SCT Inst SEPA Core Requirements	
4.35	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Payment Type Information	<i>SEPA Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-T001 The identification code of the SCT Inst Scheme.</i> <i>AT-T008 The category purpose of the SCT Inst Instruction.</i> Payment Type Information Set of elements used to further specify the type of transaction. PmtTpInf PaymentTypeInformation27
4.36	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Payment Method	ISO Name ISO Definition XML Tag Type	Payment Method Specifies the means of payment that will be used to move the amount of money. PmtMtd PaymentMethod4Code
4.37	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Mandate Related Information	ISO Name ISO Definition XML Tag Type	Mandate Related Information Provides further details of the mandate signed between the creditor and the debtor. MndtRltdInf MandateRelatedInformation14
4.38	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Remittance Information	<i>SEPA Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-T009 The Remittance information.</i> Remittance Information Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system. RmtInf RemittanceInformation16
4.39	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Ultimate Debtor	<i>SEPA Rulebook</i> <i>SEPA Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>AT-P006 The name of the Originator Reference Party.</i> <i>AT-P007 The Identification Code of the Originator Reference Party.</i> <i>Only 'Party' is allowed.</i> Ultimate Debtor Ultimate party that owes an amount of money to the (ultimate) creditor. UltmtDbtr Party40Choice
4.40	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Debtor	<i>SEPA Rulebook</i> <i>SEPA Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>AT-P001 The name of the Originator.</i> <i>AT-P005 The address of the Originator.</i> <i>AT-P004 The Originator identification Code.</i> <i>Only 'Party' is allowed.</i> Debtor Party that owes an amount of money to the (ultimate) creditor. Dbtr Party40Choice
4.41	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Debtor Account	<i>SEPA Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-D001 The IBAN of the account of the Originator.</i> <i>AT-P003 The Proxy/Alias of the account of the Originator.</i> Debtor Account Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction. DbtrAcct CashAccount38
4.42	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Debtor Agent	<i>SEPA Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-D002 The BIC code of the Originator PSP.</i> Debtor Agent Financial institution servicing an account for the debtor. DbtrAgt BranchAndFinancialInstitutionIdentification6



#	SEPA Mult	Message Element	Inter-PSP Negative Response to a Recall of a SCT Inst SEPA Core Requirements	
4.43	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Debtor Agent Account	ISO Name ISO Definition XML Tag Type	Debtor Agent Account Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain. DbtrAgtAcct CashAccount38
4.44	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Creditor Agent	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-C002 The BIC code of the Beneficiary PSP.</i> Creditor Agent Financial institution servicing an account for the creditor. CdtrAgt BranchAndFinancialInstitutionIdentification6
4.45	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Creditor Agent Account	ISO Name ISO Definition XML Tag Type	Creditor Agent Account Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction. CdtrAgtAcct CashAccount38
4.46	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Creditor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-E001 The name of the Beneficiary.</i> <i>AT-E004 The address of the Beneficiary.</i> <i>AT-E005 The Beneficiary identification code.</i> Only 'Party' is allowed. Creditor Party to which an amount of money is due. Cdtr Party40Choice
4.47	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Creditor Account	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-C001 The IBAN of the account of the Beneficiary.</i> <i>AT-E003 The Proxy/Alias of the account of the Beneficiary.</i> Creditor Account Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction. CdtrAcct CashAccount38
4.48	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Ultimate Creditor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-E007 The name of the Beneficiary Reference Party.</i> <i>AT-E010 The identification code of the Beneficiary Reference Party.</i> Only 'Party' is allowed. Ultimate Creditor Ultimate party to which an amount of money is due. UltmtCdtr Party40Choice
4.49	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Purpose	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T007 The purpose of the SCT Inst Instruction.</i> Purpose Underlying reason for the payment transaction. Usage: Purpose is used by the end customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain. Purp Purpose2Choice



#	SEPA Mult	Message Element	Inter-PSP Negative Response to a Recall of a SCT Inst SEPA Core Requirements	
5.0	0..1	Resolution Of Investigation V09 +Modification Details	ISO Name ISO Definition XML Tag Type	Modification Details Specifies the details of the underlying transaction being modified. ModDtls PaymentTransaction107
6.0	0..1	Resolution Of Investigation V09 +Claim Non Receipt Details	ISO Name ISO Definition XML Tag Type	Claim Non Receipt Details Specifies the details of the underlying transaction for which a claim non receipt has been initiated. ClmNonRctDtls ClaimNonReceipt2Choice
7.0	0..1	Resolution Of Investigation V09 +Statement Details	ISO Name ISO Definition XML Tag Type	Statement Details Details on the underlying statement entry. StmntDtls StatementResolutionEntry4
8.0	0..1	Resolution Of Investigation V09 +Correction Transaction	ISO Name ISO Definition XML Tag Type	Correction Transaction References a transaction initiated to fix the case under investigation. CrrectnTx CorrectiveTransaction4Choice
9.0	0..1	Resolution Of Investigation V09 +Resolution Related Information	ISO Name ISO Definition XML Tag Type	Resolution Related Information Reference to fix the case under investigation as part of the resolution. RsltnRltdInf ResolutionData1
10.0	0..n	Resolution Of Investigation V09 +Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1



2.6 Inter-PSP Positive Response to a Recall of an SCT Inst Dataset (DS-06)

2.6.1 Use of the Payment Return (pacs.004.001.09)

The positive response to a:

- Recall of an SCT Inst message (camt.056.001.08);
- Request for Status Update on a Recall of an SCT Inst (pacs.028.001.03, refer to section 'Request for Status Update on a Recall of an SCT Inst below);

is to be made using an inter-PSP return credit transfer message (pacs.004.001.09), where the following apply:

- Index 1.9 'Interbank Settlement Date' to be populated with AT-R056 'The Settlement Date for the positive response to a Recall'.
- Index 3.13 'Returned Interbank Settlement Amount' to be populated with AT-R054 'The returned amount of the positive response to the Recall in euro'.
- Index 3.17 'Returned Instructed Amount' may be used.
- Index 3.22 'Amount' (under 'Charges Information') to be populated with AT-R055 'The fee for the positive response to the Recall in euro', if any.
- Index 3.24 'Financial Institution Identification' (under 'Agent' under 'Charges Information') to be populated with AT-C002 'The BIC code of the Beneficiary PSP'.
- Index 3.31 'Originator' to be populated with AT-R002 'The Identification of the type of party initiating the "R" message'.
- Index 3.33 'Reason/Code' (under 'Return Reason Information') to be populated only with "FOCR" (Following Cancellation Request).
- Index 3.35 'Additional Information' (under Return Reason Information) to be used with a mandatory occurrence starting with "ATR053/" followed by the information as per attribute description 'The specific reference of the Originator PSP initiating the Recall'.

The message caters for a single or group positive response.

Note: Attribute AT-R001 is implied by the 'Message Name', 'pacs.004.001.09', the 'Original Message Name Identification' must begin with 'pacs.008' (the addition of a variant number and version number is optional), 'Reason' under 'Return Reason Information' set to "FOCR" and 'Payment Type Information' mentioning "INST" (Transaction is related to an Instant Credit Transfer) under 'Local Instrument/Code'.

Note: Message elements under 'Original Transaction Reference' sequence are based on DS-02 attributes.



#	SEPA Mult	Message Element	Inter-PSP Positive Response to a Recall of a SCT Inst SEPA Core Requirements	
		Document	XML Tag Type	Document Document
	1..1	Payment Return V09	ISO Name ISO Definition XML Tag Type	Payment Return V09 Scope The PaymentReturn message is sent by an agent to the previous agent in the payment chain to undo a payment previously settled. PmtRtr PaymentReturnV09
1.0	1..1	Payment Return V09 +Group Header	ISO Name ISO Definition XML Tag Type	Group Header Set of characteristics shared by all individual transactions included in the message. GrpHdr GroupHeader90
1.1	1..1	Payment Return V09 +Group Header ++Message Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Message Identification Point to point reference, as assigned by the instructing party and sent to the next party in the chain, to unambiguously identify the message. Usage: The instructing party has to make sure that MessageIdentification is unique per instructed party for a pre-agreed period. MsgId Max35Text 1 .. 35 1 .. 35
1.2	1..1	Payment Return V09 +Group Header ++Creation Date Time	ISO Name ISO Definition XML Tag Type	Creation Date Time Date and time at which the message was created. CreDfTm ISODateTime
1.3	0..2	Payment Return V09 +Group Header ++Authorisation	ISO Name ISO Definition XML Tag Type	Authorisation User identification or any user key to be used to check whether the initiating party is allowed to initiate transactions from the account specified in the message. Usage: The content is not of a technical nature, but reflects the organisational structure at the initiating side. The authorisation element can typically be used in relay scenarios, payment initiations, payment returns or payment reversals that are initiated on behalf of a party different from the initiating party. Authstn Authorisation1Choice
1.4	0..1	Payment Return V09 +Group Header ++Batch Booking	ISO Name ISO Definition XML Tag Type	Batch Booking Identifies whether a single entry per individual transaction or a batch entry for the sum of the amounts of all transactions within the group of a message is requested. Usage: Batch booking is used to request and not order a possible batch booking. BtchBookg BatchBookingIndicator
1.5	1..1	Payment Return V09 +Group Header ++Number Of Transactions	ISO Name ISO Definition XML Tag Type Pattern	Number Of Transactions Number of individual transactions contained in the message. NbOfTxS Max15NumericText [0-9]{1,15}



#	SEPA Mult	Message Element	Inter-PSP Positive Response to a Recall of a SCT Inst SEPA Core Requirements
1.6	0..1	Payment Return V09 +Group Header ++Control Sum	<p>ISO Name Control Sum</p> <p>ISO Definition Total of all individual amounts included in the message, irrespective of currencies.</p> <p>XML Tag CtrlSum</p> <p>Type DecimalNumber</p> <p>SEPA FractDigits 17</p> <p>TotalDigits 18</p>
1.7	0..1	Payment Return V09 +Group Header ++Group Return	<p>ISO Name Group Return</p> <p>ISO Definition Indicates whether the return applies to the whole group of transactions or to individual transactions within the original group(s).</p> <p>XML Tag GrpRtr</p> <p>Type TrueFalseIndicator</p>
1.8	1..1	Payment Return V09 +Group Header ++Total Returned Interbank Settlement Amount	<p>SEPA Usage Rule(s) <i>Mandatory. Only 'EUR' is allowed. Amount must be 0.01 or more and 99999999999999.99 or less. The fractional part has a maximum of two digits.</i></p> <p>SEPA Format Rule(s)</p> <p>ISO Name Total Returned Interbank Settlement Amount</p> <p>ISO Definition Total amount of money moved between the instructing agent and the instructed agent in the return message.</p> <p>XML Tag TtlRtrdIntrBkSttlmAmt</p> <p>Type ActiveCurrencyAndAmount</p> <p>SEPA FractDigits 2</p> <p>TotalDigits 18</p> <p>SEPA Inclusive 0.01 .. 99999999999999.99</p>
1.9	1..1	Payment Return V09 +Group Header ++Interbank Settlement Date	<p>SEPA Rulebook <i>AT-R056 The Settlement Date for the positive response to a Recall.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Interbank Settlement Date</p> <p>ISO Definition Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.</p> <p>XML Tag IntrBkSttlmDt</p> <p>Type ISODate</p>
1.10	1..1	Payment Return V09 +Group Header ++Settlement Information	<p>ISO Name Settlement Information</p> <p>ISO Definition Specifies the details on how the settlement of the transaction(s) between the instructing agent and the instructed agent is completed.</p> <p>XML Tag SttlmInf</p> <p>Type SettlementInstruction7</p>
1.11	1..1	Payment Return V09 +Group Header ++Settlement Information +++Settlement Method	<p>SEPA Usage Rule(s) <i>Only "CLRG", "INGA" and "INDA" are allowed.</i></p> <p>ISO Name Settlement Method</p> <p>ISO Definition Method used to settle the (batch of) payment instructions.</p> <p>XML Tag SttlmMtd</p> <p>Type SettlementMethod1Code</p> <p>SEPA Code Restrictions</p> <p>CLRG <i>ClearingSystem Settlement is done through a payment clearing system.</i></p> <p>INDA <i>InstructedAgent Settlement is done by the agent instructed to execute a payment instruction.</i></p> <p>INGA <i>InstructingAgent Settlement is done by the agent instructing and forwarding the payment to the next party in the payment chain.</i></p>



#	SEPA Mult	Message Element	Inter-PSP Positive Response to a Recall of a SCT Inst SEPA Core Requirements
1.12	0..1	Payment Return V09 +Group Header ++Settlement Information +++Settlement Account	<i>SEPA Usage Rule(s)</i> Only 'Identification' is allowed. ISO Name Settlement Account ISO Definition A specific purpose account used to post debit and credit entries as a result of the transaction. XML Tag StlmAcct Type CashAccount38
1.13	0..1	Payment Return V09 +Group Header ++Settlement Information +++Clearing System	ISO Name Clearing System ISO Definition Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed. XML Tag ClrSys Type ClearingSystemIdentification3Choice
	1..1		XML Tag xs:choice
1.14	1..1	Payment Return V09 +Group Header ++Settlement Information +++Clearing System ++++Code	ISO Name Code ISO Definition Infrastructure through which the payment instruction is processed, as published in an external clearing system identification code list. XML Tag Cd Type ExternalCashClearingSystem1 Code ISO Length 1 .. 3 SEPA Length 1 .. 3
1.15	1..1	Payment Return V09 +Group Header ++Settlement Information +++Clearing System ++++Proprietary	ISO Name Proprietary ISO Definition Clearing system identification in a proprietary form. XML Tag Prtry Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35
1.16	0..1	Payment Return V09 +Group Header ++Settlement Information +++Instructing Reimbursement Agent	ISO Name Instructing Reimbursement Agent ISO Definition Agent through which the instructing agent will reimburse the instructed agent. Usage: If InstructingAgent and InstructedAgent have the same reimbursement agent, then only InstructingReimbursementAgent must be used. XML Tag InstgRmbrsmntAgt Type BranchAndFinancialInstitutionIdentification6
1.17	0..1	Payment Return V09 +Group Header ++Settlement Information +++Instructing Reimbursement Agent Account	ISO Name Instructing Reimbursement Agent Account ISO Definition Unambiguous identification of the account of the instructing reimbursement agent account at its servicing agent in the payment chain. XML Tag InstgRmbrsmntAgtAcct Type CashAccount38
1.18	0..1	Payment Return V09 +Group Header ++Settlement Information +++Instructed Reimbursement Agent	ISO Name Instructed Reimbursement Agent ISO Definition Agent at which the instructed agent will be reimbursed. Usage: If InstructedReimbursementAgent contains a branch of the InstructedAgent, then the party in InstructedAgent will claim reimbursement from that branch/will be paid by that branch. Usage: If InstructingAgent and InstructedAgent have the same reimbursement agent, then only InstructingReimbursementAgent must be used. XML Tag InstdRmbrsmntAgt Type BranchAndFinancialInstitutionIdentification6
1.19	0..1	Payment Return V09 +Group Header ++Settlement Information +++Instructed Reimbursement Agent Account	ISO Name Instructed Reimbursement Agent Account ISO Definition Unambiguous identification of the account of the instructed reimbursement agent account at its servicing agent in the payment chain. XML Tag InstdRmbrsmntAgtAcct Type CashAccount38



#	SEPA Mult	Message Element	Inter-PSP Positive Response to a Recall of a SCT Inst SEPA Core Requirements	
1.20	0..1	Payment Return V09 +Group Header ++Settlement Information +++Third Reimbursement Agent	ISO Name ISO Definition XML Tag Type	Third Reimbursement Agent Agent at which the instructed agent will be reimbursed. Usage: If ThirdReimbursementAgent contains a branch of the InstructedAgent, then the party in InstructedAgent will claim reimbursement from that branch/will be paid by that branch. ThrdRmbrsmntAgt BranchAndFinancialInstitutionIdentification6
1.21	0..1	Payment Return V09 +Group Header ++Settlement Information +++Third Reimbursement Agent Account	ISO Name ISO Definition XML Tag Type	Third Reimbursement Agent Account Unambiguous identification of the account of the third reimbursement agent account at its servicing agent in the payment chain. ThrdRmbrsmntAgtAcct CashAccount38
1.22	0..1	Payment Return V09 +Group Header ++Instructing Agent	<i>SEPA Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>Only 'BICFI' is allowed.</i> Instructing Agent Agent that instructs the next party in the chain to carry out the (set of) instruction(s). Usage: The instructing agent is the party sending the return message and not the party that sent the original instruction that is being returned. InstgAgt BranchAndFinancialInstitutionIdentification6
1.23	0..1	Payment Return V09 +Group Header ++Instructed Agent	<i>SEPA Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>Only 'BICFI' is allowed.</i> Instructed Agent Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s). Usage: The instructed agent is the party receiving the return message and not the party that received the original instruction that is being returned. InstdAgt BranchAndFinancialInstitutionIdentification6
2.0	0..1	Payment Return V09 +Original Group Information	<i>SEPA Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>Sub-elements of 'Original Group Information' must be present in either 'Original Group Information' or in 'Transaction Information'.</i> Original Group Information Information concerning the original group of transactions, to which the message refers. OrgnlGrpInf OriginalGroupHeader18
2.1	1..1	Payment Return V09 +Original Group Information ++Original Message Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Message Identification Point to point reference, as assigned by the original instructing party, to unambiguously identify the original message. OrgnlMsgId Max35Text 1 .. 35 1 .. 35
2.2	1..1	Payment Return V09 +Original Group Information ++Original Message Name Identification	<i>SEPA Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>Must begin with 'pacs.008'. The addition of a variant number and version number is optional.</i> Original Message Name Identification Specifies the original message name identifier to which the message refers. OrgnlMsgNmId Max35Text 1 .. 35 1 .. 35
2.3	0..1	Payment Return V09 +Original Group Information ++Original Creation Date Time	ISO Name ISO Definition XML Tag Type	Original Creation Date Time Date and time at which the original message was created. OrgnlCreDtTm ISODateTime



#	SEPA Mult	Message Element	Inter-PSP Positive Response to a Recall of a SCT Inst SEPA Core Requirements
2.4	0..n	Payment Return V09 +Original Group Information ++Return Reason Information	ISO Name Return Reason Information ISO Definition Provides detailed information on the return reason. XML Tag RtrRsnInf Type PaymentReturnReason6
3.0	1..n	Payment Return V09 +Transaction Information	SEPA Usage Rule(s) <i>Mandatory.</i> ISO Name Transaction Information ISO Definition Information concerning the original transactions, to which the return message refers. XML Tag TxInf Type PaymentTransaction112
3.1	1..1	Payment Return V09 +Transaction Information ++Return Identification	SEPA Usage Rule(s) <i>Mandatory.</i> <i>This ID must be forwarded to the Originator PSP and optionally to the Originator (and therefore it is not a point-to-point reference).</i> ISO Name Return Identification ISO Definition Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the returned transaction. Usage: The instructing party is the party sending the return message and not the party that sent the original instruction that is being returned. XML Tag RtrId Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35
3.2	0..1	Payment Return V09 +Transaction Information ++Original Group Information	SEPA Usage Rule(s) <i>Sub-elements of 'Original Group Information' must be present in either 'Original Group Information' or in 'Transaction Information'.</i> ISO Name Original Group Information ISO Definition Provides information on the original message. XML Tag OrgnlGrpInf Type OriginalGroupInformation29
3.3	1..1	Payment Return V09 +Transaction Information ++Original Group Information +++Original Message Identification	ISO Name Original Message Identification ISO Definition Point to point reference assigned by the original instructing party to unambiguously identify the original message. XML Tag OrgnlMsgId Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35
3.4	1..1	Payment Return V09 +Transaction Information ++Original Group Information +++Original Message Name Identification	SEPA Usage Rule(s) <i>Must begin with 'pacs.008'. The addition of a variant number and version number is optional.</i> ISO Name Original Message Name Identification ISO Definition Specifies the original message name identifier to which the message refers, for example, pacs.003.001.01 or MT103. XML Tag OrgnlMsgNmId Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35
3.5	0..1	Payment Return V09 +Transaction Information ++Original Group Information +++Original Creation Date Time	ISO Name Original Creation Date Time ISO Definition Original date and time at which the message was created. XML Tag OrgnlCreDtTm Type ISODateTime



#	SEPA Mult	Message Element	Inter-PSP Positive Response to a Recall of a SCT Inst SEPA Core Requirements
3.6	0..1	Payment Return V09 +Transaction Information ++Original Instruction Identification	<p>SEPA Usage Rule(s) <i>Mandatory if provided in the original instruction.</i></p> <p>ISO Name Original Instruction Identification</p> <p>ISO Definition Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction.</p> <p>XML Tag OrgnlInstrId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>
3.7	1..1	Payment Return V09 +Transaction Information ++Original End To End Identification	<p>SEPA Rulebook <i>AT-T014 The Originator's reference of the SCT Inst Instruction.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Original End To End Identification</p> <p>ISO Definition Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction.</p> <p>XML Tag OrgnlEndToEndId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>
3.8	1..1	Payment Return V09 +Transaction Information ++Original Transaction Identification	<p>SEPA Rulebook <i>AT-T054 The Originator PSP's reference of the SCT Inst Transaction message.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p><i>Must contain a reference that is meaningful to the Originator's PSP and is unique over time.</i></p> <p>ISO Name Original Transaction Identification</p> <p>ISO Definition Unique identification, as assigned by the original first instructing agent, to unambiguously identify the transaction.</p> <p>XML Tag OrgnlTxId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>
3.9	0..1	Payment Return V09 +Transaction Information ++Original UETR	<p>ISO Name Original UETR</p> <p>ISO Definition Universally unique identifier to provide the original end-to-end reference of a payment transaction.</p> <p>XML Tag OrgnlUETR</p> <p>Type UUIDv4Identifier</p> <p>Pattern [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}</p>
3.10	0..1	Payment Return V09 +Transaction Information ++Original Clearing System Reference	<p>ISO Name Original Clearing System Reference</p> <p>ISO Definition Unique reference, as assigned by the original clearing system, to unambiguously identify the original instruction.</p> <p>XML Tag OrgnlClrSysRef</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>



#	SEPA Mult	Message Element	Inter-PSP Positive Response to a Recall of a SCT Inst SEPA Core Requirements
3.11	1..1	Payment Return V09 +Transaction Information ++Original Interbank Settlement Amount	<p>SEPA Rulebook AT-T002 The amount of the SCT Inst in euro. SEPA Usage Rule(s) Mandatory. Only 'EUR' is allowed. Amount must be 0.01 or more and 999999999.99 or less.</p> <p>SEPA Format Rule(s) The fractional part has a maximum of two digits.</p> <p>ISO Name Original Interbank Settlement Amount ISO Definition Amount of money moved between the instructing agent and the instructed agent, as provided in the original instruction.</p> <p>XML Tag OrgnlIntrBkStlmAmt Type ActiveOrHistoricCurrencyAndAmount SEPA FractDigits 2 TotalDigits 18 SEPA Inclusive 0.01 .. 999999999.99</p>
3.12	0..1	Payment Return V09 +Transaction Information ++Original Interbank Settlement Date	<p>ISO Name Original Interbank Settlement Date ISO Definition Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.</p> <p>Usage: the OriginalInterbankSettlementDate is the interbank settlement date of the original instruction return message, and not of the return message.</p> <p>XML Tag OrgnlIntrBkStlmDt Type ISODate</p>
3.13	1..1	Payment Return V09 +Transaction Information ++Returned Interbank Settlement Amount	<p>SEPA Rulebook AT-R054 The returned amount of the positive response to the Recall in euro. SEPA Usage Rule(s) The amount must be equal to the 'Original Inter-PSP Settlement Amount' less - if present - the 'Amount' under 'Charges Information'. Only 'EUR' is allowed. Amount must be 0.01 or more and 999999999.99 or less.</p> <p>SEPA Format Rule(s) The fractional part has a maximum of two digits.</p> <p>ISO Name Returned Interbank Settlement Amount ISO Definition Amount of money to be moved between the instructing agent and the instructed agent in the returned instruction.</p> <p>XML Tag RtrdIntrBkStlmAmt Type ActiveCurrencyAndAmount SEPA FractDigits 2 TotalDigits 18 SEPA Inclusive 0.01 .. 999999999.99</p>
3.14	0..1	Payment Return V09 +Transaction Information ++Interbank Settlement Date	<p>ISO Name Interbank Settlement Date ISO Definition Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.</p> <p>Usage: the InterbankSettlementDate is the interbank settlement date of the return message, and not of the original instruction.</p> <p>XML Tag IntrBkStlmDt Type ISODate</p>



#	SEPA Mult	Message Element	Inter-PSP Positive Response to a Recall of a SCT Inst SEPA Core Requirements
3.15	0..1	Payment Return V09 +Transaction Information ++Settlement Priority	<p>ISO Name Settlement Priority</p> <p>ISO Definition Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the settlement instruction.</p> <p>Usage: the SettlementPriority is the settlement priority of the return message, and not of the original instruction.</p> <p>XML Tag Type SttlmPrty Priority3Code</p>
3.16	0..1	Payment Return V09 +Transaction Information ++Settlement Time Indication	<p>ISO Name Settlement Time Indication</p> <p>ISO Definition Provides information on the occurred settlement time(s) of the payment transaction.</p> <p>XML Tag Type SttlmTmIndctn SettlementDateTimeIndication1</p>
3.17	0..1	Payment Return V09 +Transaction Information ++Returned Instructed Amount	<p>SEPA Usage Rule(s) Only 'EUR' is allowed. Amount must be 0.01 or more and 999999999.99 or less. SEPA Format Rule(s) The fractional part has a maximum of two digits.</p> <p>ISO Name Returned Instructed Amount</p> <p>ISO Definition Amount of money to be moved between the debtor and the creditor, before deduction of charges, in the returned transaction. Usage: This amount has to be transported unchanged through the transaction chain.</p> <p>XML Tag Type RtrdInstdAmt ActiveOrHistoricCurrencyAndAmount</p> <p>SEPA FractDigits 2</p> <p>TotalDigits 18</p> <p>SEPA Inclusive 0.01 .. 999999999.99</p>
3.18	0..1	Payment Return V09 +Transaction Information ++Exchange Rate	<p>ISO Name Exchange Rate</p> <p>ISO Definition Factor used to convert an amount from one currency into another. This reflects the price at which one currency was bought with another currency.</p> <p>XML Tag Type XchgRate BaseOneRate</p> <p>SEPA FractDigits 10</p> <p>TotalDigits 11</p>
3.19	0..1	Payment Return V09 +Transaction Information ++Compensation Amount	<p>ISO Name Compensation Amount</p> <p>ISO Definition Amount of money asked or paid as compensation for the processing of the instruction.</p> <p>XML Tag Type CompstnAmt ActiveOrHistoricCurrencyAndAmount</p> <p>SEPA FractDigits 5</p> <p>TotalDigits 18</p> <p>SEPA Inclusive 0 ..</p>
3.20	0..1	Payment Return V09 +Transaction Information ++Charge Bearer	<p>SEPA Usage Rule(s) Only "SLEV" is allowed.</p> <p>ISO Name Charge Bearer</p> <p>ISO Definition Specifies which party/parties will bear the charges associated with the processing of the payment transaction.</p> <p>Usage: The ChargeBearer applies to the return message, not to the original instruction.</p> <p>XML Tag Type ChrgBr ChargeBearerType1Code</p> <p>SEPA Code Restrictions</p> <p>SLEV FollowingServiceLevel Charges are to be applied following the rules</p>



#	SEPA Mult	Message Element	Inter-PSP Positive Response to a Recall of a SCT Inst SEPA Core Requirements
			SEPA Code Restrictions
			<i>agreed in the service level and/or scheme.</i>
3.21	0..1	Payment Return V09 +Transaction Information ++Charges Information	SEPA Usage Rule(s) Only one occurrence is allowed. ISO Name Charges Information ISO Definition Provides information on the charges to be paid by the charge bearer(s) related to the processing of the return transaction. XML Tag ChrgsInf Type Charges7
3.22	1..1	Payment Return V09 +Transaction Information ++Charges Information +++Amount	SEPA Rulebook AT-R055 The fee for the positive response to the Recall in euro. SEPA Usage Rule(s) Only 'EUR' is allowed. Amount must be 0.01 or more and 99999999.99 or less. SEPA Format Rule(s) The fractional part has a maximum of two digits. ISO Name Amount ISO Definition Transaction charges to be paid by the charge bearer. XML Tag Amt Type ActiveOrHistoricCurrencyAndAmount SEPA FractDigits 2 TotalDigits 18 SEPA Inclusive 0.01 .. 99999999.99
3.23	1..1	Payment Return V09 +Transaction Information ++Charges Information +++Agent	ISO Name Agent ISO Definition Agent that takes the transaction charges or to which the transaction charges are due. XML Tag Agt Type BranchAndFinancialInstitutionIdentification6
3.24	1..1	Payment Return V09 +Transaction Information ++Charges Information +++Agent ++++Financial Institution Identification	SEPA Rulebook AT-C002 The BIC code of the Beneficiary PSP. SEPA Usage Rule(s) Only 'BICFI' is allowed. ISO Name Financial Institution Identification ISO Definition Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme. XML Tag FinInstnId Type FinancialInstitutionIdentification18
3.25	0..1	Payment Return V09 +Transaction Information ++Charges Information +++Agent ++++Branch Identification	ISO Name Branch Identification ISO Definition Identifies a specific branch of a financial institution. Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level. XML Tag BrnchId Type BranchData3
3.26	0..1	Payment Return V09 +Transaction Information ++Clearing System Reference	ISO Name Clearing System Reference ISO Definition Unique reference, as assigned by the clearing system, to unambiguously identify the return instruction. XML Tag ClrSysRef Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35



#	SEPA Mult	Message Element	Inter-PSP Positive Response to a Recall of a SCT Inst SEPA Core Requirements
3.27	0..1	Payment Return V09 +Transaction Information ++Instructing Agent	<p>SEPA Usage Rule(s) Only 'BICFI' is allowed.</p> <p>ISO Name Instructing Agent</p> <p>ISO Definition Agent that instructs the next party in the chain to carry out the (set of) instruction(s).</p> <p>Usage: The instructing agent is the party sending the return message and not the party that sent the original instruction that is being returned.</p> <p>XML Tag InstgAgt</p> <p>Type BranchAndFinancialInstitutionIdentification6</p>
3.28	0..1	Payment Return V09 +Transaction Information ++Instructed Agent	<p>SEPA Usage Rule(s) Only 'BICFI' is allowed.</p> <p>ISO Name Instructed Agent</p> <p>ISO Definition Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s).</p> <p>Usage: The instructed agent is the party receiving the return message and not the party that received the original instruction that is being returned.</p> <p>XML Tag InstdAgt</p> <p>Type BranchAndFinancialInstitutionIdentification6</p>
3.29	0..1	Payment Return V09 +Transaction Information ++Return Chain	<p>ISO Name Return Chain</p> <p>ISO Definition Provides all parties (agents and non-agents) involved in a return transaction.</p> <p>XML Tag RtrChain</p> <p>Type TransactionParties7</p>
3.30	1..1	Payment Return V09 +Transaction Information ++Return Reason Information	<p>SEPA Usage Rule(s) <i>Mandatory.</i> <i>Only one occurrence of 'Return Reason Information' is allowed.</i></p> <p>ISO Name Return Reason Information</p> <p>ISO Definition Provides detailed information on the return reason.</p> <p>XML Tag RtrRsnInf</p> <p>Type PaymentReturnReason6</p>
3.31	1..1	Payment Return V09 +Transaction Information ++Return Reason Information +++Originator	<p>SEPA Rulebook <i>AT-R002 Identification of the type of party initiating the "R"-message.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory</i> <i>Limited to 'AnyBIC' for an Agent or 'Name' for a non-financial institution.</i> <i>'Name' is limited to 70 characters in length.</i></p> <p>ISO Name Originator</p> <p>ISO Definition Party that issues the return.</p> <p>XML Tag Orgtr</p> <p>Type PartyIdentification135</p>
3.32	1..1	Payment Return V09 +Transaction Information ++Return Reason Information +++Reason	<p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Reason</p> <p>ISO Definition Specifies the reason for the return.</p> <p>XML Tag Rsn</p> <p>Type ReturnReason5Choice</p>
	1..1		XML Tag xs:choice
3.33	1..1	Payment Return V09 +Transaction Information ++Return Reason Information +++Reason ++++Code	<p>SEPA Usage Rule(s) Only "FOCR" is allowed.</p> <p>ISO Name Code</p> <p>ISO Definition Reason for the return, as published in an external reason code list.</p> <p>XML Tag Cd</p> <p>Type ExternalReturnReason1Code</p> <p>ISO Length 1 .. 4</p> <p>SEPA Length 1 .. 4</p>
			SEPA Code Restrictions
			FOCR <i>FollowingCancellationRequest</i> <i>Return following a cancellation request</i>



#	SEPA Mult	Message Element	Inter-PSP Positive Response to a Recall of a SCT Inst SEPA Core Requirements
3.34	1..1	Payment Return V09 +Transaction Information ++Return Reason Information +++Reason ++++Proprietary	ISO Name Proprietary ISO Definition Reason for the return, in a proprietary form. XML Tag Prtry Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35
3.35	1..1	Payment Return V09 +Transaction Information ++Return Reason Information +++Additional Information	SEPA Rulebook AT-R053 The specific reference of the Originator PSP initiating the Recall. SEPA Usage Rule(s) Mandatory. Only one occurrence starting with "ATR053/" followed by the information as per attribute description is allowed. ISO Name Additional Information ISO Definition Further details on the return reason. XML Tag AddtlInf Type Max105Text ISO Length 1 .. 105 SEPA Length 1 .. 105
3.36	1..1	Payment Return V09 +Transaction Information ++Original Transaction Reference	SEPA Rulebook An exact copy of all attributes of the received DS-02 which is being returned. SEPA Usage Rule(s) Mandatory. The message elements under 'Original Transaction Reference' must be populated with the same value as the message elements of the original instruction. ISO Name Original Transaction Reference ISO Definition Key elements used to identify the original transaction that is being referred to. XML Tag OrgnlTxRef Type OriginalTransactionReference28
3.37	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Interbank Settlement Amount	ISO Name Interbank Settlement Amount ISO Definition Amount of money moved between the instructing agent and the instructed agent. XML Tag IntrBkSttlmAmt Type ActiveOrHistoricCurrencyAndAmount SEPA FractDigits 5 TotalDigits 18 SEPA Inclusive 0 ..
3.38	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Amount	ISO Name Amount ISO Definition Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party. XML Tag Amt Type AmountType4Choice
3.39	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Interbank Settlement Date	SEPA Rulebook AT-T051 The Settlement Date of the SCT Inst Transaction. ISO Name Interbank Settlement Date ISO Definition Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. XML Tag IntrBkSttlmDt Type ISODate
3.40	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Requested Collection Date	ISO Name Requested Collection Date ISO Definition Date and time at which the creditor requests that the amount of money is to be collected from the debtor. XML Tag ReqdCollmDt Type ISODate



#	SEPA Mult	Message Element	Inter-PSP Positive Response to a Recall of a SCT Inst SEPA Core Requirements	
3.41	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Requested Execution Date	ISO Name ISO Definition XML Tag Type	Requested Execution Date Date at which the initiating party requests the clearing agent to process the payment. Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank. ReqdExctnDt DateAndDateTime2Choice
3.42	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Creditor Scheme Identification	ISO Name ISO Definition XML Tag Type	Creditor Scheme Identification Credit party that signs the mandate. CdrSchmeld PartyIdentification135
3.43	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Settlement Information	ISO Name ISO Definition XML Tag Type	Settlement Information Specifies the details on how the settlement of the original transaction(s) between the instructing agent and the instructed agent was completed. StlmInf SettlementInstruction7
3.44	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Payment Type Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	AT-T001 The identification code of the SCT Inst Scheme. AT-T008 The category purpose of the SCT Inst Instruction. Payment Type Information Set of elements used to further specify the type of transaction. PmtTpInf PaymentTypeInformation27
3.45	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Payment Method	ISO Name ISO Definition XML Tag Type	Payment Method Specifies the means of payment that will be used to move the amount of money. PmtMtd PaymentMethod4Code
3.46	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Mandate Related Information	ISO Name ISO Definition XML Tag Type	Mandate Related Information Provides further details of the mandate signed between the creditor and the debtor. MndtRltdInf MandateRelatedInformation14
3.47	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Remittance Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	AT-T009 The Remittance information. Remittance Information Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system. RmtInf RemittanceInformation16
3.48	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Ultimate Debtor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-P006 The name of the Originator Reference Party. AT-P007 The identification code of the Originator Reference Party. Only 'Party' is allowed. Ultimate Debtor Ultimate party that owes an amount of money to the (ultimate) creditor. UltmtDbtr Party40Choice



#	SEPA Mult	Message Element	Inter-PSP Positive Response to a Recall of a SCT Inst SEPA Core Requirements	
3.49	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Debtor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-P001 The name of the Originator.</i> <i>AT-P005 The address of the Originator.</i> <i>AT-P004 The Originator identification code.</i> Only 'Party' is allowed. Debtor Party that owes an amount of money to the (ultimate) creditor. Dbtr Party40Choice
3.50	1..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Debtor Account	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-D001 The IBAN of the account of the Originator.</i> <i>AT-P003 The Proxy/Alias of the account of the Originator.</i> Debtor Account Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction. DbtrAcct CashAccount38
3.51	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Debtor Agent	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-D002 The BIC code of the Originator PSP.</i> Debtor Agent Financial institution servicing an account for the debtor. DbtrAgt BranchAndFinancialInstitutionIdentification6
3.52	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Debtor Agent Account	ISO Name ISO Definition XML Tag Type	Debtor Agent Account Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain. DbtrAgtAcct CashAccount38
3.53	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Creditor Agent	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-C002 The BIC code of the Beneficiary PSP.</i> Creditor Agent Financial institution servicing an account for the creditor. CdtrAgt BranchAndFinancialInstitutionIdentification6
3.54	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Creditor Agent Account	ISO Name ISO Definition XML Tag Type	Creditor Agent Account Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction. CdtrAgtAcct CashAccount38
3.55	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Creditor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-E001 The name of the Beneficiary.</i> <i>AT-E004 The address of the Beneficiary.</i> <i>AT-E005 The Beneficiary identification code.</i> Only 'Party' is allowed. Creditor Party to which an amount of money is due. Cdtr Party40Choice
3.56	1..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Creditor Account	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-C001 The IBAN of the account of the Beneficiary.</i> <i>AT-E003 The Proxy/Alias of the account of the Beneficiary.</i> Creditor Account Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction. CdtrAcct CashAccount38



#	SEPA Mult	Message Element	Inter-PSP Positive Response to a Recall of a SCT Inst SEPA Core Requirements
3.57	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Ultimate Creditor	<p>SEPA Rulebook AT-E007 The name of the Beneficiary Reference Party. AT-E010 The identification code of the Beneficiary Reference Party.</p> <p>SEPA Usage Rule(s) Only 'Party' is allowed.</p> <p>ISO Name Ultimate Creditor</p> <p>ISO Definition Ultimate party to which an amount of money is due.</p> <p>XML Tag UltmtCdtr</p> <p>Type Party40Choice</p>
3.58	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Purpose	<p>SEPA Rulebook AT-T007 The purpose of the SCT Inst Instruction.</p> <p>ISO Name Purpose</p> <p>ISO Definition Underlying reason for the payment transaction.</p> <p>Usage: Purpose is used by the end customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.</p> <p>XML Tag Purp</p> <p>Type Purpose2Choice</p>
3.59	0..n	Payment Return V09 +Transaction Information ++Supplementary Data	<p>ISO Name Supplementary Data</p> <p>ISO Definition Additional information that cannot be captured in the structured elements and/or any other specific block.</p> <p>XML Tag SplmtryData</p> <p>Type SupplementaryData1</p>
4.0	0..n	Payment Return V09 +Supplementary Data	<p>ISO Name Supplementary Data</p> <p>ISO Definition Additional information that cannot be captured in the structured elements and/or any other specific block.</p> <p>XML Tag SplmtryData</p> <p>Type SupplementaryData1</p>



2.7 Request for Status Update on a Recall of an SCT Inst

2.7.1 Use of the FI to FI Payment Status Request (pacs.028.001.03)

This message is sent to the Beneficiary PSP in case the Originator PSP did not receive a response to a Recall of an SCT Inst, where the following applies:

- Index 3.3 'Original Instruction Identification' must be populated with the 'Cancellation Identification' (AT-R053) of the related camt.056 transaction information.

In an SCT Inst context, the message can be used for a single or group status request.

Note: The use case of the message is implied by the 'Message Name', 'pacs.028.001.03', the 'Original Message Name Identification' must begin with 'camt.056' (the addition of a variant number and version number is optional), the population of index 3.3 'Original Instruction Identification' and 'Payment Type Information' mentioning "INST" (Transaction is related to an Instant Credit Transfer) under 'Local Instrument/Code'.

Note: Message elements under 'Original Transaction Reference' are based on DS-02 attributes.



#	SEPA Mult	Message Element	Request for Status Update on a Recall SEPA Core Requirements	
		Document	XML Tag Type	Document Document
	1..1	FIto FIPayment Status Request V03	ISO Name ISO Definition XML Tag Type	FIto FIPayment Status Request V03 Scope The FinancialInstitutionToFinancialInstitutionPaymentStatusRequest message is sent by the debtor agent to the creditor agent, directly or through other agents and/or a payment clearing and settlement system. It is used to request a FItoFIPaymentStatusReport message containing information on the status of a previously sent instruction. FItoFIPmtStsReq FItoFIPaymentStatusRequestV03
1.0	1..1	FIto FIPayment Status Request V03 +Group Header	ISO Name ISO Definition XML Tag Type	Group Header Set of characteristics shared by all individual transactions included in the status request message. GrpHdr GroupHeader91
1.1	1..1	FIto FIPayment Status Request V03 +Group Header ++Message Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Message Identification Point to point reference, as assigned by the instructing party, and sent to the next party in the chain to unambiguously identify the message. Usage: The instructing party has to make sure that MessageIdentification is unique per instructed party for a pre-agreed period. MsgId Max35Text 1 .. 35 1 .. 35
1.2	1..1	FIto FIPayment Status Request V03 +Group Header ++Creation Date Time	ISO Name ISO Definition XML Tag Type	Creation Date Time Date and time at which the message was created. CreDtTm ISODateTime
1.3	0..1	FIto FIPayment Status Request V03 +Group Header ++Instructing Agent	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>Only 'BICFI' is allowed.</i> Instructing Agent Agent that instructs the next party in the chain to carry out the (set of) instruction(s). Usage: The instructing agent is the party sending the status message and not the party that sent the original instruction that is being reported on. InstgAgt BranchAndFinancialInstitutionIdentification6
1.4	0..1	FIto FIPayment Status Request V03 +Group Header ++Instructed Agent	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>Only 'BICFI' is allowed.</i> Instructed Agent Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s). Usage: The instructed agent is the party receiving the status message and not the party that received the original instruction that is being reported on. InstdAgt BranchAndFinancialInstitutionIdentification6



#	SEPA Mult	Message Element	Request for Status Update on a Recall SEPA Core Requirements
2.0	1..1	FITo FIPayment Status Request V03 +Original Group Information	SEPA Usage Rule(s) <i>Mandatory.</i> <i>Only one occurrence is allowed.</i> ISO Name Original Group Information ISO Definition Original group information concerning the group of transactions, to which the status request message refers to. XML Tag OrgnlGrpInf Type OriginalGroupInformation27
2.1	1..1	FITo FIPayment Status Request V03 +Original Group Information ++Original Message Identification	ISO Name Original Message Identification ISO Definition Point to point reference, as assigned by the original instructing party, to unambiguously identify the original message. XML Tag OrgnlMsgId Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35
2.2	1..1	FITo FIPayment Status Request V03 +Original Group Information ++Original Message Name Identification	SEPA Usage Rule(s) <i>Must begin with 'camt.056'. The addition of a variant number and version number is optional.</i> ISO Name Original Message Name Identification ISO Definition Specifies the original message name identifier to which the message refers. XML Tag OrgnlMsgNmId Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35
2.3	0..1	FITo FIPayment Status Request V03 +Original Group Information ++Original Creation Date Time	ISO Name Original Creation Date Time ISO Definition Date and time at which the original message was created. XML Tag OrgnlCreDtTm Type ISODateTime
2.4	0..1	FITo FIPayment Status Request V03 +Original Group Information ++Original Number Of Transactions	ISO Name Original Number Of Transactions ISO Definition Number of individual transactions contained in the original message. XML Tag OrgnlNbOfTxS Type Max15NumericText Pattern [0-9]{1,15}
2.5	0..1	FITo FIPayment Status Request V03 +Original Group Information ++Original Control Sum	ISO Name Original Control Sum ISO Definition Total of all individual amounts included in the original message, irrespective of currencies. XML Tag OrgnlCtrlSum Type DecimalNumber SEPA FractDigits 17 TotalDigits 18
3.0	1..n	FITo FIPayment Status Request V03 +Transaction Information	SEPA Usage Rule(s) <i>Mandatory.</i> ISO Name Transaction Information ISO Definition Information concerning the original transaction, to which the status request message refers. XML Tag TxInf Type PaymentTransaction113



#	SEPA Mult	Message Element	Request for Status Update on a Recall SEPA Core Requirements
3.1	1..1	FITo FIPayment Status Request V03 +Transaction Information ++Status Request Identification	<p>SEPA Usage Rule(s) <i>Mandatory.</i> <i>This ID must be forwarded to the Beneficiary PSP (and therefore it is not a point-to-point reference).</i></p> <p>ISO Name Status Request Identification ISO Definition Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the status request. Usage: The instructing party is the party sending the request message and not the party that sent the original instruction that is being reported on.</p> <p>XML Tag StsReqId Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35</p>
3.2	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Group Information	<p>ISO Name Original Group Information ISO Definition Point to point reference, as assigned by the original instructing party, to unambiguously identify the original message.</p> <p>XML Tag OrgnlGrpInf Type OriginalGroupInformation29</p>
3.3	1..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Instruction Identification	<p>SEPA Usage Rule(s) <i>Mandatory.</i> <i>Must be populated with a cancellation ID (AT-R053) of the relevant camt.056 Transaction Information.</i></p> <p>ISO Name Original Instruction Identification ISO Definition Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction.</p> <p>XML Tag OrgnlInstrId Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35</p>
3.4	1..1	FITo FIPayment Status Request V03 +Transaction Information ++Original End To End Identification	<p>SEPA Rulebook <i>AT-T014 Originator's reference of the SCT Inst Instruction.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Original End To End Identification ISO Definition Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction.</p> <p>XML Tag OrgnlEndToEndId Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35</p>
3.5	1..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Identification	<p>SEPA Rulebook <i>AT-T054 The Originator PSP's reference number of the SCT Inst Transaction message.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Original Transaction Identification ISO Definition Unique identification, as assigned by the original first instructing agent, to unambiguously identify the transaction.</p> <p>XML Tag OrgnlTxId Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35</p>



#	SEPA Mult	Message Element	Request for Status Update on a Recall SEPA Core Requirements	
3.6	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original UETR	ISO Name ISO Definition XML Tag Type Pattern	Original UETR Universally unique identifier to provide the original end-to-end reference of a payment transaction. OrgnUETR UUIDv4Identifier [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}
3.7	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Acceptance Date Time	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-T056 Timestamp of the SCT Inst Transaction. This information is to be retrieved from the original transaction. Acceptance Date Time Point in time when the payment order from the initiating party meets the processing conditions of the account servicing agent. This means that the account servicing agent has received the payment order and has applied checks such as authorisation, availability of funds. AcptncDtTm ISODateTime
3.8	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Clearing System Reference	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Clearing System Reference Unique reference, as assigned by a clearing system, to unambiguously identify the instruction. ClrSysRef Max35Text 1 .. 35 1 .. 35
3.9	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Instructing Agent	ISO Name ISO Definition XML Tag Type	Instructing Agent Agent that instructs the next party in the chain to carry out the (set of) instruction(s). InstgAgt BranchAndFinancialInstitutionIdentification6
3.10	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Instructed Agent	ISO Name ISO Definition XML Tag Type	Instructed Agent Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s). InstdAgt BranchAndFinancialInstitutionIdentification6
3.11	1..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Mandatory. The message elements under 'Original Transaction Reference' must be populated with the same value as the message elements of the original instruction. Original Transaction Reference Key elements used to identify the original transaction that is being referred to. OrgnTxRef OriginalTransactionReference28
3.12	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Interbank Settlement Amount	SEPA Rulebook ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits SEPA Inclusive	AT-T002 The amount of the SCT Inst in euro. Interbank Settlement Amount Amount of money moved between the instructing agent and the instructed agent. IntrBkSttlmAmt ActiveOrHistoricCurrencyAndAmount 2 18 0.01 .. 999999999.99



#	SEPA Mult	Message Element	Request for Status Update on a Recall SEPA Core Requirements
3.13	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Amount	<p>ISO Name Amount</p> <p>ISO Definition Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.</p> <p>XML Tag Amt</p> <p>Type AmountType4Choice</p>
3.14	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Interbank Settlement Date	<p>SEPA Rulebook AT-T051 The Settlement Date of the SCT Inst Transaction.</p> <p>ISO Name Interbank Settlement Date</p> <p>ISO Definition Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.</p> <p>XML Tag IntrBkSttlmDt</p> <p>Type ISODate</p>
3.15	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Requested Collection Date	<p>ISO Name Requested Collection Date</p> <p>ISO Definition Date and time at which the creditor requests that the amount of money is to be collected from the debtor.</p> <p>XML Tag ReqdColltnDt</p> <p>Type ISODate</p>
3.16	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Requested Execution Date	<p>ISO Name Requested Execution Date</p> <p>ISO Definition Date at which the initiating party requests the clearing agent to process the payment. Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank.</p> <p>XML Tag ReqdExctnDt</p> <p>Type DateAndDateTime2Choice</p>
3.17	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Creditor Scheme Identification	<p>ISO Name Creditor Scheme Identification</p> <p>ISO Definition Credit party that signs the mandate.</p> <p>XML Tag CdtrSchmeld</p> <p>Type PartyIdentification135</p>
3.18	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Settlement Information	<p>ISO Name Settlement Information</p> <p>ISO Definition Specifies the details on how the settlement of the original transaction(s) between the instructing agent and the instructed agent was completed.</p> <p>XML Tag SttlmInf</p> <p>Type SettlementInstruction7</p>
3.19	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Payment Type Information	<p>SEPA Rulebook AT-T008 The category purpose of the SCT Inst Instruction. AT-T001 The identification code of the SCT Inst Scheme.</p> <p>ISO Name Payment Type Information</p> <p>ISO Definition Set of elements used to further specify the type of transaction.</p> <p>XML Tag PmtTpInf</p> <p>Type PaymentTypeInformation27</p>
3.20	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Payment Method	<p>ISO Name Payment Method</p> <p>ISO Definition Specifies the means of payment that will be used to move the amount of money.</p> <p>XML Tag PmtMtd</p> <p>Type PaymentMethod4Code</p>
3.21	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Mandate Related Information	<p>ISO Name Mandate Related Information</p> <p>ISO Definition Provides further details of the mandate signed between the creditor and the debtor.</p> <p>XML Tag MndtRltdInf</p> <p>Type MandateRelatedInformation14</p>



#	SEPA Mult	Message Element	Request for Status Update on a Recall SEPA Core Requirements	
3.22	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Remittance Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T009 The Remittance Information sent by the Originator to the Beneficiary in the SCT Inst Instruction.</i> Remittance Information Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system. RmtInf RemittanceInformation16
3.23	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Ultimate Debtor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-P006 The name of the Originator Reference Party.</i> <i>AT-P007 The identification code of the Originator Reference Party.</i> Only 'Party' is allowed. Ultimate Debtor Ultimate party that owes an amount of money to the (ultimate) creditor. UltmtDbtr Party40Choice
3.24	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Debtor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-P001 The name of the Originator</i> <i>AT-P005 The address of the Originator</i> <i>AT-P004 The Originator identification code</i> Only 'Party' is allowed. Debtor Party that owes an amount of money to the (ultimate) creditor. Dbtr Party40Choice
3.25	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Debtor Account	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-D001 The IBAN of the account of the Originator.</i> <i>AT-P003 The Proxy/Alias of the account of the Originator</i> Debtor Account Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction. DbtrAcct CashAccount38
3.26	1..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Debtor Agent	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-D002 The BIC code of the Originator PSP.</i> Mandatory. Debtor Agent Financial institution servicing an account for the debtor. DbtrAgt BranchAndFinancialInstitutionIdentification6
3.27	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Debtor Agent Account	ISO Name ISO Definition XML Tag Type	Debtor Agent Account Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain. DbtrAgtAcct CashAccount38
3.28	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Creditor Agent	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-C002 The BIC code of the Beneficiary PSP.</i> Creditor Agent Financial institution servicing an account for the creditor. CdtrAgt BranchAndFinancialInstitutionIdentification6



#	SEPA Mult	Message Element	Request for Status Update on a Recall SEPA Core Requirements	
3.29	0..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Creditor Agent Account	ISO Name ISO Definition XML Tag Type	Creditor Agent Account Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction. CdtrAgtAcct CashAccount38
3.30	0..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Creditor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-E001 The name of the Beneficiary.</i> <i>AT-E004 The address of the Beneficiary.</i> <i>AT-E005 The Beneficiary identification code.</i> Only 'Party' is allowed. Creditor Party to which an amount of money is due. Cdtr Party40Choice
3.31	0..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Creditor Account	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-C001 The IBAN of the account of the Beneficiary.</i> <i>AT-E003 The Proxy/Alias of the account of the Beneficiary.</i> Creditor Account Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction. CdtrAcct CashAccount38
3.32	0..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Ultimate Creditor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-E007 The name of the Beneficiary Reference Party.</i> <i>AT-E010 The identification code of the Beneficiary Reference Party.</i> Only 'Party' is allowed. Ultimate Creditor Ultimate party to which an amount of money is due. UltmtCdtr Party40Choice
3.33	0..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Purpose	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T007 The purpose of the SCT Inst Instruction.</i> Purpose Underlying reason for the payment transaction. Usage: Purpose is used by the end customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain. Purp Purpose2Choice
3.34	0..n	FIto FIPayment Status Request V03 +Transaction Information ++Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1
4.0	0..n	FIto FIPayment Status Request V03 +Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1



2.8 Dataset for the SCT Inst Transaction Status Investigation Message Sent by the Originator PSP (DS-07)

2.8.1 Use of FI To FI Payment Status Request (pacs.028.001.03)

This message is sent to the Beneficiary PSP in case the Originator PSP has not received a confirmation (positive or negative) two seconds after the time-out deadline.

The message caters for a single status request only.

Note: The use case of the message is implied by the 'Message Name' set to 'pacs.028.001.03', the 'Original Message Name Identification' must begin with 'pacs.008' (the addition of a variant number and version number is optional) and 'Payment Type Information' mentioning "INST" (Transaction is related to an Instant Credit Transfer) under 'Local Instrument/Code'.

Note: Message elements under 'Original Transaction Reference' are based on DS-02 attributes.



#	SEPA Mult	Message Element	SCT Inst Transaction Status Investigation Message SEPA Core Requirements	
		Document	XML Tag Type	Document Document
	1..1	FITo FIPayment Status Request V03	ISO Name ISO Definition XML Tag Type	FITo FIPayment Status Request V03 Scope The FinancialInstitutionToFinancialInstitutionPaymentStatusRequest message is sent by the debtor agent to the creditor agent, directly or through other agents and/or a payment clearing and settlement system. It is used to request a FIToFIPaymentStatusReport message containing information on the status of a previously sent instruction. FIToFIPmtStsReq FIToFIPaymentStatusRequestV03
1.0	1..1	FITo FIPayment Status Request V03 +Group Header	ISO Name ISO Definition XML Tag Type	Group Header Set of characteristics shared by all individual transactions included in the status request message. GrpHdr GroupHeader91
1.1	1..1	FITo FIPayment Status Request V03 +Group Header ++Message Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Message Identification Point to point reference, as assigned by the instructing party, and sent to the next party in the chain to unambiguously identify the message. Usage: The instructing party has to make sure that MessageIdentification is unique per instructed party for a pre-agreed period. MsgId Max35Text 1 .. 35 1 .. 35
1.2	1..1	FITo FIPayment Status Request V03 +Group Header ++Creation Date Time	ISO Name ISO Definition XML Tag Type	Creation Date Time Date and time at which the message was created. CreDtTm ISODateTime
1.3	0..1	FITo FIPayment Status Request V03 +Group Header ++Instructing Agent	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>Only 'BICFI' is allowed.</i> Instructing Agent Agent that instructs the next party in the chain to carry out the (set of) instruction(s). Usage: The instructing agent is the party sending the status message and not the party that sent the original instruction that is being reported on. InstgAgt BranchAndFinancialInstitutionIdentification6
1.4	0..1	FITo FIPayment Status Request V03 +Group Header ++Instructed Agent	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>Only 'BICFI' is allowed.</i> Instructed Agent Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s). Usage: The instructed agent is the party receiving the status message and not the party that received the original instruction that is being reported on. InstdAgt BranchAndFinancialInstitutionIdentification6



#	SEPA Mult	Message Element	SCT Inst Transaction Status Investigation Message SEPA Core Requirements
2.0	1..1	FITo FIPayment Status Request V03 +Original Group Information	<p>SEPA Usage Rule(s) <i>Mandatory.</i> <i>Only one occurrence is allowed.</i></p> <p>ISO Name Original Group Information ISO Definition Original group information concerning the group of transactions, to which the status request message refers to.</p> <p>XML Tag OrgnlGrpInf Type OriginalGroupInformation27</p>
2.1	1..1	FITo FIPayment Status Request V03 +Original Group Information ++Original Message Identification	<p>ISO Name Original Message Identification ISO Definition Point to point reference, as assigned by the original instructing party, to unambiguously identify the original message.</p> <p>XML Tag OrgnlMsgId Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35</p>
2.2	1..1	FITo FIPayment Status Request V03 +Original Group Information ++Original Message Name Identification	<p>SEPA Usage Rule(s) <i>Must begin with 'pacs.008'. The addition of a variant number and version number is optional.</i></p> <p>ISO Name Original Message Name Identification ISO Definition Specifies the original message name identifier to which the message refers.</p> <p>XML Tag OrgnlMsgNmId Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35</p>
2.3	0..1	FITo FIPayment Status Request V03 +Original Group Information ++Original Creation Date Time	<p>ISO Name Original Creation Date Time ISO Definition Date and time at which the original message was created.</p> <p>XML Tag OrgnlCreDtTm Type ISODateTime</p>
2.4	0..1	FITo FIPayment Status Request V03 +Original Group Information ++Original Number Of Transactions	<p>ISO Name Original Number Of Transactions ISO Definition Number of individual transactions contained in the original message.</p> <p>XML Tag OrgnlNbOfTxS Type Max15NumericText Pattern [0-9]{1,15}</p>
2.5	0..1	FITo FIPayment Status Request V03 +Original Group Information ++Original Control Sum	<p>ISO Name Original Control Sum ISO Definition Total of all individual amounts included in the original message, irrespective of currencies.</p> <p>XML Tag OrgnlCtrlSum Type DecimalNumber SEPA FractDigits 17 TotalDigits 18</p>
3.0	1..1	FITo FIPayment Status Request V03 +Transaction Information	<p>SEPA Usage Rule(s) <i>Mandatory.</i> <i>Only one occurrence is allowed.</i></p> <p>ISO Name Transaction Information ISO Definition Information concerning the original transaction, to which the status request message refers.</p> <p>XML Tag TxInf Type PaymentTransaction113</p>



#	SEPA Mult	Message Element	SCT Inst Transaction Status Investigation Message SEPA Core Requirements
3.1	1..1	FIto FIPayment Status Request V03 +Transaction Information ++Status Request Identification	<p>SEPA Usage Rule(s) <i>Mandatory.</i> <i>This ID must be forwarded to the Beneficiary PSP (and therefore it is not a point-to-point reference).</i></p> <p>ISO Name Status Request Identification ISO Definition Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the status request. Usage: The instructing party is the party sending the request message and not the party that sent the original instruction that is being reported on.</p> <p>XML Tag StsReqId Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35</p>
3.2	0..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Group Information	<p>ISO Name Original Group Information ISO Definition Point to point reference, as assigned by the original instructing party, to unambiguously identify the original message.</p> <p>XML Tag OrgnlGrpInf Type OriginalGroupInformation29</p>
3.3	0..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Instruction Identification	<p>SEPA Usage Rule(s) <i>Mandatory if provided in the original instruction.</i></p> <p>ISO Name Original Instruction Identification ISO Definition Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction.</p> <p>XML Tag OrgnlInstrId Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35</p>
3.4	1..1	FIto FIPayment Status Request V03 +Transaction Information ++Original End To End Identification	<p>SEPA Rulebook <i>AT-T014 Originator's reference of the SCT Inst Instruction.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Original End To End Identification ISO Definition Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction.</p> <p>XML Tag OrgnlEndToEndId Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35</p>
3.5	1..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Transaction Identification	<p>SEPA Rulebook <i>AT-T054 The Originator PSP's reference number of the SCT Inst Transaction message.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Original Transaction Identification ISO Definition Unique identification, as assigned by the original first instructing agent, to unambiguously identify the transaction.</p> <p>XML Tag OrgnlTxId Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35</p>
3.6	0..1	FIto FIPayment Status Request V03 +Transaction Information ++Original UETR	<p>ISO Name Original UETR ISO Definition Universally unique identifier to provide the original end-to-end reference of a payment transaction.</p> <p>XML Tag OrgnlUETR Type UUIDv4Identifier Pattern [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}</p>



#	SEPA Mult	Message Element	SCT Inst Transaction Status Investigation Message SEPA Core Requirements	
3.7	1..1	FITo FIPayment Status Request V03 +Transaction Information ++Acceptance Date Time	SEPA Rulebook AT-T056 SEPA Usage Rule(s) Mandatory. ISO Name Acceptance Date Time ISO Definition Point in time when the payment order from the initiating party meets the processing conditions of the account servicing agent. This means that the account servicing agent has received the payment order and has applied checks such as authorisation, availability of funds. XML Tag AcptncDtTm Type ISODateTime	SEPA Usage Rule(s) Mandatory. <i>The message elements under 'Original Transaction Reference' must be populated with the same value as the message elements of the original instruction.</i> ISO Name Original Transaction Reference ISO Definition Key elements used to identify the original transaction that is being referred to. XML Tag OrgnlTxRef Type OriginalTransactionReference28
3.8	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Clearing System Reference	ISO Name Clearing System Reference ISO Definition Unique reference, as assigned by a clearing system, to unambiguously identify the instruction. XML Tag ClrSysRef Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35	ISO Name Instructing Agent ISO Definition Agent that instructs the next party in the chain to carry out the (set of) instruction(s). XML Tag InstgAgt Type BranchAndFinancialInstitutionIdentification6
3.9	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Instructing Agent	ISO Name Instructed Agent ISO Definition Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s). XML Tag InstdAgt Type BranchAndFinancialInstitutionIdentification6	ISO Name Interbank Settlement Amount ISO Definition Amount of money moved between the instructing agent and the instructed agent. XML Tag IntrBkSttlmAmt Type ActiveOrHistoricCurrencyAndAmount SEPA FractDigits 5 TotalDigits 18 SEPA Inclusive 0 ..
3.10	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Instructed Agent	ISO Name Amount ISO Definition Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party. XML Tag Amt Type AmountType4Choice	ISO Name Interbank Settlement Date ISO Definition Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. XML Tag IntrBkSttlmDt Type ISODate
3.11	1..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference	ISO Name Interbank Settlement Amount ISO Definition Amount of money moved between the instructing agent and the instructed agent. XML Tag IntrBkSttlmAmt Type ActiveOrHistoricCurrencyAndAmount SEPA FractDigits 5 TotalDigits 18 SEPA Inclusive 0 ..	ISO Name Amount ISO Definition Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party. XML Tag Amt Type AmountType4Choice
3.12	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Interbank Settlement Amount	ISO Name Amount ISO Definition Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party. XML Tag Amt Type AmountType4Choice	ISO Name Interbank Settlement Date ISO Definition Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. XML Tag IntrBkSttlmDt Type ISODate
3.13	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Amount	ISO Name Amount ISO Definition Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party. XML Tag Amt Type AmountType4Choice	ISO Name Interbank Settlement Date ISO Definition Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. XML Tag IntrBkSttlmDt Type ISODate
3.14	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Interbank Settlement Date	ISO Name Amount ISO Definition Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party. XML Tag Amt Type AmountType4Choice	ISO Name Interbank Settlement Date ISO Definition Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. XML Tag IntrBkSttlmDt Type ISODate



#	SEPA Mult	Message Element	SCT Inst Transaction Status Investigation Message SEPA Core Requirements	
3.15	0..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Requested Collection Date	ISO Name ISO Definition XML Tag Type	Requested Collection Date Date and time at which the creditor requests that the amount of money is to be collected from the debtor. ReqdColltnDt ISODate
3.16	0..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Requested Execution Date	ISO Name ISO Definition XML Tag Type	Requested Execution Date Date at which the initiating party requests the clearing agent to process the payment. Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank. ReqdExctnDt DateAndDateTime2Choice
3.17	0..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Creditor Scheme Identification	ISO Name ISO Definition XML Tag Type	Creditor Scheme Identification Credit party that signs the mandate. CdtrSchmeld PartyIdentification135
3.18	0..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Settlement Information	ISO Name ISO Definition XML Tag Type	Settlement Information Specifies the details on how the settlement of the original transaction(s) between the instructing agent and the instructed agent was completed. SttlmInf SettlementInstruction7
3.19	1..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Payment Type Information	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-T008 The category purpose of the SCT Inst Instruction.</i> <i>AT-T001 The identification code of the SCT Inst Scheme.</i> <i>Mandatory.</i> Payment Type Information Set of elements used to further specify the type of transaction. PmtTpInf PaymentTypeInformation27
3.20	0..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Payment Method	ISO Name ISO Definition XML Tag Type	Payment Method Specifies the means of payment that will be used to move the amount of money. PmtMtd PaymentMethod4Code
3.21	0..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Mandate Related Information	ISO Name ISO Definition XML Tag Type	Mandate Related Information Provides further details of the mandate signed between the creditor and the debtor. MndtRltdInf MandateRelatedInformation14
3.22	0..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Remittance Information	ISO Name ISO Definition XML Tag Type	Remittance Information Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system. RmtInf RemittanceInformation16
3.23	0..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Ultimate Debtor	ISO Name ISO Definition XML Tag Type	Ultimate Debtor Ultimate party that owes an amount of money to the (ultimate) creditor. UltmtDbtr Party40Choice
3.24	0..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Debtor	ISO Name ISO Definition XML Tag Type	Debtor Party that owes an amount of money to the (ultimate) creditor. Dbtr Party40Choice



#	SEPA Mult	Message Element	SCT Inst Transaction Status Investigation Message SEPA Core Requirements	
3.25	0..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Debtor Account	ISO Name ISO Definition XML Tag Type	Debtor Account Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction. DbtrAcct CashAccount38
3.26	1..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Debtor Agent	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-D002 The BIC code of the Originator Bank. Mandatory. Debtor Agent Financial institution servicing an account for the debtor. DbtrAgt BranchAndFinancialInstitutionIdentification6
3.27	0..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Debtor Agent Account	ISO Name ISO Definition XML Tag Type	Debtor Agent Account Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain. DbtrAgtAcct CashAccount38
3.28	0..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Creditor Agent	ISO Name ISO Definition XML Tag Type	Creditor Agent Financial institution servicing an account for the creditor. CdtrAgt BranchAndFinancialInstitutionIdentification6
3.29	0..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Creditor Agent Account	ISO Name ISO Definition XML Tag Type	Creditor Agent Account Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction. CdtrAgtAcct CashAccount38
3.30	0..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Creditor	ISO Name ISO Definition XML Tag Type	Creditor Party to which an amount of money is due. Cdtr Party40Choice
3.31	0..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Creditor Account	ISO Name ISO Definition XML Tag Type	Creditor Account Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction. CdtrAcct CashAccount38
3.32	0..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Ultimate Creditor	ISO Name ISO Definition XML Tag Type	Ultimate Creditor Ultimate party to which an amount of money is due. UltmtCdtr Party40Choice
3.33	0..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Purpose	ISO Name ISO Definition XML Tag Type	Purpose Underlying reason for the payment transaction. Usage: Purpose is used by the end customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain. Purp Purpose2Choice



#	SEPA Mult	Message Element	SCT Inst Transaction Status Investigation Message SEPA Core Requirements	
3.34	0..n	FIto FIPayment Status Request V03 +Transaction Information ++Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1
4.0	0..n	FIto FIPayment Status Request V03 +Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1



2.9 Request for Recall by the Originator Dataset (DS-08)

2.9.1 Use of FI To FI Payment Cancellation Request (camt.056.001.08)

The message is used to submit the request made by the Originator to cancel a pacs.008.001.08 for other reasons than those allowed in a Recall of an SCT Inst (refer to section 'Recall of an SCT Inst Dataset' above). As a consequence, the following apply:

- Index 4.3 'Cancellation Identification' can only be populated with AT-R072 'The specific reference of the Originator PSP for the Request for Recall by the Originator'.
- Index 4.19 'Originator' can only be populated with AT-P001 'The name of the Originator'.
- Index 4.20 'Reason' is to be populated with AT-R071 'Reason code for the Request for Recall by the Originator', where:
 - Index 4.21 'Code' can only be populated with ISO codes "AC03" (Wrong IBAN), "AM09" (Wrong Amount), and "CUST" (Requested By Customer).
- Index 4.23 'Additional Information' is to be populated with AT-R073 'Additional Information to AT-R071 Reason code for the Request for Recall by the Originator' which can be used in accordance with above reason codes.

The message caters for single or group cancellation requests.

Note: The use case of the message is implied by the 'Message Name', 'camt.056.001.08', the 'Original Message Name Identification' must begin with 'pacs.008' (the addition of a variant number and version number is optional), 'Originator' set to AT-P001 'The name of the Originator', 'Reason' set to "AC03", "AM09" or "CUST" (under 'Code'), and 'Payment Type Information' mentioning "INST" (Transaction is related to an Instant Credit Transfer) under 'Local Instrument/Code'

Note: Message elements under 'Original Transaction Reference' sequence are based on DS-02 attributes.

Note: Only one Request for Recall by the Originator can be sent for a given SCT Inst Transaction. The Originator PSP is not allowed to send another Request for Recall by the Originator for the same initial SCT Inst Transaction



#	SEPA Mult	Message Element	Request for Recall by the Originator (RFRO) SEPA Core Requirements	
		Document	XML Tag Type	Document Document
	1..1	FITo FIPayment Cancellation Request V08	ISO Name ISO Definition	FITo FIPayment Cancellation Request V08 Scope The FIToFIPaymentCancellationRequest message is sent by a case creator/case assigner to a case assignee. This message is used to request the cancellation of an original payment instruction. The FIToFIPaymentCancellationRequest message is exchanged between the instructing agent and the instructed agent to request the cancellation of a interbank payment message previously sent (such as FIToFICustomerCreditTransfer, FIToFICustomerDirectDebit or FinancialInstitutionCreditTransfer). The FIToFIPaymentCancellationRequest message supports both the request for cancellation (the instructed agent - or assignee - has not yet processed and forwarded the payment instruction) as well as the request for refund (payment has been fully processed already by the instructed agent - or assignee). XML Tag Type FIToFIPmtCxlReq FIToFIPaymentCancellationRequestV08
1.0	1..1	FITo FIPayment Cancellation Request V08 +Assignment	ISO Name ISO Definition	Assignment Identifies the assignment of an investigation case from an assigner to an assignee. Usage: The assigner must be the sender of this confirmation and the assignee must be the receiver. XML Tag Type Assgnmt CaseAssignment5
1.1	1..1	FITo FIPayment Cancellation Request V08 +Assignment ++Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Identification Uniquely identifies the case assignment. Id Max35Text 1 .. 35 1 .. 35
1.2	1..1	FITo FIPayment Cancellation Request V08 +Assignment ++Assigner	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>Instructing Party.</i> <i>Limited to 'BICFI' to identify a PSP, 'AnyBIC' to identify a CSM or 'LEI' or 'Name' to indicate a CSM when it has no BIC.</i> <i>'Name' is limited to 70 characters in length.</i> Assigner Party who assigns the case. Usage: This is also the sender of the message. Assgnr Party40Choice
1.3	1..1	FITo FIPayment Cancellation Request V08 +Assignment ++Assignee	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>Instructed Party.</i> <i>Limited to 'BICFI' to identify a PSP, 'AnyBIC' to identify a CSM or 'LEI' or 'Name' to indicate a CSM when it has no BIC.</i> <i>'Name' is limited to 70 characters in length.</i> Assignee Party to which the case is assigned. Usage: This is also the receiver of the message. Assgne Party40Choice



#	SEPA Mult	Message Element	Request for Recall by the Originator (RFRO) SEPA Core Requirements
1.4	1..1	FITo FIPayment Cancellation Request V08 +Assignment ++Creation Date Time	ISO Name Creation Date Time ISO Definition Date and time at which the assignment was created. XML Tag CreDtTm Type ISODateTime
2.0	0..1	FITo FIPayment Cancellation Request V08 +Case	ISO Name Case ISO Definition Identifies the investigation case. XML Tag Case Type Case5
3.0	0..1	FITo FIPayment Cancellation Request V08 +Control Data	ISO Name Control Data ISO Definition Provides details on the number of transactions and the control sum of the message. XML Tag CtrlData Type ControlData1
3.1	1..1	FITo FIPayment Cancellation Request V08 +Control Data ++Number Of Transactions	ISO Name Number Of Transactions ISO Definition Number of individual transactions contained in the message. XML Tag NbOfTxS Type Max15NumericText Pattern [0-9]{1,15}
3.2	0..1	FITo FIPayment Cancellation Request V08 +Control Data ++Control Sum	ISO Name Control Sum ISO Definition Total of all individual amounts included in the message, irrespective of currencies. XML Tag CtrlSum Type DecimalNumber SEPA FractDigits 17 TotalDigits 18
4.0	1..n	FITo FIPayment Cancellation Request V08 +Underlying	ISO Name Underlying ISO Definition Identifies the payment instruction to be cancelled. XML Tag Undrlyg Type UnderlyingTransaction23
4.1	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Original Group Information And Cancellation	ISO Name Original Group Information And Cancellation ISO Definition Provides information on the original message, to which the cancellation refers. XML Tag OrgnlGrpInfAndCxl Type OriginalGroupHeader15
4.2	1..n	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information	SEPA Usage Rule(s) <i>Mandatory.</i> ISO Name Transaction Information ISO Definition Provides information on the original transactions to which the cancellation request message refers. XML Tag TxInf Type PaymentTransaction106
4.3	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Cancellation Identification	SEPA Rulebook <i>AT-R072 The specific reference of the Originator PSP for the Request for Recall by the Originator.</i> SEPA Usage Rule(s) <i>Mandatory.</i> <i>This ID must be forwarded in the handling of the Recall message to the Beneficiary PSP and optionally to the Beneficiary (and therefore it is not a point-to-point reference).</i> ISO Name Cancellation Identification ISO Definition Unique and unambiguous identifier of a cancellation request, as assigned by the assigner. Usage: The cancellation request identification can be used for reconciliation or to link tasks relating to the cancellation request. XML Tag CxIID Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35



#	SEPA Mult	Message Element	Request for Recall by the Originator (RFRO) SEPA Core Requirements	
4.4	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Case	ISO Name ISO Definition XML Tag Type	Case Set of elements to uniquely and unambiguously identify an exception or an investigation workflow. Case Case5
4.5	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Group Information	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>Mandatory.</i> Original Group Information Provides information on the original message. OrgnlGrpInf OriginalGroupInformation29
4.6	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Group Information ++++Original Message Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Message Identification Point to point reference assigned by the original instructing party to unambiguously identify the original message. OrgnlMsgId Max35Text 1 .. 35 1 .. 35
4.7	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Group Information ++++Original Message Name Identification	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>Must begin with 'pacs.008'. The addition of a variant number and version number is optional.</i> Original Message Name Identification Specifies the original message name identifier to which the message refers, for example, pacs.003.001.01 or MT103. OrgnlMsgNmId Max35Text 1 .. 35 1 .. 35
4.8	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Group Information ++++Original Creation Date Time	ISO Name ISO Definition XML Tag Type	Original Creation Date Time Original date and time at which the message was created. OrgnlCreDtTm ISODateTime
4.9	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Instruction Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Instruction Identification Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction. OrgnlInstrId Max35Text 1 .. 35 1 .. 35
4.10	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original End To End Identification	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>AT-T014 The Originator's reference of the SCT Inst Transaction.</i> <i>Mandatory.</i> Original End To End Identification Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction. OrgnlEndToEndId Max35Text 1 .. 35 1 .. 35



#	SEPA Mult	Message Element	Request for Recall by the Originator (RFRO) SEPA Core Requirements	
4.11	1..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Identification	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>AT-T054 The Originator PSP's reference of the SCT Inst Transaction message.</i> Mandatory. Original Transaction Identification Unique identification, as assigned by the original first instructing agent, to unambiguously identify the transaction. OrgnlTxId Max35Text 1 .. 35 1 .. 35
4.12	0..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original UETR	ISO Name ISO Definition XML Tag Type Pattern	Original UETR Universally unique identifier to provide the original end-to-end reference of a payment transaction. OrgnlUETR UUIDv4Identifier [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}
4.13	0..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Clearing System Reference	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Clearing System Reference Unique reference, as assigned by the original clearing system, to unambiguously identify the original instruction. OrgnlClrSysRef Max35Text 1 .. 35 1 .. 35
4.14	1..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Interbank Settlement Amount	SEPA Rulebook SEPA Usage Rule(s) SEPA Format Rule(s) ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits SEPA Inclusive	<i>AT-T002 The amount of the SCT Inst in euro.</i> Mandatory. <i>The fractional part has a maximum of two digits.</i> Original Interbank Settlement Amount Amount of money moved between the instructing agent and the instructed agent, as provided in the original instruction. OrgnlIntrBkStlmAmt ActiveOrHistoricCurrencyAndAmount 2 18 0.01 .. 999999999.99
4.15	1..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Interbank Settlement Date	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-T051 The Settlement Date of the SCT Inst Transaction.</i> Mandatory. Original Interbank Settlement Date Date, as provided in the original transaction, on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. OrgnlIntrBkStlmDt ISODate
4.16	0..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Assigner	ISO Name ISO Definition XML Tag Type	Assigner Party who assigns the case. Usage: This is also the agent that instructs the next party in the chain to carry out the (set of) cancellation request(s). Assgnr BranchAndFinancialInstitutionIdentification6



#	SEPA Mult	Message Element	Request for Recall by the Originator (RFRO) SEPA Core Requirements
4.17	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Assignee	ISO Name Assignee ISO Definition Party to which the case is assigned. Usage: This is also the agent that is instructed by the previous party in the chain to carry out the (set of) cancellation request(s). XML Tag Assgne Type BranchAndFinancialInstitutionIdentification6
4.18	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Cancellation Reason Information	SEPA Usage Rule(s) <i>Mandatory.</i> <i>Only one occurrence is allowed.</i> ISO Name Cancellation Reason Information ISO Definition Provides detailed information on the cancellation reason. XML Tag CxIRsnInf Type PaymentCancellationReason5
4.19	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Cancellation Reason Information ++++Originator	SEPA Rulebook <i>AT-P001 The name of the Originator.</i> SEPA Usage Rule(s) <i>Mandatory.</i> <i>Only 'Name' is allowed.</i> <i>'Name' is limited to 70 characters in length.</i> ISO Name Originator ISO Definition Party that issues the cancellation request. XML Tag Orgtr Type PartyIdentification135
4.20	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Cancellation Reason Information ++++Reason	SEPA Rulebook <i>AT-R071 Reason code for the Request for Recall by the Originator.</i> SEPA Usage Rule(s) <i>Mandatory.</i> ISO Name Reason ISO Definition Specifies the reason for the cancellation. XML Tag Rsn Type CancellationReason33Choice
	1..1		XML Tag xs:choice
4.21	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Cancellation Reason Information ++++Reason +++++Code	SEPA Usage Rule(s) <i>Only codes "AC03", "AM09" and "CUST" are allowed.</i> ISO Name Code ISO Definition Reason for the cancellation request, in a coded form. XML Tag Cd Type ExternalCancellationReason1Code ISO Length 1 .. 4 SEPA Length 1 .. 4 SEPA Code Restrictions AC03 <i>InvalidCreditorAccountNumber</i> <i>Wrong account number in Credit Transfer.</i> AM09 <i>WrongAmount</i> <i>Amount is not the amount agreed or expected.</i> CUST <i>RequestedByCustomer</i> <i>Cancellation requested by the Debtor.</i>
4.22	1..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Cancellation Reason Information ++++Reason +++++Proprietary	ISO Name Proprietary ISO Definition Reason for the cancellation request, in a proprietary form. XML Tag Prtry Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35



#	SEPA Mult	Message Element	Request for Recall by the Originator (RFRO) SEPA Core Requirements
4.23	0..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Cancellation Reason Information ++++Additional Information	<p>SEPA Rulebook AT-R073 Additional information to AT-R071 Reason code for the Request for Recall by the Originator</p> <p>SEPA Usage Rule(s) Only one occurrence is allowed.</p> <p>ISO Name Additional Information</p> <p>ISO Definition Further details on the cancellation request reason.</p> <p>XML Tag AddtlInf</p> <p>Type Max105Text</p> <p>ISO Length 1 .. 105</p> <p>SEPA Length 1 .. 105</p>
4.24	1..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference	<p>SEPA Rulebook An exact copy of the original Inter-PSP Payment dataset (DS-02) which the Request for Recall by the Originator relates to.</p> <p>SEPA Usage Rule(s) Mandatory. The message elements under 'Original Transaction Reference' must be populated with the same value as the message elements of the original instruction.</p> <p>ISO Name Original Transaction Reference</p> <p>ISO Definition Key elements used to identify the original transaction that is being referred to.</p> <p>XML Tag OrgnlTxRef</p> <p>Type OriginalTransactionReference28</p>
4.25	0..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Interbank Settlement Amount	<p>ISO Name Interbank Settlement Amount</p> <p>ISO Definition Amount of money moved between the instructing agent and the instructed agent.</p> <p>XML Tag IntrBkStlmAmt</p> <p>Type ActiveOrHistoricCurrencyAndAmount</p> <p>SEPA FractDigits 5</p> <p>TotalDigits 18</p> <p>SEPA Inclusive 0 ..</p>
4.26	0..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Amount	<p>ISO Name Amount</p> <p>ISO Definition Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.</p> <p>XML Tag Amt</p> <p>Type AmountType4Choice</p>
4.27	0..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Interbank Settlement Date	<p>ISO Name Interbank Settlement Date</p> <p>ISO Definition Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.</p> <p>XML Tag IntrBkStlmDt</p> <p>Type ISODate</p>
4.28	0..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Requested Collection Date	<p>ISO Name Requested Collection Date</p> <p>ISO Definition Date and time at which the creditor requests that the amount of money is to be collected from the debtor.</p> <p>XML Tag ReqdCollmDt</p> <p>Type ISODate</p>
4.29	0..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Requested Execution Date	<p>ISO Name Requested Execution Date</p> <p>ISO Definition Date at which the initiating party requests the clearing agent to process the payment. Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank.</p> <p>XML Tag ReqdExctmDt</p> <p>Type DateAndDateTime2Choice</p>



#	SEPA Mult	Message Element	Request for Recall by the Originator (RFRO) SEPA Core Requirements	
4.30	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Creditor Scheme Identification	ISO Name ISO Definition XML Tag Type	Creditor Scheme Identification Credit party that signs the mandate. CdtmSchmeld PartyIdentification135
4.31	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Settlement Information	ISO Name ISO Definition XML Tag Type	Settlement Information Specifies the details on how the settlement of the original transaction(s) between the instructing agent and the instructed agent was completed. SttlmInf SettlementInstruction7
4.32	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Payment Type Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T001 The Identification code of the SCT Inst Scheme.</i> <i>AT-T008 The category purpose of the SCT Inst Instruction.</i> Payment Type Information Set of elements used to further specify the type of transaction. PmtTpInf PaymentTypeInfoInformation27
4.33	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Payment Method	ISO Name ISO Definition XML Tag Type	Payment Method Specifies the means of payment that will be used to move the amount of money. PmtMtd PaymentMethod4Code
4.34	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Mandate Related Information	ISO Name ISO Definition XML Tag Type	Mandate Related Information Provides further details of the mandate signed between the creditor and the debtor. MndtRltdInf MandateRelatedInformation14
4.35	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Remittance Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T009 The Remittance information.</i> Remittance Information Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system. RmtInf RemittanceInformation16
4.36	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Ultimate Debtor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-P006 The name of the Originator Reference Party.</i> <i>AT-P007 The identification code of the Originator Reference Party.</i> <i>Only 'Party' is allowed.</i> Ultimate Debtor Ultimate party that owes an amount of money to the (ultimate) creditor. UltmtDbtr Party40Choice
4.37	0..1	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Debtor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-P001 The name of the Originator.</i> <i>AT-P005 The address of the Originator.</i> <i>AT-P004 The Originator's identification code.</i> <i>Only 'Party' is allowed.</i> Debtor Party that owes an amount of money to the (ultimate) creditor. Dbtr Party40Choice



#	SEPA Mult	Message Element	Request for Recall by the Originator (RFRO) SEPA Core Requirements	
4.38	1..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Debtor Account	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-D001 The IBAN of the account of the Originator.</i> <i>AT-P003 The Proxy/Alias of the account of the Originator.</i> Debtor Account Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction. DbtrAcct CashAccount38
4.39	0..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Debtor Agent	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-D002 The BIC code of the Originator PSP.</i> Debtor Agent Financial institution servicing an account for the debtor. DbtrAgt BranchAndFinancialInstitutionIdentification6
4.40	0..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Debtor Agent Account	ISO Name ISO Definition XML Tag Type	Debtor Agent Account Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain. DbtrAgtAcct CashAccount38
4.41	0..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Creditor Agent	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-C002 The BIC code of the Beneficiary PSP.</i> Creditor Agent Financial institution servicing an account for the creditor. CdtrAgt BranchAndFinancialInstitutionIdentification6
4.42	0..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Creditor Agent Account	ISO Name ISO Definition XML Tag Type	Creditor Agent Account Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction. CdtrAgtAcct CashAccount38
4.43	0..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Creditor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-E001 The name of the Beneficiary.</i> <i>AT-E004 The address of the Beneficiary.</i> <i>AT-E005 The Beneficiary identification code.</i> Only 'Party' is allowed. Creditor Party to which an amount of money is due. Cdtr Party40Choice
4.44	1..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Creditor Account	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-C001 The IBAN of the account of the Beneficiary.</i> <i>AT-E003 The Proxy/Alias of the account of the Beneficiary.</i> Creditor Account Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction. CdtrAcct CashAccount38
4.45	0..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Ultimate Creditor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-E007 The name of the Beneficiary Reference Party.</i> <i>AT-E010 The identification code of the Beneficiary Reference Party.</i> Only 'Party' is allowed. Ultimate Creditor Ultimate party to which an amount of money is due. UltmtCdtr Party40Choice



#	SEPA Mult	Message Element	Request for Recall by the Originator (RFRO) SEPA Core Requirements	
4.46	0..1	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Transaction Reference ++++Purpose	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T007 The purpose of the SCT Inst Instruction.</i> Purpose Underlying reason for the payment transaction. Usage: Purpose is used by the end customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain. Purp Purpose2Choice
4.47	0..n	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1
5.0	0..n	FIto FIPayment Cancellation Request V08 +Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1



2.10 Inter-PSP Negative Response to the Request for Recall by the Originator Dataset (DS-09)

2.10.1 Use of Resolution of Investigation (camt.029.001.09)

In the context of a Request for Recall by the Originator of an SCT Inst, this message is to be used to transmit a negative response to a:

- Request for Recall by the Originator message (FI-to-FI Payment Cancellation Request V01, camt.056.001.08);
- a Request for Status Update on a Request for Recall by the Originator message (FI-to-FI Payment Status Request, pacs.028.001.03, refer to section 'Request for Status Update on a Request for Recall by the Originator' below);

where the following apply:

- Index 3.0 'Status': only sub-element 'Confirmation' can be used, populated with "RJCR" (Rejected Cancellation Request).
- Index 4.21 'Additional Information':
 - A mandatory occurrence starting with "ATR072/" followed by the information as per attribute description 'The specific reference of the Originator PSP for the Request for Recall by the Originator'.
 - In addition, when reason code was "AC03" (Wrong IBAN) in the camt.056, up to ten occurrences are allowed all starting with "ATR078/" followed by the information as per attribute description 'Provision of all information available to file a legal claim to recover the funds in case of reason code 'wrong unique identifier of the Beneficiary account' (optional)'.
 - As a consequence, the 'SEPA Mult.' is set to [1..11].

The message caters for a single or group negative response.

Note: The use case of the message is implied by the 'Message Name', 'camt.029.001.09', the 'Original Message Name Identification' must begin with 'pacs.008' (the addition of a variant number and version number is optional), 'Status' set to "RJCR" and 'Payment Type Information' mentioning "INST" (Transaction is related to an Instant Credit Transfer) under 'Local Instrument/Code'.

Note: Message elements under 'Original Transaction Reference' sequence are based on DS-02 attributes



#	SEPA Mult	Message Element	Inter-PSP Negative Response to a RFRO SEPA Core Requirements	
		Document	XML Tag Type	Document Document
	1..1	Resolution Of Investigation V09	ISO Name ISO Definition XML Tag Type	Resolution Of Investigation V09 Scope The ResolutionOfInvestigation message is sent by a case assignee to a case creator/case assigner. This message is used to inform of the resolution of a case, and optionally provides details about. - the corrective action undertaken by the case assignee; - information on the return where applicable. RsltnOfInvstgtn ResolutionOfInvestigationV09
1.0	1..1	Resolution Of Investigation V09 +Assignment	ISO Name ISO Definition XML Tag Type	Assignment Identifies the assignment of an investigation case from an assigner to an assignee. Usage: The assigner must be the sender of this confirmation and the assignee must be the receiver. Assgnmt CaseAssignment5
1.1	1..1	Resolution Of Investigation V09 +Assignment ++Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Identification Uniquely identifies the case assignment. Id Max35Text 1 .. 35 1 .. 35
1.2	1..1	Resolution Of Investigation V09 +Assignment ++Assigner	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>Instructing Party.</i> <i>Limited to 'BICFI' to identify a PSP, 'AnyBIC' to identify a CSM or 'LEI' or 'Name' to indicate a CSM when it has no BIC.</i> <i>'Name' is limited to 70 characters in length.</i> Assigner Party who assigns the case. Usage: This is also the sender of the message. Assgnr Party40Choice
1.3	1..1	Resolution Of Investigation V09 +Assignment ++Assignee	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>Instructed Party.</i> <i>Limited to 'BICFI' to identify a PSP, 'AnyBIC' to identify a CSM or 'LEI' or 'Name' to indicate a CSM when it has no BIC.</i> <i>'Name' is limited to 70 characters in length.</i> Assignee Party to which the case is assigned. Usage: This is also the receiver of the message. Assgne Party40Choice
1.4	1..1	Resolution Of Investigation V09 +Assignment ++Creation Date Time	ISO Name ISO Definition XML Tag Type	Creation Date Time Date and time at which the assignment was created. CreDtTm ISODateTime
2.0	0..1	Resolution Of Investigation V09 +Resolved Case	ISO Name ISO Definition XML Tag Type	Resolved Case Identifies a resolved case. RslvdCase Case5
3.0	1..1	Resolution Of Investigation V09 +Status	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>Only 'Confirmation' is allowed.</i> Status Indicates the status of the investigation. Sts InvestigationStatus5Choice
	1..1		XML Tag	xs:choice



#	SEPA Mult	Message Element	Inter-PSP Negative Response to a RFRO SEPA Core Requirements
3.1	1..1	Resolution Of Investigation V09 +Status ++Confirmation	<p>SEPA Usage Rule(s) Only "RJCR" is allowed.</p> <p>ISO Name Confirmation</p> <p>ISO Definition Specifies the status of the investigation, in a coded form.</p> <p>XML Tag Conf</p> <p>Type ExternalInvestigationExecutionConfirmation1Code</p> <p>ISO Length 1 .. 4</p> <p>SEPA Length 1 .. 4</p> <p>SEPA Code Restrictions</p> <p>RJCR <i>RejectedCancellationRequest</i> Used when a requested cancellation has been rejected.</p>
3.2	1..n	Resolution Of Investigation V09 +Status ++Rejected Modification	<p>ISO Name Rejected Modification</p> <p>ISO Definition Reason for the rejection of a modification request, in a coded form.</p> <p>XML Tag RjctdMod</p> <p>Type ModificationStatusReason1Choice</p>
3.3	1..1	Resolution Of Investigation V09 +Status ++Duplicate Of	<p>ISO Name Duplicate Of</p> <p>ISO Definition Indicates a duplicated case. Usage: When present, the case identified in the message must be closed. The case identified as duplicated (in this component) will be pursued.</p> <p>XML Tag DplctOf</p> <p>Type Case5</p>
3.4	1..1	Resolution Of Investigation V09 +Status ++Assignment Cancellation Confirmation	<p>ISO Name Assignment Cancellation Confirmation</p> <p>ISO Definition Indicates whether the cancellation of the assignment is confirmed or rejected. Usage: If yes, the cancellation of the assignment is confirmed. If no, the cancellation of the assignment is rejected and the investigation process will continue.</p> <p>XML Tag AssgnmtCxlConf</p> <p>Type YesNoIndicator</p>
4.0	1..n	Resolution Of Investigation V09 +Cancellation Details	<p>SEPA Usage Rule(s) Mandatory.</p> <p>ISO Name Cancellation Details</p> <p>ISO Definition Specifies the details of the underlying transactions being cancelled.</p> <p>XML Tag CxlDtls</p> <p>Type UnderlyingTransaction22</p>
4.1	0..1	Resolution Of Investigation V09 +Cancellation Details ++Original Group Information And Status	<p>ISO Name Original Group Information And Status</p> <p>ISO Definition Provides information on the original cancellation message, to which the resolution refers.</p> <p>XML Tag OrgnlGrpInfAndSts</p> <p>Type OriginalGroupHeader14</p>
4.2	0..n	Resolution Of Investigation V09 +Cancellation Details ++Original Payment Information And Status	<p>ISO Name Original Payment Information And Status</p> <p>ISO Definition Provides information on the original (group of) transactions, to which the cancellation status refers.</p> <p>XML Tag OrgnlPmtInfAndSts</p> <p>Type OriginalPaymentInstruction30</p>
4.3	1..n	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status	<p>SEPA Usage Rule(s) Mandatory.</p> <p>ISO Name Transaction Information And Status</p> <p>ISO Definition Provides details on the original transactions to which the cancellation request message refers.</p> <p>XML Tag TxInfAndSts</p> <p>Type PaymentTransaction102</p>



#	SEPA Mult	Message Element	Inter-PSP Negative Response to a RFRO SEPA Core Requirements
4.4	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Cancellation Status Identification	<p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Cancellation Status Identification</p> <p>ISO Definition Unique and unambiguous identifier of a cancellation request status, as assigned by the assigner.</p> <p>Usage: The cancellation status identification can be used for reconciliation or to link tasks relating to the cancellation request.</p> <p>XML Tag CxlStsId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>
4.5	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Resolved Case	<p>ISO Name Resolved Case</p> <p>ISO Definition Identifies the resolved case.</p> <p>XML Tag RslvdCase</p> <p>Type Case5</p>
4.6	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Group Information	<p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Original Group Information</p> <p>ISO Definition Provides information on the original message.</p> <p>XML Tag OrgnlGrpInf</p> <p>Type OriginalGroupInformation29</p>
4.7	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Group Information ++++Original Message Identification	<p>ISO Name Original Message Identification</p> <p>ISO Definition Point to point reference assigned by the original instructing party to unambiguously identify the original message.</p> <p>XML Tag OrgnlMsgId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>
4.8	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Group Information ++++Original Message Name Identification	<p>SEPA Usage Rule(s) <i>Must begin with 'pacs.008'. The addition of a variant number and version number is optional.</i></p> <p>ISO Name Original Message Name Identification</p> <p>ISO Definition Specifies the original message name identifier to which the message refers, for example, pacs.003.001.01 or MT103.</p> <p>XML Tag OrgnlMsgNmId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>
4.9	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Group Information ++++Original Creation Date Time	<p>ISO Name Original Creation Date Time</p> <p>ISO Definition Original date and time at which the message was created.</p> <p>XML Tag OrgnlCreDtTm</p> <p>Type ISODateTime</p>
4.10	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Instruction Identification	<p>ISO Name Original Instruction Identification</p> <p>ISO Definition Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction.</p> <p>XML Tag OrgnlInstrId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>



#	SEPA Mult	Message Element	Inter-PSP Negative Response to a RFRO SEPA Core Requirements
4.11	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original End To End Identification	<p>SEPA Rulebook AT-T014 The Originator's reference of the SCT Inst Instruction.</p> <p>SEPA Usage Rule(s) Mandatory.</p> <p>ISO Name Original End To End Identification</p> <p>ISO Definition Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction.</p> <p>XML Tag OrgnlEndToEndId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>
4.12	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Identification	<p>SEPA Rulebook AT-T054 The Originator PSP's reference of the SCT Inst Transaction message.</p> <p>SEPA Usage Rule(s) Mandatory.</p> <p>ISO Name Original Transaction Identification</p> <p>ISO Definition Unique identification, as assigned by the original first instructing agent, to unambiguously identify the transaction.</p> <p>XML Tag OrgnlTxId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>
4.13	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Clearing System Reference	<p>ISO Name Original Clearing System Reference</p> <p>ISO Definition Unique reference, as assigned by the original clearing system, to unambiguously identify the original instruction.</p> <p>XML Tag OrgnlClrSysRef</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>
4.14	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original UETR	<p>ISO Name Original UETR</p> <p>ISO Definition Universally unique identifier to provide the original end-to-end reference of a payment transaction.</p> <p>XML Tag OrgnUETR</p> <p>Type UUIDv4Identifier</p> <p>Pattern [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}</p>
4.15	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Transaction Cancellation Status	<p>SEPA Usage Rule(s) Mandatory Only "RJCR" is allowed.</p> <p>ISO Name Transaction Cancellation Status</p> <p>ISO Definition Specifies the status of the transaction cancellation request.</p> <p>XML Tag TxCxlSts</p> <p>Type CancellationIndividualStatus1Code</p> <p>SEPA Code Restrictions</p> <p>RJCR RejectedCancellationRequest Cancellation request is rejected</p>
4.16	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Cancellation Status Reason Information	<p>SEPA Usage Rule(s) Mandatory. Only one occurrence is allowed.</p> <p>ISO Name Cancellation Status Reason Information</p> <p>ISO Definition Provides detailed information on the cancellation status reason.</p> <p>XML Tag CxlStsRsnInf</p> <p>Type CancellationStatusReason4</p>



#	SEPA Mult	Message Element	Inter-PSP Negative Response to a RFRO SEPA Core Requirements
4.17	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Cancellation Status Reason Information ++++Originator	<p>SEPA Rulebook AT-E001 The Name of the Beneficiary or AT-C002 The BIC code of the Beneficiary PSP.</p> <p>SEPA Usage Rule(s) Mandatory. Limited to 'AnyBIC' for an Agent or 'Name' for a non-financial institution. 'Name' is limited to 70 characters in length.</p> <p>ISO Name Originator ISO Definition Party that issues the cancellation status. XML Tag Orgtr Type PartyIdentification135</p>
4.18	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Cancellation Status Reason Information ++++Reason	<p>SEPA Rulebook AT-R077 Reason Code for non-acceptance of the Request for Recall by the Originator.</p> <p>SEPA Usage Rule(s) Mandatory.</p> <p>ISO Name Reason ISO Definition Specifies the reason for the status report. XML Tag Rsn Type CancellationStatusReason3Choice</p>
	1..1		XML Tag xs:choice
4.19	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Cancellation Status Reason Information ++++Reason +++++Code	<p>SEPA Usage Rule(s) Only "AC04", "AM04", "ARDT", "CUST", "LEGL", "NOAS" and "NOOR" are allowed.</p> <p>ISO Name Code ISO Definition Reason for the cancellation status, in a coded form. XML Tag Cd Type ExternalPaymentCancellationRejection1Code ISO Length 1 .. 4 SEPA Length 1 .. 4</p> <p>SEPA Code Restrictions</p> <p>AC04 ClosedAccountNumber Account number specified has been closed on the receiver's books.</p> <p>AM04 InsufficientFunds Amount of funds available to cover specified message amount is insufficient.</p> <p>ARDT AlreadyReturned Cancellation not accepted as the transaction has already been returned.</p> <p>CUST CustomerDecision Reported when the cancellation cannot be accepted because of a customer decision (Creditor).</p> <p>LEGL LegalDecision Reported when the cancellation cannot be accepted because of regulatory rules.</p> <p>NOAS NoAnswerFromCustomer No response from beneficiary (to the cancellation request).</p> <p>NOOR NoOriginalTransactionReceived Original transaction (subject to cancellation) never received.</p>
4.20	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Cancellation Status Reason Information ++++Reason +++++Proprietary	<p>ISO Name Proprietary ISO Definition Reason for the status, in a proprietary form. XML Tag Prtry Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35</p>



#	SEPA Mult	Message Element	Inter-PSP Negative Response to a RFRO SEPA Core Requirements	
4.21	1..11	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Cancellation Status Reason Information ++++Additional Information	<p>SEPA Rulebook AT-R072 The specific reference of the Originator PSP for the Request for Recall by the Originator. AT-R078 Provision of all information available to file a legal claim to recover the funds in case of reason code 'wrong unique identifier of the Beneficiary account'.</p> <p>SEPA Usage Rule(s) Mandatory. First occurrence is mandatory and must start with "ATR072/" followed by the information as per attribute description. When reason code was "AC03" (Wrong IBAN) in the camt.056, then up to ten further optional occurrences are allowed, all starting with "ATR078/" followed by the information as per attribute description.</p> <p>ISO Name Additional Information ISO Definition Further details on the cancellation status reason. XML Tag AddtlInf Type Max105Text ISO Length 1 .. 105 SEPA Length 1 .. 105</p>	
4.22	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Resolution Related Information	<p>ISO Name Resolution Related Information ISO Definition Reference of a return or a reversal transaction that is initiated to fix the case under investigation as part of the resolution. XML Tag RsltnRltdInf Type ResolutionData1</p>	
4.23	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Interbank Settlement Amount	<p>ISO Name Original Interbank Settlement Amount ISO Definition Amount of money moved between the instructing agent and the instructed agent, as provided in the original instruction. XML Tag OrgnlIntrBkStlmAmt Type ActiveOrHistoricCurrencyAndAmount SEPA FractDigits 5 TotalDigits 18 SEPA Inclusive 0 ..</p>	
4.24	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Interbank Settlement Date	<p>ISO Name Original Interbank Settlement Date ISO Definition Date, as provided in the original transaction, on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. XML Tag OrgnlIntrBkStlmDt Type ISODate</p>	
4.25	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Assigner	<p>ISO Name Assigner ISO Definition Party who assigns the case. Usage: This is also the agent that instructs the next party in the chain to carry out the (set of) cancellation request(s). XML Tag Assgnr Type Party40Choice</p>	
4.26	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Assignee	<p>ISO Name Assignee ISO Definition Party to which the case is assigned. Usage: This is also the agent that is instructed by the previous party in the chain to carry out the (set of) cancellation request(s). XML Tag Assgne Type Party40Choice</p>	



#	SEPA Mult	Message Element	Inter-PSP Negative Response to a RFRO SEPA Core Requirements
4.27	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference	<p>SEPA Rulebook An exact copy of all attributes of the initially sent DS-02 which is to be cancelled.</p> <p>SEPA Usage Rule(s) Mandatory. The yellow shaded message elements under 'Original Transaction Reference' must be populated with the same value as the message elements of the original instruction.</p> <p>ISO Name Original Transaction Reference ISO Definition Key elements used to identify the original transaction that is being referred to.</p> <p>XML Tag OrgnlTxRef Type OriginalTransactionReference28</p>
4.28	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Interbank Settlement Amount	<p>SEPA Rulebook AT-T002 The amount of the SCT Inst in euro.</p> <p>ISO Name Interbank Settlement Amount ISO Definition Amount of money moved between the instructing agent and the instructed agent.</p> <p>XML Tag IntrBkSttlmAmt Type ActiveOrHistoricCurrencyAndAmount</p> <p>SEPA FractDigits 2 TotalDigits 18 SEPA Inclusive 0.01 .. 999999999.99</p>
4.29	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Amount	<p>ISO Name Amount ISO Definition Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.</p> <p>XML Tag Amt Type AmountType4Choice</p>
4.30	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Interbank Settlement Date	<p>SEPA Rulebook AT-T051 The Settlement Date of the SCT Inst Transaction.</p> <p>ISO Name Interbank Settlement Date ISO Definition Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.</p> <p>XML Tag IntrBkSttlmDt Type ISODate</p>
4.31	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Requested Collection Date	<p>ISO Name Requested Collection Date ISO Definition Date and time at which the creditor requests that the amount of money is to be collected from the debtor.</p> <p>XML Tag ReqdColltnDt Type ISODate</p>
4.32	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Requested Execution Date	<p>ISO Name Requested Execution Date ISO Definition Date at which the initiating party requests the clearing agent to process the payment. Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank.</p> <p>XML Tag ReqdExctnDt Type DateAndDateTime2Choice</p>
4.33	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Creditor Scheme Identification	<p>ISO Name Creditor Scheme Identification ISO Definition Credit party that signs the mandate.</p> <p>XML Tag CdrSchmeld Type PartyIdentification135</p>
4.34	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Settlement Information	<p>ISO Name Settlement Information ISO Definition Specifies the details on how the settlement of the original transaction(s) between the instructing agent and the instructed agent was completed.</p> <p>XML Tag SttlmInf Type SettlementInstruction7</p>



#	SEPA Mult	Message Element	Inter-PSP Negative Response to a RFRO SEPA Core Requirements	
4.35	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Payment Type Information	<i>SEPA Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-T001 The identification code of the SCT Inst Scheme.</i> <i>AT-T008 The category purpose of the SCT Inst Instruction.</i> Payment Type Information Set of elements used to further specify the type of transaction. PmtTpInf PaymentTypeInformation27
4.36	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Payment Method	ISO Name ISO Definition XML Tag Type	Payment Method Specifies the means of payment that will be used to move the amount of money. PmtMtd PaymentMethod4Code
4.37	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Mandate Related Information	ISO Name ISO Definition XML Tag Type	Mandate Related Information Provides further details of the mandate signed between the creditor and the debtor. MndtRltdInf MandateRelatedInformation14
4.38	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Remittance Information	<i>SEPA Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-T009 The Remittance information.</i> Remittance Information Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system. RmtInf RemittanceInformation16
4.39	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Ultimate Debtor	<i>SEPA Rulebook</i> <i>SEPA Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>AT-P006 The name of the Originator Reference Party.</i> <i>AT-P007 The Identification Code of the Originator Reference Party.</i> <i>Only 'Party' is allowed.</i> Ultimate Debtor Ultimate party that owes an amount of money to the (ultimate) creditor. UltmtDbtr Party40Choice
4.40	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Debtor	<i>SEPA Rulebook</i> <i>SEPA Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>AT-P001 The name of the Originator.</i> <i>AT-P005 The address of the Originator.</i> <i>AT-P004 The Originator identification Code.</i> <i>Only 'Party' is allowed.</i> Debtor Party that owes an amount of money to the (ultimate) creditor. Dbtr Party40Choice
4.41	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Debtor Account	<i>SEPA Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-D001 The IBAN of the account of the Originator.</i> <i>AT-P003 The Proxy/Alias of the account of the Originator.</i> Debtor Account Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction. DbtrAcct CashAccount38
4.42	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Debtor Agent	<i>SEPA Rulebook</i> ISO Name ISO Definition XML Tag Type	<i>AT-D002 The BIC code of the Originator PSP.</i> Debtor Agent Financial institution servicing an account for the debtor. DbtrAgt BranchAndFinancialInstitutionIdentification6



#	SEPA Mult	Message Element	Inter-PSP Negative Response to a RFRO SEPA Core Requirements	
4.43	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Debtor Agent Account	ISO Name ISO Definition XML Tag Type	Debtor Agent Account Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain. DbtrAgtAcct CashAccount38
4.44	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Creditor Agent	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-C002 The BIC code of the Beneficiary PSP.</i> Creditor Agent Financial institution servicing an account for the creditor. CdtrAgt BranchAndFinancialInstitutionIdentification6
4.45	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Creditor Agent Account	ISO Name ISO Definition XML Tag Type	Creditor Agent Account Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction. CdtrAgtAcct CashAccount38
4.46	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Creditor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-E001 The name of the Beneficiary.</i> <i>AT-E004 The address of the Beneficiary.</i> <i>AT-E005 The Beneficiary identification code.</i> Only 'Party' is allowed. Creditor Party to which an amount of money is due. Cdtr Party40Choice
4.47	1..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Creditor Account	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-C001 The IBAN of the account of the Beneficiary.</i> <i>AT-E003 The Proxy/Alias of the account of the Beneficiary.</i> Creditor Account Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction. CdtrAcct CashAccount38
4.48	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Ultimate Creditor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-E007 The name of the Beneficiary Reference Party.</i> <i>AT-E010 The identification code of the Beneficiary Reference Party.</i> Only 'Party' is allowed. Ultimate Creditor Ultimate party to which an amount of money is due. UltmtCdtr Party40Choice
4.49	0..1	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Transaction Reference ++++Purpose	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T007 The purpose of the SCT Inst Instruction.</i> Purpose Underlying reason for the payment transaction. Usage: Purpose is used by the end customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain. Purp Purpose2Choice



#	SEPA Mult	Message Element	Inter-PSP Negative Response to a RFRO SEPA Core Requirements	
5.0	0..1	Resolution Of Investigation V09 +Modification Details	ISO Name ISO Definition XML Tag Type	Modification Details Specifies the details of the underlying transaction being modified. ModDtls PaymentTransaction107
6.0	0..1	Resolution Of Investigation V09 +Claim Non Receipt Details	ISO Name ISO Definition XML Tag Type	Claim Non Receipt Details Specifies the details of the underlying transaction for which a claim non receipt has been initiated. ClmNonRctDtls ClaimNonReceipt2Choice
7.0	0..1	Resolution Of Investigation V09 +Statement Details	ISO Name ISO Definition XML Tag Type	Statement Details Details on the underlying statement entry. StmntDtls StatementResolutionEntry4
8.0	0..1	Resolution Of Investigation V09 +Correction Transaction	ISO Name ISO Definition XML Tag Type	Correction Transaction References a transaction initiated to fix the case under investigation. CrrectnTx CorrectiveTransaction4Choice
9.0	0..1	Resolution Of Investigation V09 +Resolution Related Information	ISO Name ISO Definition XML Tag Type	Resolution Related Information Reference to fix the case under investigation as part of the resolution. RsltnRltdInf ResolutionData1
10.0	0..n	Resolution Of Investigation V09 +Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1



2.11 Inter-PSP Positive Response to the Request for Recall by the Originator (DS-09)

2.11.1 Use of inter-PSP return credit transfer message (pacs.004.001.09)

In the context of a Request for Recall by the Originator of an SCT Inst, this message is to be used to transmit a positive response to a:

- Request for Recall by the Originator message (FI-to-FI Payment Cancellation Request V01, camt.056.001.08)
- Request for Status Update of a Request for Recall by the Originator message (FI-to-FI Payment Status Request, pacs.028.001.03, refer to section 'Request for Status Update on a Request for Recall by the Originator' below)

where the following applies:

- Index 1.9 'Interbank Settlement Date' to be populated with AT-R076 'The settlement date for the positive response to the Request for Recall by the Originator'.
- Index 3.13 'Returned Interbank Settlement Amount' to be populated with AT-R074 'The returned amount of the positive response to the Request for Recall by the Originator in euro'.
- Index 3.17 'Returned Instructed Amount' may be used.
- Index 3.22 'Amount' (under 'Charges Information') to be populated with AT-R075 'Fee for the positive response to the Request for Recall by the Originator in euro', if any.
- Index 3.24 'Financial Institution Identification' (under 'Agent' under 'Charges Information') to be populated with AT-C002 'The BIC code of the Beneficiary PSP'.
- Index 3.31 'Originator' to be populated with AT-R002 'The Identification of the type of party initiating the "R" message'.
- Index 3.33 'Reason/Code' (under 'Return Reason Information') to be populated only with "FOCR" (Following Cancellation Request).
- Index 3.35 'Additional Information' under 'Return Reason Information' to be used with a mandatory occurrence starting with "ATR072/" followed by the information as per attribute description 'The specific reference of the Originator PSP for the Request for Recall by the Originator'.

The message caters for a single or group positive response.

Note: Attribute AT-R001 'The type of R-message' is implied is implied by the 'Message Name', 'pacs.004.001.09', the 'Original Message Name Identification' must begin with 'pacs.008' (the addition of a variant number and version number is optional), 'Reason' under 'Return Reason Information' set to "FOCR" and 'Payment Type Information' mentioning "INST" (Transaction is related to an Instant Credit Transfer) under 'Local Instrument/Code'.

Note: Message elements under 'Original Transaction Reference' sequence are based on DS-02 attributes.



#	SEPA Mult	Message Element	Inter-PSP Positive Response to a RFRO SEPA Core Requirements	
		Document	XML Tag Type	Document Document
	1..1	Payment Return V09	ISO Name ISO Definition XML Tag Type	Payment Return V09 Scope The PaymentReturn message is sent by an agent to the previous agent in the payment chain to undo a payment previously settled. PmtRtr PaymentReturnV09
1.0	1..1	Payment Return V09 +Group Header	ISO Name ISO Definition XML Tag Type	Group Header Set of characteristics shared by all individual transactions included in the message. GrpHdr GroupHeader90
1.1	1..1	Payment Return V09 +Group Header ++Message Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Message Identification Point to point reference, as assigned by the instructing party and sent to the next party in the chain, to unambiguously identify the message. Usage: The instructing party has to make sure that MessageIdentification is unique per instructed party for a pre-agreed period. MsgId Max35Text 1 .. 35 1 .. 35
1.2	1..1	Payment Return V09 +Group Header ++Creation Date Time	ISO Name ISO Definition XML Tag Type	Creation Date Time Date and time at which the message was created. CreDfTm ISODateTime
1.3	0..2	Payment Return V09 +Group Header ++Authorisation	ISO Name ISO Definition XML Tag Type	Authorisation User identification or any user key to be used to check whether the initiating party is allowed to initiate transactions from the account specified in the message. Usage: The content is not of a technical nature, but reflects the organisational structure at the initiating side. The authorisation element can typically be used in relay scenarios, payment initiations, payment returns or payment reversals that are initiated on behalf of a party different from the initiating party. Authstn Authorisation1Choice
1.4	0..1	Payment Return V09 +Group Header ++Batch Booking	ISO Name ISO Definition XML Tag Type	Batch Booking Identifies whether a single entry per individual transaction or a batch entry for the sum of the amounts of all transactions within the group of a message is requested. Usage: Batch booking is used to request and not order a possible batch booking. BtchBookg BatchBookingIndicator
1.5	1..1	Payment Return V09 +Group Header ++Number Of Transactions	ISO Name ISO Definition XML Tag Type Pattern	Number Of Transactions Number of individual transactions contained in the message. NbOfTxs Max15NumericText [0-9]{1,15}



#	SEPA Mult	Message Element	Inter-PSP Positive Response to a RFRO SEPA Core Requirements
1.6	0..1	Payment Return V09 +Group Header ++Control Sum	<p>ISO Name Control Sum</p> <p>ISO Definition Total of all individual amounts included in the message, irrespective of currencies.</p> <p>XML Tag CtrlSum</p> <p>Type DecimalNumber</p> <p>SEPA FractDigits 17</p> <p>TotalDigits 18</p>
1.7	0..1	Payment Return V09 +Group Header ++Group Return	<p>ISO Name Group Return</p> <p>ISO Definition Indicates whether the return applies to the whole group of transactions or to individual transactions within the original group(s).</p> <p>XML Tag GrpRtr</p> <p>Type TrueFalseIndicator</p>
1.8	1..1	Payment Return V09 +Group Header ++Total Returned Interbank Settlement Amount	<p>SEPA Usage Rule(s) <i>Mandatory.</i> <i>Only 'EUR' is allowed.</i> <i>Amount must be 0.01 or more and 99999999999999.99 or less.</i> <i>The fractional part has a maximum of two digits.</i></p> <p>SEPA Format Rule(s)</p> <p>ISO Name Total Returned Interbank Settlement Amount</p> <p>ISO Definition Total amount of money moved between the instructing agent and the instructed agent in the return message.</p> <p>XML Tag TtlRtrdIntrBkSttlmAmt</p> <p>Type ActiveCurrencyAndAmount</p> <p>SEPA FractDigits 2</p> <p>TotalDigits 18</p> <p>SEPA Inclusive 0.01 .. 99999999999999.99</p>
1.9	1..1	Payment Return V09 +Group Header ++Interbank Settlement Date	<p>SEPA Rulebook <i>AT-R076 The settlement date for the positive response to the Request for Recall by the Originator.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Interbank Settlement Date</p> <p>ISO Definition Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.</p> <p>XML Tag IntrBkSttlmDt</p> <p>Type ISODate</p>
1.10	1..1	Payment Return V09 +Group Header ++Settlement Information	<p>ISO Name Settlement Information</p> <p>ISO Definition Specifies the details on how the settlement of the transaction(s) between the instructing agent and the instructed agent is completed.</p> <p>XML Tag SttlmInf</p> <p>Type SettlementInstruction7</p>
1.11	1..1	Payment Return V09 +Group Header ++Settlement Information +++Settlement Method	<p>SEPA Usage Rule(s) <i>Only "CLRG", "INGA" and "INDA" are allowed.</i></p> <p>ISO Name Settlement Method</p> <p>ISO Definition Method used to settle the (batch of) payment instructions.</p> <p>XML Tag SttlmMtd</p> <p>Type SettlementMethod1Code</p> <p>SEPA Code Restrictions</p> <p>CLRG <i>ClearingSystem</i> <i>Settlement is done through a payment clearing system.</i></p> <p>INDA <i>InstructedAgent</i> <i>Settlement is done by the agent instructed to execute a payment instruction.</i></p> <p>INGA <i>InstructingAgent</i> <i>Settlement is done by the agent instructing and forwarding the payment to the next party in the payment chain.</i></p>



#	SEPA Mult	Message Element	Inter-PSP Positive Response to a RFRO SEPA Core Requirements
1.12	0..1	Payment Return V09 +Group Header ++Settlement Information +++Settlement Account	<i>SEPA Usage Rule(s)</i> Only 'Identification' is allowed. ISO Name Settlement Account ISO Definition A specific purpose account used to post debit and credit entries as a result of the transaction. XML Tag StlmAcct Type CashAccount38
1.13	0..1	Payment Return V09 +Group Header ++Settlement Information +++Clearing System	ISO Name Clearing System ISO Definition Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed. XML Tag ClrSys Type ClearingSystemIdentification3Choice
	1..1		XML Tag xs:choice
1.14	1..1	Payment Return V09 +Group Header ++Settlement Information +++Clearing System ++++Code	ISO Name Code ISO Definition Infrastructure through which the payment instruction is processed, as published in an external clearing system identification code list. XML Tag Cd Type ExternalCashClearingSystem1 Code ISO Length 1 .. 3 SEPA Length 1 .. 3
1.15	1..1	Payment Return V09 +Group Header ++Settlement Information +++Clearing System ++++Proprietary	ISO Name Proprietary ISO Definition Clearing system identification in a proprietary form. XML Tag Prtry Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35
1.16	0..1	Payment Return V09 +Group Header ++Settlement Information +++Instructing Reimbursement Agent	ISO Name Instructing Reimbursement Agent ISO Definition Agent through which the instructing agent will reimburse the instructed agent. Usage: If InstructingAgent and InstructedAgent have the same reimbursement agent, then only InstructingReimbursementAgent must be used. XML Tag InstgRmbrsmntAgt Type BranchAndFinancialInstitutionIdentification6
1.17	0..1	Payment Return V09 +Group Header ++Settlement Information +++Instructing Reimbursement Agent Account	ISO Name Instructing Reimbursement Agent Account ISO Definition Unambiguous identification of the account of the instructing reimbursement agent account at its servicing agent in the payment chain. XML Tag InstgRmbrsmntAgtAcct Type CashAccount38
1.18	0..1	Payment Return V09 +Group Header ++Settlement Information +++Instructed Reimbursement Agent	ISO Name Instructed Reimbursement Agent ISO Definition Agent at which the instructed agent will be reimbursed. Usage: If InstructedReimbursementAgent contains a branch of the InstructedAgent, then the party in InstructedAgent will claim reimbursement from that branch/will be paid by that branch. Usage: If InstructingAgent and InstructedAgent have the same reimbursement agent, then only InstructingReimbursementAgent must be used. XML Tag InstdRmbrsmntAgt Type BranchAndFinancialInstitutionIdentification6
1.19	0..1	Payment Return V09 +Group Header ++Settlement Information +++Instructed Reimbursement Agent Account	ISO Name Instructed Reimbursement Agent Account ISO Definition Unambiguous identification of the account of the instructed reimbursement agent account at its servicing agent in the payment chain. XML Tag InstdRmbrsmntAgtAcct Type CashAccount38



#	SEPA Mult	Message Element	Inter-PSP Positive Response to a RFRO SEPA Core Requirements	
1.20	0..1	Payment Return V09 +Group Header ++Settlement Information +++Third Reimbursement Agent	ISO Name ISO Definition XML Tag Type	Third Reimbursement Agent Agent at which the instructed agent will be reimbursed. Usage: If ThirdReimbursementAgent contains a branch of the InstructedAgent, then the party in InstructedAgent will claim reimbursement from that branch/will be paid by that branch. ThrdRmbrsmntAgt BranchAndFinancialInstitutionIdentification6
1.21	0..1	Payment Return V09 +Group Header ++Settlement Information +++Third Reimbursement Agent Account	ISO Name ISO Definition XML Tag Type	Third Reimbursement Agent Account Unambiguous identification of the account of the third reimbursement agent account at its servicing agent in the payment chain. ThrdRmbrsmntAgtAcct CashAccount38
1.22	0..1	Payment Return V09 +Group Header ++Instructing Agent	<i>SEPA Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>Only 'BICFI' is allowed.</i> Instructing Agent Agent that instructs the next party in the chain to carry out the (set of) instruction(s). Usage: The instructing agent is the party sending the return message and not the party that sent the original instruction that is being returned. InstgAgt BranchAndFinancialInstitutionIdentification6
1.23	0..1	Payment Return V09 +Group Header ++Instructed Agent	<i>SEPA Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>Only 'BICFI' is allowed.</i> Instructed Agent Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s). Usage: The instructed agent is the party receiving the return message and not the party that received the original instruction that is being returned. InstdAgt BranchAndFinancialInstitutionIdentification6
2.0	0..1	Payment Return V09 +Original Group Information	<i>SEPA Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type	<i>Sub-elements of 'Original Group Information' must be present in either 'Original Group Information' or in 'Transaction Information'.</i> Original Group Information Information concerning the original group of transactions, to which the message refers. OrgnlGrpInf OriginalGroupHeader18
2.1	1..1	Payment Return V09 +Original Group Information ++Original Message Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Message Identification Point to point reference, as assigned by the original instructing party, to unambiguously identify the original message. OrgnlMsgId Max35Text 1 .. 35 1 .. 35
2.2	1..1	Payment Return V09 +Original Group Information ++Original Message Name Identification	<i>SEPA Usage Rule(s)</i> ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>Must begin with 'pacs.008'. The addition of a variant number and version number is optional.</i> Original Message Name Identification Specifies the original message name identifier to which the message refers. OrgnlMsgNmId Max35Text 1 .. 35 1 .. 35
2.3	0..1	Payment Return V09 +Original Group Information ++Original Creation Date Time	ISO Name ISO Definition XML Tag Type	Original Creation Date Time Date and time at which the original message was created. OrgnlCreDtTm ISODateTime



#	SEPA Mult	Message Element	Inter-PSP Positive Response to a RFRO SEPA Core Requirements	
2.4	0..n	Payment Return V09 +Original Group Information ++Return Reason Information	ISO Name ISO Definition XML Tag Type	Return Reason Information Provides detailed information on the return reason. RtrRsnInf PaymentReturnReason6
3.0	1..n	Payment Return V09 +Transaction Information	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>Mandatory.</i> Transaction Information Information concerning the original transactions, to which the return message refers. TxInf PaymentTransaction112
3.1	1..1	Payment Return V09 +Transaction Information ++Return Identification	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>Mandatory.</i> <i>This ID must be forwarded to the Originator PSP and optionally to the Originator (and therefore it is not a point-to-point reference).</i> Return Identification Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the returned transaction. Usage: The instructing party is the party sending the return message and not the party that sent the original instruction that is being returned. RtrId Max35Text 1 .. 35 1 .. 35
3.2	0..1	Payment Return V09 +Transaction Information ++Original Group Information	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>Sub-elements of 'Original Group Information' must be present in either 'Original Group Information' or in 'Transaction Information'.</i> Original Group Information Provides information on the original message. OrgnlGrpInf OriginalGroupInformation29
3.3	1..1	Payment Return V09 +Transaction Information ++Original Group Information +++Original Message Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Original Message Identification Point to point reference assigned by the original instructing party to unambiguously identify the original message. OrgnlMsgId Max35Text 1 .. 35 1 .. 35
3.4	1..1	Payment Return V09 +Transaction Information ++Original Group Information +++Original Message Name Identification	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	<i>Must begin with 'pacs.008'. The addition of a variant number and version number is optional.</i> Original Message Name Identification Specifies the original message name identifier to which the message refers, for example, pacs.003.001.01 or MT103. OrgnlMsgNmId Max35Text 1 .. 35 1 .. 35
3.5	0..1	Payment Return V09 +Transaction Information ++Original Group Information +++Original Creation Date Time	ISO Name ISO Definition XML Tag Type	Original Creation Date Time Original date and time at which the message was created. OrgnlCreDtTm ISODateTime



#	SEPA Mult	Message Element	Inter-PSP Positive Response to a RFRO SEPA Core Requirements
3.6	0..1	Payment Return V09 +Transaction Information ++Original Instruction Identification	<p>SEPA Usage Rule(s) <i>Mandatory if provided in the original instruction.</i></p> <p>ISO Name Original Instruction Identification</p> <p>ISO Definition Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction.</p> <p>XML Tag OrgnlInstrId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>
3.7	1..1	Payment Return V09 +Transaction Information ++Original End To End Identification	<p>SEPA Rulebook <i>AT-T014 The Originator's reference of the SCT Inst Instruction.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Original End To End Identification</p> <p>ISO Definition Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction.</p> <p>XML Tag OrgnlEndToEndId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>
3.8	1..1	Payment Return V09 +Transaction Information ++Original Transaction Identification	<p>SEPA Rulebook <i>AT-T054 The Originator PSP's reference of the SCT Inst Transaction message.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p><i>Must contain a reference that is meaningful to the Originator's PSP and is unique over time.</i></p> <p>ISO Name Original Transaction Identification</p> <p>ISO Definition Unique identification, as assigned by the original first instructing agent, to unambiguously identify the transaction.</p> <p>XML Tag OrgnlTxId</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>
3.9	0..1	Payment Return V09 +Transaction Information ++Original UETR	<p>ISO Name Original UETR</p> <p>ISO Definition Universally unique identifier to provide the original end-to-end reference of a payment transaction.</p> <p>XML Tag OrgnlUETR</p> <p>Type UUIDv4Identifier</p> <p>Pattern [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}</p>
3.10	0..1	Payment Return V09 +Transaction Information ++Original Clearing System Reference	<p>ISO Name Original Clearing System Reference</p> <p>ISO Definition Unique reference, as assigned by the original clearing system, to unambiguously identify the original instruction.</p> <p>XML Tag OrgnlClrSysRef</p> <p>Type Max35Text</p> <p>ISO Length 1 .. 35</p> <p>SEPA Length 1 .. 35</p>



#	SEPA Mult	Message Element	Inter-PSP Positive Response to a RFRO SEPA Core Requirements
3.11	1..1	Payment Return V09 +Transaction Information ++Original Interbank Settlement Amount	<p>SEPA Rulebook AT-T002 The amount of the SCT Inst in euro. SEPA Usage Rule(s) Mandatory. Only 'EUR' is allowed. Amount must be 0.01 or more and 999999999.99 or less.</p> <p>SEPA Format Rule(s) The fractional part has a maximum of two digits.</p> <p>ISO Name Original Interbank Settlement Amount ISO Definition Amount of money moved between the instructing agent and the instructed agent, as provided in the original instruction.</p> <p>XML Tag OrgnlIntrBkSttlmAmt Type ActiveOrHistoricCurrencyAndAmount SEPA FractDigits 2 TotalDigits 18 SEPA Inclusive 0.01 .. 999999999.99</p>
3.12	0..1	Payment Return V09 +Transaction Information ++Original Interbank Settlement Date	<p>ISO Name Original Interbank Settlement Date ISO Definition Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.</p> <p>Usage: the OriginalInterbankSettlementDate is the interbank settlement date of the original instruction return message, and not of the return message.</p> <p>XML Tag OrgnlIntrBkSttlmDt Type ISODate</p>
3.13	1..1	Payment Return V09 +Transaction Information ++Returned Interbank Settlement Amount	<p>SEPA Rulebook AT-R074 The returned amount of the positive response to the Request for Recall by the Originator in euro. SEPA Usage Rule(s) The amount must be equal to the 'Original Interbank Settlement Amount' less - if present - the 'Amount' under 'Charges Information'. Only 'EUR' is allowed. Amount must be 0.01 or more and 999999999.99 or less.</p> <p>SEPA Format Rule(s) The fractional part has a maximum of two digits.</p> <p>ISO Name Returned Interbank Settlement Amount ISO Definition Amount of money to be moved between the instructing agent and the instructed agent in the returned instruction.</p> <p>XML Tag RtrdIntrBkSttlmAmt Type ActiveCurrencyAndAmount SEPA FractDigits 2 TotalDigits 18 SEPA Inclusive 0.01 .. 999999999.99</p>
3.14	0..1	Payment Return V09 +Transaction Information ++Interbank Settlement Date	<p>ISO Name Interbank Settlement Date ISO Definition Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.</p> <p>Usage: the InterbankSettlementDate is the interbank settlement date of the return message, and not of the original instruction.</p> <p>XML Tag IntrBkSttlmDt Type ISODate</p>



#	SEPA Mult	Message Element	Inter-PSP Positive Response to a RFRO SEPA Core Requirements	
3.15	0..1	Payment Return V09 +Transaction Information ++Settlement Priority	ISO Name ISO Definition XML Tag Type	Settlement Priority Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the settlement instruction. Usage: the SettlementPriority is the settlement priority of the return message, and not of the original instruction. SttlmPrty Priority3Code
3.16	0..1	Payment Return V09 +Transaction Information ++Settlement Time Indication	ISO Name ISO Definition XML Tag Type	Settlement Time Indication Provides information on the occurred settlement time(s) of the payment transaction. SttlmTmIndctn SettlementDateTimeIndication1
3.17	0..1	Payment Return V09 +Transaction Information ++Returned Instructed Amount	SEPA Usage Rule(s) SEPA Format Rule(s) ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits SEPA Inclusive	<i>Only 'EUR' is allowed.</i> <i>Amount must be 0.01 or more and 999999999.99 or less.</i> <i>The fractional part has a maximum of two digits.</i> Returned Instructed Amount Amount of money to be moved between the debtor and the creditor, before deduction of charges, in the returned transaction. Usage: This amount has to be transported unchanged through the transaction chain. RtrdInstdAmt ActiveOrHistoricCurrencyAndAmount 2 18 0.01 .. 999999999.99
3.18	0..1	Payment Return V09 +Transaction Information ++Exchange Rate	ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits	Exchange Rate Factor used to convert an amount from one currency into another. This reflects the price at which one currency was bought with another currency. XchgRate BaseOneRate 10 11
3.19	0..1	Payment Return V09 +Transaction Information ++Compensation Amount	ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits SEPA Inclusive	Compensation Amount Amount of money asked or paid as compensation for the processing of the instruction. CompstnAmt ActiveOrHistoricCurrencyAndAmount 5 18 0 ..
3.20	0..1	Payment Return V09 +Transaction Information ++Charge Bearer	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type SEPA Code Restrictions SLEV	<i>Only "SLEV" is allowed.</i> Charge Bearer Specifies which party/parties will bear the charges associated with the processing of the payment transaction. Usage: The ChargeBearer applies to the return message, not to the original instruction. ChrgBr ChargeBearerType1Code <i>FollowingServiceLevel</i> <i>Charges are to be applied following the rules</i>



#	SEPA Mult	Message Element	Inter-PSP Positive Response to a RFRO SEPA Core Requirements
			SEPA Code Restrictions
			<i>agreed in the service level and/or scheme.</i>
3.21	0..1	Payment Return V09 +Transaction Information ++Charges Information	SEPA Usage Rule(s) Only one occurrence is allowed. ISO Name Charges Information ISO Definition Provides information on the charges to be paid by the charge bearer(s) related to the processing of the return transaction. XML Tag ChrgsInf Type Charges7
3.22	1..1	Payment Return V09 +Transaction Information ++Charges Information +++Amount	SEPA Rulebook AT-R075 Fee for the positive response to a Request for Recall by the Originator in euro. SEPA Usage Rule(s) Only 'EUR' is allowed. Amount must be 0.01 or more and 999999999.99 or less. SEPA Format Rule(s) The fractional part has a maximum of two digits. ISO Name Amount ISO Definition Transaction charges to be paid by the charge bearer. XML Tag Amt Type ActiveOrHistoricCurrencyAndAmount SEPA FractDigits 2 TotalDigits 18 SEPA Inclusive 0.01 .. 999999999.99
3.23	1..1	Payment Return V09 +Transaction Information ++Charges Information +++Agent	ISO Name Agent ISO Definition Agent that takes the transaction charges or to which the transaction charges are due. XML Tag Agt Type BranchAndFinancialInstitutionIdentification6
3.24	1..1	Payment Return V09 +Transaction Information ++Charges Information +++Agent ++++Financial Institution Identification	SEPA Rulebook AT-C002 The BIC code of the Beneficiary PSP. SEPA Usage Rule(s) Only 'BICFI' is allowed. ISO Name Financial Institution Identification ISO Definition Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme. XML Tag FinInstnId Type FinancialInstitutionIdentification18
3.25	0..1	Payment Return V09 +Transaction Information ++Charges Information +++Agent ++++Branch Identification	ISO Name Branch Identification ISO Definition Identifies a specific branch of a financial institution. Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level. XML Tag BrnchId Type BranchData3
3.26	0..1	Payment Return V09 +Transaction Information ++Clearing System Reference	ISO Name Clearing System Reference ISO Definition Unique reference, as assigned by the clearing system, to unambiguously identify the return instruction. XML Tag ClrSysRef Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35



#	SEPA Mult	Message Element	Inter-PSP Positive Response to a RFRO SEPA Core Requirements
3.27	0..1	Payment Return V09 +Transaction Information ++Instructing Agent	<p>SEPA Usage Rule(s) Only 'BICFI' is allowed.</p> <p>ISO Name Instructing Agent</p> <p>ISO Definition Agent that instructs the next party in the chain to carry out the (set of) instruction(s).</p> <p>Usage: The instructing agent is the party sending the return message and not the party that sent the original instruction that is being returned.</p> <p>XML Tag InstgAgt</p> <p>Type BranchAndFinancialInstitutionIdentification6</p>
3.28	0..1	Payment Return V09 +Transaction Information ++Instructed Agent	<p>SEPA Usage Rule(s) Only 'BICFI' is allowed.</p> <p>ISO Name Instructed Agent</p> <p>ISO Definition Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s).</p> <p>Usage: The instructed agent is the party receiving the return message and not the party that received the original instruction that is being returned.</p> <p>XML Tag InstdAgt</p> <p>Type BranchAndFinancialInstitutionIdentification6</p>
3.29	0..1	Payment Return V09 +Transaction Information ++Return Chain	<p>ISO Name Return Chain</p> <p>ISO Definition Provides all parties (agents and non-agents) involved in a return transaction.</p> <p>XML Tag RtrChain</p> <p>Type TransactionParties7</p>
3.30	1..1	Payment Return V09 +Transaction Information ++Return Reason Information	<p>SEPA Usage Rule(s) <i>Mandatory.</i> Only one occurrence of 'Return Reason Information' is allowed.</p> <p>ISO Name Return Reason Information</p> <p>ISO Definition Provides detailed information on the return reason.</p> <p>XML Tag RtrRsnInf</p> <p>Type PaymentReturnReason6</p>
3.31	1..1	Payment Return V09 +Transaction Information ++Return Reason Information +++Originator	<p>SEPA Rulebook AT-R002 The Identification of the type of party initiating the "R" message.</p> <p>SEPA Usage Rule(s) <i>Mandatory.</i> Only 'Name' is allowed. 'Name' is limited to 70 characters in length.</p> <p>ISO Name Originator</p> <p>ISO Definition Party that issues the return.</p> <p>XML Tag Orgtr</p> <p>Type PartyIdentification135</p>
3.32	1..1	Payment Return V09 +Transaction Information ++Return Reason Information +++Reason	<p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Reason</p> <p>ISO Definition Specifies the reason for the return.</p> <p>XML Tag Rsn</p> <p>Type ReturnReason5Choice</p>
	1..1		XML Tag xs:choice
3.33	1..1	Payment Return V09 +Transaction Information ++Return Reason Information +++Reason ++++Code	<p>SEPA Usage Rule(s) Only "FOCR" is allowed.</p> <p>ISO Name Code</p> <p>ISO Definition Reason for the return, as published in an external reason code list.</p> <p>XML Tag Cd</p> <p>Type ExternalReturnReason1Code</p> <p>ISO Length 1 .. 4</p> <p>SEPA Length 1 .. 4</p>
			SEPA Code Restrictions
			FOCR FollowingCancellationRequest Return following a cancellation request



#	SEPA Mult	Message Element	Inter-PSP Positive Response to a RFRO SEPA Core Requirements
3.34	1..1	Payment Return V09 +Transaction Information ++Return Reason Information +++Reason ++++Proprietary	ISO Name Proprietary ISO Definition Reason for the return, in a proprietary form. XML Tag Prtry Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35
3.35	1..1	Payment Return V09 +Transaction Information ++Return Reason Information +++Additional Information	SEPA Rulebook AT-R072 The specific reference of the Originator PSP for the Request for Recall by the Originator. SEPA Usage Rule(s) Mandatory. Only one occurrence starting with "ATR072/" followed by the information as per attribute description is allowed. ISO Name Additional Information ISO Definition Further details on the return reason. XML Tag AddtlInf Type Max105Text ISO Length 1 .. 105 SEPA Length 1 .. 105
3.36	1..1	Payment Return V09 +Transaction Information ++Original Transaction Reference	SEPA Rulebook An exact copy of all attributes of the received DS-02 which is being returned. SEPA Usage Rule(s) Mandatory. The message elements under 'Original Transaction Reference' must be populated with the same value as the message elements of the original instruction. ISO Name Original Transaction Reference ISO Definition Key elements used to identify the original transaction that is being referred to. XML Tag OrgnlTxRef Type OriginalTransactionReference28
3.37	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Interbank Settlement Amount	ISO Name Interbank Settlement Amount ISO Definition Amount of money moved between the instructing agent and the instructed agent. XML Tag IntrBkSttlmAmt Type ActiveOrHistoricCurrencyAndAmount SEPA FractDigits 5 TotalDigits 18 SEPA Inclusive 0 ..
3.38	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Amount	ISO Name Amount ISO Definition Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party. XML Tag Amt Type AmountType4Choice
3.39	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Interbank Settlement Date	SEPA Rulebook AT-T051 The Settlement Date of the SCT Inst Transaction. ISO Name Interbank Settlement Date ISO Definition Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. XML Tag IntrBkSttlmDt Type ISODate
3.40	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Requested Collection Date	ISO Name Requested Collection Date ISO Definition Date and time at which the creditor requests that the amount of money is to be collected from the debtor. XML Tag ReqdCollmDt Type ISODate



#	SEPA Mult	Message Element	Inter-PSP Positive Response to a RFRO SEPA Core Requirements	
3.41	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Requested Execution Date	ISO Name ISO Definition XML Tag Type	Requested Execution Date Date at which the initiating party requests the clearing agent to process the payment. Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank. ReqdExctnDt DateAndDateTime2Choice
3.42	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Creditor Scheme Identification	ISO Name ISO Definition XML Tag Type	Creditor Scheme Identification Credit party that signs the mandate. CdrSchmeld PartyIdentification135
3.43	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Settlement Information	ISO Name ISO Definition XML Tag Type	Settlement Information Specifies the details on how the settlement of the original transaction(s) between the instructing agent and the instructed agent was completed. StlmInf SettlementInstruction7
3.44	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Payment Type Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	AT-T001 The identification code of the SCT Inst Scheme. AT-T008 The category purpose of the SCT Inst Instruction. Payment Type Information Set of elements used to further specify the type of transaction. PmtTpInf PaymentTypeInformation27
3.45	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Payment Method	ISO Name ISO Definition XML Tag Type	Payment Method Specifies the means of payment that will be used to move the amount of money. PmtMtd PaymentMethod4Code
3.46	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Mandate Related Information	ISO Name ISO Definition XML Tag Type	Mandate Related Information Provides further details of the mandate signed between the creditor and the debtor. MndtRltdInf MandateRelatedInformation14
3.47	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Remittance Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	AT-T009 The Remittance information. Remittance Information Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system. RmtInf RemittanceInformation16
3.48	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Ultimate Debtor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-P006 The name of the Originator Reference Party. AT-P007 The identification code of the Originator Reference Party. Only 'Party' is allowed. Ultimate Debtor Ultimate party that owes an amount of money to the (ultimate) creditor. UltmtDbtr Party40Choice



#	SEPA Mult	Message Element	Inter-PSP Positive Response to a RFRO SEPA Core Requirements	
3.49	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Debtor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-P001 The name of the Originator.</i> <i>AT-P005 The address of the Originator.</i> <i>AT-P004 The Originator identification code.</i> <i>Only 'Party' is allowed.</i> Debtor Party that owes an amount of money to the (ultimate) creditor. Dbtr Party40Choice
3.50	1..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Debtor Account	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-D001 The IBAN of the account of the Originator.</i> <i>AT-P003 The Proxy/Alias of the account of the Originator.</i> Debtor Account Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction. DbtrAcct CashAccount38
3.51	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Debtor Agent	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-D002 The BIC code of the Originator PSP.</i> Debtor Agent Financial institution servicing an account for the debtor. DbtrAgt BranchAndFinancialInstitutionIdentification6
3.52	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Debtor Agent Account	ISO Name ISO Definition XML Tag Type	Debtor Agent Account Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain. DbtrAgtAcct CashAccount38
3.53	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Creditor Agent	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-C002 The BIC code of the Beneficiary PSP.</i> Creditor Agent Financial institution servicing an account for the creditor. CdtrAgt BranchAndFinancialInstitutionIdentification6
3.54	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Creditor Agent Account	ISO Name ISO Definition XML Tag Type	Creditor Agent Account Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction. CdtrAgtAcct CashAccount38
3.55	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Creditor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-E001 The name of the Beneficiary.</i> <i>AT-E004 The address of the Beneficiary.</i> <i>AT-E005 The Beneficiary identification code.</i> <i>Only 'Party' is allowed.</i> Creditor Party to which an amount of money is due. Cdtr Party40Choice
3.56	1..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Creditor Account	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-C001 The IBAN of the account of the Beneficiary.</i> <i>AT-E003 The Proxy/Alias of the account of the Beneficiary.</i> Creditor Account Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction. CdtrAcct CashAccount38



#	SEPA Mult	Message Element	Inter-PSP Positive Response to a RFRO SEPA Core Requirements	
3.57	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Ultimate Creditor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-E007 The name of the Beneficiary Reference Party.</i> <i>AT-E010 The identification code of the Beneficiary Reference Party.</i> Only 'Party' is allowed. Ultimate Creditor Ultimate party to which an amount of money is due. UltmtCdtr Party40Choice
3.58	0..1	Payment Return V09 +Transaction Information ++Original Transaction Reference +++Purpose	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T007 The purpose of the SCT Inst Instruction.</i> Purpose Underlying reason for the payment transaction. Usage: Purpose is used by the end customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain. Purp Purpose2Choice
3.59	0..n	Payment Return V09 +Transaction Information ++Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1
4.0	0..n	Payment Return V09 +Supplementary Data	ISO Name ISO Definition XML Tag Type	Supplementary Data Additional information that cannot be captured in the structured elements and/or any other specific block. SplmtryData SupplementaryData1



2.12 Request for Status Update on a Request for Recall by the Originator

2.12.1 Use of FI To FI Payment Status Request (pacs.028.001.03)

This message is sent to the Beneficiary PSP in case the Originator PSP did not receive a response to a Request for Recall by the Originator, where the following applies:

- Index 3.3 'Original Instruction Identification' must be populated with a cancellation ID (AT-R072) of the related camt.056 Transaction Information.

In an SCT Inst context, the message is used for a single or group status request.

Note: The use case of the message is implied by the 'Message Name', 'pacs.028.001.03', the 'Original Message Name Identification' must begin with 'camt.056' (the addition of a variant number and version number is optional), the population of index 3.3 'Original Instruction Identification' and 'Payment Type Information' mentioning "INST" (Transaction is related to an Instant Credit Transfer) under 'Local Instrument/Code'.

Note: Message elements under 'Original Transaction Reference' are based on DS-02 attributes.



#	SEPA Mult	Message Element	Request for Status Update on a RFRO SEPA Core Requirements	
		Document	XML Tag Type	Document Document
	1..1	FIto FIPayment Status Request V03	ISO Name ISO Definition XML Tag Type	FIto FIPayment Status Request V03 Scope The FinancialInstitutionToFinancialInstitutionPaymentStatusRequest message is sent by the debtor agent to the creditor agent, directly or through other agents and/or a payment clearing and settlement system. It is used to request a FItoFIPaymentStatusReport message containing information on the status of a previously sent instruction. FItoFIPmtStsReq FItoFIPaymentStatusRequestV03
1.0	1..1	FIto FIPayment Status Request V03 +Group Header	ISO Name ISO Definition XML Tag Type	Group Header Set of characteristics shared by all individual transactions included in the status request message. GrpHdr GroupHeader91
1.1	1..1	FIto FIPayment Status Request V03 +Group Header ++Message Identification	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Message Identification Point to point reference, as assigned by the instructing party, and sent to the next party in the chain to unambiguously identify the message. Usage: The instructing party has to make sure that MessageIdentification is unique per instructed party for a pre-agreed period. MsgId Max35Text 1 .. 35 1 .. 35
1.2	1..1	FIto FIPayment Status Request V03 +Group Header ++Creation Date Time	ISO Name ISO Definition XML Tag Type	Creation Date Time Date and time at which the message was created. CreDtTm ISODateTime
1.3	0..1	FIto FIPayment Status Request V03 +Group Header ++Instructing Agent	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>Only 'BICFI' is allowed.</i> Instructing Agent Agent that instructs the next party in the chain to carry out the (set of) instruction(s). Usage: The instructing agent is the party sending the status message and not the party that sent the original instruction that is being reported on. InstgAgt BranchAndFinancialInstitutionIdentification6
1.4	0..1	FIto FIPayment Status Request V03 +Group Header ++Instructed Agent	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>Only 'BICFI' is allowed.</i> Instructed Agent Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s). Usage: The instructed agent is the party receiving the status message and not the party that received the original instruction that is being reported on. InstdAgt BranchAndFinancialInstitutionIdentification6



#	SEPA Mult	Message Element	Request for Status Update on a RFRO SEPA Core Requirements
2.0	1..1	FITo FIPayment Status Request V03 +Original Group Information	SEPA Usage Rule(s) <i>Mandatory.</i> <i>Only one occurrence is allowed.</i> ISO Name Original Group Information ISO Definition Original group information concerning the group of transactions, to which the status request message refers to. XML Tag OrgnlGrpInf Type OriginalGroupInformation27
2.1	1..1	FITo FIPayment Status Request V03 +Original Group Information ++Original Message Identification	ISO Name Original Message Identification ISO Definition Point to point reference, as assigned by the original instructing party, to unambiguously identify the original message. XML Tag OrgnlMsgId Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35
2.2	1..1	FITo FIPayment Status Request V03 +Original Group Information ++Original Message Name Identification	SEPA Usage Rule(s) <i>Must begin with 'camt.056'. The addition of a variant number and version number is optional.</i> ISO Name Original Message Name Identification ISO Definition Specifies the original message name identifier to which the message refers. XML Tag OrgnlMsgNmId Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35
2.3	0..1	FITo FIPayment Status Request V03 +Original Group Information ++Original Creation Date Time	ISO Name Original Creation Date Time ISO Definition Date and time at which the original message was created. XML Tag OrgnlCreDtTm Type ISODateTime
2.4	0..1	FITo FIPayment Status Request V03 +Original Group Information ++Original Number Of Transactions	ISO Name Original Number Of Transactions ISO Definition Number of individual transactions contained in the original message. XML Tag OrgnlNbOfTxS Type Max15NumericText Pattern [0-9]{1,15}
2.5	0..1	FITo FIPayment Status Request V03 +Original Group Information ++Original Control Sum	ISO Name Original Control Sum ISO Definition Total of all individual amounts included in the original message, irrespective of currencies. XML Tag OrgnlCtrlSum Type DecimalNumber SEPA FractDigits 17 TotalDigits 18
3.0	1..n	FITo FIPayment Status Request V03 +Transaction Information	SEPA Usage Rule(s) <i>Mandatory.</i> ISO Name Transaction Information ISO Definition Information concerning the original transaction, to which the status request message refers. XML Tag TxInf Type PaymentTransaction113



#	SEPA Mult	Message Element	Request for Status Update on a RFRO SEPA Core Requirements
3.1	1..1	FITo FIPayment Status Request V03 +Transaction Information ++Status Request Identification	<p>SEPA Usage Rule(s) <i>Mandatory.</i> <i>This ID must be forwarded to the Beneficiary PSP (and therefore it is not a point-to-point reference).</i></p> <p>ISO Name Status Request Identification ISO Definition Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the status request. Usage: The instructing party is the party sending the request message and not the party that sent the original instruction that is being reported on.</p> <p>XML Tag StsReqId Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35</p>
3.2	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Group Information	<p>ISO Name Original Group Information ISO Definition Point to point reference, as assigned by the original instructing party, to unambiguously identify the original message.</p> <p>XML Tag OrgnlGrpInf Type OriginalGroupInformation29</p>
3.3	1..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Instruction Identification	<p>SEPA Usage Rule(s) <i>Mandatory.</i> <i>Must be populated with a cancellation ID (AT-R072) of the relevant camt.056 Transaction Information.</i></p> <p>ISO Name Original Instruction Identification ISO Definition Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction.</p> <p>XML Tag OrgnlInstrId Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35</p>
3.4	1..1	FITo FIPayment Status Request V03 +Transaction Information ++Original End To End Identification	<p>SEPA Rulebook <i>AT-T014 Originator's reference of the SCT Inst Instruction.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Original End To End Identification ISO Definition Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction.</p> <p>XML Tag OrgnlEndToEndId Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35</p>
3.5	1..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Identification	<p>SEPA Rulebook <i>AT-T054 The Originator PSP's reference number of the SCT Inst Transaction message.</i></p> <p>SEPA Usage Rule(s) <i>Mandatory.</i></p> <p>ISO Name Original Transaction Identification ISO Definition Unique identification, as assigned by the original first instructing agent, to unambiguously identify the transaction.</p> <p>XML Tag OrgnlTxId Type Max35Text ISO Length 1 .. 35 SEPA Length 1 .. 35</p>



#	SEPA Mult	Message Element	Request for Status Update on a RFRO SEPA Core Requirements	
3.6	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original UETR	ISO Name ISO Definition XML Tag Type Pattern	Original UETR Universally unique identifier to provide the original end-to-end reference of a payment transaction. OrgnUETR UUIDv4Identifier [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}
3.7	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Acceptance Date Time	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	AT-T056 Timestamp of the SCT Inst Transaction. This information is to be retrieved from the original transaction. Acceptance Date Time Point in time when the payment order from the initiating party meets the processing conditions of the account servicing agent. This means that the account servicing agent has received the payment order and has applied checks such as authorisation, availability of funds. AcptncDtTm ISODateTime
3.8	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Clearing System Reference	ISO Name ISO Definition XML Tag Type ISO Length SEPA Length	Clearing System Reference Unique reference, as assigned by a clearing system, to unambiguously identify the instruction. ClrSysRef Max35Text 1 .. 35 1 .. 35
3.9	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Instructing Agent	ISO Name ISO Definition XML Tag Type	Instructing Agent Agent that instructs the next party in the chain to carry out the (set of) instruction(s). InstgAgt BranchAndFinancialInstitutionIdentification6
3.10	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Instructed Agent	ISO Name ISO Definition XML Tag Type	Instructed Agent Agent that is instructed by the previous party in the chain to carry out the (set of) instruction(s). InstdAgt BranchAndFinancialInstitutionIdentification6
3.11	1..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference	SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	Mandatory. The message elements under 'Original Transaction Reference' must be populated with the same value as the message elements of the original instruction. Original Transaction Reference Key elements used to identify the original transaction that is being referred to. OrgnTxRef OriginalTransactionReference28
3.12	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Interbank Settlement Amount	SEPA Rulebook ISO Name ISO Definition XML Tag Type SEPA FractDigits TotalDigits SEPA Inclusive	AT-T002 The amount of the SCT Inst in euro. Interbank Settlement Amount Amount of money moved between the instructing agent and the instructed agent. IntrBkSttlmAmt ActiveOrHistoricCurrencyAndAmount 2 18 0.01 .. 999999999.99



#	SEPA Mult	Message Element	Request for Status Update on a RFRO SEPA Core Requirements	
3.13	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Amount	ISO Name ISO Definition XML Tag Type	Amount Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party. Amt AmountType4Choice
3.14	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Interbank Settlement Date	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T051 The Settlement Date of the SCT Inst Transaction.</i> Interbank Settlement Date Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due. IntrBkStlmDt ISODate
3.15	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Requested Collection Date	ISO Name ISO Definition XML Tag Type	Requested Collection Date Date and time at which the creditor requests that the amount of money is to be collected from the debtor. ReqdColltnDt ISODate
3.16	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Requested Execution Date	ISO Name ISO Definition XML Tag Type	Requested Execution Date Date at which the initiating party requests the clearing agent to process the payment. Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank. ReqdExctnDt DateAndDateTime2Choice
3.17	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Creditor Scheme Identification	ISO Name ISO Definition XML Tag Type	Creditor Scheme Identification Credit party that signs the mandate. CdtrSchmeld PartyIdentification135
3.18	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Settlement Information	ISO Name ISO Definition XML Tag Type	Settlement Information Specifies the details on how the settlement of the original transaction(s) between the instructing agent and the instructed agent was completed. StlmInf SettlementInstruction7
3.19	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Payment Type Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T008 The category purpose of the SCT Inst Instruction.</i> <i>AT-T001 The identification code of the SCT Inst Scheme.</i> Payment Type Information Set of elements used to further specify the type of transaction. PmtTpInf PaymentTypeInfo27
3.20	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Payment Method	ISO Name ISO Definition XML Tag Type	Payment Method Specifies the means of payment that will be used to move the amount of money. PmtMtd PaymentMethod4Code
3.21	0..1	FITo FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Mandate Related Information	ISO Name ISO Definition XML Tag Type	Mandate Related Information Provides further details of the mandate signed between the creditor and the debtor. MndtRltdInf MandateRelatedInformation14



#	SEPA Mult	Message Element	Request for Status Update on a RFRO SEPA Core Requirements	
3.22	0..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Remittance Information	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-T009 The Remittance Information sent by the Originator to the Beneficiary in the SCT Inst Instruction.</i> Remittance Information Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system. RmtInf RemittanceInformation16
3.23	0..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Ultimate Debtor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-P006 The name of the Originator Reference Party.</i> <i>AT-P007 The identification code of the Originator Reference Party.</i> Only 'Party' is allowed. Ultimate Debtor Ultimate party that owes an amount of money to the (ultimate) creditor. UltmtDbtr Party40Choice
3.24	0..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Debtor	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-P001 The name of the Originator</i> <i>AT-P005 The address of the Originator</i> <i>AT-P004 The Originator identification code</i> Only 'Party' is allowed. Debtor Party that owes an amount of money to the (ultimate) creditor. Dbtr Party40Choice
3.25	0..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Debtor Account	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-D001 The IBAN of the account of the Originator.</i> <i>AT-P003 The Proxy/Alias of the account of the Originator</i> Debtor Account Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction. DbtrAcct CashAccount38
3.26	1..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Debtor Agent	SEPA Rulebook SEPA Usage Rule(s) ISO Name ISO Definition XML Tag Type	<i>AT-D002 The BIC code of the Originator PSP.</i> Mandatory. Debtor Agent Financial institution servicing an account for the debtor. DbtrAgt BranchAndFinancialInstitutionIdentification6
3.27	0..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Debtor Agent Account	ISO Name ISO Definition XML Tag Type	Debtor Agent Account Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain. DbtrAgtAcct CashAccount38
3.28	0..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Creditor Agent	SEPA Rulebook ISO Name ISO Definition XML Tag Type	<i>AT-C002 The BIC code of the Beneficiary PSP.</i> Creditor Agent Financial institution servicing an account for the creditor. CdtrAgt BranchAndFinancialInstitutionIdentification6



#	SEPA Mult	Message Element	Request for Status Update on a RFRO SEPA Core Requirements
3.29	0..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Creditor Agent Account	ISO Name Creditor Agent Account ISO Definition Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction. XML Tag CdrAgtAcct Type CashAccount38
3.30	0..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Creditor	SEPA Rulebook AT-E001 The name of the Beneficiary. AT-E004 The address of the Beneficiary. AT-E005 The Beneficiary identification code. SEPA Usage Rule(s) Only 'Party' is allowed. ISO Name Creditor ISO Definition Party to which an amount of money is due. XML Tag Cdr Type Party40Choice
3.31	0..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Creditor Account	SEPA Rulebook AT-C001 The IBAN of the account of the Beneficiary. AT-E003 The Proxy/Alias of the account of the Beneficiary. ISO Name Creditor Account ISO Definition Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction. XML Tag CdrAcct Type CashAccount38
3.32	0..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Ultimate Creditor	SEPA Rulebook AT-E007 The name of the Beneficiary Reference Party. AT-E010 The identification code of the Beneficiary Reference Party. SEPA Usage Rule(s) Only 'Party' is allowed. ISO Name Ultimate Creditor ISO Definition Ultimate party to which an amount of money is due. XML Tag UltmtCdr Type Party40Choice
3.33	0..1	FIto FIPayment Status Request V03 +Transaction Information ++Original Transaction Reference +++Purpose	SEPA Rulebook AT-T007 The purpose of the SCT Inst Instruction. ISO Name Purpose ISO Definition Underlying reason for the payment transaction. Usage: Purpose is used by the end customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain. XML Tag Purp Type Purpose2Choice
3.34	0..n	FIto FIPayment Status Request V03 +Transaction Information +++Supplementary Data	ISO Name Supplementary Data ISO Definition Additional information that cannot be captured in the structured elements and/or any other specific block. XML Tag SplmtryData Type SupplementaryData1
4.0	0..n	FIto FIPayment Status Request V03 +Supplementary Data	ISO Name Supplementary Data ISO Definition Additional information that cannot be captured in the structured elements and/or any other specific block. XML Tag SplmtryData Type SupplementaryData1



3 LIST OF CHANGES IN THE SCT INST INTER-PSP IMPLEMENTATION GUIDELINES - RELATIVE TO 2023 VERSION V1.2

Note: This list is for informational purposes only. The changes included in the body of the document are the ones in effect and also encompass those resulting from errata document EPC053-23.

SYMBOLS USED

1. Column one contains the identification number of the Change
2. Column two contains the reference(s) to the relevant Index Number
3. Column three contains the reference(s) to the relevant section or message element (including full path)
4. Column four contains a description of the change
5. Column five contains the type of change:
 - TYPO: Typing and layout errors
 - CLAR: Clarification of the text
 - CHAN: Change in or further alignment with the Rulebook content

N°	#	Section / Message Element	Description	Type
1.		0.1 References	Inclusion of following references: - XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004 - EPC153-22 EPC Guidance Document: Provision of Addresses under the EPC Payment Schemes - EPC088-22 EPC Guidance Document – Improve Transparency for Retail Payment End-Users Removal of reference to “EPC0023-16 Maximum Amount for instructions under SCT Inst Scheme Rulebook”.	CHAN
2.		0.3 Purpose of Document	Update in Note (see bold text): “In section 4.2.3. B of the SCT Inst Rulebook it is stated that “Participants are free to agree on a bilateral or multilateral basis with other Participants on a target maximum execution time of less than 510 seconds”	CHAN
3.		1.5.2 Timestamps	Inclusion of new section	CHAN
4.		1.7 Change over date	Inclusion of note: “As of 22 November 2026 at 03:30 CET only the use of structured and hybrid addresses will be allowed (i.e. the provision of unstructured addresses is no longer allowed as from this date). For further details, please see EPC Guidance Document “Provision of Addresses under the EPC Payment Schemes” [11].”	CHAN
2.1 Inter-PSP Payment Dataset (DS-02)				
5.	1.6	FiTo FiCustomer Credit Transfer V08 +Group Header ++Total Interbank	SEPA Usage Rule updated as follows (see bold text):	CHAN



N°	#	Section / Message Element	Description	Type
		Settlement Amount	"Amount must be 0.01 or more and 9999999999999999.99 or less. or up to the maximum amount per instruction that can be processed under the Scheme as defined in document EPC023-16 "Maximum Amount for Instructions under the SCT Instant Rulebook" , or the maximum amount as agreed between individual Participants or communities of Participants."	
6.	2.8	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Interbank Settlement Amount	SEPA Usage Rule updated as follows (see bold text): "Amount must be 0.01 or more and 9999999999.99 or less. or up to the maximum amount per instruction that can be processed under the Scheme as defined in document EPC023-16 "Maximum Amount for Instructions under the SCT Instant Rulebook" , or the maximum amount as agreed between individual Participants or communities of Participants."	CHAN
7.	2.13	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Acceptance Date Time	SEPA Usage Rule updated as follows (see bold text): "The Timestamps must be unambiguous and least include milliseconds. The representation of milliseconds must follow the W3C recommendation." Inclusion of timestamp pattern: [0-9]{4}(-[0-9]{2}){2}T[0-9]{2}(:[0-9]{2}){2}(\.[0-9]{0,2}[1-9])?(Z ([-+][0-9]{2}(:[0-9]{2})?))	CHAN
8.	2.37	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Ultimate Debtor +++Identification ++++Organisation Identification	SEPA Usage Rule updated as follows to be able to comply with the new Funds Transfer Regulation (FTR) (see bold text): "Either 'AnyBIC', 'LEI' and/ or one occurrence of 'Other' is allowed."	CHAN
9.	2.44	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address	SEPA Usage Rules updated as follows: "STRUCTURED: Usage is recommended. 'Town Name' and 'Country' are mandatory. 'Address Line' is not allowed. It is recommended to provide as many structured elements as possible. HYBRID: 'Town Name' and 'Country' are mandatory. At least one occurrence of 'Address line' is mandatory. UNSTRUCTURED: (As of 22 November 2026 at 03:30 CET only the use of structured and hybrid addresses will be allowed - based on available information at the moment of publication): At least one occurrence of 'Address line' is mandatory. 'Postal Address' sub-elements other than 'Address Line' and 'Country' are forbidden. The use of 'Country' is mandatory when either the Debtor Agent or Creditor Agent is located in a non-EEA SEPA country or territory." If 'Address Line' is used, then 'Postal Address'	CHAN



N°	#	Section / Message Element	Description	Type
			sub-elements other than 'Country' are forbidden. A combination of 'Address Line' and 'Country' is allowed; it is recommended when either the Debtor Agent or Creditor Agent is a non-EEA SEPA PSP. If 'Address Line' is not used, then at least 'Town Name' and 'Country' must be used.	
10.	2.60	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Postal Address ++++Address Line	SEPA Usage Rule updated as follows: "Up to two occurrences are allowed." Only two occurrences are allowed. If 'Address Line' is used, then 'Postal Address' sub-elements other than 'Country' are forbidden. A combination of 'Address Line' and 'Country' is allowed; it is recommended when either Debtor Agent or Creditor Agent is a non-EEA SEPA PSP.	CHAN
11.	2.62	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Debtor +++Identification ++++Organisation Identification	SEPA Usage Rule updated as follows to be able to comply with the new Funds Transfer Regulation (FTR) (see bold text): "Either 'AnyBIC', 'LEI' and /or one occurrence of 'Other' is allowed."	CHAN
12.	2.80	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address	SEPA Usage Rules updated as follows: "STRUCTURED: Usage is recommended. 'Town Name' and 'Country' are mandatory. 'Address Line' is not allowed. It is recommended to provide as many structured elements as possible. HYBRID: 'Town Name' and 'Country' are mandatory. At least one occurrence of 'Address line' is mandatory. UNSTRUCTURED: (As of 22 November 2026 at 03:30 CET only the use of structured and hybrid addresses will be allowed - based on available information at the moment of publication): At least one occurrence of 'Address line' is mandatory. 'Postal Address' sub-elements other than 'Address Line' and 'Country' are forbidden." If 'Address Line' is used, then 'Postal Address' sub-elements other than 'Country' are forbidden. A combination of 'Address Line' and 'Country' is allowed. If 'Address Line' is not used, then at least 'Town Name' and 'Country' must be used.	CHAN
13.	2.96	FITo FICustomer Credit Transfer V08 +Credit Transfer Transaction Information ++Creditor +++Postal Address ++++Address Line	SEPA Usage Rule updated as follows: "Up to two occurrences are allowed." Only two occurrences are allowed. If 'Address Line' is used, then 'Postal Address' sub-elements other than 'Country' are forbidden. A combination of 'Address Line' and 'Country' is allowed.	CHAN
2.2 Negative Confirmation Message (DS-03)				
14.		2.2.1	Note updated as follows (see bold text):	CHAN



N°	#	Section / Message Element	Description	Type
			"Attribute AT-R001 'The type of R-message' is implied by the 'Message Name', 'pacs.002.001.10', the 'Original Message Name Identification' must begin with 'pacs.008' (the addition of a variant number and version number is optional) set to 'pacs.008.001.08' , 'Group Status' or 'Transaction Status' set to "RJCT" and 'Payment Type Information' mentioning "INST" (Transaction is related to an Instant Credit Transfer) under 'Local Instrument/Code'."	
15.	2.2	FITo FIPayment Status Report V10 +Original Group Information And Status ++Original Message Name Identification	SEPA Usage Rule updated as follows: " Only pacs.008.001.08 is allowed. Must begin with 'pacs.008'. The addition of a variant number and version number is optional."	CHAN
16.		2.2.2	Removal of reason code "AM02" (Amount Exceeds the maximum authorized amount for SCT Inst) in line with the definition of AT-R004 'The reason code for non-acceptance of the SCT Inst' in the 2025 SCT Inst Rulebook.	CHAN
2.3. Positive Confirmation Message (DS-03)				
17.		2.3.1	Note updated as follows (see bold text): "The use case of the message is implied by the Name', 'pacs.002.001.10', the 'Original Message Name Identification' must begin with 'pacs.008' (the addition of a variant number and version number is optional) set to 'pacs.008.001.08' , 'Group Status' set to "ACCP" and 'Payment Type Information' mentioning "INST" (Transaction is related to an Instant Credit Transfer) under 'Local Instrument/Code'."	CHAN
18.	2.2	FITo FIPayment Status Report V10 +Original Group Information And Status ++Original Message Name Identification	SEPA Usage Rule updated as follows: " Only pacs.008.001.08 is allowed. Must begin with 'pacs.008'. The addition of a variant number and version number is optional."	CHAN
2.4 Recall of an SCT Inst Dataset (DS-05)				
19.		2.4.1	Note updated as follows (see bold text): "Attribute AT-R001 'The type of R-message' is implied by the 'Message Name' set to 'camt.056.001.08', the 'Original Message Name Identification' must begin with 'pacs.008' (the addition of a variant number and version number is optional) set to 'pacs.008.001.08' , 'Reason' set to "DUPL", "FRAD" or "TECH" (under 'Code') and 'Payment Type Information' mentioning "INST" (Transaction is related to an Instant Credit Transfer) under 'Local Instrument/Code'." Inclusion of following note: "Only one Recall can be sent for a given SCT Inst Transaction during the periods mentioned in the SCT Inst Rulebook [1]. The Originator PSP is not allowed to send another SCT Inst Recall for the same initial SCT Inst Transaction."	CHAN



N°	#	Section / Message Element	Description	Type
20.	4.7	FIto FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Group Information ++++Original Message Name Identification	SEPA Usage Rule updated as follows: " Only pacs.008.001.08 is allowed. Must begin with 'pacs.008'. The addition of a variant number and version number is optional."	CHAN
2.5 Inter-PSP Negative Response to a Recall of an SCT Inst Dataset (DS-06)				
21.		2.5.1	Note updated as follows (see bold text): "Attribute AT-R001 'The type of R-message' is implied by the 'Message Name', 'camt.029.001.09', the 'Original Message Name Identification' must begin with 'pacs.008' (the addition of a variant number and version number is optional) set to 'pacs.008.001.08' , 'Status' set to "RJCR" and 'Payment Type Information' mentioning "INST" (Transaction is related to an Instant Credit Transfer) under 'Local Instrument/Code'."	CHAN
22.	4.8	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Group Information ++++Original Message Name Identification	SEPA Usage Rule updated as follows: " Only pacs.008.001.08 is allowed. Must begin with 'pacs.008'. The addition of a variant number and version number is optional."	CHAN
2.6 Inter-PSP Positive Response to a Recall of an SCT Inst Dataset (DS-06)				
23.		2.6.1	Note updated as follows (see bold text): "Attribute AT-R001 is implied by the 'Message Name', 'pacs.004.001.09', the 'Original Message Name Identification' must begin with 'pacs.008' (the addition of a variant number and version number is optional) set to 'pacs.008.001.08' , 'Reason' under 'Return Reason Information' set to "FOCR" and 'Payment Type Information' mentioning "INST" (Transaction is related to an Instant Credit Transfer) under 'Local Instrument/Code'."	CHAN
24.	2.2 3.4	Payment Return V09 +Original Group Information ++Original Message Name Identification Payment Return V09 +Transaction Information ++Original Group Information +++Original Message Name Identification	SEPA Usage Rule updated as follows: " Only pacs.008.001.08 is allowed. Must begin with 'pacs.008'. The addition of a variant number and version number is optional."	CHAN
2.7 Request for Status Update on a Recall of an SCT Inst				
25.		2.7.1	Note updated as follows (see bold text):	CHAN



N°	#	Section / Message Element	Description	Type
			<p>"The use case of the message is implied by the 'Message Name', 'pacs.028.001.03', the 'Original Message Name Identification' must begin with 'camt.056' (the addition of a variant number and version number is optional) set to 'camt.056.001.08', the population of index 3.3 'Original Instruction Identification' and 'Payment Type Information' mentioning "INST" (Transaction is related to an Instant Credit Transfer) under 'Local Instrument/Code'."</p>	
26.	2.2	FITo FIPayment Status Request V03 +Original Group Information ++Original Message Name Identification	SEPA Usage Rule updated as follows: "Only camt.056.001.08 is allowed. Must begin with 'camt.056'. The addition of a variant number and version number is optional."	CHAN
2.8 Dataset for the SCT Inst Transaction Status Investigation Message Sent by the Originator PSP (DS-07)				
27.		2.8.1.	SEPA Usage Rule updated as follows (see bold text): "This message is sent to the Beneficiary PSP in case the Originator PSP has not received a confirmation message (positive or negative) two five seconds after the time-out deadline." Note updated as follows (see bold text): "The use case of the message is implied by the 'Message Name' set to 'pacs.028.001.03', the 'Original Message Name Identification' must begin with 'pacs.008' (the addition of a variant number and version number is optional) set to 'pacs.008.001.08' and 'Payment Type Information' mentioning "INST" (Transaction is related to an Instant Credit Transfer) under 'Local Instrument/Code'."	CHAN
28.	2.2	FITo FIPayment Status Request V03 +Original Group Information ++Original Message Name Identification	SEPA Usage Rule updated as follows: "Only pacs.008.001.08 is allowed. Must begin with 'pacs.008'. The addition of a variant number and version number is optional."	CHAN
2.9 Request for Recall by the Originator Dataset (DS-08)				
29.		2.9.1	Note updated as follows (see bold text): "The use case of the message is implied by the 'Message Name', 'camt.056.001.08', the 'Original Message Name Identification' must begin with 'pacs.008' (the addition of a variant number and version number is optional) set to 'pacs.008.001.08' , 'Originator' set to AT-P001 'The name of the Originator', 'Reason' set to "AC03", "AM09" or "CUST" (under 'Code'), and 'Payment Type Information' mentioning "INST" (Transaction is related to an Instant Credit Transfer) under 'Local Instrument/Code'." Inclusion of following note:	CHAN



N°	#	Section / Message Element	Description	Type
			"Only one Request for Recall by the Originator can be sent for a given SCT Inst Transaction. The Originator PSP is not allowed to send another Request for Recall by the Originator for the same initial SCT Inst Transaction."	
30.	4.7	FITo FIPayment Cancellation Request V08 +Underlying ++Transaction Information +++Original Group Information ++++Original Message Name Identification	SEPA Usage Rule updated as follows: "Only pacs.008.001.08 is allowed. Must begin with 'pacs.008'. The addition of a variant number and version number is optional."	CHAN
2.10 Inter-PSP Negative Response to the Request for Recall by the Originator Dataset (DS-09)				
31.		2.10.1	Note updated as follows (see bold text): "The use case of the message is implied by the 'Message Name', 'camt.029.001.09', the 'Original Message Name Identification' must begin with 'pacs.008' (the addition of a variant number and version number is optional) set to 'pacs.008.001.08' , 'Status' set to "RJCR" and 'Payment Type Information' mentioning "INST" (Transaction is related to an Instant Credit Transfer) under 'Local Instrument/Code'."	CHAN
32.	4.8	Resolution Of Investigation V09 +Cancellation Details ++Transaction Information And Status +++Original Group Information ++++Original Message Name Identification	SEPA Usage Rule updated as follows: "Only pacs.008.001.08 is allowed. Must begin with 'pacs.008'. The addition of a variant number and version number is optional."	CHAN
2.11 Inter-PSP Positive Response to the Request for Recall by the Originator (DS-09)				
33.		2.11.1	Note updated as follows (see bold text): "Attribute AT-R001 'The type of R-message' is implied is implied by the 'Message Name', 'pacs.004.001.09', the 'Original Message Name Identification' must begin with 'pacs.008' (the addition of a variant number and version number is optional) set to 'pacs.008.001.08' , 'Reason' under 'Return Reason Information' set to "FOCR" and 'Payment Type Information' mentioning "INST" (Transaction is related to an Instant Credit Transfer) under 'Local Instrument/Code'."	CHAN
34.	2.2 3.4	Payment Return V09 +Original Group Information ++Original Message Name Identification Payment Return V09 +Transaction Information ++Original Group Information +++Original Message Name Identification	SEPA Usage Rule updated as follows: "Only pacs.008.001.08 is allowed. Must begin with 'pacs.008'. The addition of a variant number and version number is optional."	CHAN
2.12 Request for Status Update on a Request for Recall by the Originator				



N°	#	Section / Message Element	Description	Type
35.		2.12.1	Note updated as follows (see bold text): "The use case of the message is implied by the 'Message Name', 'pacs.028.001.03', the 'Original Message Name Identification' must begin with 'camt.056' (the addition of a variant number and version number is optional) set to 'camt.056.001.08' , the population of index 3.3 'Original Instruction Identification' and 'Payment Type Information' mentioning "INST" (Transaction is related to an Instant Credit Transfer) under 'Local Instrument/Code'."	CHAN
36.	2.2	FITo FIPayment Status Request V03 +Original Group Information ++Original Message Name Identification	SEPA Usage Rule updated as follows: "Only camt.056.001.08 is allowed. Must begin with 'camt.056'. The addition of a variant number and version number is optional."	CHAN